

ACRME — Functional Design Document (FDD)

Title	Azure Capacity Reservation Management Engine (ACRME) — Functional Design Document
Version	1.0 (net-new)
Date	2 September 2026
Status	Draft for review — supersedes the Executive Design Document as the functional design of record
Baseline	Azure Capacity & Quota Management — Consolidated Requirements Baseline v2.2 (27 Aug 2026)
Owner	Vishnuvardhan Reddy · Principal Cloud Architect
Audience	Business, architecture, operations, audit, onboarding, FinOps
Companion	Technical Design Document (acrme_technical_design_document.md)

Purpose. This FDD describes **what** ACRME does — its functional behaviour, flows, states, and rules — traceable to every requirement in Baseline v2.2. It is implementation-neutral; the **how** (components, data, algorithms, interfaces, security, NFRs) is in the companion TDD. This document is **self-contained**: all normative detail (readiness states, engine modes, formulas, classification tables, validation rules) is inlined, not referenced externally.

Reconciliation note (v2.2). This document reflects the confirmed v2.2 design decisions: **single governed quota pool** as the primary model (QUA-004); **max-not-sum** DR destination sizing (DR-017); **exact-production-region-first** onboarding with a governed **seed record** (PLC-001..005); distributed, reciprocal DR with a **source→destination DR index** (DR-016/018) and **standby activation waves** (DR-019); and **Switzerland North** as the pre-configured EU cross-geo DR extension for the Middle East (REG-002) — **conditional and currently inactive** because Middle East DR is DR_NOT_OFFERED pending legal review (DR-014, DEC-001; see Section 4.4/Section 8 below).

Middle East DR (DR-014, DEC-001) — currently NOT offered. As it stands, DR is **not offered** in the Middle East. Legal owns the Middle East programme and data-sovereignty/residency laws (a largely government/medical customer base) mean cross-border DR cannot meet residency requirements (baseline Section

2, Section 5.2, Section 6). Middle East placement defaults to `dr_region = NOT_OFFERED`; **production may still exist without DR**. Switzerland North is a pre-configured cross-geo extension that becomes usable **only if/when Legal approves DEC-001**. This is a pending decision and a major architectural risk (baseline Section 25).

1. Introduction

1.1 Purpose and scope

ACRME governs Azure capacity reservations and VM-family quota across a managed fleet so that every managed deployment has **both** reserved physical capacity and deployable quota, in the right region/zone/SKU, before it is allowed to proceed — while keeping idle cost low through lean DR and dynamic reconciliation.

In scope (baseline Section 5): capacity reservation lifecycle (CAP), quota governance and pooling (QUA), combined deployment readiness (RDY), region selection and customer placement (PLC/REG), disaster recovery (DR), cost/FinOps signals (FIN), AEP/provisioning integration (INT), data/state (DAT), observability (OBS), governance (GOV), operations (OPS), and non-functional behaviour (NFR).

Out of scope: the actual provisioning of customer workloads (owned by AEP), Azure control-plane implementation, and any automation not gated by policy in Phase 1 (destructive VM-association changes remain blocked — see Section 4.5).

1.2 Definitions

Term	Meaning
CRG	Capacity Reservation Group — Azure construct holding reserved capacity per region/zone/SKU.
CVAL	Customer validation environment; its capacity may contribute to DR readiness under earmark.
AEP	Azure/Application Enablement Platform — the provisioning consumer of ACRME readiness.
Seed record	Authoritative customer record holding production, CVAL, and DR regional placement (PLC-003).

Term	Meaning
Single governed quota pool	One governed quota group per region/quota family covering Prod + NonProd/CVAL + DR (QUA-004).
DR bootstrap capacity	Minimum reserved standby capacity to initiate recovery, not a fixed % of production (DR-007).
max-not-sum	Destination DR sizing = largest single non-concurrent protected source portion (DR-017).
Source→destination DR index	Reverse-of-seed mapping driving source-specific standby activation (DR-018).
Readiness state	Machine-readable deployment-readiness verdict returned to AEP (RDY-002).

1.3 Traceability approach

Every functional capability in Section 4 cites the requirement IDs it satisfies. Section 9 is a full matrix mapping **every** Baseline v2.2 ID (REG/ENV/CAP/QUA/RDY/PLC/DR/FIN/INT/DAT/OBS/GOV/NFR/OPS + POC/DEC/DEP dependencies) to an FDD section.

2. Solution Overview

ACRME is a policy-driven control engine sitting between the customer/onboarding intent and Azure's capacity and quota control planes. It continuously reconciles desired vs actual state and answers a single question for every managed deployment: *is this deployment ready, and if not, exactly why?*

Capability map → requirement groups:

Capability	Requirement group	FDD section
Capacity reservation management	CAP	Section 4.1
Quota governance & single-pool management	QUA	Section 4.2
Combined deployment readiness	RDY	Section 4.3
Region selection & customer placement (seed)	PLC, REG	Section 4.4

Capability	Requirement group	FDD section
Disaster recovery (distributed, max-not-sum)	DR, ENV	Section 4.5
Cost & FinOps	FIN	Section 4.6
Provisioning & AEP integration	INT	Section 4.7
Observability & governance & operations	OBS, GOV, OPS	Section 4.8
Data & state (functional view)	DAT	Section 6
Non-functional behaviour	NFR	Section 4 (each), Section 6

F1 — System context

flowchart TB

```

Onboard[Onboarding / Product teams] -->|exact prod region, customer intent| ACRME
AEP[AEP / Provisioning] -->|readiness query| ACRME
ACRME -->|DeploymentReadinessResult| AEP
Ops[Platform operators / DR coordinator] -->|approvals, overrides, DR declaration| ACRME
FinOps[FinOps] -->|cost policy, buffer policy| ACRME
Audit[Auditors] -->|read audit trail| ACRME
ACRME -->|reservations, CRGs| AzCap[Azure Capacity Control Plane]
ACRME -->|quota pool ops| AzQuota[Azure Quota / groupQuotas]
ACRME -->|metrics, alerts| Obs[Observability platform]
AzCap --> ACRME
AzQuota --> ACRME

```

F2 — Capability map

flowchart LR

```

ACRME((ACRME Engine))
ACRME --> C1[Capacity mgmt<br/>CAP]
ACRME --> C2[Quota single pool<br/>QUA]
ACRME --> C3[Readiness<br/>RDY]
ACRME --> C4[Placement + Seed<br/>PLC / REG]
ACRME --> C5[Disaster recovery<br/>DR / ENV]
ACRME --> C6[Cost / FinOps<br/>FIN]
ACRME --> C7[AEP integration<br/>INT]
ACRME --> C8[Observability / Governance / Ops<br/>OBS / GOV / OPS]

```

3. Actors and Stakeholders

Actor	Role in ACRME	Key requirements
Onboarding / product team	Supplies exact production region and customer intent; requests placement.	PLC-001, PLC-002, REG-001
AEP / provisioning	Queries readiness before deploying; consumes readiness contract.	INT-001..007, RDY-001..004
Platform operator	Approves increases/overrides, runs reconciliation, manages scope files.	GOV-001..009, OPS-001..005, CAP-006
DR coordinator	Declares DR events, orders priority waves, authorises CVAL release, drives failback.	DR-004..013, DR-019
FinOps	Sets cost/buffer policy; monitors idle cost and overcommit.	FIN-001..008
Auditor	Reads immutable audit trail of all decisions and mutations.	GOV-004..009, DAT-005
Microsoft/Azure	Capacity & quota provider and feature-maturity dependency.	DEP-001, POC-001..011

F3 — Actor / use-case overview

```

flowchart TB
    subgraph Actors
        O[Onboarding]
        A[AEP]
        Op[Operator]
        DR[DR coordinator]
        F[FinOps]
        Au[Auditor]
    end
    O --> UC1((Onboard + place customer))
    A --> UC2((Query deployment readiness))
    Op --> UC3((Reconcile capacity/quota))
    Op --> UC4((Approve increase / override))
    DR --> UC5((Declare DR + activate standby))

```

```
DR --> UC6((Run DR drill / failback))
F --> UC7((Set cost/buffer policy))
Au --> UC8((Audit decisions))
```

4. Functional Capabilities

4.1 Capacity reservation management (CAP-001..019)

- ACRME maintains reservation state per subscription/region/zone/SKU-family/environment/product and correlates it with quota state (CAP-001, CAP-002). [Decided]
- **Steady-state reservation floor** is normative: **Target Reserved Capacity = Allocated VM Count + Configured Buffer** (CAP-003). Associated-but-deallocated VMs are reported separately and do not automatically preserve paid reservation (CAP-004, CAP-013). [Decided]
- Azure resource creation precedes config activation: create/validate the CRG/reservation first, then activate the deployment config that references it (CAP-007, CAP-008). [Decided]
- **Zero-capacity, not deletion**: an unused managed reservation is reduced to zero where Azure permits; deletion is a separate approved decommissioning workflow (CAP-009, CAP-010). [Decided]
- Over-allocation (reserved < associated demand) is explicit and policy-approved, never silent (CAP-011, CAP-012). Capacity sharing across subscriptions is validated for SKU/region/zone/authorisation (CAP-014..019). [Decided]

4.2 Quota management — single governed pool (QUA-001..014)

- **Primary model (QUA-004): one governed quota pool per region and quota family**, covering Prod, NonProd/CVAL, and DR together. All eligible default per-region quota is hoarded into the pool (QUA-003) and allocated on demand to whichever environment needs it — maximising flexibility, improving utilisation, and **cutting quota-increase requests to Microsoft**. [Decided]
- **Prod protection inside the shared pool** is by logical earmark, not physical separation: **Prod_Reserved_Floor** and **DR_Earmark_vCPU** are never allocatable to NonProd; NonProd allocation fail-safes at **Allocatable_NonProd = 0** (QUA-006..009). [Decided]
- **Quota-as-governor (QUA-005)**: quota caps deployable capacity per product/env/subscription/region/family; every increase is justified and recorded — unallocated pooled quota is not auto-distributed. [Decided]
- **Exception topology (QUA-004 clause)**: a two-group/multi-group model is used only when Azure Quota Group limits or a mandatory Prod-isolation governance boundary make one pool impossible; each such case is recorded in the Decision Log and reverts to one pool when the constraint

lifts. [Decided]

- Reclamation never drops a subscription below current usage, committed demand, Prod buffer, or approved DR need (QUA-010..014). [Decided]

4.3 Combined readiness (RDY-001..004)

ACRME returns a single machine-readable **deployment readiness state** to AEP (RDY-001, RDY-002). The enumerated states are normative:

READY | READY_WITH_RISK | QUOTA_DEFICIT | RESERVATION_DEFICIT |
CAPACITY_UNAVAILABLE | STALE_STATE | POLICY_BLOCKED | VALIDATION_REQUIRED

Readiness combines capacity **and** quota **and** freshness: a reservation without deployable quota is READY_WITH_RISK/QUOTA_DEFICIT, never “ready” (RDY-003). State older than the configured maximum, when synchronous refresh fails, is STALE_STATE and fails safe (RDY-004, NFR-002). [Decided]

F8 — Deployment readiness state model (RDY-002)

stateDiagram-v2

```
[*] --> Evaluating
Evaluating --> READY: capacity+quota ok & fresh
Evaluating --> READY_WITH_RISK: reserved>deployable quota (policy)
Evaluating --> QUOTA_DEFICIT: consumer quota short
Evaluating --> RESERVATION_DEFICIT: reserved < required
Evaluating --> CAPACITY_UNAVAILABLE: Azure cannot supply
Evaluating --> STALE_STATE: snapshot too old & refresh failed
Evaluating --> POLICY_BLOCKED: policy/exception required
Evaluating --> VALIDATION_REQUIRED: unknown/preview behaviour
READY --> [*]
READY_WITH_RISK --> [*]
QUOTA_DEFICIT --> Evaluating: quota allocated
RESERVATION_DEFICIT --> Evaluating: capacity added
STALE_STATE --> Evaluating: refresh succeeds
```

4.4 Region selection & customer placement (PLC-001..010, REG-001..003)

- **Exact production region is the default validated input (PLC-001).** ACRME validates the supplied region against the versioned catalogue rather than deriving it from a broad geography. [Decided]
- **Geography-only selection is an exception path (PLC-002):** it requires explicit exception approval and customer acknowledgement that the derived production region becomes **fixed** (the seed) until a governed migration changes it. [Decided]
- **Seed-once, reuse-across-products (PLC-003..005):** the first valid decision writes CustomerSeedRecord; later products/environments for the

same customer/geography reuse it. Seed changes require an approved migration workflow. [Decided]

- CVAL and DR are selected after production is fixed, using current readiness, environment separation (ENV-003), restriction flags, workload distribution, quota/capacity, and freshness (PLC-006..009). [Derived]
- **CVAL/DR co-location double-count guard (PLC-010):** earmarked CVAL capacity counts toward DR headroom, never as both live CVAL and available DR. [Decided]
- **Region catalogue (REG-001..003):** versioned, configuration-driven; three-region minimum per geography is normative; region examples come from authoritative config (REG-002 — “Belgium” was corrected to **Switzerland North**). [Decided]

Region classification (functional view): Standard (auto-selectable/scored), Restricted (production-only by exception, never CVAL/DR), Cross-Geo Extension (DR-only, approved paths — Middle East → **Switzerland North**, *pre-configured but inactive pending DEC-001*), and DR_NOT_OFFERED (no cross-border substitution; **default for the Middle East** per DR-014). The DR_NOT_OFFERED flag is evaluated **before** any cross-geo extension, so an inactive extension is never auto-applied. [Decided]

F4 — Onboarding + placement flow

flowchart TD

```

Start[Placement request] --> Seed{Seed exists?}
Seed -- Yes --> Reuse[Reuse CustomerSeedRecord]
Seed -- No --> Mode{Input mode}
Mode -- Exact prod region default --> ValP[Validate production region vs catalogue]
Mode -- Geography exception --> Appr{Exception approved + acknowledged?}
Appr -- No --> PB[POLICY_BLOCKED]
Appr -- Yes --> DerP[Derive prod from Standard regions - becomes fixed seed]
ValP --> Ok{Valid, supported, fresh?}
DerP --> Ok
Ok -- No --> Reason[Readiness reason state]
Ok -- Yes --> CVAL[Select/validate CVAL - env separation]
CVAL --> DR[Select DR or DR_NOT_OFFERED]
DR --> Idx[Contribute to SourceDestinationDRIndex]
Idx --> Hold[Atomic placement hold]
Hold --> Write[Write CustomerSeedRecord]
Reuse --> Out[Return DeploymentReadinessResult]
Write --> Out

```

4.5 Disaster recovery (DR-001..019)

- **Distributed, reciprocal DR (DR-016):** each region concurrently hosts Prod, CVAL, and DR standby for multiple *different* source regions. No dedicated DR-only regions. [Decided]

- **Lean bootstrap (DR-007):** DR holds a configurable bootstrap target by workload/product/region/zone/SKU — never a fixed 30-40% clone; zero bootstrap only by explicit approved policy. [Decided]
- **max-not-sum sizing (DR-017):** each destination sizes to the largest single non-concurrent protected source portion; a SUM override covers contractual simultaneous-failure needs. [Decided]
- **Source→destination index (DR-018)** drives **source-specific standby activation in business-priority waves (DR-009, DR-019)** via staged acquisition (DR-006), reversible on failback (DR-013). [Decided]
- **Staged capacity acquisition order (DR-006):** bootstrap → destination quota/capacity → approved CVAL release → approved sharing → pooled quota → Azure request with exposed deficit. Because all environments share one governed quota pool, the emergency DR draw needs **no cross-group transfer**. [Decided]
- **DR_NOT_OFFERED (DR-014):** where sovereignty/contract forbids cross-border DR, the seed records no DR and ACRME never silently substitutes. **This is the current position for the Middle East** (DEC-001, under legal review): ME defaults to `dr_region = NOT_OFFERED`, contributes no `SourceDestinationDRIndex` entries, consumes no DR earmark, and is never a DR source or destination; ME **production may still exist without DR**. The Switzerland North extension activates only if Legal clears DEC-001. [Decided]
- **DR drills and role flip (DR-010..012):** annual drill/rotation validate the model without a real incident; destructive VM-association changes remain **blocked in Phase 1**. [Decided]

F6 — Distributed DR reference model (Section 12A)

See the rendered reference diagram (reused): `adr/diagrams/acrme_three_region_capacity_model.png` — each region hosts Prod + CVAL + DR standby tagged with its `src Rn` source region; each destination sizes by max-not-sum.

F7 — DR event → standby activation waves

sequenceDiagram

```

participant DRC as DR coordinator
participant ENG as ACRME engine
participant IDX as SourceDestinationDRIndex
participant POOL as Single governed quota pool
participant AZ as Azure
DRC->>ENG: Declare source-region failure (authorised)
ENG->>ENG: engine_mode = DR_EVENT_ACTIVE
ENG->>IDX: Read standby sets for failed source
IDX-->>ENG: Customers + priority waves
loop each priority wave
```

```

    ENG->>POOL: Draw pool headroom then reclaimable NonProd
    POOL-->>ENG: Capacity earmark released
    ENG->>AZ: Acquire deficit if any (exposed)
    ENG->>ENG: standby -> allocated/active
    ENG->>DRC: Wave complete + audit checkpoint
end
DRC->>ENG: Failback authorised
ENG->>ENG: FAILBACK_PENDING -> STEADY_STATE (reversible)

```

4.6 Cost & FinOps (FIN-001..008)

- Idle reservation cost is surfaced and alerted (FIN-001, FIN-002); lean DR + max-not-sum minimises idle standby cost (FIN-003). [Decided]
- Cost-before-expansion: increases carry cost exposure and justification (FIN-004, FIN-005). [Decided]
- Shared-DR **overcommit accounting** exposes `Overcommit_Ratio` per destination so the savings of distributed DR are visible and bounded by a safety ceiling (FIN-006..008, POC-011). [Derived]

4.7 Provisioning & AEP integration (INT-001..007)

- ACRME exposes a functional contract: input (customer, exact region, SKU/family, environment, product, intended demand) → output (`DeploymentReadinessResult` + reason + operation handle) (INT-001..003). [Decided]
- All mutating calls are **idempotent** with operation handles and expected-state versions; AEP polls rather than assuming synchronous completion (INT-004..006, NFR-007). [Decided]
- AEP never treats provider quota as proof of consumer deployability (INT-007, POC-001). [Assumed]

4.8 Observability, governance & operations (OBS, GOV, OPS)

- **Observability (OBS-001..005)**: metrics/alerts for buffer deficit, per-destination DR max-source coverage and gap, source destination mapping dashboard, activation state by wave, idle cost, staleness. [Decided]
- **Governance (GOV-001..009)**: RBAC, managed identity, approval gates, break-glass, immutable audit of every decision and mutation with before/after values and correlation IDs; versioned scope files with decision traceability (DAT-005). [Decided]
- **Operations (OPS-001..005)**: runbooks for DR declaration, standby activation, CVAL release, quota allocation, sharing activation, emergency override, regional recovery, and failback. [Decided]

5. End-to-End Functional Flows

1. **Onboarding + placement** (F4): exact-region validation (or geography exception) → CVAL/DR selection → seed write → readiness.
2. **Steady-state reconciliation** (F5): every ~6 min, compare **Allocated + Buffer** to reserved; scale up (or alert deficit), guarded scale-down, never delete.
3. **Single-region DR event** (F7): declare → index lookup → priority-wave activation from the shared pool → audited failback.
4. **DR drill / failback**: scheduled role-flip validating the index, waves, and reversibility without a real incident.

F5 — Steady-state reconciliation behaviour

flowchart TD

```
Tick[Reconciliation tick ~6 min] --> Read[Read scope, reservation, allocated, associated]
Read --> Fresh{State fresh?}
Fresh -- No --> Stale[STALE_STATE + refresh]
Fresh -- Yes --> Cmp{reserved vs Allocated+Buffer}
Cmp -- below --> Up[Attempt scale-up]
Up --> Sup{Azure supplies?}
Sup -- No --> Def[Hold safe state + expose buffer deficit alert]
Sup -- Yes --> Ok[Confirm + snapshot]
Cmp -- above --> Guard[Scale-down guards: hold interval, DR earmark, CVAL earmark, maintain]
Guard --> Down[Reduce toward target - never below Allocated+Buffer, never delete]
Down --> Ok
Cmp -- equal --> Ok
```

6. Functional States and Data (functional view)

Engine mode machine (functional view, DR-004..008, NFR-002):

STEADY_STATE → DR_DECLARATION_PENDING → DR_EVENT_ACTIVE → FAILBACK_PENDING → STEADY_STATE
INCIDENT_HOLD (safe degraded)

Entering DR_EVENT_ACTIVE does not auto-authorise service-impacting CVAL action; each action keeps its own policy gate.

Functional data entities (DAT-001..006): CustomerSeedRecord (PLC-003), SourceDestinationDRIndex (DR-018), CVALEarmarkRecord (PLC-010), PlacementPolicy (versioned catalogue), reservation/quota snapshots with freshness metadata, and the immutable decision/audit log. Full technical schema is in the TDD Section 6.

7. Acceptance Criteria Mapping (baseline Section 20)

Acceptance theme	Functional evidence	Section
Deployment allowed only when capacity+quota+freshness pass	Readiness states, fail-safe on stale	Section 4.3, F8
Exact-region-first onboarding, seed reuse	Placement flow, seed record	Section 4.4, F4
Lean, distributed, max-not-sum DR with source-specific activation	DR capabilities, activation waves	Section 4.5, F6, F7
Single governed quota pool with Prod protection	Quota capability, earmarks	Section 4.2
No silent deletion / no cross-border DR substitution	Zero-capacity, DR_NOT_OFFERED	Section 4.1, Section 4.5
Full auditability of decisions and mutations	Governance	Section 4.8

8. Assumptions, Decisions, POC Dependencies (baseline Section 22–Section 24)

Ref	Item	Functional impact
POC-001	Consumer quota under shared reservation	Readiness must validate consumer quota until proven.
POC-006/007	DR topology & bootstrap sizing	Confirms distributed model and lean targets.
POC-011	max-not-sum overcommit safety	Sets overcommit safety ceiling / alert.

Ref	Item	Functional impact
DEC-001	Middle East DR policy	Current position: DR_NOT_OFFERED (DR is NOT offered in the Middle East) due to data-sovereignty/residency; under legal review. Governs whether the pre-configured Switzerland North extension ever activates. Until legal approval, ME defaults to dr_region = NOT_OFFERED .
DEC-002	Failback duration	~1-year run vs ~30-day failback.
DEC-003	Geography exception approver	Governs the PLC-002 exception path.
DEP-001	Quota Group / groupType maturity	Single-pool enforcement depends on feature maturity.

9. Requirement Traceability Matrix (Baseline v2.2 → FDD)

Requirement group (IDs)	FDD section(s)
REG-001..003	Section 4.4 (catalogue, three-region min, Switzerland North)
ENV-001..007	Section 4.4 (env separation), Section 4.5 (roles)
CAP-001..019	Section 4.1, Section 5(2), F5
QUA-001..014	Section 4.2
RDY-001..004	Section 4.3, F8
PLC-001..010	Section 4.4, F4
DR-001..019	Section 4.5, F6, F7, Section 6
FIN-001..008	Section 4.6
INT-001..007	Section 4.7, F1
DAT-001..006	Section 6
OBS-001..005	Section 4.8

Requirement group (IDs)	FDD section(s)
GOV-001..009	Section 4.8, Section 7
NFR-001..010	Section 4.3 (fail-safe), Section 4.7 (idempotency), Section 5, Section 6
OPS-001..005	Section 4.8, Section 5
POC-001..011 / DEC-001..003 / DEP-001	Section 8

Every Baseline v2.2 requirement ID resolves to at least one FDD section above. Detailed component/algorithm-level traceability is completed in the TDD Section 17.

Document Status: Draft for review · **Next:** ratify alongside the TDD; supersede the Executive Design Document (archived).