

GE23131-Programming Using C-2024

Quiz navigation

- 1
- 2
- 3

Show one page at a time

Finish review

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Monday, 25 November 2024, 7:35 PM
Duration	27 days 21 hours

Question **1**

Correct

Marked out of 3.00

 [Flag question](#)

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.
The lines after that contain a different values for size of the chessboard

Output format:

Print a chessboard of dimensions size * size. Print a Print W for white spaces and B for black spaces.

Input:

- 2
- 3
- 5

Output:

- WBW
- BWB
- WBW
- WBWBW
- BWBWB
- WBWBW
- BWBWB
- WBWBW

Answer: (penalty regime: 0 %)

```
4   int n;
5   scanf("%d",&n);
6   while(n--){
7       int i;
8       scanf("%d",&i);
9       for(int j=1;j<=i;j++){
10          if(j%2!=0){
11              int c=1;
12              char a = 'W';
13              while(c<=i){
14                  printf("%c",a);
15                  a=(a=='W')?'B':'W';
16                  c++;
17              }
18              printf("\n");
19          }
20          else{
21              char z='B';
22              int m=1;
23              while(m<=i){
24                  printf("%c",z);
25                  z=(z=='W')?'B':'W';
26                  m++;
27              }
28              printf("\n");
29          }
30      }
31  }
32  }
33 }
```

	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBW	WBWBW	

Passed all tests! ✓

Question **2**
Correct
Marked out of 5.00
[Flag question](#)

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases
Each test case contains an integer N and also the starting character of the chessboard

Print the chessboard as per the given examples

Sample Input / Output

Input:

2
2 W
3 B

Output:

WB
BW
BWB
WBW
BWB

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2
3 int main(){
4     int n;
5     scanf("%d",&n);
6     while(n--){
7         int i;
8         char ch;
9         scanf("%d %c",&i,&ch);
10        for(int j=1;j<=i;j++){
11            if(ch == 'W'){
12                char a='W';
13                int c =1;
14                while(c<=i){
15                    printf("%c",a);
16                    a=(a=='W')?'B':'W';
17                    c++;
18                }
19                ch=(ch=='W')?'B':'W';
20                printf("\n");
21            }
22            else{
23                char z='B';
24                int m=1;
25                while(m<=i){
26                    printf("%c",z);
27                    z=(z=='W')?'B':'W';
28                    m++;
29                }
30            }
31        }
32    }
```

```
33 | ..... }
34 |   }
35 | }
```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! ✓

Question **3**

Correct

Marked out of 7.00

 [Flag question](#)

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be :

```
10203010011012
**4050809
****607
```

If N= 4, then pattern will be:

```
1020304017018019020
**50607014015016
****809012013
*****10011
```

Constraints

2 <= N <= 100

Input Format

First line contains T, the number of test cases

Output

First line print Case #i where i is the test case number
In the subsequent line, print the pattern

Test Case 1

3
3
4
5

Output

Case #1
10203010011012
**4050809
****607
Case #2
1020304017018019020
**50607014015016
****809012013
*****10011
Case #3
102030405026027028029030
**6070809022023024025
****10011012019020021
*****13014017018
*****15016

Answer: (penalty regime: 0 %)

```
1 | #include <stdio.h>
2 |
3 | int main(){
4 |     int n,v,p3,c,in,i,i1,i2,t,ti;
5 |     scanf("%d",&t);
6 |     for(ti=0;ti<t;ti++){
7 |         v=0;
8 |         scanf("%d",&n);
9 |         printf("Case #%d\n",ti+1);
10 |        for(i=0;i<n;i++){
11 |            c=0;
```

```
15
16
17     }
18     for(i1=i;i1<n;i1++){
19         if(i>0) c++;
20         printf("%d0",++v);
21     }
22     if(i==0){
23         p3=v+(v*(v-1))+1;
24         in=p3;
25     }
26     in=in-c;
27     p3=in;
28     for(i2=i;i2<n;i2++){
29         printf("%d",p3++);
30         if(i2!=n-1) printf("0");
31     }printf("\n");
32 }
33
34 }
35 }
```

	Input	Expected	Got	
✓	3	Case #1	Case #1	✓
	3	10203010011012	10203010011012	
	4	**4050809	**4050809	
	5	****607	****607	
		Case #2	Case #2	
		1020304017018019020	1020304017018019020	
		**50607014015016	**50607014015016	
		****809012013	****809012013	
		*****10011	*****10011	
		Case #3	Case #3	
		102030405026027028029030	102030405026027028029030	
		**6070809022023024025	**6070809022023024025	
		***10011012019020021	***10011012019020021	
		*****13014017018	*****13014017018	
		*****15016	*****15016	

Passed all tests! ✓