

MODEL NAME

12K 3 STAR INV INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



3 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	12K 3 STAR INV
Chassis Type	-	830-17"
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	3400
Rated ISEER, (Watt)	W	4.35
COMPRESSOR		
Type	-	Rotary
Brand	-	Highly
INDOOR FAN MOTOR		
Type	-	DC
Brand	-	Nidec / Kryon / Picl
Power Input	watts	35W
Capacitor	uF	NA
Motor Speed	RPM	1280
EVAPORATOR		
a. Number of Rows	-	2
b. Tube Pitch (a) x Row	mm	21x12.7
c. Fin Material Type	-	Slit
d. Tube Outside Dia.	mm	7mm and IGT
e. Coil Length x Height	mm	620x25.4x378
INDOOR UNIT		
Fan Indoor Fan Diameter	mm	107x610
Indoor Air Flow	m3/h	850
Unit Dimension (W*D*H)	mm	830x235x315
Packing (W*D*H)	mm	920X365X300
INDOOR FAN		
Brand	-	Nidec / Kryon / Picl
Output Power	-	33W
Motor Speed	-	900
Diameter	mm	380
No. of Blade	-	3
CONDENSER		
a. Numbor of Rows	-	1
c. Tube Outside Dia. and Type	-	5mm and IGT
d. Coil Length x Height	mm	670x11.52x429
Expansion Type	-	Capillary
Unit Dimension (W*H*D)	mm	700x300x480
Packing (W*H*D)	mm	770x360x520
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant Type	-	R32
REFRIGERANT PIPE		
Liquid Side (SVC)	mm	6.35
Gas Side (SVC)	mm	9.52



MODEL NAME

17K 3 STAR INV

INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



3 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	17K 3 STAR INV
Chassis Type	-	930-20"
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	4800
Rated ISEER, (Watt)	W	4.35
COMPRESSOR		
Type	-	Rotary
Brand	-	Highly
INDOOR FAN MOTOR		
Type	-	DC
Brand	-	Nidec /Kryon/Picl
Power Input	watts	35W
Capacitor	uF	NA
Motor speed	RPM	1280
EVAPORATOR		
a. Number of rows	-	2
b. Tube pitch(a) x row	mm	21x12.7
c. Fin material Type	-	Slit
d. Tube outside dia.	mm	7mm and IGT
e. Coil length x heigh	mm	725x25.4x378
INDOOR UNIT		
Fan Indoor fan Diamete	mm	107x710
Indoor air flow	m3/h	1000
Unit dimension (W*D*H)	mm	930x315x235
Packing (W*D*H)	mm	1020X365X300
INDOOR FAN		
Brand	-	Nidec /Kryon/Picl
output power	-	45W
Motor speed	-	900
Diameter	mm	445
No. of Blade	-	3
CONDENSER		
a. Number of rows	-	1
c. Tube outside dia.and type	-	5mm and IGT
d. Coil length x heig	mm	805x11.52x507
Expansion Type	-	Capillary
Unit dimension (W*H*D)	mm	840X300X560
Packing (W*H*D)	mm	920X355X605
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant type	-	R32
REFRIGERANT PIPE		
Liquid side (SVC)	mm	6.35
Gas side (SVC)	mm	12.7



MODEL NAME

17K 5 STAR INV

INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



5 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	17K 5 STAR INV
Chassis Type	-	930-22"
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	4800
Rated ISEER, (Watt)	W	5.65
COMPRESSOR		
Type	-	Rotary
Brand	-	Highly
INDOOR FAN MOTOR		
Type	-	DC
Brand	-	Nidec / Kryon/Picl
Power Input	watts	35W
Capacitor	uF	NA
Motor Speed	RPM	1280
EVAPORATOR		
a. Number of Rows	-	2
b. Tube Pitch (a) x Row	mm	21x12.7
c. Fin Material Type	-	Slit
d. Tube Outside Dia.	mm	7mm and IGT
e. Coil Length x Height	mm	725x25.4x378
INDOOR UNIT		
Fan Indoor Fan Diameter	mm	107x710
Indoor Air Flow	m3/h	1000
Unit Dimension (W*D*H)	mm	930x315x235
Packing (W*D*H)	mm	1020X365X300
INDOOR FAN		
Brand	-	Nidec / Kryon/Picl
Output Power	-	45W
Motor Speed	-	900
Diameter	mm	445
No. of Blade	-	3
CONDENSER		
a. Number of Rows	-	2
c. Tube Outside Dia. and Type	-	5mm and IGT
d. Coil Length x Height	mm	805x23.04x546
Expansion Type	-	EEV
Unit Dimension (W*H*D)	mm	900X360X600
Packing (W*H*D)	mm	980X415X645
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant Type	-	R32
REFRIGERANT PIPE		
Liquid Side (SVC)	mm	6.35
Gas Side (SVC)	mm	12.7



MODEL NAME

18K 3 STAR INV

INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



3 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	18K 3 STAR INV
Chassis Type	-	930-20"
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	5100
Rated ISEER, (Watt)	W	4.35
COMPRESSOR		
Type	-	Rotary
Brand	-	Highly
INDOOR FAN MOTOR		
Type	-	DC
Brand	-	Nidec /Kryon/Picl
Power Input	watts	35W
Capacitor	uF	NA
Motor Speed	RPM	1280
EVAPORATOR		
a. Number of Rows	-	2
b. Tube Pitch (a) x Row	mm	21x12.7
c. Fin Material Type	-	Slit
d. Tube Outside Dia.	mm	7mm and IGT
e. Coil Length x Height	mm	725x25.4x378
INDOOR UNIT		
Fan Indoor Fan Diameter	mm	107x710
Indoor Air Flow	m3/h	1000
Unit Dimension (W*D*H)	mm	930x315x235
Packing (W*D*H)	mm	1020X365X300
INDOOR FAN		
Brand	-	Nidec /Kryon/Picl
Output Power	-	45W
Motor Speed	-	900
Diameter	mm	445
No. of Blade	-	3
CONDENSER		
a. Number of Rows	-	1
c. Tube Outside Dia. and Type	-	5mm and IGT
d. Coil Length x Height	mm	805x11.52x507
Expansion Type	-	Capillary
Unit Dimension (W*H*D)	mm	840X300X560
Packing (W*H*D)	mm	920X355X605
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant Type	-	R32
REFRIGERANT PIPE		
Liquid Side (SVC)	mm	6.35
Gas Side (SVC)	mm	12.7



MODEL NAME

18K 5 STAR INV

INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



5 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	18K 5 STAR INV
Chassis Type	-	1100-22"
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	5100
Rated ISEER, (Watt)	W	5.65
COMPRESSOR		
Type	-	Rotary
Brand	-	Highly
INDOOR FAN MOTOR		
Type	-	DC
Brand	-	Nidec /Kryon/Picl
Power Input	watts	57W
Capacitor	uF	NA
Motor Speed	RPM	1350
EVAPORATOR		
a. Number of Rows	-	2
b. Tube Pitch (a) x Row	mm	21x12.7
c. Fin Material Type	-	Slit
d. Tube Outside Dia.	mm	7mm and IGT
e. Coil Length x Height	mm	887x25.4x378
INDOOR UNIT		
Fan Indoor Fan Diameter	mm	107x875
Indoor Air Flow	m3/h	1100
Unit Dimension (W*D*H)	mm	1100x315x235
Packing (W*D*H)	mm	1190X365X300
INDOOR FAN		
Brand	-	Nidec /Kryon/Picl
Output Power	-	45W
Motor Speed	-	900
Diameter	mm	445
No. of Blade	-	3
CONDENSER		
a. Number of Rows	-	2
c. Tube Outside Dia. and Type	-	5mm and IGT
d. Coil Length x Height	mm	805x23.04x546
Expansion Type	-	EEV
Unit Dimension (W*H*D)	mm	900X360X600
Packing (W*H*D)	mm	980X415X645
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant Type	-	R32
REFRIGERANT PIPE		
Liquid Side (SVC)	mm	6.35
Gas Side (SVC)	mm	12.7



MODEL NAME

22K 3 STAR INV

INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



3 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	22K 3 STAR INV
Chassis Type	-	1100-22"
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	6300
Rated ISEER, (Watt)	W	4.35
COMPRESSOR		
Type	-	Rotary
Brand	-	Highly
INDOOR FAN MOTOR		
Type	-	DC
Brand	-	Nidec /Kryon/Picl
Power Input	watts	57W
Capacitor	uF	NA
Motor speed	RPM	1350
EVAPORATOR		
a. Number of rows	-	2
b. Tube pitch(a) x row	mm	21x12.7
c. Fin material Type	-	Slit
d. Tube outside dia.	mm	7mm and IGT
e. Coil length x height	mm	887x25.4x378
INDOOR UNIT		
Fan Indoor Fan Diameter	mm	107x875
Indoor Air Flow	m3/h	1100
Unit Dimension (W*D*H)	mm	1100x315x235
Packing (W*D*H)	mm	1190X365X300
INDOOR FAN		
Brand	-	Nidec /Kryon/Picl
Output Power	-	45W
Motor Speed	-	900
Diameter	mm	445
No. of Blade	-	3
CONDENSER		
a. Number of Rows	-	2
c. Tube Outside Dia. and Type	-	5mm and IGT
d. Coil Length x Height	mm	805x23.04x546
Expansion Type	-	Capillary
Unit Dimension (W*H*D)	mm	900X360X600
Packing (W*H*D)	mm	980X415X645
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant Type	-	R32
REFRIGERANT PIPE		
Liquid Side (SVC)	mm	6.35
Gas Side (SVC)	mm	15.88



Plot No. 16, Ecotech III, Greater Noida,
Tusyana, Uttar Pradesh - 201318

MODEL NAME

18K 3 STAR INV WINDOW INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



3 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	18K 3 STAR INV WINDOW
Chassis Type	-	Window
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	4800
Rated ISEER, (Watt)	W	3.35
INDOOR FAN MOTOR		
Type	-	AC
Brand	-	MERATHAN / PICL
Power Input	watts	110W
Capacitor	uF	2.5
Motor Speed	RPM	1300
EVAPORATOR		
a. Number of Rows	-	2
b. Tube Pitch (a) x Row	mm	21x12.7
c. Fin Material Type	-	Slit
d. Tube Outside Dia.	mm	7mm and IG1
e. Coil Length x Height	mm	887x25.4x378
INDOOR UNIT		
Fan Indoor Fan Diameter	mm	107x560
Indoor Air Flow	m3/h	900
Unit Dimension (W*D*H)	mm	660x690x428
Packing (W*D*H)	mm	780X790X500
INDOOR FAN		
Brand	-	Nidec /Kryon/Picl
Output Power	-	45W
Motor Speed	-	1050
Diameter	mm	390
No. of Blade	-	3
CONDENSER		
a. Number of Rows	-	1
c. Tube Outside Dia. and Type	-	5mm and IGT
d. Coil Length x Height	mm	718x17.46x480
Expansion Type	-	Capillary
Unit Dimension (W*H*D)	mm	660X420X780
Packing (W*H*D)	mm	780X490X890
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant Type	-	R32
REFRIGERANT PIPE		
Liquid Side (SVC)	mm	NA
Gas Side (SVC)	mm	NA



Plot No. 16, Ecotech III, Greater Noida,
Tusyana, Uttar Pradesh - 201318

MODEL NAME

22K 5 STAR INV WINDOW INVERTER



KEY FEATURES



R32
REFRIGERANT



ENERGY
EFFICIENT



ROTARY
COMPRESSOR



POWERFUL
COOLING



INVERTER
TECHNOLOGY



5 STAR
RATED



LOW NOISE
OPERATION



RELIABLE
PERFORMANCE

PARAMETER	UNIT	22K 5 STAR INV WINDOW
Chassis Type	-	Window
Type	-	Inverter
Cooling Capacity, (Watt) (Min, Full, Max)	W	6100
Rated ISEER, (Watt)	W	5.20
INDOOR FAN MOTOR		
Type	-	AC
Brand	-	MERATHAN / PICL
Power Input	watts	160W
Capacitor	uF	3.5
Motor Speed	RPM	1300
EVAPORATOR		
a. Number of Rows	-	2
b. Tube Pitch (a) x Row	mm	21x12.7
c. Fin Material Type	-	Slit
d. Tube Outside Dia.	mm	7mm and IG1
e. Coil Length x Height	mm	887x25.4x378
INDOOR UNIT		
Fan Indoor Fan Diameter	mm	107x560
Indoor Air Flow	m3/h	1100
Unit Dimension (W*D*H)	mm	660x690x428
Packing (W*D*H)	mm	780X790X500
INDOOR FAN		
Brand	-	Nidec /Kryon/Picl
Output Power	-	45W
Motor Speed	-	1050
Diameter	mm	390
No. of Blade	-	3
CONDENSER		
a. Number of Rows	-	1
c. Tube Outside Dia. and Type	-	5mm and IGT
d. Coil Length x Height	mm	718x17.46x480
Expansion Type	-	Capillary
Unit Dimension (W*H*D)	mm	660X420X780
Packing (W*H*D)	mm	780X490X890
Connecting Wire	-	NA
Installation Kit	-	Y
Refrigerant Type	-	R32
REFRIGERANT PIPE		
Liquid Side (SVC)	mm	6.35
Gas Side (SVC)	mm	12.7

