

WORK ORDER

Customer :	Test Customer	Input Info:	6/26/2026
Reference :	test 1400x2000	SupplyAndFit	
Job No :	90	Page 1	Print Info: 6/26/2026

Main Options	
Colour (External)	White [SP]
Colour (Internal)	White [SP]
Frame (Standard) (Top)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Bottom)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Left)	SPQ-6-11252 68mm 6 Chamber
Frame (Standard) (Right)	SPQ-6-11252 68mm 6 Chamber
Transom	SPQ-5-30252 78mm
Mullion	SPQ-5-30252 78mm
Joint (Structural T/Z) (Transom)	Welded (Standard)
Joint (Structural T/Z) (Mullion)	Welded (Standard)
Bead	28mm
Sash Type	Door right hung
Cylinder	Brass Cylinder
Handle (Door)	White Handle Lever/Lever (Short Backplate)
Hinge (Door)	Flag Hinge
Hinge Colour (Door)	White Flag Hinge
Hinge Position (Door)	3 Hinges
Lock (Door) (Single Door)	Standard Door Lock
Glazing Method	Glazed
Glass Type	4-20-4 Clear Tuff Low E
Glass Gas Fill	Argon
Opening Direction	Open In
Component Type	Glass
Drainage	Concealed Drainage
Location	Please Specify
Horizontal Split Position	Equal Split
Vertical Split Position	By Dimensions



Sections Required:			Qty	Length	End Prep	Reinforcing	Length
Hor	Bead	28mm Bead	6	633	[-]		
Vert	Bead	28mm Bead	4	333	[-]		
Vert	Bead	28mm Bead	2	1533	[-]		
Hor	Bead	28mm Bead	2	479	[-]		
Vert	Bead	28mm Bead	2	1379	[-]		
Hor	Frame	Frame 6 Chamber	2	1400	\ - /		
Vert	Frame	Frame 6 Chamber	2	2000	\ - /		
Hor	Frame	T Transom/Mullion	1	2020	< - >	26 x 26 U Steel Reinforcement	1864
Hor	Frame	T Transom/Mullion	2	749	< - >		
Hor	Sash	Door Sash Z	2	649	\ - /	28 x 44.5 U Steel Reinforcement	439
Vert	Sash	Door Sash Z	2	1549	\ - /	28 x 44.5 U Steel Reinforcement	339
Hor	Sash	28 x 44.5 U Steel Reinforcement	2	439	[-]		
Vert	Sash	28 x 44.5 U Steel Reinforcement	2	1339	[-]		

Accessories Required:	Qty	Unit Of Measurement
Run Up Block	1	Unit
Gasket 02	11752	Metres
Glazing Bridge Packer	23	Unit
Gasket 01	8792	Metres
White Handle Lever/Lever (Short Backplate)	1	Unit
Flag Hinge White	3	Unit
R/H Keep Set	1	Unit
Standard Door Lock	1	Unit
Brass Cylinder	1	Unit

Glass Required:	Qty	Width	Length
01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	623	323

WORK ORDER

Customer :	Test Customer		Input Info:	6/26/2026
Reference :	test 1400x2000	SupplyAndFit		
Job No :	90	Page 2	Print Info:	6/26/2026

Glass Required:	Qty	Width	Length
02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	469	1369
03 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	623	323
04 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar	1	623	1523