

# WORK ORDER

|            |                       |              |                       |
|------------|-----------------------|--------------|-----------------------|
| Customer:  | Test Customer         | Input Info:  | 7/30/2026             |
| Reference: | sunnyplast order test | SupplyAndFit |                       |
| Job No:    | 169                   | Page 1       | Print Info: 7/30/2026 |

| Main Options                      |                                            |
|-----------------------------------|--------------------------------------------|
| Colour (External)                 | White [SP]                                 |
| Colour (Internal)                 | White [SP]                                 |
| Frame (Standard) (Top)            | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Bottom)         | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Left)           | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Right)          | SPQ-6-11252 68mm 6 Chamber                 |
| Transom                           | SPQ-5-30252 78mm                           |
| Add-on (Top)                      | SPQ-2-75252 25mm                           |
| Joint (Structural T/Z) (Transo... | Welded (Standard)                          |
| Bead                              | 28mm                                       |
| Sash Type                         | Door left hung                             |
| Cylinder                          | Brass Cylinder                             |
| Handle (Door)                     | White Handle Lever/Lever (Short Backplate) |
| Hinge (Door)                      | Flag Hinge                                 |
| Hinge Colour (Door)               | White Flag Hinge                           |
| Hinge Position (Door)             | 3 Hinges                                   |
| Lock (Door) (Single Door)         | Standard Door Lock                         |
| Glazing Method                    | Glazed                                     |
| Glass Type                        | 4-20-4 Clear Tuff Low E                    |
| Glass Gas Fill                    | Argon                                      |
| Opening Direction                 | Open In                                    |
| Component Type                    | Glass                                      |
| Drainage                          | Concealed Drainage                         |
| Location                          | Please Specify                             |
| Vertical Split Position           | By Dimensions                              |



| Sections Required: |       |                   | Qty | Length | End Prep | Reinforcing                     | Length |
|--------------------|-------|-------------------|-----|--------|----------|---------------------------------|--------|
| Hor                | Bead  | 28mm Bead         | 4   | 750    | [ - ]    |                                 |        |
| Vert               | Bead  | 28mm Bead         | 2   | 1456   | [ - ]    |                                 |        |
| Vert               | Bead  | 28mm Bead         | 2   | 231    | [ - ]    |                                 |        |
| Hor                | Frame | Frame 6 Chamber   | 2   | 1005   | \ - /    |                                 |        |
| Vert               | Frame | Frame 6 Chamber   | 2   | 1980   | \ - /    |                                 |        |
| Hor                | Sash  | Door Sash Z       | 2   | 925    | \ - /    | 28 x 44.5 U Steel Reinforcement | 710    |
| Vert               | Sash  | Door Sash Z       | 2   | 1900   | \ - /    | 28 x 44.5 U Steel Reinforcement | 1685   |
| ?                  | Sash  | T Transom/Mullion | 1   | 871    | < - >    |                                 |        |

| Accessories Required:                      | Qty   | Unit Of Measurement |
|--------------------------------------------|-------|---------------------|
| Run Up Block                               | 1     | Unit                |
| Gasket 01                                  | 11.26 | Metres              |
| White Handle Lever/Lever (Short Backplate) | 1     | Unit                |
| Flag Hinge White                           | 3     | Unit                |
| L/H Keep Set                               | 1     | Unit                |
| Standard Door Lock                         | 1     | Unit                |
| Brass Cylinder                             | 1     | Unit                |
| Gasket 02                                  | 6.294 | Metres              |
| Glazing Bridge Packer                      | 16    | Unit                |

| Glass Required:                                            | Qty | Width | Length |
|------------------------------------------------------------|-----|-------|--------|
| 01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 740   | 221    |
| 02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 740   | 1446   |

# WORK ORDER

|            |                       |              |                       |
|------------|-----------------------|--------------|-----------------------|
| Customer:  | Test Customer         | Input Info:  | 7/30/2026             |
| Reference: | sunnyplast order test | SupplyAndFit |                       |
| Job No:    | 169                   | Page 2       | Print Info: 7/30/2026 |

| Main Options                      |                                            |
|-----------------------------------|--------------------------------------------|
| Colour (External)                 | White [SP]                                 |
| Colour (Internal)                 | White [SP]                                 |
| Frame (Standard) (Top)            | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Bottom)         | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Left)           | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Right)          | SPQ-6-11252 68mm 6 Chamber                 |
| Transom                           | SPQ-5-30252 78mm                           |
| Add-on (Bottom)                   | SPQ-2-75252 25mm                           |
| Joint (Structural T/Z) (Transo... | Welded (Standard)                          |
| Bead                              | 28mm                                       |
| Sash Type                         | Door left hung                             |
| Cylinder                          | Brass Cylinder                             |
| Handle (Door)                     | White Handle Lever/Lever (Short Backplate) |
| Hinge (Door)                      | Flag Hinge                                 |
| Hinge Colour (Door)               | White Flag Hinge                           |
| Hinge Position (Door)             | 3 Hinges                                   |
| Lock (Door) (Single Door)         | Standard Door Lock                         |
| Glazing Method                    | Glazed                                     |
| Glass Type                        | 4-20-4 Clear Tuff Low E                    |
| Glass Gas Fill                    | Argon                                      |
| Opening Direction                 | Open In                                    |
| Component Type                    | Glass                                      |
| Drainage                          | Concealed Drainage                         |
| Location                          | Please Specify                             |
| Vertical Split Position           | By Dimensions                              |



| Sections Required: |       |                   | Qty | Length | End Prep | Reinforcing                     | Length |
|--------------------|-------|-------------------|-----|--------|----------|---------------------------------|--------|
| Hor                | Bead  | 28mm Bead         | 4   | 750    | [ - ]    |                                 |        |
| Vert               | Bead  | 28mm Bead         | 2   | 831    | [ - ]    |                                 |        |
| Vert               | Bead  | 28mm Bead         | 2   | 856    | [ - ]    |                                 |        |
| Hor                | Frame | Frame 6 Chamber   | 2   | 1005   | \ - /    |                                 |        |
| Vert               | Frame | Frame 6 Chamber   | 2   | 1980   | \ - /    |                                 |        |
| Hor                | Sash  | Door Sash Z       | 2   | 925    | \ - /    | 28 x 44.5 U Steel Reinforcement | 710    |
| Vert               | Sash  | Door Sash Z       | 2   | 1900   | \ - /    | 28 x 44.5 U Steel Reinforcement | 1685   |
| ?                  | Sash  | T Transom/Mullion | 1   | 871    | < - >    |                                 |        |

| Accessories Required:                      | Qty   | Unit Of Measurement |
|--------------------------------------------|-------|---------------------|
| Run Up Block                               | 1     | Unit                |
| Gasket 01                                  | 11.26 | Metres              |
| White Handle Lever/Lever (Short Backplate) | 1     | Unit                |
| Flag Hinge White                           | 3     | Unit                |
| L/H Keep Set                               | 1     | Unit                |
| Standard Door Lock                         | 1     | Unit                |
| Brass Cylinder                             | 1     | Unit                |
| Gasket 02                                  | 6.294 | Metres              |
| Glazing Bridge Packer                      | 16    | Unit                |

| Glass Required:                                            | Qty | Width | Length |
|------------------------------------------------------------|-----|-------|--------|
| 01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 740   | 846    |
| 02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 740   | 821    |

# WORK ORDER

|            |                       |              |                       |
|------------|-----------------------|--------------|-----------------------|
| Customer:  | Test Customer         | Input Info:  | 7/30/2026             |
| Reference: | sunnyplast order test | SupplyAndFit |                       |
| Job No:    | 169                   | Page 3       | Print Info: 7/30/2026 |

| Main Options                     |                                            |
|----------------------------------|--------------------------------------------|
| Colour (External)                | White [SP]                                 |
| Colour (Internal)                | White [SP]                                 |
| Frame (Standard) (Top)           | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Bottom)        | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Left)          | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Right)         | SPQ-6-11252 68mm 6 Chamber                 |
| Mullion                          | SPQ-5-30252 78mm                           |
| Add-on (Left)                    | SPQ-2-75252 25mm                           |
| Joint (Structural T/Z) (Mullion) | Welded (Standard)                          |
| Bead                             | 28mm                                       |
| Sash Type                        | Door left hung                             |
| Cylinder                         | Brass Cylinder                             |
| Handle (Door)                    | White Handle Lever/Lever (Short Backplate) |
| Hinge (Door)                     | Flag Hinge                                 |
| Hinge Colour (Door)              | White Flag Hinge                           |
| Hinge Position (Door)            | 3 Hinges                                   |
| Lock (Door) (Single Door)        | Standard Door Lock                         |
| Glazing Method                   | Glazed                                     |
| Glass Type                       | 4-20-4 Clear Tuff Low E                    |
| Glass Gas Fill                   | Argon                                      |
| Opening Direction                | Open In                                    |
| Component Type                   | Glass                                      |
| Drainage                         | Concealed Drainage                         |
| Location                         | Please Specify                             |
| Horizontal Split Position        | By Dimensions                              |



| Sections Required: |       |                   | Qty | Length | End Prep | Reinforcing                     | Length |
|--------------------|-------|-------------------|-----|--------|----------|---------------------------------|--------|
| Vert               | Bead  | 28mm Bead         | 4   | 1750   | [ - ]    |                                 |        |
| Hor                | Bead  | 28mm Bead         | 2   | 356    | [ - ]    |                                 |        |
| Hor                | Bead  | 28mm Bead         | 2   | 331    | [ - ]    |                                 |        |
| Hor                | Frame | Frame 6 Chamber   | 2   | 980    | \ - /    |                                 |        |
| Vert               | Frame | Frame 6 Chamber   | 2   | 2005   | \ - /    |                                 |        |
| Hor                | Sash  | Door Sash Z       | 2   | 900    | \ - /    | 28 x 44.5 U Steel Reinforcement | 685    |
| Vert               | Sash  | Door Sash Z       | 2   | 1925   | \ - /    | 28 x 44.5 U Steel Reinforcement | 1710   |
| ?                  | Sash  | T Transom/Mullion | 1   | 1871   | < - >    | 26 x 26 U Steel Reinforcement   | 1710   |

| Accessories Required:                      | Qty       | Unit Of Measurement |
|--------------------------------------------|-----------|---------------------|
| Run Up Block                               | 1         | Unit                |
| Gasket 01                                  | 15.099999 | Metres              |
| White Handle Lever/Lever (Short Backplate) | 1         | Unit                |
| Flag Hinge White                           | 3         | Unit                |
| L/H Keep Set                               | 1         | Unit                |
| Standard Door Lock                         | 1         | Unit                |
| Brass Cylinder                             | 1         | Unit                |
| Gasket 02                                  | 8.294     | Metres              |
| Glazing Bridge Packer                      | 16        | Unit                |

| Glass Required:                                            | Qty | Width | Length |
|------------------------------------------------------------|-----|-------|--------|
| 01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 346   | 1740   |
| 02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 321   | 1740   |

# WORK ORDER

|            |                       |              |                       |
|------------|-----------------------|--------------|-----------------------|
| Customer:  | Test Customer         | Input Info:  | 7/30/2026             |
| Reference: | sunnyplast order test | SupplyAndFit |                       |
| Job No:    | 169                   | Page 4       | Print Info: 7/30/2026 |

| Main Options                     |                                            |
|----------------------------------|--------------------------------------------|
| Colour (External)                | White [SP]                                 |
| Colour (Internal)                | White [SP]                                 |
| Frame (Standard) (Top)           | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Bottom)        | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Left)          | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Right)         | SPQ-6-11252 68mm 6 Chamber                 |
| Horizontal Midrail (Standard)    | SPQ-5-30252 78mm                           |
| Add-on (Right)                   | SPQ-2-75252 25mm                           |
| Joint (Structural T/Z) (Midrail) | Welded (Standard)                          |
| Bead                             | 28mm                                       |
| Sash Type                        | Door left hung                             |
| Cylinder                         | Brass Cylinder                             |
| Handle (Door)                    | White Handle Lever/Lever (Short Backplate) |
| Hinge (Door)                     | Flag Hinge                                 |
| Hinge Colour (Door)              | White Flag Hinge                           |
| Hinge Position (Door)            | 3 Hinges                                   |
| Lock (Door) (Single Door)        | Standard Door Lock                         |
| Glazing Method                   | Glazed                                     |
| Glass Type                       | 4-20-4 Clear Tuff Low E                    |
| Glass Gas Fill                   | Argon                                      |
| Opening Direction                | Open In                                    |
| Component Type                   | Glass                                      |
| Drainage                         | Concealed Drainage                         |
| Location                         | Please Specify                             |
| Vertical Split Position          | By Dimensions                              |



| Sections Required: |       |                   | Qty | Length | End Prep | Reinforcing                     | Length |
|--------------------|-------|-------------------|-----|--------|----------|---------------------------------|--------|
| Hor                | Bead  | 28mm Bead         | 4   | 725    | [ - ]    |                                 |        |
| Vert               | Bead  | 28mm Bead         | 2   | 756    | [ - ]    |                                 |        |
| Vert               | Bead  | 28mm Bead         | 2   | 956    | [ - ]    |                                 |        |
| Hor                | Frame | Frame 6 Chamber   | 2   | 980    | \ - /    |                                 |        |
| Vert               | Frame | Frame 6 Chamber   | 2   | 2005   | \ - /    |                                 |        |
| Hor                | Sash  | Door Sash Z       | 2   | 900    | \ - /    | 28 x 44.5 U Steel Reinforcement | 685    |
| Vert               | Sash  | Door Sash Z       | 2   | 1925   | \ - /    | 28 x 44.5 U Steel Reinforcement | 1710   |
| ?                  | Sash  | T Transom/Mullion | 1   | 846    | < - >    |                                 |        |

| Accessories Required:                      | Qty   | Unit Of Measurement |
|--------------------------------------------|-------|---------------------|
| Run Up Block                               | 1     | Unit                |
| Gasket 01                                  | 11.26 | Metres              |
| White Handle Lever/Lever (Short Backplate) | 1     | Unit                |
| Flag Hinge White                           | 3     | Unit                |
| L/H Keep Set                               | 1     | Unit                |
| Standard Door Lock                         | 1     | Unit                |
| Brass Cylinder                             | 1     | Unit                |
| Gasket 02                                  | 6.244 | Metres              |
| Glazing Bridge Packer                      | 16    | Unit                |

| Glass Required:                                            | Qty | Width | Length |
|------------------------------------------------------------|-----|-------|--------|
| 01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 715   | 946    |
| 02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 715   | 746    |

# WORK ORDER

|            |                       |              |                       |
|------------|-----------------------|--------------|-----------------------|
| Customer:  | Test Customer         | Input Info:  | 7/30/2026             |
| Reference: | sunnyplast order test | SupplyAndFit |                       |
| Job No:    | 169                   | Page 5       | Print Info: 7/30/2026 |

| Main Options                      |                                            |
|-----------------------------------|--------------------------------------------|
| Colour (External)                 | White [SP]                                 |
| Colour (Internal)                 | White [SP]                                 |
| Frame (Standard) (Top)            | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Bottom)         | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Left)           | SPQ-6-11252 68mm 6 Chamber                 |
| Frame (Standard) (Right)          | SPQ-6-11252 68mm 6 Chamber                 |
| Vertical Midrail                  | SPQ-5-30252 78mm                           |
| Joint (Structural T/Z) (Vertic... | Welded (Standard)                          |
| Bead                              | 28mm                                       |
| Sash Type                         | Door left hung                             |
| Cylinder                          | Brass Cylinder                             |
| Handle (Door)                     | White Handle Lever/Lever (Short Backplate) |
| Hinge (Door)                      | Flag Hinge                                 |
| Hinge Colour (Door)               | White Flag Hinge                           |
| Hinge Position (Door)             | 3 Hinges                                   |
| Lock (Door) (Single Door)         | Standard Door Lock                         |
| Glazing Method                    | Glazed                                     |
| Glass Type                        | 4-20-4 Clear Tuff Low E                    |
| Glass Gas Fill                    | Argon                                      |
| Opening Direction                 | Open In                                    |
| Component Type                    | Glass                                      |
| Drainage                          | Concealed Drainage                         |
| Location                          | Please Specify                             |
| Horizontal Split Position         | By Dimensions                              |



| Sections Required: |       |                   | Qty | Length | End Prep | Reinforcing                     | Length |
|--------------------|-------|-------------------|-----|--------|----------|---------------------------------|--------|
| Vert               | Bead  | 28mm Bead         | 4   | 1750   | [ - ]    |                                 |        |
| Hor                | Bead  | 28mm Bead         | 4   | 356    | [ - ]    |                                 |        |
| Hor                | Frame | Frame 6 Chamber   | 2   | 1005   | \ - /    |                                 |        |
| Vert               | Frame | Frame 6 Chamber   | 2   | 2005   | \ - /    |                                 |        |
| Hor                | Sash  | Door Sash Z       | 2   | 925    | \ - /    | 28 x 44.5 U Steel Reinforcement | 710    |
| Vert               | Sash  | Door Sash Z       | 2   | 1925   | \ - /    | 28 x 44.5 U Steel Reinforcement | 1710   |
| ?                  | Sash  | T Transom/Mullion | 1   | 1871   | < - >    | 26 x 26 U Steel Reinforcement   | 1710   |

| Accessories Required:                      | Qty   | Unit Of Measurement |
|--------------------------------------------|-------|---------------------|
| Run Up Block                               | 1     | Unit                |
| Gasket 01                                  | 11.36 | Metres              |
| White Handle Lever/Lever (Short Backplate) | 1     | Unit                |
| Flag Hinge White                           | 3     | Unit                |
| L/H Keep Set                               | 1     | Unit                |
| Standard Door Lock                         | 1     | Unit                |
| Brass Cylinder                             | 1     | Unit                |
| Gasket 02                                  | 8.344 | Metres              |
| Glazing Bridge Packer                      | 16    | Unit                |

| Glass Required:                                            | Qty | Width | Length |
|------------------------------------------------------------|-----|-------|--------|
| 01 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 346   | 1740   |
| 02 (Frame-01) 4-20-4 Clear Tuff Low E : Thermal Spacer Bar | 1   | 346   | 1740   |