

Python Complete Theory Guide

From Basics to Advanced Concepts

Table of Contents

1. [Python Basics](#)
 2. [Object-Oriented Programming \(OOP\)](#)
 3. [Multithreading](#)
 4. [Multiprocessing](#)
 5. [Dynamic Programming](#)
 6. [Design Patterns](#)
-

1. Python Basics

1.1 Data Types and Variables

Theory

Python is dynamically typed, meaning you don't need to declare variable types explicitly. The interpreter infers the type at runtime.

Built-in Data Types:

- **Numeric:** int, float, complex
- **Sequence:** str, list, tuple, range
- **Mapping:** dict
- **Set:** set, frozenset
- **Boolean:** bool
- **None:** NoneType

Key Concepts:

- Variables are references to objects in memory
- Python uses automatic memory management (garbage collection)
- Everything in Python is an object
- Mutable vs Immutable objects

Mutable Objects (can be changed after creation):

- list, dict, set, bytearray

Immutable Objects (cannot be changed after creation):

- int, float, str, tuple, frozenset, bool

Type Conversion

Python supports both implicit (automatic) and explicit (manual) type conversion.

1.2 Control Flow

Conditional Statements

Python uses indentation (typically 4 spaces) to define code blocks instead of braces.

if-elif-else Structure:

- Executes code based on boolean conditions
- `elif` is short for "else if"
- Conditions are evaluated top-to-bottom
- First true condition executes, rest are skipped

Ternary Operator: Shorthand for simple if-else: `value_if_true if condition else value_if_false`

Loops

For Loop:

- Iterates over sequences (lists, strings, ranges, etc.)
- Uses iterator protocol under the hood
- `range(start, stop, step)` generates sequences efficiently

While Loop:

- Continues while condition is True
- Risk of infinite loops if condition never becomes False
- Useful when number of iterations is unknown

Loop Control:

- `break`: Exit loop immediately
- `continue`: Skip to next iteration
- `else`: Executes if loop completes without break

1.3 Functions

Theory

Functions are first-class objects in Python, meaning they can be:

- Assigned to variables
- Passed as arguments
- Returned from other functions
- Stored in data structures

Function Components:

1. **def keyword:** Defines function
2. **Function name:** Identifier
3. **Parameters:** Input placeholders
4. **Docstring:** Documentation (optional but recommended)
5. **Function body:** Code to execute
6. **return statement:** Output (optional, defaults to None)

Parameter Types

Positional Arguments:

- Matched by position
- Must be provided in correct order

Keyword Arguments:

- Matched by name
- Order doesn't matter
- More readable for functions with many parameters

Default Parameters:

- Provide default values
- Must come after non-default parameters
- **Warning:** Don't use mutable defaults (like lists)

Variable Arguments:

- `*args`: Tuple of positional arguments

- `**kwargs`: Dictionary of keyword arguments
- Allows flexible function signatures

Scope and Namespaces

LEGB Rule (name resolution order):

1. **Local**: Inside current function
2. **Enclosing**: In enclosing functions (for nested functions)
3. **Global**: Module level
4. **Built-in**: Python's built-in names

Keywords:

- `global`: Modify global variable from inside function
- `nonlocal`: Modify enclosing function's variable (for closures)

Lambda Functions

- Anonymous functions (no name)
 - Single expression only
 - Syntax: `lambda parameters: expression`
 - Commonly used with `map()`, `filter()`, `sorted()`
 - Less readable for complex logic
-

1.4 Data Structures

Lists

Theory:

- Dynamic arrays (can grow/shrink)
- Ordered and indexed (0-based)
- Allow duplicate elements
- Mutable (can be modified)
- Heterogeneous (can contain different types)

Time Complexity:

- Access by index: $O(1)$
- Append: $O(1)$ amortized
- Insert/Delete at beginning: $O(n)$

- Search: $O(n)$

Important Methods:

- `append()`: Add to end - $O(1)$
- `insert()`: Add at position - $O(n)$
- `pop()`: Remove from end - $O(1)$
- `remove()`: Remove by value - $O(n)$
- `extend()`: Add multiple items - $O(k)$ where k is items added
- `sort()`: In-place sort - $O(n \log n)$

List Comprehensions:

- Concise way to create lists
- Syntax: `[expression for item in iterable if condition]`
- More Pythonic and often faster than loops
- Can be nested but readability decreases

Tuples

Theory:

- Immutable sequences
- Ordered and indexed
- Can contain duplicates
- Faster than lists for read operations
- Used for heterogeneous data
- Can be used as dictionary keys (if all elements are immutable)

Use Cases:

- Returning multiple values from functions
- Protecting data from modification
- Dictionary keys
- Performance optimization

Dictionaries

Theory:

- Hash tables (key-value pairs)
- Unordered (before Python 3.7) / Insertion-ordered (Python 3.7+)

- Keys must be immutable and unique
- Values can be any type
- Extremely fast lookups

Time Complexity:

- Access/Insert/Delete by key: $O(1)$ average case
- Search by value: $O(n)$

Important Methods:

- `get()`: Safe access with default
- `keys()`: View of keys
- `values()`: View of values
- `items()`: View of (key, value) pairs
- `update()`: Merge dictionaries
- `pop()`: Remove and return value
- `setdefault()`: Get or set default

Dictionary Comprehensions:

- Syntax: `{key_expr: value_expr for item in iterable}`

Sets

Theory:

- Unordered collection of unique elements
- Implemented using hash tables
- Fast membership testing
- Support mathematical set operations

Time Complexity:

- Add/Remove/Contains: $O(1)$ average
- Union/Intersection: $O(\text{len}(s) + \text{len}(t))$

Set Operations:

- Union: `|` or `union()`
- Intersection: `&` or `intersection()`
- Difference: `-` or `difference()`
- Symmetric Difference: `^` or `symmetric_difference()`

1.5 String Operations

Theory

Strings in Python are:

- Immutable sequences of Unicode characters
- Enclosed in single ("), double (""), or triple ('' or ''') quotes
- Triple quotes allow multi-line strings
- Support indexing and slicing
- Rich set of built-in methods

String Immutability:

- Every string operation creates a new string
- Original string is never modified
- Can impact performance for many concatenations

String Methods

Case Conversion:

- `upper()`, `lower()`, `capitalize()`, `title()`, `swapcase()`

Search/Test:

- `find()`, `index()`, `count()`, `startswith()`, `endswith()`
- `isalpha()`, `isdigit()`, `isalnum()`, `isspace()`

Modification:

- `replace()`, `strip()`, `lstrip()`, `rstrip()`
- `split()`, `join()`

String Formatting

f-strings (Python 3.6+):

- Most modern and readable
- Embedded expressions with `{}`
- Support format specifications: `{value:width.precision}`

`format()` method:

- More flexible than % formatting
- Positional and keyword arguments
- Reusable format strings

% formatting (old style):

- C-style formatting
- Less recommended but still common in legacy code

Slicing

Syntax: `string[start:stop:step]`

- start: inclusive (default 0)
 - stop: exclusive (default len)
 - step: increment (default 1)
 - Negative indices count from end
 - Negative step reverses direction
-

1.6 File Handling

Theory

File operations in Python follow:

1. **Open:** Create file object
2. **Read/Write:** Perform operations
3. **Close:** Release resources

File Modes:

- `'r'`: Read (default)
- `'w'`: Write (truncates file)
- `'a'`: Append
- `'x'`: Exclusive creation (fails if exists)
- `'b'`: Binary mode
- `'t'`: Text mode (default)
- `'+'`: Read and write

Best Practice: Use context managers (`with` statement) to ensure files are properly closed even if errors occur.

Reading Files

Methods:

- `read()`: Entire file as string
- `readline()`: Single line
- `readlines()`: List of lines
- Iteration: Most memory-efficient for large files

Writing Files

Methods:

- `write()`: Write string
- `writelines()`: Write list of strings (no newlines added)

File Pointer:

- `seek(offset, whence)`: Move file pointer
 - `tell()`: Get current position
-


1.7 Exception Handling

Theory

Exceptions are runtime errors that disrupt normal program flow. Python uses exception objects to represent errors.

Exception Hierarchy:

BaseException



Exception Handling Blocks

try-except:

- Catch and handle specific exceptions
- Multiple except blocks for different exceptions
- Generic Exception catches all (use cautiously)

else:

- Executes if no exception occurred
- Runs after try, before finally
- Good for code that should only run on success

finally:

- Always executes (even if exception or return)
- Used for cleanup (close files, release resources)
- Executes even if exception is re-raised

Raising Exceptions

raise statement:

- Trigger exceptions programmatically
- Can raise built-in or custom exceptions
- Can re-raise caught exceptions

Custom Exceptions:

- Inherit from Exception class
 - Add custom attributes/methods
 - Make error handling more specific
-

1.8 Comprehensions and Generators

List Comprehensions

Theory:

- Concise way to create lists
- More readable than traditional loops
- Often faster than equivalent for loops
- Should fit on one line for readability

Structure: `[expression for item in iterable if condition]`

Dictionary Comprehensions

Structure: `{key_expr: value_expr for item in iterable if condition}`

Set Comprehensions

Structure: `{expression for item in iterable if condition}`

Generator Expressions

Theory:

- Like list comprehensions but return generator objects
- Lazy evaluation (compute values on-demand)
- Memory efficient for large datasets
- Single-use (can't iterate twice)

Structure: `(expression for item in iterable if condition)`

Generator Functions

Theory:

- Functions that use `yield` instead of `return`
- Maintain state between calls
- Produce values one at a time
- Memory efficient for sequences
- Can be infinite

Key Differences from Regular Functions:

- Don't compute all values upfront
 - State is preserved between yields
 - Can receive values via `send()`
 - Can be closed with `close()`
-

1.9 Decorators

Theory

Decorators are functions that modify the behavior of other functions or classes without changing their source code.

Core Concepts:

- Functions are first-class objects
- Functions can be nested
- Functions can be passed as arguments
- Closures capture enclosing scope

How Decorators Work:

1. Take a function as input
2. Define a wrapper function with modified behavior
3. Return the wrapper function
4. Replace original function with wrapper

Syntax:

```
python
```

```
@decorator
def function():
    pass

# Equivalent to:
function = decorator(function)
```

Types of Decorators

Function Decorators:

- Modify function behavior
- Add functionality (logging, timing, caching)
- Enforce access control

Class Decorators:

- Modify class behavior
- Add methods/attributes
- Implement patterns (Singleton, etc.)

Decorators with Arguments:

- Need an extra layer of nesting
- Outer function takes decorator arguments
- Returns actual decorator

Built-in Decorators:

- `@property`: Convert method to attribute
- `@staticmethod`: Method doesn't access instance/class
- `@classmethod`: Method receives class as first argument
- `@functools.wraps`: Preserve original function metadata

1.10 Iterators and Iteration

Theory

Iterable:

- Object that can return an iterator
- Implements `__iter__()` method

- Examples: list, tuple, dict, set, str

Iterator:

- Object representing stream of data
- Implements `__iter__()` and `__next__()`
- Raises `StopIteration` when exhausted
- Maintains state (current position)

Iteration Protocol:

1. Call `iter(obj)` to get iterator
2. Call `next(iterator)` repeatedly
3. Catch `StopIteration` exception

for Loop Internals:

```
python

#for item in iterable:
#    process(item)

iterator = iter(iterable)
while True:
    try:
        item = next(iterator)
        process(item)
    except StopIteration:
        break
```

2. Object-Oriented Programming (OOP)

2.1 Classes and Objects

Theory

Object-Oriented Programming is a paradigm based on "objects" that contain data (attributes) and code (methods).

Key Concepts:

- **Class:** Blueprint for creating objects
- **Object:** Instance of a class
- **Attribute:** Data stored in object

- **Method:** Function defined in class

Class Definition:

- Use `class` keyword
- Class names use PascalCase convention
- Can inherit from other classes
- Contains attributes and methods

Instance vs Class Attributes:

- **Instance attributes:** Unique to each object
- **Class attributes:** Shared by all instances
- Define instance attributes in `__init__()`
- Define class attributes in class body

Methods:

- **Instance methods:** Operate on instance (`self`)
- **Class methods:** Operate on class (`@classmethod, cls`)
- **Static methods:** Independent utility functions (`@staticmethod`)

The init Method

- Constructor-like method (initializer)
- Called automatically when object is created
- First parameter is always `self` (instance reference)
- Used to set initial state

The self Parameter

- Reference to current instance
 - Must be first parameter of instance methods
 - Name is convention (could be anything)
 - Python doesn't pass it automatically (explicit)
-

2.2 The Four Pillars of OOP

Encapsulation

Theory: Bundling data and methods that operate on that data within a single unit (class), and restricting access

to some components.

Access Levels in Python:

- **Public:** Accessible everywhere (normal naming)
- **Protected:** By convention, single underscore prefix `_attribute`
- **Private:** Name mangling, double underscore prefix `__attribute`

Name Mangling:

- `_attribute` becomes `_ClassName__attribute`
- Prevents accidental access/override in subclasses
- Not true privacy (can still access if needed)

Properties:

- Python's way of implementing getters/setters
- Use `@property` decorator
- Make attribute access look like direct access
- Allows validation, computation, lazy loading

Benefits:

- Data hiding and protection
- Flexibility to change implementation
- Validation and error checking
- Controlled access

Inheritance

Theory: Mechanism where a new class (child/derived) inherits attributes and methods from existing class (parent/base).

Types of Inheritance:

1. Single Inheritance:

- One parent class
- Simple hierarchy
- Most common type

2. Multiple Inheritance:

- Multiple parent classes
- Diamond problem possible

- Method Resolution Order (MRO) critical
- Python uses C3 linearization

3. Multilevel Inheritance:

- Chain of inheritance ($A \rightarrow B \rightarrow C$)
- Each level adds functionality
- Deep hierarchies can be complex

4. Hierarchical Inheritance:

- Multiple children from one parent
- Common base, specialized children

Method Resolution Order (MRO):

- Order in which Python searches for methods
- Use `ClassName.__mro__` or `ClassName.mro()`
- C3 linearization algorithm
- Left-to-right, depth-first

super() Function:

- Call parent class methods
- Respects MRO in multiple inheritance
- Don't need to name parent class
- Cooperative multiple inheritance

Method Overriding:

- Child class redefines parent method
- Same name, different implementation
- Can call parent method with `super()`

Benefits:

- Code reusability
- Extensibility
- Hierarchical classification
- Polymorphism support

Polymorphism

Theory: Ability of objects of different classes to be treated as objects of a common base class. "Many forms" - same interface, different implementations.

Types:

1. Compile-time Polymorphism (Method Overloading):

- Python doesn't support true overloading
- Can simulate with default arguments
- Can use `*args` and `**kwargs`
- Can check argument types manually

2. Runtime Polymorphism (Method Overriding):

- Child class overrides parent method
- Determined at runtime
- Basis of polymorphic behavior

Duck Typing:

- "If it walks like a duck and quacks like a duck, it's a duck"
- Type determined by behavior, not inheritance
- Very Pythonic approach
- Flexible but less safe

Benefits:

- Flexibility and extensibility
- Simplified code
- Easy to add new types
- Interface-based programming

Abstraction

Theory: Hiding complex implementation details and showing only necessary features. Focus on "what" it does, not "how" it does it.

Abstract Base Classes (ABC):

- Cannot be instantiated
- Define interface contract
- Enforce implementation in subclasses
- Use `abc` module

Abstract Methods:

- Decorated with `@abstractmethod`
- Must be implemented by concrete subclasses
- Subclass can't be instantiated if method not implemented

Benefits:

- Reduces complexity
 - Enforces structure
 - Separates interface from implementation
 - Supports code maintenance
-

2.3 Special Methods (Magic Methods)

Theory

Special methods (dunder methods) allow your classes to implement Python's built-in behaviors.

Common Categories:

Object Lifecycle:

- `__init__(self)`: Constructor
- `__new__(cls)`: Object creation (before **init**)
- `__del__(self)`: Destructor (rarely used)

String Representation:

- `__str__(self)`: Informal string (for users) - `str()`
- `__repr__(self)`: Official representation (for developers) - `repr()`
- Should return string

Comparison Operators:

- `__eq__(self, other)`: `==` operator
- `__ne__(self, other)`: `!=` operator
- `__lt__(self, other)`: `<` operator
- `__le__(self, other)`: `<=` operator
- `__gt__(self, other)`: `>` operator
- `__ge__(self, other)`: `>=` operator

Arithmetic Operators:

- `__add__(self, other)`: + operator
- `__sub__(self, other)`: - operator
- `__mul__(self, other)`: * operator
- `__truediv__(self, other)`: / operator
- `__floordiv__(self, other)`: // operator
- `__mod__(self, other)`: % operator
- `__pow__(self, other)`: ** operator

Container Methods:

- `__len__(self)`: len() function
- `__getitem__(self, key)`: indexing []
- `__setitem__(self, key, value)`: assignment []
- `__delitem__(self, key)`: deletion del []
- `__contains__(self, item)`: in operator
- `__iter__(self)`: for loop support

Callable:

- `__call__(self, ...)`: Make instance callable like function

Context Manager:

- `__enter__(self)`: with statement entry
 - `__exit__(self, exc_type, exc_val, exc_tb)`: with statement exit
-

2.4 Composition vs Inheritance

Theory

Inheritance: "is-a" relationship

- Car is a Vehicle
- Dog is an Animal
- Creates tight coupling

Composition: "has-a" relationship

- Car has an Engine

- Person has an Address
- Creates loose coupling

When to Use Each:

Use Inheritance When:

- Clear hierarchical relationship exists
- Subclass truly "is-a" type of parent
- Need to override parent behavior
- Polymorphism is important

Use Composition When:

- Need functionality from multiple sources
- Relationship is "has-a" not "is-a"
- Want flexibility to change implementation
- Avoid deep inheritance hierarchies

Problems with Deep Inheritance:

- Fragile base class problem
- Difficulty understanding behavior
- Hard to modify
- Tight coupling

Benefits of Composition:

- More flexible
 - Easier to test
 - Reduces coupling
 - Follows "favor composition over inheritance" principle
-

2.5 Class Design Principles

SOLID Principles

S - Single Responsibility Principle:

- Class should have one reason to change
- One responsibility per class
- Improves maintainability

O - Open/Closed Principle:

- Open for extension, closed for modification
- Add new functionality without changing existing code
- Use inheritance and composition

L - Liskov Substitution Principle:

- Subclasses should be substitutable for base classes
- Subclass can't weaken base class behavior
- Maintains polymorphism

I - Interface Segregation Principle:

- Many specific interfaces better than one general
- Clients shouldn't depend on unused methods
- Use ABC with focused interfaces

D - Dependency Inversion Principle:

- Depend on abstractions, not concretions
 - High-level modules independent of low-level
 - Both depend on abstractions
-

3. Multithreading

3.1 Threading Fundamentals

Theory

Process vs Thread:

Process:

- Independent execution unit
- Own memory space
- Heavy-weight
- Inter-process communication is complex
- Python: multiprocessing module

Thread:

- Lightweight execution unit within process
- Shares memory space with other threads
- Light-weight
- Easier communication (shared memory)
- Python: threading module

Concurrency vs Parallelism:

Concurrency:

- Multiple tasks making progress (not necessarily simultaneous)
- Task switching gives illusion of simultaneity
- Single-core CPU can be concurrent

Parallelism:

- Multiple tasks executing simultaneously
- Requires multiple cores
- Subset of concurrency

Python Threading

threading Module:

- Built-in module for thread management
- Two main ways to create threads:
 1. Create Thread object with target function
 2. Subclass Thread and override run()

Thread Lifecycle:

1. **New:** Thread object created
2. **Runnable:** start() called
3. **Running:** Executing
4. **Blocked:** Waiting for resource
5. **Dead:** Execution completed

Main Thread:

- Program starts with main thread
- Child threads can be created
- Program ends when all threads complete (daemon=False)

3.2 The Global Interpreter Lock (GIL)

Theory

What is GIL:

- Mutex that protects Python objects
- Only one thread executes Python bytecode at a time
- Even on multi-core systems
- Specific to CPython implementation

Why GIL Exists:

- Simplifies memory management
- Makes C extensions easier
- Historical design decision
- Protects reference counting

Impact:

CPU-bound tasks:

- GIL limits to single core
- No true parallelism
- Multithreading can be slower (context switching overhead)
- Use multiprocessing instead

I/O-bound tasks:

- Threads release GIL during I/O operations
- Can benefit from multithreading
- Waiting for network, disk, user input
- GIL not a bottleneck

Workarounds:

1. Use multiprocessing for CPU-bound tasks
 2. Use async/await for I/O-bound tasks
 3. Use alternative Python implementations (Jython, IronPython)
 4. Write C extensions that release GIL
-

3.3 Thread Synchronization

Theory

Race Condition:

- Multiple threads access shared data
- At least one modifies it
- Outcome depends on timing
- Results are unpredictable
- Leads to data corruption

Critical Section:

- Code that accesses shared resources
- Must be protected from concurrent access
- Only one thread at a time

Synchronization Primitives

Lock (Mutex):

- Most basic synchronization primitive
- Binary: locked or unlocked
- acquire() and release()
- Only thread that acquired can release
- Can cause deadlocks

RLock (Reentrant Lock):

- Can be acquired multiple times by same thread
- Must be released equal number of times
- Tracks owning thread and recursion level
- Useful for recursive functions

Semaphore:

- Counter-based synchronization
- Allows N threads to access resource
- Useful for resource pools (connection pools, etc.)
- acquire() decrements, release() increments

BoundedSemaphore:

- Like Semaphore but prevents over-release
- Raises error if released too many times
- Safer than regular Semaphore

Event:

- Thread communication mechanism
- Boolean flag with signaling
- wait() blocks until set
- set() wakes all waiting threads
- clear() resets flag

Condition:

- Complex synchronization scenarios
- Associated with a lock
- wait() releases lock and blocks
- notify() or notify_all() wakes threads
- Used for producer-consumer patterns

Barrier:

- Synchronization point for fixed number of threads
 - All threads must reach barrier before continuing
 - Useful for multi-phase algorithms
 - wait() blocks until all threads arrive
-

3.4 Thread Safety

Theory**Thread-Safe:**

- Can be safely used by multiple threads concurrently
- No race conditions
- Correct behavior guaranteed

Thread-Unsafe:

- Not safe for concurrent access
- Can cause race conditions
- Needs external synchronization

Python Built-in Thread Safety:

Thread-Safe:

- List operations (mostly)
- Dict operations (mostly)
- print() function
- Most built-in types

Not Thread-Safe:

- Compound operations (check-then-act)
- Multiple operations together
- Custom data structures (without locks)

Making Code Thread-Safe:

1. Use locks around critical sections
 2. Use thread-safe data structures (queue.Queue)
 3. Avoid shared mutable state
 4. Use immutable objects
 5. Use thread-local storage
-

3.5 Thread Communication

Theory

Queue Module:

- Thread-safe queues
- Blocks on empty get() or full put()
- Perfect for producer-consumer pattern
- No manual locking needed

Types:

- **Queue:** FIFO (First In First Out)

- **LifoQueue:** LIFO (Last In First Out) - Stack
- **PriorityQueue:** Items retrieved by priority

Queue Methods:

- `put(item, block=True, timeout=None)`: Add item
- `get(block=True, timeout=None)`: Remove and return item
- `task_done()`: Mark task complete
- `join()`: Block until all tasks done
- `qsize()`: Approximate size
- `empty()`: Check if empty
- `full()`: Check if full

Thread-Local Data:

- Data specific to each thread
 - Use `threading.local()`
 - Like global but per-thread
 - No synchronization needed
-

3.6 Threading Best Practices

When to Use Threads:

- I/O-bound operations
- Network requests
- File I/O
- Database operations
- User interfaces (keep responsive)

When NOT to Use Threads:

- CPU-bound operations (use multiprocessing)
- Simple sequential tasks
- When shared state is complex

Best Practices:

1. Minimize shared state
2. Use high-level primitives (Queue, not Lock)

3. Avoid daemon threads for important work
 4. Always handle exceptions in threads
 5. Use context managers for locks (with statement)
 6. Document thread-safety expectations
 7. Test with thread sanitizers
 8. Keep critical sections small
 9. Avoid nested locks (deadlock risk)
 10. Use thread pools (ThreadPoolExecutor)
-

3.7 ThreadPoolExecutor

Theory

Executor Pattern:

- High-level interface for async execution
- Manages thread pool
- Submits tasks and gets futures
- Handles thread lifecycle

concurrent.futures Module:

- Modern threading/multiprocessing interface
- ThreadPoolExecutor for threads
- ProcessPoolExecutor for processes
- Similar API for both

Benefits:

- Automatic thread management
- Reuses threads (no creation overhead)
- Clean shutdown
- Future objects for results
- Exception handling built-in

Future Objects:

- Represents future result
- Methods: result(), done(), cancel()
- Can add callbacks

- Exception propagation

Methods:

- `submit(fn, *args, **kwargs)`: Submit single task
 - `map(fn, *iterables)`: Submit multiple tasks
 - `shutdown(wait=True)`: Clean shutdown
-

4. Multiprocessing

4.1 Multiprocessing Fundamentals

Theory

Why Multiprocessing:

- Bypass GIL limitation
- True parallelism
- Utilize multiple CPU cores
- Better for CPU-bound tasks

Process Creation:

- Each process has own memory space
- Separate Python interpreter
- Higher overhead than threads
- More isolated (safer)

multiprocessing Module:

- Similar API to threading
- Process class instead of Thread
- Process creation methods:
 1. Target function
 2. Subclass Process

Start Methods:

- **spawn**: New Python interpreter (Windows default)
- **fork**: Copy parent process (Unix default)
- **forkserver**: Server creates new processes

Considerations:

- Windows always uses spawn
 - fork faster but can have issues
 - spawn safer, slower startup
 - Set with `set_start_method()`
-

4.2 Inter-Process Communication (IPC)

Theory

Processes don't share memory, so need special mechanisms to communicate.

Queue

multiprocessing.Queue:

- Process-safe queue
- Uses pipes and locks
- Similar to `threading.Queue`
- Can transfer picklable objects

Key Differences from `threading.Queue`:

- Uses serialization (pickle)
- Higher overhead
- All objects must be picklable
- Can be slower

Pipe

Theory:

- Two-way communication channel
- Returns two connection objects
- Faster than Queue for two processes
- No built-in locking (can corrupt)

Methods:

- `send(obj)`: Send object
- `recv()`: Receive object

- `close()`: Close connection
- `poll([timeout])`: Check if data available

Duplex vs Simplex:

- Duplex: Both ends can send/receive (default)
- Simplex: One-way communication

Shared Memory

Value and Array:

- Shared memory primitives
- Synchronized access built-in
- Faster than Queue/Pipe
- Limited to simple types

Manager:

- Proxy objects for shared state
- Supports complex types (list, dict)
- Higher overhead than Value/Array
- Process-safe automatically

Manager Types:

- list, dict, Namespace, Lock, RLock, Semaphore, etc.
 - Proxies handle synchronization
 - Can be used across network
-

4.3 Process Synchronization

Theory

Similar to threading but for processes.

Lock:

- Mutual exclusion
- Prevent simultaneous access
- Similar to threading.Lock
- Uses OS primitives

RLock:

- Reentrant lock
- Same process can acquire multiple times

Semaphore:

- Counter-based
- Limit concurrent access

Event:

- Signal between processes
- set(), clear(), wait()

Condition:

- Complex synchronization
- Wait for specific conditions

Barrier:

- Synchronization point
 - Fixed number of processes
-

4.4 Process Pools

Theory**Pool Class:**

- Manage worker processes
- Distribute tasks automatically
- Reuse processes
- High-level interface

Methods:**map():**

- Parallel version of built-in map()
- Blocks until complete
- Returns results in order

- Chunks tasks automatically

imap():

- Lazy version of map()
- Returns iterator
- Memory efficient
- Results as they complete

imap_unordered():

- Like imap but results in completion order
- Faster than imap
- Order not preserved

apply():

- Execute function once
- Blocks until complete
- Deprecated, use apply_async

apply_async():

- Asynchronous version
- Returns AsyncResult object
- Can add callback

starmap():

- Like map but unpacks arguments
- Useful for multiple arguments

starmap_async():

- Asynchronous starmap

Context Manager:

- Use with statement
 - Automatic cleanup
 - Ensures termination
-

4.5 ProcessPoolExecutor

Theory

concurrent.futures:

- Modern interface
- Consistent with ThreadPoolExecutor
- Higher-level than Pool

Advantages:

- Future objects
- Exception handling
- Clean API
- Interchangeable with ThreadPoolExecutor

Methods: Same as ThreadPoolExecutor:

- `submit()`
- `map()`
- `shutdown()`

Choosing Pool vs Executor:

- **Pool:** More control, more methods
 - **Executor:** Simpler, modern, futures
-

4.6 Best Practices

When to Use Multiprocessing:

- CPU-bound tasks
- Number crunching
- Image/video processing
- Data analysis
- Scientific computing

When NOT to Use:

- I/O-bound tasks (use threading/async)
- Simple tasks (overhead not worth it)

- Requires shared complex state

Best Practices:

1. Minimize data transfer between processes
2. Use pools for many small tasks
3. Keep processes independent
4. Pickle overhead consideration
5. Use appropriate start method
6. Handle exceptions properly
7. Clean shutdown (terminate if needed)
8. Profile before optimizing
9. Consider memory usage
10. Use chunksize for map operations

Common Pitfalls:

- Pickling limitations (lambda, local functions)
 - Fork safety issues
 - Resource leaks
 - Not joining processes
 - Race conditions in shared memory
-

5. Dynamic Programming

5.1 Dynamic Programming Fundamentals

Theory

What is Dynamic Programming: Dynamic Programming (DP) is an optimization technique that solves complex problems by breaking them down into simpler subproblems and storing the results to avoid redundant calculations.

Key Characteristics:

1. **Optimal Substructure:** Optimal solution contains optimal solutions to subproblems
2. **Overlapping Subproblems:** Same subproblems are solved multiple times

When to Use DP:

- Problem can be divided into overlapping subproblems
- Optimal solution can be constructed from optimal solutions to subproblems

- Brute force has repeated calculations
- Counting problems
- Optimization problems (min/max)

DP vs Divide and Conquer:

- **Divide and Conquer:** Subproblems are independent (Merge Sort, Quick Sort)
 - **DP:** Subproblems overlap (Fibonacci, Shortest Path)
-

5.2 Approaches to Dynamic Programming

Top-Down (Memoization)

Theory:

- Start with original problem
- Recursively break into subproblems
- Store (memoize) results of subproblems
- Check cache before computing

Characteristics:

- Natural recursive structure
- Easy to implement from recursive solution
- Only computes needed subproblems
- Call stack overhead
- Risk of stack overflow for deep recursion

Implementation Techniques:

1. Dictionary for memoization
2. LRU cache decorator
3. Manual recursion with cache

When to Use:

- Natural recursive formulation
- Not all subproblems needed
- Easier to understand
- Proof of concept

Bottom-Up (Tabulation)

Theory:

- Start with smallest subproblems
- Build up to original problem
- Fill table iteratively
- No recursion

Characteristics:

- Iterative implementation
- No call stack overhead
- Computes all subproblems
- More space efficient (can optimize)
- Often faster in practice

Implementation Techniques:

1. 1D array/list
2. 2D array/matrix
3. Space optimization (rolling arrays)

When to Use:

- All subproblems needed
 - Space optimization important
 - Avoid recursion depth issues
 - Production code
-

5.3 Common DP Patterns

1D DP

Pattern:

- Single dimension problem
- $\boxed{\text{dp}[i]}$ represents solution for position i
- Typically linear recurrence relation

Examples:

- Fibonacci sequence
- Climbing stairs
- House robber
- Coin change (min coins)

General Structure:

1. Define dp array
2. Initialize base cases
3. Fill array using recurrence relation
4. Return $dp[n]$ or final value

2D DP

Pattern:

- Two dimensions
- $dp[i][j]$ represents solution for (i,j)
- Grid or two-sequence problems

Examples:

- Longest common subsequence
- Edit distance
- Matrix chain multiplication
- 0/1 knapsack

General Structure:

1. Create 2D table
2. Initialize base cases (first row/column)
3. Fill table row by row or column by column
4. Return $dp[m][n]$ or final cell

Knapsack Pattern

0/1 Knapsack:

- Item included or not (binary choice)
- $dp[i][w]$ = max value with items $0..i$ and weight w

Unbounded Knapsack:

- Unlimited quantity of each item

- Simpler recurrence relation

Variations:

- Subset sum
- Partition problem
- Coin change

Subsequence/Substring Pattern

Subsequence:

- Elements in order but not consecutive
- Skip elements allowed

Substring:

- Consecutive elements
- No skipping

Common Problems:

- Longest common subsequence (LCS)
- Longest increasing subsequence (LIS)
- Palindromic subsequence
- Edit distance

Grid/Path Pattern

Characteristics:

- 2D grid navigation
- Move constraints (right, down, etc.)
- Count paths or find optimal path

Examples:

- Unique paths
 - Minimum path sum
 - Dungeon game
 - Triangle minimum path
-

5.4 DP Optimization Techniques

Space Optimization

Rolling Array:

- Use only necessary rows/columns
- Reduce 2D to 1D
- Reduce space from $O(n^2)$ to $O(n)$

In-place Modification:

- Use input array for DP table
- Only when input can be modified

Two Variable Technique:

- For Fibonacci-like sequences
- Keep only last two values
- $O(1)$ space

Time Optimization

State Reduction:

- Eliminate unnecessary states
- Combine related states
- Simplify recurrence relation

Greedy Observation:

- Some DP problems have greedy property
- Can reduce from DP to greedy
- Much faster

Binary Search Integration:

- Longest increasing subsequence
 - Reduces $O(n^2)$ to $O(n \log n)$
-

5.5 Steps to Solve DP Problems

Step 1: Identify if it's DP

- Optimal substructure?
- Overlapping subproblems?
- Asking for optimal/count/possible?

Step 2: Define State

- What do you need to track?
- What are the parameters?
- What does $dp[i]$ or $dp[i][j]$ represent?

Step 3: Formulate Recurrence Relation

- How to compute $dp[i]$ from previous states?
- What are the choices at each step?
- Base cases?

Step 4: Decide Top-Down or Bottom-Up

- Complexity of recursion?
- All subproblems needed?
- Space constraints?

Step 5: Implement and Test

- Start with memoization (easier)
- Convert to tabulation for optimization
- Test with examples
- Check edge cases

Step 6: Optimize

- Can space be reduced?
- Can states be combined?
- Is there a greedy solution?

5.6 Common DP Problems Categories

Linear DP

- Single sequence
- Fibonacci, climbing stairs

- House robber variants
- Decode ways

Interval DP

- Range-based problems
- Burst balloons
- Matrix chain multiplication
- Palindrome partitioning

Grid DP

- 2D navigation
- Unique paths
- Minimum path sum
- Maximal rectangle

Knapsack DP

- Subset selection
- 0/1 knapsack
- Unbounded knapsack
- Subset sum
- Partition problems

String DP

- Two strings comparison
- Longest common subsequence
- Edit distance
- Wildcard matching
- Regular expression

Tree DP

- Tree structure problems
- House robber III
- Binary tree cameras
- Maximum path sum

State Machine DP

- Multiple states at each step
 - Best time to buy/sell stock
 - Paint house
 - State transitions
-

5.7 Memoization Decorators

`functools.lru_cache`

Theory:

- Least Recently Used cache
- Decorator for automatic memoization
- Maximum cache size (maxsize parameter)
- Thread-safe
- Only works with hashable arguments

Parameters:

- `maxsize`: Maximum cache entries (None = unlimited)
- `typed`: Separate cache for different types

Cache Info:

- `cache_info()`: Statistics
- `cache_clear()`: Clear cache

Limitations:

- Arguments must be hashable
 - Not suitable for mutable arguments
 - Memory usage with large cache
-

6. Design Patterns

6.1 Introduction to Design Patterns

Theory

What are Design Patterns: Reusable solutions to commonly occurring problems in software design. Not code,

but templates for solving problems.

Benefits:

- Proven solutions
- Common vocabulary
- Best practices
- Faster development
- Easier maintenance
- Better communication

Gang of Four (GoF): Published "Design Patterns: Elements of Reusable Object-Oriented Software" (1994)
Defined 23 classic patterns in 3 categories

Categories:

1. **Creational:** Object creation mechanisms
2. **Structural:** Object composition and relationships
3. **Behavioral:** Object interaction and responsibility

When to Use Patterns:

- Solving common problems
- Need flexibility and maintainability
- Team communication
- Large codebases

When NOT to Use:

- Over-engineering simple problems
 - Forcing patterns where they don't fit
 - Premature optimization
-

6.2 Creational Patterns

Singleton Pattern

Intent: Ensure a class has only one instance and provide global access point to it.

Use Cases:

- Database connections
- Configuration managers

- Logging
- Thread pools
- Caches

Implementation Approaches:

1. Class Variable:

- Simple implementation
- Not thread-safe

2. new Method:

- Controls instance creation
- More Pythonic

3. Decorator:

- Reusable across classes
- Clean syntax

4. Metaclass:

- Most robust
- Controls class creation

Pros:

- Controlled access to sole instance
- Global access point
- Lazy initialization possible

Cons:

- Global state (testing issues)
- Can violate Single Responsibility Principle
- Difficult to subclass
- Hidden dependencies

Thread Safety:

- Add locks for thread-safe creation
- Use double-checked locking
- Or rely on module-level instance

Factory Pattern

Intent: Define interface for creating objects, but let subclasses decide which class to instantiate.

Types:

Simple Factory:

- Not a true GoF pattern
- Function/method creates objects
- Encapsulates creation logic

Factory Method:

- Defines interface for creating objects
- Subclasses override to specify type
- Template Method pattern for creation

Abstract Factory:

- Creates families of related objects
- Multiple factory methods
- Ensures consistency

Use Cases:

- Object type determined at runtime
- Complex creation logic
- Multiple related objects
- Decoupling object creation from usage

Pros:

- Loose coupling
- Single Responsibility Principle
- Open/Closed Principle
- Easy to extend

Cons:

- Can introduce complexity
- Many subclasses

Builder Pattern

Intent: Separate construction of complex object from its representation. Build object step by step.

Use Cases:

- Complex objects with many parameters
- Different representations of same data
- Step-by-step construction
- Immutable objects

Components:

- **Product:** Object being built
- **Builder:** Abstract interface
- **Concrete Builder:** Implements construction steps
- **Director:** Constructs using Builder (optional)

Pros:

- Construct complex objects step-by-step
- Same construction process, different representations
- Isolates complex construction code
- Fluent interface (method chaining)

Cons:

- More code and classes
- Increased complexity

Prototype Pattern

Intent: Create new objects by copying existing objects (prototypes).

Use Cases:

- Creating objects is expensive
- Many similar objects needed
- Avoid subclass explosion
- Runtime configuration

Implementation:

- Use `copy` module
- Shallow copy: `copy.copy()`

- Deep copy: `copy.deepcopy()`

Pros:

- Avoids expensive creation
- Reduces subclassing
- Can add/remove products at runtime
- Configure objects with varying values

Cons:

- Deep copying complex objects can be tricky
 - Circular references issues
-

6.3 Structural Patterns

Adapter Pattern

Intent: Convert interface of class into another interface clients expect. Allows incompatible interfaces to work together.

Use Cases:

- Legacy code integration
- Third-party library incompatibility
- Reusing existing classes with incompatible interfaces

Types:

- **Class Adapter:** Uses inheritance (multiple inheritance)
- **Object Adapter:** Uses composition (more flexible)

Components:

- **Target:** Interface client expects
- **Adaptee:** Existing incompatible interface
- **Adapter:** Converts Adaptee to Target

Pros:

- Reuse existing code
- Single Responsibility Principle
- Open/Closed Principle

- Flexibility

Cons:

- Increased complexity
- Sometimes easier to change existing class

Decorator Pattern

Intent: Attach additional responsibilities to object dynamically. Flexible alternative to subclassing.

Use Cases:

- Add functionality without modifying class
- Combine multiple behaviors
- Runtime decoration
- Avoid explosion of subclasses

Python Implementation:

- Function decorators (using @)
- Class decorators
- Wrapper classes

Components:

- **Component:** Abstract interface
- **Concrete Component:** Object to decorate
- **Decorator:** Wraps component
- **Concrete Decorator:** Adds responsibilities

Pros:

- More flexible than inheritance
- Responsibilities added/removed at runtime
- Combine multiple decorators
- Single Responsibility Principle

Cons:

- Many small objects
- Order matters
- Can be hard to debug

Facade Pattern

Intent: Provide unified interface to set of interfaces in subsystem. Higher-level interface makes subsystem easier to use.

Use Cases:

- Simplify complex systems
- Layer architecture
- Library wrappers
- API design

Components:

- **Facade:** Simple interface to complex subsystem
- **Subsystem Classes:** Complex functionality

Pros:

- Simplifies usage
- Loose coupling
- Layered architecture
- Easier testing

Cons:

- Can become god object
- May limit functionality

Proxy Pattern

Intent: Provide surrogate or placeholder for another object to control access to it.

Types:

Virtual Proxy:

- Lazy initialization
- Create expensive object on demand

Protection Proxy:

- Access control
- Check permissions

Remote Proxy:

- Represents object in different address space
- Network communication

Cache Proxy:

- Store results
- Avoid expensive operations

Use Cases:

- Lazy loading
- Access control
- Caching
- Logging
- Remote objects

Pros:

- Control object access
- Lazy initialization
- Additional functionality transparently
- Open/Closed Principle

Cons:

- Added complexity
- Slower response (sometimes)

Composite Pattern

Intent: Compose objects into tree structures to represent part-whole hierarchies. Treat individual objects and compositions uniformly.

Use Cases:

- Tree structures
- File systems
- GUI components
- Organization hierarchies

Components:

- **Component:** Abstract interface for all objects
- **Leaf:** Individual object (no children)

- **Composite:** Container of components

Pros:

- Treat single objects and compositions uniformly
- Easy to add new component types
- Open/Closed Principle

Cons:

- Can be overly general
 - Hard to restrict components
-

6.4 Behavioral Patterns

Observer Pattern

Intent: Define one-to-many dependency between objects. When one object changes state, all dependents are notified and updated automatically.

Also Known As:

- Publish-Subscribe
- Event-Listener

Use Cases:

- Event handling systems
- MVC architecture (Model notifies View)
- Distributed event handling
- Real-time updates

Components:

- **Subject:** Maintains list of observers, notifies on change
- **Observer:** Interface for objects to be notified
- **Concrete Subject:** Stores state, sends notifications
- **Concrete Observer:** Maintains reference to subject, implements update

Pros:

- Loose coupling
- Dynamic relationships (add/remove observers at runtime)

- Broadcast communication
- Open/Closed Principle

Cons:

- Observers notified in random order
- Memory leaks if not unsubscribed
- Can cause unexpected updates

Strategy Pattern

Intent: Define family of algorithms, encapsulate each one, and make them interchangeable. Strategy lets algorithm vary independently from clients.

Use Cases:

- Multiple algorithms for same task
- Avoid conditional statements
- Different variants of algorithm
- Runtime algorithm selection

Components:

- **Strategy:** Interface for algorithm
- **Concrete Strategy:** Implements algorithm
- **Context:** Uses Strategy interface

Pros:

- Swap algorithms at runtime
- Isolate algorithm implementation
- Replace inheritance with composition
- Open/Closed Principle

Cons:

- Increased number of classes
- Clients must be aware of strategies
- Communication overhead

Command Pattern

Intent: Encapsulate request as object. Allows parameterization of clients with different requests, queue requests, and support undoable operations.

Use Cases:

- Undo/Redo functionality
- Macro recording
- Transaction systems
- Job queues
- GUI buttons/menu items

Components:

- **Command:** Interface for executing operation
- **Concrete Command:** Implements execute, binds receiver and action
- **Invoker:** Asks command to execute
- **Receiver:** Performs actual work
- **Client:** Creates and configures commands

Pros:

- Decouples invoker from receiver
- Easy to add new commands (Open/Closed)
- Supports undo/redo
- Supports command composition
- Deferred execution

Cons:

- Increased number of classes
- Complexity for simple operations

Template Method Pattern

Intent: Define skeleton of algorithm in base class, but let subclasses override specific steps without changing algorithm structure.

Use Cases:

- Common algorithm structure, varying steps
- Frameworks (define extension points)
- Code reuse
- Inversion of control

Components:

- **Abstract Class:** Defines template method and abstract steps
- **Concrete Class:** Implements abstract steps

Template Method:

- Final method in base class
- Calls abstract and concrete methods
- Defines algorithm structure

Pros:

- Code reuse
- Control over algorithm structure
- Hooks for customization

Cons:

- Limited flexibility
- Violates Liskov Substitution (sometimes)
- Template can become complex

Iterator Pattern

Intent: Provide way to access elements of aggregate object sequentially without exposing underlying representation.

Use Cases:

- Traverse collections
- Hide internal structure
- Support multiple traversals
- Uniform interface for different structures

Python Built-in Support:

- `iter__()` method
- `next__()` method
- `for` loop uses iterator protocol
- `iter()` and `next()` built-in functions

Components:

- **Iterator:** Interface with `next()` and `has_next()`
- **Concrete Iterator:** Implements traversal

- **Aggregate:** Interface for creating iterator
- **Concrete Aggregate:** Returns concrete iterator

Pros:

- Clean collection traversal
- Multiple traversals simultaneously
- Uniform interface
- Single Responsibility Principle

Cons:

- Overkill for simple collections
- Less efficient than direct access (sometimes)

State Pattern

Intent: Allow object to alter behavior when internal state changes. Object appears to change class.

Use Cases:

- Objects with state-dependent behavior
- Large conditional statements based on state
- State machines
- Game AI

Components:

- **Context:** Maintains current state, delegates to state object
- **State:** Interface for state-specific behavior
- **Concrete State:** Implements behavior for specific state

Pros:

- Organizes state-specific code
- Makes state transitions explicit
- Single Responsibility Principle
- Open/Closed Principle

Cons:

- Overkill for few states
- Increases number of classes

Chain of Responsibility Pattern

Intent: Avoid coupling sender of request to receiver by giving multiple objects a chance to handle request. Chain receiving objects and pass request along chain.

Use Cases:

- Multiple objects can handle request
- Handler not known beforehand
- Logging frameworks
- Event bubbling
- Middleware

Components:

- **Handler:** Interface for handling requests
- **Concrete Handler:** Handles request or passes to next
- **Client:** Initiates request to chain

Pros:

- Reduced coupling
- Flexibility in assigning responsibilities
- Can add/remove handlers dynamically

Cons:

- Request might go unhandled
 - Can be hard to debug
 - Performance concerns (long chain)
-

6.5 Advanced Patterns

Dependency Injection

Intent: Provide dependencies to object from outside rather than object creating them. Inversion of Control (IoC).

Types:

- **Constructor Injection:** Pass dependencies via constructor
- **Setter Injection:** Pass via setter methods
- **Interface Injection:** Client implements interface for injection

Benefits:

- Loose coupling
- Easy testing (mock dependencies)
- Better code organization
- Flexibility

Implementation in Python:

- Manual injection
- Dependency injection frameworks (injector, dependency_injector)

Repository Pattern

Intent: Mediate between domain and data mapping layers. Collection-like interface for accessing domain objects.

Use Cases:

- Data access abstraction
- Centralize data logic
- Testing (mock repositories)
- Multiple data sources

Benefits:

- Separation of concerns
- Centralized data access logic
- Easy to test
- Swap data sources

Unit of Work Pattern

Intent: Maintain list of objects affected by business transaction and coordinates writing changes. Manages transactions.

Use Cases:

- Database transactions
- Multiple repository operations
- Ensure atomicity
- Track changes

Benefits:

- Transaction management
 - Batch database updates
 - Consistency
 - Rollback on failure
-

6.6 Anti-Patterns to Avoid

God Object:

- Object knows/does too much
- Violates Single Responsibility
- Hard to maintain

Spaghetti Code:

- Unstructured, hard to follow
- Tangled dependencies
- Difficult to modify

Golden Hammer:

- Using same solution for all problems
- "If all you have is a hammer..."
- Inappropriate pattern usage

Premature Optimization:

- Optimizing before needed
- Adds complexity
- Profile first!

Cargo Cult Programming:

- Using code without understanding
 - Copy-paste without thinking
 - Ritual behavior
-

6.7 Pattern Selection Guide

Problem: Need single instance → Singleton

Problem: Create object without specifying exact class → Factory Method, Abstract Factory

Problem: Build complex object step-by-step → Builder

Problem: Clone existing object → Prototype

Problem: Incompatible interfaces → Adapter

Problem: Add functionality dynamically → Decorator

Problem: Simplify complex system → Facade

Problem: Control access to object → Proxy

Problem: Part-whole hierarchies → Composite

Problem: Notify dependent objects of changes → Observer

Problem: Swap algorithms at runtime → Strategy

Problem: Encapsulate requests → Command

Problem: Define algorithm skeleton → Template Method

Problem: Traverse collection → Iterator

Problem: State-dependent behavior → State

Problem: Pass request along chain → Chain of Responsibility

6.8 Pythonic Patterns

Duck Typing

"If it walks like a duck and quacks like a duck..."

- Don't check types, check behavior
- More flexible than inheritance
- Very Pythonic

EAFP vs LBYL

EAFP (Easier to Ask Forgiveness than Permission):

- Try operation, handle exception
- Pythonic approach

LBYL (Look Before You Leap):

- Check before operation
- More defensive

- Not Pythonic

Context Managers

Theory:

- Manage resources (files, locks, connections)
- Use `with` statement
- Implement `__enter__` and `__exit__`
- Or use `@contextmanager` decorator

Benefits:

- Guaranteed cleanup
- Exception safe
- Clean syntax

Descriptors

Theory:

- Define `__get__`, `__set__`, `__delete__`
- Control attribute access
- Power behind properties
- Advanced technique

Use Cases:

- Validation
- Lazy properties
- Type checking
- Caching

Conclusion

This comprehensive guide covers:

1. **Python Basics:** Core language features and data structures
2. **OOP:** Classes, inheritance, polymorphism, abstraction, encapsulation
3. **Multithreading:** Concurrent execution, synchronization, GIL
4. **Multiprocessing:** True parallelism, IPC, process pools

5. **Dynamic Programming:** Optimization technique, memoization, patterns
6. **Design Patterns:** Reusable solutions to common problems

Key Takeaways:

- **Master the basics** before moving to advanced topics
- **Understand theory** but focus on practical application
- **Choose the right tool** for the problem (threads vs processes)
- **Optimize when needed**, not prematurely
- **Learn patterns** but don't force them
- **Write Pythonic code** - use language idioms
- **Test your code** - especially concurrent code
- **Profile before optimizing** - measure don't guess
- **Document your code** - explain why, not what
- **Keep learning** - Python ecosystem is vast

Practice Resources:

- LeetCode / HackerRank for algorithms and DP
- Real projects for OOP and design patterns
- Concurrent applications for threading/multiprocessing
- Open source contributions
- Code reviews
- Reading others' code

Next Steps:

1. Implement examples from each section
2. Build projects using these concepts
3. Read others' code using these patterns
4. Refactor existing code applying learned principles
5. Explore advanced topics (async/await, metaclasses, etc.)

Happy coding! 