FINDING TIME COMPLEXITY OF ALGORITHMS

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;

    int s =1;

    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```
#include<stdio.h>

int main(){
    int n;
    scanf("%d", &n);
    int i=1, s=1;
    int count=0;
    while(s<=n){
       count++;
       i++;
       count++;
       s += i;
       count++;
    }
    count+=3;
    printf("%d", count);
    return 0;
}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main(){
    int n, count=0;
    scanf("%d", &n);

    if(n==1){
        count++;
    }
    else{
        count++;

        for(int i=1;i<=n;i++){


            count++;
            count++;
            count++;
            count++;

            count++;
        }
        count++;

    }
    printf("%d", count);
    return 0;
}
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
int main(){
    int n, count =0;
    scanf("%d", &n);

    for(int i=1;i<=n;i++){
        count++;

        if(n%i==0){
            count++;
            }
        count++;



    }
    count++;
    printf("%d", count);
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
int ct = 0;
void function(int n){
    int c=0;
    ct++;
    for(int i=n/2;i<n;i++){
        ct++;
        for(int j=1;j<n;j=2*j){
            ct++;
            for(int k=1;k<n;k=k*2){
                ct++;
                c++;
                ct++;
            }
            ct++;
        }
        ct++;
    }
    ct++;
}
int main(){
    int n;
    scanf("%d", &n);
    function(n);
    printf("%d", ct);
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
int c=0;
void reverse(int n){
    int rev=0, remainder;
    c++;
    while(n!=0){
        c++;
        remainder=n%10;
        c++;
        rev=rev*10+remainder;
        c++;
        n/=10;
        c++;
    }
    c++;
}
int main(){
    int n;
    scanf("%d",&n);
    reverse(n);
    c++;
    printf("%d",c);
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.