

1. Selecting Elements

```
document.querySelector("p")
```

Gets the **first** `<p>` tag.

```
document.querySelector(".box")
```

Gets the first element with **class** `box`.

```
document.querySelector("#id")
```

Gets the element with that **id**.

2. Reading & Changing Content

```
document.body.innerHTML = 'hello';
```

Change the entire body content.

Text vs HTML (If element contains: `<b>Hello</b>` World)

```
element.innerHTML
```

→ `"<b>Hello</b> World"` (Includes tags).

```
element.innerText
```

→ `"Hello World"` (Text only, ignores tags).

Inputs (`<input>` tags)

```
document.querySelector("input").value
```

Read what user typed.

```
document.querySelector("input").value = "hi"
```

Write text into the box.

⚠ Never use `innerHTML` for inputs! User text is in `.value`

3. DOM Values are Strings (Type Coercion)

⚠ Everything you pull from the DOM is a String.

```
Number(value)
```

Manually convert string to Number.

```
'25' - 5
```

→ **20** (JS auto-converts for `-`, `*`, `/`)

```
'25' + 5
```

→ **"255"** ⚠ Joins strings! Always use `Number()` for math.

4. Events & Event Object

Common Listeners:

`onclick`, `onkeydown`, `onscroll`, `onmouseenter`

Every event listener gets an **event object** automatically.

```
element.onclick = function(event) {
```

event contains all the details of the action.

```
  console.log(event.key);
```

Which key was pressed.

```
console.log(event.target);  
}
```

Which specific element was clicked/triggered.

Other Useful Properties

```
document.title = "new title";
```

Change the page tab title.