


# Advance AWS Projects.


## PROJECT 1:

### 1. Deploying a web server in Windows Instance:


**Task A: Create a windows instance using AMI: Windows Server 2019 base:**



**Task B: Select Keypair and launch the instance.**




## IP Address of the Instance:




## 2.Launching the Server


Task A: Select Instance and connect to using RDP client.




## Download RDP file and Get password:




## Connect RDP file With Using Get Password:




## IIS Web Server:



## Task B: Install IIS Web Server using with PowerShell IIS:




## Task C: Verify Successful Installation of IIS Web Server:




## PROJECT 2:

### 2. Deploying a Web Server in Windows Instance Ubuntu Server 20.04 LTS (HVM).







## Select Keypair and Launch Ubuntu Instance:



## Ip Address of the instance:



## Install nginx Web Server Using bash:




```
Learn with Let's Upgrade - Bash x Connect to instance | EC2 Man x i-00370b3e017460354 (Ubuntu x) i5 Windows Server x +
us-east-2.console.aws.amazon.com/ec2/console?ubuntu=i-00370b3e017460354
Selecting previously unselected package nginx.
Preparing to unpack .../16-nginx_1.18.0-0ubuntu1_all.deb ...
Unpacking nginx (1.18.0-0ubuntu1) ...
Setting up libxpm4:amd64 (1:3.5.12-1) ...
Setting up nginx-common (1.18.0-0ubuntu1) ...
Created symlink /etc/systemd/system/multi-user.target.wants/nginx.service - /lib/systemd/system/nginx.service.
Setting up libjpeg8:amd64 (2.1-3.1build1) ...
Setting up libnginx-mod-http-xslt-filter (1.18.0-0ubuntu1) ...
Setting up libwebp6:amd64 (0.6.1-2) ...
Setting up fonts-dejavu-core (2.37-1) ...
Setting up libjpeg-turbo8:amd64 (2.0.3-0ubuntu1,20.04.1) ...
Setting up libjpeg8:amd64 (8c-2ubuntu8) ...
Setting up libnginx-mod-mail (1.18.0-0ubuntu1) ...
Setting up fontconfig-config (2.13.1-2ubuntu3) ...
Setting up libnginx-mod-stream (1.18.0-0ubuntu1) ...
Setting up libtiff5:amd64 (4.1.0+git191117-2build1) ...
Setting up libfontconfig1:amd64 (2.13.1-2ubuntu3) ...
Setting up libgd3:amd64 (2.2.5-5.2ubuntu2) ...
Setting up libnginx-mod-http-image-filter (1.18.0-0ubuntu1) ...
Setting up nginx-core (1.18.0-0ubuntu1) ...
Setting up nginx (1.18.0-0ubuntu1) ...
Processing triggers for ufw (0.36-6) ...
Processing triggers for systemd (245.4-4ubuntu3.2) ...
Processing triggers for man-db (2.9.1-1) ...
Processing triggers for libc-bin (2.31-0ubuntu9) ...
ubuntu@ip-172-31-46-79:~$
```

i-00370b3e017460354 (Ubuntu nginx)

Public IPs: 3.137.154.160 Private IPs: 172.31.46.79

Activate Windows. Go to Settings to activate Windows.


## Verify Successful Installation of nginx:




## PROJECT 3:

### 3.Working with Storage Volumes.

#### 1.Create a new Windows Instance:





#### Ip Address of the Instance:







## 2.Create a Volume in the same region as the Windows Machine:



## Volume Created:




## 3. Attach the Volume to the Windows Machine:




# Launching the Server:


## 1.Download RDP file and Get Password:




## 2.Connect RDP file With Using Get Password:




### 3.Open Virtual Machine Remote Desktop Connection:




### Open Server Manager:











## Open File and Storage Devices:









## Select Volume and Bring Online:











## Verify New Volume:




## PROJECT 4:

### 4. Working with Elastic IP's.

#### 1.Install a Linux Instance (Apache Server):




#### 2.Select Keypair and Launch Instance:





### 3. Check Web Server is Active (Running):



```
Complete!  
[root@ip-172-31-7-218 ec2-user]# system start httpd  
bash: system: command not found  
[root@ip-172-31-7-218 ec2-user]# systemctl start httpd  
bash: systemctl: command not found  
[root@ip-172-31-7-218 ec2-user]# systemctl start httpd  
[root@ip-172-31-7-218 ec2-user]# systemctl enable httpd  
Created symlink from /etc/systemd/system/multi-user.target.wants/httpd.service to /usr/lib/systemd/system/httpd.service.  
[root@ip-172-31-7-218 ec2-user]# systemctl status httpd  
● httpd.service - The Apache HTTP Server  
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; vendor preset: disabled)  
   Active: active (running) since Thu 2020-10-08 05:47:11 UTC; 1min 28s ago  
     Docs: man:httpd.service(8)  
  Main PID: 12809 (httpd)  
    Status: "Total requests: 0; Idle/Busy workers 100/0; Requests/sec: 0; Bytes served/sec: 0 B/sec"  
    CGroup: /system.slice/httpd.service  
            └─12809 /usr/sbin/httpd -DFOREGROUND  
              └─12810 /usr/sbin/httpd -DFOREGROUND  
                └─12811 /usr/sbin/httpd -DFOREGROUND  
                  └─12812 /usr/sbin/httpd -DFOREGROUND  
                    └─12813 /usr/sbin/httpd -DFOREGROUND  
                      └─12814 /usr/sbin/httpd -DFOREGROUND  
  
Oct 08 05:47:11 ip-172-31-7-218.us-east-2.compute.internal systemd[1]: Starting The Apache HTTP Server...  
Oct 08 05:47:11 ip-172-31-7-218.us-east-2.compute.internal systemd[1]: Started The Apache HTTP Server.  
[root@ip-172-31-7-218 ec2-user]#
```

i-06148198caa142cfb (apache)

Public IP: 3.133.110.212 Private IP: 172.31.7.218



Activate Windows. Go to Settings to activate Windows.




### 4. After Check Apache Test Page:




# Elastic IP's

## Allocate Elastic IP Address:







## After Allocation of Elastic IP:





## Change the IP Address:



## Apache Server Page:



## Release Elastic Ip Address:







# PROJECT 5:

## 5.Working with S3:


### 1.Open Amazon S3:



### 2.Create Bucket:






### 3.Bucket Created:




### A.Working with S3-jpg:

#### 1.Upload jpg File:







## 2.Copy URL and Paste it Browser It Shows Access Denied:




### 3.Edit Permissions and Confirm:





## 4.Our jpg Make Public




## 5.Now Verify Your jpg:





## B. Working with Static Web Hosting:



### 1.Open Static Web Hosting:





### 2.Create Two Text Files:





### 3.Files Save in Static Web Hosting:



## 4.Upload Files and Make Public:




## 5.Copy URL and Paste it in Browser:






## C. Working with Versioning:

### 1.Create New Bucket:



### 2.Enable Versioning and Save:



Learn with Let's Upgrade - Online x S3 Management Console x vishu1115 website on east-2 x

s3.console.aws.amazon.com/s3/buckets/vishu1115/?region=us-east-2&tab=overview

Services v

US East (Ohio)

vishu1115

Overview Properties Permissions Management Access points

Type a prefix and press Enter to search. Press ESC to clear

Upload + Create folder Download Actions

Viewing 1 to 1

Name	Last modified	Size	Storage class
versindemo.txt.txt	Oct 8, 2020 1:34:40 PM GMT+0530	29.0 B	Standard

Viewing 1 to 1

Operations 0 In progress 1 Success 0 Error

Activate Windows Go to Settings to activate Windows.

Feedback English (US)

© 2009 - 2020, Amazon Internet Services Private Ltd. or its affiliates. All rights reserved. Privacy Policy Terms of Use

Type here to search

Learn with Let's Upgrade - Online x S3 Management Console x vishu1115 website on east-2 x

s3.console.aws.amazon.com/s3/buckets/vishu1115/?region=us-east-2&tab=overview&showversions=true

Services v

US East (Ohio)

vishu1115

Overview Properties Permissions Management Access points

Type a prefix and press Enter to search. Press ESC to clear

Upload + Create folder Download Actions Versions Hide Show

Viewing 1 to 2

Name	Version ID	Last modified	Size	Storage class
versindemo.txt.txt		Oct 8, 2020 1:42:57 PM		
Oct 8, 2020 1:42:57 PM (Latest version)	j006w10heQYz37GT4Zx8eg017...		68.0 B	Standard
Oct 8, 2020 1:42:20 PM	HXYFq2K1NnfyauR0eCGjyWX...		58.0 B	Standard

Viewing 1 to 2



Operations 0 In progress 18 Success 0 Error


Activate Windows Go to Settings to activate Windows.

Feedback English (US)

© 2009 - 2020, Amazon Internet Services Private Ltd. or its affiliates. All rights reserved. Privacy Policy Terms of Use

Type here to search






## Q1: Explain life cycle effects on instances:

**Stop, start, reboot, terminate-public IP, Private Ip, Applications installed.**

### Instance Life Cycle:

1. An EC2 instance is a virtual server in the AWS cloud, launched from an Amazon Machine Image (AMI).
2. AMI provides the operating system, application server, and applications for the instance.
3. When an instance is launched, it receives private DNS name that other instances within the same EC2 network can use to contact the instance. Optionally, it receives a public DNS name that can be used to contact the instance from the Internet.

4. The following illustration represents the transitions between instance states. Notice that you can't stop and start an instance store-backed instance.



### Instance start and stop:

1. Only EBS-backed instance can be stopped and started. Instance store-backed instance cannot be stopped and started.
2. An instance can be stopped & started in case the instance fails a status check or is not running as expected.

### STOP:

1. After the instance is stopped, it enters the stopping state and then to the stopped state.
2. Charges are only incurred for the EBS storage and not for the instance hourly charge or data transfer.
3. While the instance is stopped, its root volume can be treated like any other volume, and modified for e.g. repair file system problems or update software or change the instance type, user data, EBS optimization attributes etc.
4. Volume can be detached from the stopped instance, and attached to a running instance, modified, detached from the running instance, and then reattached to the stopped instance. It should be reattached using the storage device.

name that's specified as the root device in the block device mapping for the instance.



## **START:**

1. When the instance is started, it enters into pending state and then into running
2. An instance when stopped and started is launched on a new host
3. Any data on an instance store volume (not root volume) would be lost while data on the EBS volume persists

## **Instance reboot:**

1. Both EBS-backed and Instance store-backed instances can be rebooted
2. An instance retains its public DNS, public and private IP address during the reboot
3. Data on the EBS and Instance store volume is also retained
4. Amazon recommends to use Amazon EC2 to reboot the instance instead of running the operating system reboot command from your instance as it performs a hard reboot if the instance does not cleanly shutdown within four minutes also creates an API record in CloudTrail, if enabled.

## **Instance Termination:**

1. An instance can be terminated, and it enters into the shutting-down and then the terminated state
2. After an instance is terminated, it can't be connected and no charges are incurred
3. EBS-backed instance supports Instance Initiated Shutdown Behaviour attribute which determines whether the instance would be stopped or terminated when a shutdown command is initiated from the instance itself for e.g. shutdown, halt or power off command in Linux
4. Default behaviour for the instance to be stopped.
5. A shutdown command for an Instance store-backed instance will always terminate the instance

Characteristic	Reboot	Stop/start (Amazon EBS-backed instances only)	Hibernate (Amazon EBS-backed instances only)	Terminate
Private and public IPv4 addresses	These addresses stay the same	The instance keeps its private IPv4 address. The instance gets a new public IPv4 address, unless it has an Elastic IP address, which doesn't change during a stop/start.	The instance keeps its private IPv4 address. The instance gets a new public IPv4 address, unless it has an Elastic IP address, which doesn't change during a stop/start.	None