Status	Finished
Started	Sunday, 11 October 2026, 2:27 PM
Completed	Sunday, 11 October 2026, 2:37 PM
Duration	10 mins 3 secs
Grade	**11.00** out of 15.00 (**73.33**%)

Question **1**

Incorrect

Mark 0.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

a. A new set will be created with the unique elements of set1 and set2. ✗

b. A new set will be created with the elements of both set1 and set2

c. Elements of set1 will get appended to set2

d. Elements of set2 will get appended to set1

Question **2**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. (25,19,18,17)

b. (16,17,18)

c. (16,17,18,19) ✓

d. Error

Question **3**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. Yes, No ✓

b. "==" is not supported for set in Python

c. No, No

d. Yes, Yes

Question **4**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain only strings as its elements.

b. In Python, a tuple can contain only integers as its elements.

c. In Python, a tuple can contain either string or integer but not both at a time.

d. In Python, a tuple can contain both integers and strings as its elements. ✓

Question **5**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {4} ✓

b. {2}

c. {1,3,2}

d. {1,3,4}

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

a. (1,2,3)(4,5,6)

b. Error

c. (1,2,3,3,2,1)

d. (1,2,3,4,5,6) ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. True ✓

True

b. False

True

c. True

False

d. False

False

Question **8**

Correct

Mark 1.00 out of 1.00

```
What is the output of the following code?
```

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

b. (30, 40, 50)(40, 50, 60, 70, 80)

c. (30, 40, 50) (10, 20, 30, 40)

d. (10, 20, 30, 40) (40, 50, 60, 70, 80)

Question **9**

Incorrect

Mark 0.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

- a. Error ✗
- b. 2
- c. 117
- d. 100

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

- a. SynatxError: Different types cannot be used with sets
- b. {40, 10, 50, 20, 60, 30}
- c. {40, '10', 50, 20, 60, 30}
- d. {40, 10, '10', 50, 20, 60, 30} ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

- a. i,iii ✓
- b. i,ii
- c. ii,iv
- d. iii,iv

Question **12**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

- a. We can change the tuple once created
- b. None of these
- c. A tuple maintains the order of items ✓
- d. A tuple is unordered

Question **13**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
my_t1 = (1, 2, 3, 4)
my_t1.append( (5, 6, 7) )
print(len(my_t1))
```

- a. 5
- b. 2
- c. 1
- d. Error ✓

Question **14**

Incorrect

Mark 0.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. (1, 4, 8)

b. [1, 2, 4, 3, 8, 9] ✗

c. [1, 4, 8]

d. [2, 3, 9]

Question **15**

Incorrect

Mark 0.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['8', '30', '3', '2']

b. ['2', '3', '8', '30']

c. ['30', '8', '3', '2'] ✗

d. ['2', '3', '30', '8']