RAJALAKSHMI ENGINEERING COLLEGE

RAJALAKSHMI NAGAR, THANDALAM _ 602 105



CS23331 - DESIGN AND ANALYSIS OF ALGORITHMS

Laboratory Record Note Book

Name : Vishwa T

Year / Branch / Section : 2nd year-Computer Science and Design

University Register No. : 2116251701062

College Roll No. : 251701062

Semester : 3rd

Academic Year : 2025-2026

INDEX PAGE

Exp.No	Name of the Experiment	Date of Completion
1.	Finding Complexity using Counter method	26/08/2026
2.	Finding Complexity using Counter method	26/08/2026
3.	Finding Complexity using Counter method	26/08/2026
4.	Finding Complexity using Counter method	11/10/2026
5.	Finding Complexity using Counter method	11/10/2026
6.	1-G Coin Problem	28/09/2026
7.	2-G Cookies Problem	28/09/2026
8.	3-G Burger Problem	10/10/2026
9.	4-G Array Sum max problem	28/09/2026
10.	5-G Product of Array elements-Minimum	28/09/2026

11.	**1-Number of Zeros in a Given Array**	**28/09/2026**
12.	**2-Majority Element**	**28/09/2026**
13.	**3-Finding Floor Value**	**28/09/2026**
14.	**4-Two Elements sum to x**	**30/09/2026**
15.	**5-Implementation of Quick Sort**	**30/09/2026**
16.	**1-DP-Playing with Numbers**	**05/10/2026**
17.	**2-DP-Playing with Chessboard**	**07/10/2026**
18.	**3-DP-Longest Common Subsequence**	**07/10/2026**
19.	**4-DP-Longest non-decreasing Subsequence**	**07/10/2026**

Started on	Wednesday, 26 August 2026, 10:24 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 10:32 PM
Time taken	7 mins 52 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
```

```
{
    int i= 1;
    int s =1;
    while(s <= n)
    {
        i++;
        s += i;
    }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

Reset answer

```c
#include<stdio.h>
int main() {
    int n;
    int count = 0;

    if(scanf("%d", &n) != 1){
        return 0;
    }

    int i = 1;
    count++;
    int s = 1;
    count++;

    count++;
    while (s <= n){
        count++;
        i++;

        count++;
        s += i;
        count++;
    }
    printf("%d\n", count);
    return 0;
}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 26 August 2026, 10:52 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 11:09 PM
Time taken	16 mins 21 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

Reset answer

```c
#include<stdio.h>
void func(int n){
    int count = 0;
    count++;
    if(n == -1){
        count++;
    }
    else{
        count++;
        for(int i=1;i <= n;i++){
            count++;
            count++;
            for(int j=1;j <= n;j++){
                count++;
                count++;

                break;
            }

            count++;
        }
    }
    printf("%d",count);
}
int main(){
    int n;
    scanf("%d",&n);
    func(n);
    return 0;
}
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 26 August 2026, 11:10 PM
State	Finished
Completed on	Wednesday, 26 August 2026, 11:16 PM
Time taken	5 mins 48 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```c
#include<stdio.h>
int main(){
    int n,i,count=0,counter = 0;
    scanf("%d",&n);
    for(i = 1;i <= n;i++){
        counter++;
        if(n%i == 0)
        count++;
    }
    counter += n+1;
    counter += count;
    printf("%d",counter);
    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔

	Input	Expected	Got	
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Sunday, 11 October 2026, 1:27 PM
State	Finished
Completed on	Sunday, 11 October 2026, 2:15 PM
Time taken	47 mins 33 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```c
#include <stdio.h>
int main()
{
    int n;
    scanf("%d",&n);
    int c=0;
    c++;
    c++;

    for (int i = n/2;i<n;i++)
    {
        c++;
        c++;

    for (int j=1;j<n;j=2*j)
{
    c++;
    c++;
    for (int j=1;j<n;j=2*j)
{
    c++;
    c++;
}
}
}

    printf("%d", c);

    return 0;
}
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Sunday, 11 October 2026, 2:16 PM
State	Finished
Completed on	Sunday, 11 October 2026, 2:17 PM
Time taken	53 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```c
#include<stdio.h>
int main()
{
    int n,rev=0,remainder;
    int c=0;
    scanf("%d",&n);


    c++;
    c++;
    c++;
    while (n!=0)
    {
        c++;
        remainder=n%10;

        c++;
        rev=rev*10+remainder;

        c++;
        n/=10;

        c++;
    }

    printf("%d",c);
    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

RAJALAKSHMI ENGINEERING COLLEGE

Vishwa T 251701062-2025-CSD

V2

Started on	Monday, 28 September 2026, 8:29 PM
State	Finished
Completed on	Monday, 28 September 2026, 8:31 PM
Time taken	1 min 31 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int v, count = 0;
    int coins[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
```

```
    scanf("%d", &v);

    for (int i = 0; i < 9; i++) {
        count += v / coins[i];
        v = v % coins[i];
    }

    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Vishwa T 251701062-2025-CSD

V2

Started on	Monday, 28 September 2026, 8:31 PM
State	Finished
Completed on	Monday, 28 September 2026, 8:31 PM
Time taken	31 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b) {
    return (*(int *)a - *(int *)b);
}

int main() {
    int n, m;
    scanf("%d", &n);

    int g[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &g[i]);

    scanf("%d", &m);

    int s[m];
    for (int i = 0; i < m; i++)
        scanf("%d", &s[i]);

    qsort(g, n, sizeof(int), compare);
    qsort(s, m, sizeof(int), compare);

    int i = 0, j = 0, count = 0;

    while (i < n && j < m) {
        if (s[j] >= g[i]) {
            count++;
            i++;
        }
        j++;
```

```
    }

    printf("%d", count);

    return 0;
}
```

	Input	Expected	Got	
✔	2 1 2 3 1 2 3	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Started on	Saturday, 10 October 2026, 8:21 PM
State	Finished
Completed on	Saturday, 10 October 2026, 8:57 PM
Time taken	35 mins 38 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3

burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2)$ = 1 + 9 + 18 = 28.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance

he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

3

5 10 7

Sample Output

76

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int a[n];
    for(int i=0;i<n;i++)
    {
        scanf("%d",&a[i]);
    }
    for(int i=0;i<n-1;i++)
    {
        for(int j=i+1;j<n;j++)
        {
            if(a[i]<a[j])
            {
                int temp=a[i];
                a[i]=a[j];
                a[j]=temp;
            }
        }
    }
    long long ans=0;
    long long p=1;
    for(int i=0;i<n;i++){
        ans +=(long long)a[i]*p;
        p*=n;
    }printf("%lld",ans);
```

```
28      return 0;
29  }
```

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 2	4 7 4 9 6	389	389	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Monday, 28 September 2026, 9:00 PM
State	Finished
Completed on	Monday, 28 September 2026, 9:08 PM
Time taken	7 mins 54 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
#include<stdlib.h>
int compare(const void *a,const void *b)
{
    return(*(int *)a - *(int *)b);
}
int main(){
    int n;
    scanf("%d",&n);
```

```
    int arr[n];
    for (int i=0;i<n;i++)
        scanf("%d",&arr[i]);
    qsort(arr,n,sizeof(int),compare);
    long long sum =0;
    for(int i=0;i<n;i++)
        sum += (long long)arr[i]*i;
    printf("%lld",sum);
    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Monday, 28 September 2026, 9:10 PM
State	Finished
Completed on	Monday, 28 September 2026, 9:23 PM
Time taken	13 mins 13 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
#include<stdlib.h>
int compare(const void *a,const void *b)
{
    return(*(int *)a - *(int *)b);
}
int main(){
    int n;
    scanf("%d",&n);

    int a[n],b[n];

    for(int i=0;i<n;i++)
```

```
14          scanf("%d",&a[i]);
15
16      for(int i=0;i<n;i++)
17          scanf("%d",&b[i]);
18
19      qsort(a,n,sizeof(int),compare);
20      qsort(b,n,sizeof(int),compare);
21
22      int sum = 0;
23      for(int i=0;i<n;i++)
24          sum += a[i]*b[n-1-i];
25      printf("%d",sum);
26
27      return 0;
28
29  }
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔

	Input	Expected	Got	
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Monday, 28 September 2026, 3:26 PM
State	Finished
Completed on	Monday, 28 September 2026, 3:28 PM
Time taken	1 min 42 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int firstZero(int arr[], int low, int high) {
    if (low > high)
        return -1;

    int mid = low + (high - low) / 2;

    // Check if arr[mid] is the first zero
    if (arr[mid] == 0 && (mid == 0 || arr[mid - 1] == 1))
        return mid;

    if (arr[mid] == 1)
        return firstZero(arr, mid + 1, high);
    else
        return firstZero(arr, low, mid - 1);
```

```c
}

int main() {
    int m;
    scanf("%d", &m);

    int arr[m];

    for (int i = 0; i < m; i++) {
        scanf("%d", &arr[i]);
    }

    int index = firstZero(arr, 0, m - 1);

    int count;
    if (index == -1)
        count = 0;
    else
        count = m - index;

    printf("%d\n", count);

    return 0;
}

```

	Input	Expected	Got	
✔	5 1 1 1 0 0	2	2	✔
✔	10 1 1 1 1 1 1 1 1 1 1	0	0	✔

	Input	Expected	Got	
✔	8 0 0 0 0 0 0 0 0	8	8	✔

	Input	Expected	Got	
✔	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Vishwa T 251701062-2025-CSD

V2

Started on	Monday, 28 September 2026, 3:29 PM
State	Finished
Completed on	Monday, 28 September 2026, 9:23 PM
Time taken	5 hours 54 mins
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
//😂😂😂😊😊😂😂😊😊😊
#include <stdio.h>

int countOccurrences(int nums[], int left, int right, int target) {
    int count = 0;

    for (int i = left; i <= right; i++) {
        if (nums[i] == target)
            count++;
    }

    return count;
}

int majorityElement(int nums[], int left, int right) {
    // Only one element
    if (left == right)
        return nums[left];

    int mid = left + (right - left) / 2;

    int leftMajority = majorityElement(nums, left, mid);
    int rightMajority = majorityElement(nums, mid + 1, right);

    // Both halves have the same majority element
```

```
    if (leftMajority == rightMajority)
        return leftMajority;

    int leftCount = countOccurrences(nums, left, right, leftMajority);
    int rightCount = countOccurrences(nums, left, right, rightMajority);

    return (leftCount > rightCount) ? leftMajority : rightMajority;
}

int main() {
    int n;
    scanf("%d", &n);

    int nums[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &nums[i]);
    }

    printf("%d\n", majorityElement(nums, 0, n - 1));

    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Started on	Monday, 28 September 2026, 9:29 PM
State	Finished
Completed on	Monday, 28 September 2026, 9:48 PM
Time taken	18 mins 30 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int findFloor(int a[],int low,int high,int x)
{
    if(low > high)
        return-1;

    if(x>=a[high])
        return a[high];

    if(x<a[low])
        return-1;

    int mid = (low+high)/2;

    if(a[mid]==x)
```

```
        return a[mid];

    if(a[mid] < x)
    {
        int result = findFloor(a,mid +1,high,x);

        if(result == -1)
            return a[mid];
        return result;
    }
    return findFloor(a,low,mid-1,x);
}

int main()
{
    int n,x;
    scanf("%d",&n);
    int a[n];

    for(int i=0;i<n;i++)
        scanf("%d",&a[i]);
    scanf("%d",&x);
    printf("%d",findFloor(a,0,n-1,x));
    return 0;
}
```

	Input	Expected	Got	
✔	6 1 2 8 10 12 19 5	2	2	✔
✔	5 10 22 85 108 129 100	85	85	✔

	Input	Expected	Got	
✔	7 3 5 7 9 11 13 15 10	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 30 September 2026, 9:11 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 9:23 PM
Time taken	12 mins 16 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as “No”.

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value “x”)

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int findPair(int arr[],int left,int right,int x,int*a,int*b)
{
    if(left >= right)
        return 0;

    if(arr[left] + arr[right] == x)
    {
        *a = arr[left];
        *b = arr[right];
        return 1;

    }

    if(arr[left] + arr[right] < x)
        return findPair(arr,left + 1,right,x,a,b);
```

```
    else
        return findPair(arr,left,right - 1,x,a,b);
}

int main()
{
    int n,x,i;
    int arr[100];
    int a,b;
    scanf("%d",&n);

    for(i= 0;i<n;i++)
        scanf("%d",&arr[i]);

    scanf("%d",&x);

    if(findPair(arr,0,n-1,x,&a,&b))
    {
        printf("%d\n",a);
        printf("%d\n",b);
    }
    else
    {
        printf("No\n");
    }
    return 0;
}
```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 30 September 2026, 9:26 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 9:41 PM
Time taken	15 mins 39 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:

The first line contains the no of elements in the list-n

The next n lines contain the elements.

Output:

Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

Answer:

```
#include<stdio.h>
void quickSort(int a[],int low,int high)
{
    int i,j,pivot,temp;

    if(low<high)
    {
        pivot = a[low];
        i = low;
        j = high;
```

```
        while(i<j)
        {
            while(a[i] <= pivot && i < high)
                i++;
            while(a[j] > pivot)
                j--;

            if(i < j)
            {
                temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }
        }

        temp = a[low];
        a[low] = a[j];
        a[j] = temp;

        quickSort(a,low,j - 1);
        quickSort(a,j + 1,high);
    }
}

int main()
{
    int n,i;
    int a[100];

    scanf("%d",&n);

    for(i = 0;i<n;i++)
    {
        scanf("%d",&a[i]);
    }
    quickSort(a,0,n - 1);
    for(i = 0;i<n;i++)
```

```
49          printf("%d ",a[i]);
50      return 0;
51  }
```

	Input	Expected	Got	
✔	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✔
✔	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✔
✔	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Monday, 5 October 2026, 8:15 AM
State	Finished
Completed on	Monday, 5 October 2026, 8:20 AM
Time taken	5 mins
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer ‘n’ and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: *6*
Output:*6*
Explanation: *There are 6 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1
3+3
1+1+1+3
1+1+3+1
1+3+1+1
3+1+1+1

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways ‘n’ can be represented using 1 and 3

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    long long dp[n + 1];
    dp[0] = 1;

    for (int i = 1; i <= n; i++) {
        dp[i] = dp[i - 1];

        if (i >= 3) {
            dp[i] += dp[i - 3];
        }
    }

    printf("%lld", dp[n]);

    return 0;
}
```

	Input	Expected	Got	
✔	6	6	6	✔
✔	25	8641	8641	✔
✔	100	24382819596721629	24382819596721629	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Started on	Wednesday, 7 October 2026, 9:40 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 9:49 PM
Time taken	9 mins 3 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>

int main(){
    int n, a[100][100];
    scanf("%d", &n);

    for(int i = 0; i < n; i++)
    for(int j = 0; j < n; j++)
    scanf("%d", &a[i][j]);

    for(int i=0;i<n;i++)
    for(int j=0;j<n;j++) {
        if(i>0 && j>0)
                a[i][j] += a[i-1][j]
> a[i][j-1] ? a[i-1][j] : a[i][j-1];
        else if(i>0)
            a[i][j] += a[i-1]
[j];
        else if(j>0)
            a[i][j] += a[i]
[j-1];
    }
    printf("%d", a[n-1][n-1]);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 4 2 3 4 8 7 1	19	19	✔
✔	3 1 3 1 1 5 1 4 2 1	12	12	✔
✔	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Started on	Wednesday, 7 October 2026, 9:54 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 10:05 PM
Time taken	10 mins 51 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1		a	g	**g**	**t**	**a**	**b**
s2	**g**	x	**t**	**x**	**a**	**y**	**b**

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
#include<string.h>

int main()
{
    char s1[100],s2[100];
    int dp[101][101];
    int i,j;

    scanf("%s",s1);
    scanf("%s",s2);

    int n = strlen(s1);
    int m = strlen(s2);
    for(i = 0; i<=n;i++)
    {
        for(j = 0;j<=m;j++)
        {
            if(i == 0 || j == 0)
                dp[i][j] = 0;
            else if(s1[i - 1] == s2[j - 1])
                dp[i][j] = dp[i - 1][j - 1] + 1;
            else
            {
                if(dp[i - 1][j] > dp[i][j-1])
                    dp[i][j] = dp[i - 1][j];
                else
                    dp[i][j] = dp[i][j - 1];

            }
        }
    }
    printf("%d",dp[n][m]);
    return 0;
}
```

	Input	Expected	Got	
✔	aab azb	2	2	✔
✔	ABCD ABCD	4	4	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 7 October 2026, 10:06 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 10:15 PM
Time taken	8 mins 46 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>

int main(){
    int n;
    scanf("%d",&n);
    int a[n], dp[n];
    int i,j,max = 1;
    for(i = 0;i < n;i++){
        scanf("%d",&a[i]);
        dp[i] = 1;
    }
    for(i = 1;i < n;i++){
        for(j = 0; j < i;j++){
            if(a[j] <= a[i]&& dp[j] + 1 > dp[i]){
                dp[i] = dp[j] + 1;
            }
        }
```

```
        if(dp[i] > max)
            max = dp[i];

    }
    printf("%d",max);

    return 0;
}
```

	Input	Expected	Got	
✔	9 -1 3 4 5 2 2 2 2 3	6	6	✔
✔	7 1 2 2 4 5 7 6	6	6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.