

Android VisionableSDK v1.3.23 Release Notes (Jun 11, 2026)

CHANGES/FIXES

Fix intermittent crash during frame publishing caused by resizing video (camera resolution)

Fix intermittent crash during device list fetching

V1.3.22 RELEASE NOTES

CHANGES/FIXES

Updated JSON serialization and deserialization for ModeratorSDK

V1.3.21 RELEASE NOTES

CHANGES/FIXES

Enhanced frame handling performance within the underlying video library and optimized SDK publishing

V1.3.20 RELEASE NOTES

CHANGES/FIXES

PTZ Control and info enhancements, to support better remote and local control

V1.3.19.1 RELEASE NOTES

CHANGES/FIXES

Added sanity checks and memory alignment for in memory sharing feature.

Fixed returned frame size for in memory sharing feature

V1.3.19 RELEASE NOTES

CHANGES/FIXES

Fixed in memory sharing crashing and RGB sharing support

V1.3.18.1 RELEASE NOTES

CHANGES/FIXES

Fixed issue with ModeratorSDK commands publishing to meeting

V1.3.18 RELEASE NOTES

CHANGES/FIXES

FFmpeg version upgrade to 8.0

Android 16KB support

Provide API to set userAgent from client side for internal https requests

V1.3.17 RELEASE NOTES

CHANGES/FIXES

Fixed crash in underlying video library

V1.3.16 RELEASE NOTES

CHANGES/FIXES

Added Mute\unmute callback for local participant

Added moderator disabled device callback

Updated Moderator SDK to work in request - response mode to avoid waiting for response from client

Updated Moderator SDK to send request status instead of failure only

BREAKING: participantAmplitudeChanged is no longer sent when local user got microphone enabled \ disabled

BREAKING: ModeratorSDK delegate no longer uses callbacks for onRequest methods. Instead requestId is passed to client and should be used later with sendModeratorResponse

V1.3.15 RELEASE NOTES

CHANGES/FIXES

Fix high memory usage when reported resolution is negative

Fix GETROOT timeout that occurs after system suspend and resume

V1.3.14 RELEASE NOTES

CHANGES/FIXES

Added participantAmplitudeChanged notification when local participant is muted \ unmuted

Added deviceListUpdated notification when local participant is muted \ unmuted

Fixed loss, jitter and network bars values for network conditions update

Fixed check if local participant is moderator

Android SDK version increment to match other platforms

V1.3.11 RELEASE NOTES

CHANGES/FIXES

Moderator SDK commands support for Android

V1.3.10 RELEASE NOTES

CHANGES/FIXES

Fixed crash during network conditions processing

Fixed issue with Android rotation for Android versions < 12

Enhance NAT traversal logging for IGAudio in IGVideo

Update SDK logging to close file on name change

V1.3.9 RELEASE NOTES

CHANGES/FIXES

Update of dependency libraries.

Network statistics codec profile name fix

V1.3.8 RELEASE NOTES

CHANGES/FIXES

Fixed crash on during join to meeting

V1.3.7 RELEASE NOTES:

CHANGES/FIXES

Correct AudioStreamCondition and VideoStreamCondition member types

V1.3.6 RELEASE NOTES:

CHANGES/FIXES

Update logging to open file once and flush content after full log message has been written to
filestream

V1.3.5 RELEASE NOTES:

CHANGES/FIXES

Updated Audio and Video library dependencies

Corrected Network Stats types and added streamId

Fixed issue with displaying camera buffer on Android device rotation

Added configuration capability to Audio and Video

V1.3.3 RELEASE NOTES:

CHANGES/FIXES

No changes, bump version to match other platform SDKs

V1.3.1 RELEASE NOTES:

API CHANGES

Added new callbacks for audio and video network conditions.

public void audioConditionUpdate(AudioCondition ac);

public void videoConditionUpdate(VideoCondition ac);

Added dedicated objects for conditions data:

AudioCondition – represents general audio network condition and contains data for audio streams

AudioStreamCondition - represents audio stream specific network conditions

VideoCondition - represents general video network condition and contains data for video streams

VideoStreamCondition - represents video stream specific network conditions

CHANGES/FIXES

Minor fixes in jni layer for typing (int32_t and int64_t objects).

KNOWN ISSUES

Same as in v1.3.0

V1.3.0 RELEASE NOTES:

API CHANGES

Added APIs to allow for an “Image Capture” device. This is a device that the application “creates” with an API call by specifying a directory to which image files can be written to (via a new API call) and from which the underlying video engine can read image files to be sent up into a meeting.

```
public static int enableImageCapture(String displayName,  
String directory, String mode)
```

Asks the SDK to create a new image device. The `displayName` parameter is the name that will appear in the corresponding `VideoInfo siteName` field for this stream. The `directory` parameter is an absolute path to a directory on the local device that can be written to. This absolute path **must** contain a trailing directory separator. The `mode` parameter is a screen sharing mode to be used for this stream (such as “BEST SCREEN”).

Returns an integer ID to be used with other API calls that need to reference this device.

Successful execution of this API call will generate an immediate `participantVideoAdded` callback for this user in all applications connected to the meeting.

```
public static boolean disableImageCapture(int deviceId)
```

Disables a previously created image capture device. The `deviceId` parameter is the identifier returned by the corresponding call to `enableImageCaptureDevice` (which created this capture device). Returns a `boolean` indicating whether or not the call was successful

```
public static boolean imageCapturePutImage(int deviceId,  
byte [] imageBuffer, int width, int height, int size)
```

Send a YUV420P image into the meeting for the specified device. The `deviceId` parameter is the identifier returned by the call to `enableImageCaptureDevice` the application used to create the capture device being used. The `imageBuffer` parameter is a byte array containing an unpadded YUV420P image. The `width` and `height` parameters are the width and height of the image, respectively. The `size` parameter is the size of the byte array being passed in. Returns a Boolean indicating whether or not the image was successfully received.

CHANGES/FIXES

Fixed bug that prevented background blurring from persisting when a device is rotated.

KNOWN ISSUES

While the ability to specify a dedicated Looper upon which all delegate methods are invoked, the current Android MeetingSDK does not attempt to create a dedicated Looper if one is not specified. This will result in all delegate method calls being made on the same thread being used to parse low-level audio and video events coming from our audio/video engine.