

Apple MeetingSDK v0.5.18 Release Notes. (April 19, 2023)

NOTE:

Version 0.5.x of the Visionable Apple MeetingSDK is a transitional release that begins to expose functionality available in Visionable's "V3" server architecture. As this architecture is not expected to be in production until 1Q2023, any 0.5.x releases of the MeetingSDK are likely to be unstable and change frequently.

If you are looking to write an application that interfaces with Visionable's V2 architecture, you should remain with v0.4 of the MeetingSDK.

We expect that stability will be established against the V3 architecture with v0.6 of the SDK due when the V3 architecture officially goes into production.

OVERARCHING CHANGES (this text present for ALL v0.5.x releases)

Starting with v0.5, the Visionable MeetingSDK has been re-architected to rely on a layer of cross-platform C++-based code to manage the parsing of XML objects coming from our audio/video engine, for establishing model objects representing Meetings and Participants, and for firing "delegate methods/callbacks" notifying your application of changes in state for the current meeting. Prior to v0.5, these functions were individually implemented per-platform supported in that platform's native language. Moving all of this functionality into a common, C++ codebase should result in consistent behavior when dealing with Visionable back-end servers.

CONNECTING TO V3 SERVERS (this text present for ALL v0.5.x releases)

In Visionable's V3 architecture, a special token (referred to as an MJWT token) is required to join a meeting. There are two types of MJWT tokens: a *guest* MJWT token that doesn't correspond to Visionable user and an *authenticated* MJWT token that is obtained by passing a JWT token obtained from Visionable's authentication system (not covered here). To retrieve an MJWT token, use the new `initializeMeetingWithToken` API call *instead of* the original `initializeMeeting` API call (which is used only with V2 servers).

```
public func initializeMeetingWithToken(meetingUUID: String,  
server: String, token: String?, completion: @escaping  
(Bool,String) -> ( ))
```

This function still takes a `meetingUUID` and a `server` name but now also takes a `token` parameter that is either `nil` if you wish to obtain a guest MJWT or it contains a JWT token if you want to obtain an authenticated MJWT.

The completion routine for `initializeMeetingWithToken` now is called with a second parameter (String) that contains the MJWT token (guest or authenticated).

Once you obtain an MJWT, you now join the meeting with a call to `joinMeetingWithToken`:

```
public func joinMeetingWithToken(server: String, meetingUUID:
String, token: String, userUUID: String = "", name: String,
completion: @escaping (Bool) -> ( ))
```

This function takes the `server` name you are connecting to, the `meetingUUID` for the meeting, the MJWT in the `token` parameter, an option `userUUID` to be associated with the user (pass an empty string to have the SDK generate a `userUUID`), and the `name` of the user to be shown in the meeting.

Using these two calls will allow you to connect to a V3 meeting. Once connected, all other SDK functionality is the same as with V2 servers.

CONNECTING TO V2 SERVERS

The APIs for connecting to V2 servers have changed slightly. The `initializeMeeting` API call now looks like this:

```
public func initializeMeeting(meetingUUID: String, server:
String, completion: @escaping (Bool,String) -> ( ))
```

The completion routine now is called with a second argument that is the AES256 encryption key used for the meeting. Previous SDKs just cached this internally, however now you need to receive it from `initializeMeeting` and pass it to the `joinMeeting` call.

The `joinMeeting` call now requires you to pass all connection parameters. If the “`userUUID`” parameter is an empty string, the SDK will generate a guest-based identifier to associate with this participant:

```
public func joinMeeting(server: String, meetingUUID: String,
key: String, userUUID: String = "", name: String, completion:
@escaping (Bool) -> ( ))
```

See previous release notes in the v0.5.x series for API changes that were new in previous releases. The rest of these release notes pertain only to the v0.5.18 release.

API CHANGES

None

CHANGES/FIXES

A fix to resolve an issue with desktop share highlighting not being disabled properly when multiple desktops are being shared and then sharing is stopped for one of them.

A fix to prevent potential crashes if a meeting is joined while a video preview is still active. Note that while the crash has been resolved, attempting to join a meeting and enable a camera while a preview for the same camera is still active is not supported.

Added more complete logging statements when MeetingDelegate callbacks are invoked.

KNOWN ISSUES

The new `previewVideoUpdated` delegate method may *not* be called when a device rotates. This will be resolved in a future SDK release.

In support of the new threading model, all delegate methods are executed on a serial `OperationQueue` that is created by the SDK. Future versions will allow you to specify an `OperationQueue` that you create (or use the main queue)

The `VideoView.isScreenShare()` API call will likely return `true` for non screen-share video streams if they are being sent at 4K resolution.

The online documentation for the Apple MeetingSDK does not reflect the API changes made in the v0.5.10 release nor the logfile changes made in the v0.5.15 release.