

CMPT 331 - SPRING 2022 - DR. LABOUSEUR

Programming In The Past

Jake Vissicchio
Jake.Vissicchio1@Marist.edu

September 27, 2022

1 Log

Log		
Date:	Hours Spent:	Tasks/Accomplishments/Issues/Thoughts:
2/18	1	In Fortran you need to know the actual length of a string variable which could be really annoying if you have a long string
2/18	2	I kept getting this error "non-conforming tab character". I was able to fix it by removing all tabs but now the code is much harder to read so that is pretty annoying
2/18	3	Having trouble figuring out how to get each character in my string. Also just realized I am already off on my prediction. Also having trouble thinking of the math to handle when we reach the end of the alphabet to go back to the start after shifting
2/18	4	Tested "THIS IS A STRING FROM ALAN" and realized I need to add an if statement to not shift the ASCII for spaces which converts to 32. So now it works. I think decrypt shouldn't be too bad since its just encrypting backwards instead of forwards
2/18	4 1/2	I was right about it not being bad at all so that's good. Onto solve
2/18	5	I thought I understood solve but I am getting a runtime error. My problem could stem from the fact that I have in encrypt that the string has a length of 26 while the string I want to solve is "HAL" and that has a length of 3. I need to find a way for it to find out the length of the string passed to it without being hardcoded.
2/18	5 1/2	Solve now works with "HAL". I also set a toUpper subroutine which was funny because most languages just have an easy toUpperCase method or some sort, but this one effects the spaces too so it won't work in this case.
2/19	6	Moving onto Pascal and thinking it won't take nearly as long as Fortran.
2/19	6 1/2	Really weird issue in if/else statements and I finally figured out what was wrong. Turns out you put no semicolon for the if statement but you do for the else
2/19	6 1/2	Now I am getting the error "Operator is not overloaded"
2/19	6 3/4	Turns out my parentheses were off in my math. ZABC now works as intended for Encrypt.

page 2 of 18

Log ctnd.

Date:	Hours Spent:	Tasks/Accomplishments/Issues/Thoughts:
2/19	7	Decrypt is not working as intended, I believe my math might be slightly off because I am getting weird characters.
2/19	7 1/4	For some reason the program believes $-1 \bmod 26 = -1$ when it should equal 25.

2 Commentary

This section includes random thoughts that came to my head while I was doing the assignment (sort of like a diary).

2.1 Fortran

- Starting out with Fortran. I'm using ideone and just making a Hello World Program and so far not too complicated.
- What's the deal with all of these '*'s.
- Writing lines without a semicolon at the end just feels wrong.
- String variables are obnoxious. `character(x)`
- ifs aren't too bad considering it's kind of like how you would say it in so the "then" makes sense.
- I saw something that says implicit none should always be used in the beginning so I'm going to take their advice. It prevents confusion which is always good.
- `do` is the keyword for handling loops which is not too confusing
- subroutines seem a little confusing with `intent(in)` and `intent(inout)`
- I caught myself accidentally typing a bracket when making my encrypt subroutine. Makes me miss Java.
- `'!'` as a comment identifier is a little odd but it works
- non-conforming tab member is an extremely obnoxious error and the only way I found out how to fix it was making my code harder to read
- noticed you cannot declare `i` as an integer in the same line of the `do` statement unlike in Java when you can easily say `int i = 0` right in the `for` statement
- I found `achar` and `iachar` to convert `ascii` and strings which will help with the shifting
- I found that you can use strings kind of like arrays allowing you to get a specific index or character with `(x:x)` with `x` being an integer
- So for encrypt I can loop through the string getting each character and shifting it then move to the next character.
- the math is kind of difficult so I started testing in visual studio with Java

to find out how to make 90 go to 65 when adding 1.

- After doing some research on caesar ciphers and found a discrete math video. I saw the math without ASCII values would be the $(value + shift) \% 26$. (26 represents the total number of letters in the alphabet) So we can do the math with ASCII values by first subtracting 65, which is 'A' in ASCII, from the value, then add the shift, then mod 26 which will give the remainder which would be number from 0 - 25 depending on our value, then adding the 65 back in, which should give us the final index for the shift.

- there is no `x%y` for mod in fortran, instead you put `modulo(x, y)` which is kind of weird

- a little after writing 4 3/4 in the log I realized the problem could be because I forgot to put `write within solve` so that could be why it is not printing anything. - nevermind, still getting a runtime error

- also realized I can call `encrypt` inside of `decrypt` and `solve` since it reuses a lot of code

- after doing a lot of research I found `character(*)` which assumes the length of the string passed. It must be a dummy argument or a `PARAMETER` or else I get an error so it won't actually work in the first declaration at the top.

- `Solve` prints kind of weird, the numbers are very far right from "Caesar " but it works

2.2 PASCAL

- Still using ideone. Printed "Hello World"

- variables are interesting. I usually tend to put my variables at the top anyway for neatness so it actually is a really good idea to force neatness on programmers since it will really help in group settings.

- familiar with `:=` because Alan++ uses it. I also like it because it adds a layer of readability since it allows you not to confuse `"="` with `"=="`

- the for loops have a very "English" feel with it having keywords like `"to"` and `"do"` which increase readability but slows down writability

- `begin` and `end` are basically `" "` and `" "` in other languages like java but I do have to say I like the brackets better much more writable

- similar to what I did for Fortran I can treat my string as an array and go through each letter and shift them
- instead of using iachar and achar like I did for Fortran, it has chr and ord
- Pascal was a nice step up from Fortran.

2.3 Scala

- Still using ideone. Printed "Hello World". One weird thing I noticed is how long it takes to compile compared to the other languages.
- while researching I notice it being quite similar to Java with its use of objects and brackets.
- Scala for loops using "i-" is good in a readable perspective however it's kind of annoying the write.
- The errors are really annoying and do not give a lot of context
- I was able to get encrypt to print properly but it took some hair pulling on the way.
- I was able to get decrypt to print properly after foolishly being confused why I was going back double until I realized it's because I was negatively shifting from the original string rather than the new encrypted string so I needed to make use of return in my methods.
- Honestly do not have a ton to say about Scala since using it just kind of felt like a "poor-man's" Java, but I do really enjoy it since it's readable and more writable than the languages I have worked on so far.

2.4 Ruby

- Wow Ruby looks incredibly simple at a glance. Has a similar feel to Python.
- I used a similar implementation to Scala and it was able to work well.
- I used str.bytes with str being a String which allows me to get an array of ASCII values to use for encrypt.
- The code is arguably very poorly readable but by far the easiest to write compared to the other languages in the project.

- This is most likely going in the top of my list because it was the least amount of hair pulled.
- I believe Ruby would be an amazing language to start with for beginners because of how lenient it is, however because it is too lenient I can see it causing a lot of problems with readability in a group setting.

3 Code Listings

3.1 Fortran

```
!The ide was having issues with indents so the code looks a little messy because
!of that
PROGRAM MAIN
implicit none
!variables
character(26) :: str = 'za bc'
integer :: shift = 1
!integer :: i
call toUpper(str)
print *, str
call encrypt(str, shift)
write(*,*) str
call decrypt(str, shift)
write(*,*) str
call solve('HAL', 26)

contains

subroutine encrypt(string, shiftAmount)
character(*) :: string
integer :: shiftAmount
integer :: i
!loop from 1 to the length of the given string
do i = 1, len(string)
!we need to skip spaces
if(iachar(string(i : i)) == 32) then
string(i : i) = achar(32)
else
string(i : i) = achar(modulo(iachar(string(i : i)) - 65 + shiftAmount, 26) + 65)
end if
end do
```

```

end subroutine

subroutine decrypt(string , shiftAmount)
character(*) :: string
!integer :: j
integer :: shiftAmount
!we need to inverse the shiftAmount to bring us back to where we started
shiftAmount = shiftAmount * (-1)
!integer :: j for some weird reason I was getting an error with
!declaring j here
!loop from 1 to the length of the given string
call encrypt(string , shiftAmount)
end subroutine

subroutine solve(string , maxShiftValue)
character(*) :: string
integer :: maxShiftValue
character(len(string)) :: tempString
integer :: k
!loop all the way to the maxShiftValue given , encrypting for
each value up until then
do k = 0, maxShiftValue
tempString = string
call encrypt(tempString , k)
write(*,*) 'Caesar ', k, ': ', tempString
end do
end subroutine

subroutine toUpper(string)
character(*) :: string
integer :: l
!loop from 1 to the length of the given string
do l = 1, len(string)
!we need to skip spaces
if(iachar(string(l : l)) >= 97 ) then
if (iachar(string(l : l)) <= 122 ) then
string(l : l) = achar(iachar(string(l : l)) - 32)
end if
end if
end do
end subroutine

END

```

3.2 Pascal

```
program ideone;
procedure encrypt(var myStr: string; shiftAmount: integer);
var
    i: integer;
    charVal: integer;
begin
    for i := 1 to length(myStr) do
    begin
        charVal := ord(myStr[i]);
        if (charVal = 32) then
            myStr[i] := chr(32)
        else
            begin
                if (shiftAmount < 0) then
                    shiftAmount := shiftAmount + 26;
                myStr[i] := chr(((ord(myStr[i]) - 65 + shiftAmount)
                    mod 26) + 65);
            end;
        end;
    end;
end;

procedure decrypt(var myStr: string; shiftAmount: integer);
begin
    shiftAmount := shiftAmount * -1;
    encrypt(myStr, shiftAmount);
end;

procedure solve(var myStr: string; maxShiftValue: integer);
var
    tempString: string;
    j: integer;
begin
    for j := 0 to maxShiftValue do
    begin
        tempString := myStr;
        encrypt(tempString, j);
        writeln('Caesar ', j, ': ', tempString);
    end;
end;

var
    str: string;
    shift: integer;
    solveStr: string;
```



```

        maxShift: integer;
        newStr: string;
begin
    str := 'za bc';
    shift := 1;
    newStr := upcase(str);
    writeln(newStr);
    encrypt(newStr, shift);
    writeln(newStr);
    decrypt(newStr, shift);
    writeln(newStr);
    solveStr := 'HAL';
    maxShift := 26;
    solve(solveStr, maxShift);
End.

```

3.3 Scala

```

object Main
{
    def main(args: Array[String])
    {
        var str: String = "zabc";
        var upperStr: String = "";
        upperStr = str.toUpperCase();
        var shift: Int = 1;
        println(upperStr);
        //this.encrypt(upperStr, shift);
        var encryptedString: String = this.encrypt(upperStr, shift);
        this.decrypt(encryptedString, shift);
        this.solve("HAL", 26);
    } //main

    def encrypt(myStr: String, shiftAmount: Int): String =
    {
        var i: Int = 0;
        var chars = myStr.toCharArray();
        var newShift: Int = shiftAmount;
        var newString: String = "";
        for (i <- chars)
        {
            if (i.toInt == 32)
            {
                print(" ");
                newString = newString + " ";
            }
        }
    }
}

```

```

        }
        else
        {
            if (shiftAmount < 0)
            {
                newShift = shiftAmount + 26;
            }
            var charNum = i.toInt;
            print((((charNum - 65 + newShift) % 26) + 65).toChar);
            newString = newString + (((charNum - 65 + newShift)
                % 26) + 65).toChar);
        }
    }//for
    println("");
    return newString;
} //encrypt

def decrypt (myStr: String, shiftAmount: Int)
{
    var inverseShift: Int = shiftAmount * -1;
    this.encrypt(myStr, inverseShift);
} //decrypt

def solve (myStr: String, maxShiftValue: Int)
{
    var tempStr: String = "";
    var j: Int = 0;
    for (j <- 0 to maxShiftValue)
    {
        tempStr = myStr;
        print (" Caesar " + j + ": ");
        this.encrypt(tempStr, j);
    }
} //solve
} //Main

```

3.4 Ruby

```

def encrypt (myStr, shiftAmount)
    i = 0;
    charNums = myStr.bytes;
    newStr = ""
    for i in 0...charNums.length do
        if charNums[i] == 32

```

```

        print (" ");
        newStr = newStr + " "
    else
        print (((charNums[i] - 65 + shiftAmount) % 26)
            + 65).chr);
        newStr = newStr + (((charNums[i] - 65 + shiftAmount)
            % 26) + 65).chr)
    end
end
puts (" ")
return newStr
end

def decrypt (myStr, shiftAmount)
    encrypt myStr, -shiftAmount
end

def solve (myStr, maxShiftValue)
    j = 0
    for j in 0...maxShiftValue + 1
        tempStr = myStr
        print "Caesar "
        print j
        print ": "
        encrypt tempStr, j
    end
end

end

str = "za bc"
shift = 1
str = str.upcase
puts str
encryptedStr = encrypt str, shift
decrypt encryptedStr, shift
solve "HAL", 26

```

4 Output

4.1 Fortran

```

!shift of 1
ZA BC
AB CD
ZA BC

```

Caesar	0	:HAL
Caesar	1	:IBM
Caesar	2	:JCN
Caesar	3	:KDO
Caesar	4	:LEP
Caesar	5	:MFQ
Caesar	6	:NGR
Caesar	7	:OHS
Caesar	8	:PIT
Caesar	9	:QJU
Caesar	10	:RKV
Caesar	11	:SLW
Caesar	12	:TMX
Caesar	13	:UNY
Caesar	14	:VOZ
Caesar	15	:WPA
Caesar	16	:XQB
Caesar	17	:YRC
Caesar	18	:ZSD
Caesar	19	:ATE
Caesar	20	:BUF
Caesar	21	:CVG
Caesar	22	:DWH
Caesar	23	:EXI
Caesar	24	:FYJ
Caesar	25	:GZK
Caesar	26	:HAL

!shift of 8

THIS IS A TEST STRING FROM ALAN
 BPQA QA I BMAB ABZQVO NZWU ITIV
 THIS IS A TEST STRING FROM ALAN

Caesar	0	:GZZGIQ
Caesar	1	:HAAHJR
Caesar	2	:IBBIKS
Caesar	3	:JCCJLT
Caesar	4	:KDDKMU
Caesar	5	:LEELNV
Caesar	6	:MFFMOW
Caesar	7	:NGGNPX
Caesar	8	:OHHOQY
Caesar	9	:PIIPRZ
Caesar	10	:QJJQSA
Caesar	11	:RKKRTB
Caesar	12	:SLLSUC
Caesar	13	:TMMIVD

Caesar	14	:UNNUWE
Caesar	15	:VOOVXF
Caesar	16	:WPFWYG
Caesar	17	:XQQXZH
Caesar	18	:YRRYAI
Caesar	19	:ZSSZBJ
Caesar	20	:ATTACK
Caesar	21	:BUUBDL
Caesar	22	:CVVCEM
Caesar	23	:DWWDEN
Caesar	24	:EXXEGO
Caesar	25	:FYFHP
Caesar	26	:GZZGIQ

4.2 Pascal

```
//shift of 1
ZA BC
AB CD
ZA BC
Caesar 0: HAL
Caesar 1: IBM
Caesar 2: JCN
Caesar 3: KDO
Caesar 4: LEP
Caesar 5: MFQ
Caesar 6: NGR
Caesar 7: OHS
Caesar 8: PIT
Caesar 9: QJU
Caesar 10: RKV
Caesar 11: SLW
Caesar 12: TMX
Caesar 13: UNY
Caesar 14: VOZ
Caesar 15: WPA
Caesar 16: XQB
Caesar 17: YRC
Caesar 18: ZSD
Caesar 19: ATE
Caesar 20: BUF
Caesar 21: CVG
Caesar 22: DWH
Caesar 23: EXI
Caesar 24: FYJ
```

Caesar 25: GZK
Caesar 26: HAL

```
//shift of 10
THIS IS A TEST STRING FROM JAKE VISSICCHIO
DRSC SC K DOCD CDBSXQ PBYW TKUO FSCCSMMRSY
THIS IS A TEST STRING FROM JAKE VISSICCHIO
Caesar 0: IFMMP
Caesar 1: JGNNQ
Caesar 2: KHOOR
Caesar 3: LIPPS
Caesar 4: MJQQT
Caesar 5: NKRRU
Caesar 6: OLSSV
Caesar 7: PMITW
Caesar 8: QNUUX
Caesar 9: ROVVY
Caesar 10: SPWWZ
Caesar 11: TQXXA
Caesar 12: URYYB
Caesar 13: VSZZC
Caesar 14: WTAAD
Caesar 15: XUBBE
Caesar 16: YVCCF
Caesar 17: ZWDDG
Caesar 18: AXEEH
Caesar 19: BYFFI
Caesar 20: CZGGJ
Caesar 21: DAHHK
Caesar 22: EBIL
Caesar 23: FCJJM
Caesar 24: GDKKN
Caesar 25: HELLO
Caesar 26: IFMMP
```

4.3 Scala

```
//shift of 1
ZA BC
AB CD
ZA BC
Caesar 0: HAL
Caesar 1: IBM
Caesar 2: JCN
Caesar 3: KDO
```

Caesar 4: LEP
Caesar 5: MFQ
Caesar 6: NGR
Caesar 7: OHS
Caesar 8: PIT
Caesar 9: QJU
Caesar 10: RKV
Caesar 11: SLW
Caesar 12: TMX
Caesar 13: UNY
Caesar 14: VOZ
Caesar 15: WPA
Caesar 16: XQB
Caesar 17: YRC
Caesar 18: ZSD
Caesar 19: ATE
Caesar 20: BUF
Caesar 21: CVG
Caesar 22: DWH
Caesar 23: EXI
Caesar 24: FYJ
Caesar 25: GZK
Caesar 26: HAL

//shift of 15
ALAN IS THE BEST
PAPC XH IWT QTHI
ALAN IS THE BEST
Caesar 0: KBLF
Caesar 1: LCMG
Caesar 2: MDNH
Caesar 3: NEOI
Caesar 4: OFPJ
Caesar 5: PGQK
Caesar 6: QHRL
Caesar 7: RISM
Caesar 8: SJTN
Caesar 9: TKUO
Caesar 10: ULVP
Caesar 11: VMWQ
Caesar 12: WNXR
Caesar 13: XOYS
Caesar 14: YPZT
Caesar 15: ZQAU
Caesar 16: ARBV
Caesar 17: BSCW

Caesar 18: CTDX
Caesar 19: DUEY
Caesar 20: EVFZ
Caesar 21: FWGA
Caesar 22: GXHB
Caesar 23: HYIC
Caesar 24: IZJD
Caesar 25: JAKE
Caesar 26: KBLF

4.4 Ruby

#shift of 1
ZA BC
AB CD
ZA BC
Caesar 0: HAL
Caesar 1: IBM
Caesar 2: JCN
Caesar 3: KDO
Caesar 4: LEP
Caesar 5: MFQ
Caesar 6: NGR
Caesar 7: OHS
Caesar 8: PIT
Caesar 9: QJU
Caesar 10: RKV
Caesar 11: SLW
Caesar 12: TMX
Caesar 13: UNY
Caesar 14: VOZ
Caesar 15: WPA
Caesar 16: XQB
Caesar 17: YRC
Caesar 18: ZSD
Caesar 19: ATE
Caesar 20: BUF
Caesar 21: CVG
Caesar 22: DWH
Caesar 23: EXI
Caesar 24: FYJ
Caesar 25: GZK
Caesar 26: HAL

#shift of 20

HOW MUCH WOOD CAN A WOODCHUCK CHUCK IF A WOODCHUCK COULD CHUCK WOOD
BIQ GOWB QIIX WUH U QIIXWBOWE WBOWE CZ U QIIXWBOWE WIOFX WBOWE QIIX
HOW MUCH WOOD CAN A WOODCHUCK CHUCK IF A WOODCHUCK COULD CHUCK WOOD

Caesar 0: TUBST
Caesar 1: UVCTU
Caesar 2: VWDUV
Caesar 3: WXEW
Caesar 4: XYFWX
Caesar 5: YZGXY
Caesar 6: ZAHYZ
Caesar 7: ABIZA
Caesar 8: BCJAB
Caesar 9: CDKBC
Caesar 10: DELCD
Caesar 11: EFMDE
Caesar 12: FGNEF
Caesar 13: GHOFG
Caesar 14: HIPGH
Caesar 15: IJQHI
Caesar 16: JKRIJ
Caesar 17: KLSJK
Caesar 18: LMTKL
Caesar 19: MNULM
Caesar 20: NOVNM
Caesar 21: OPWNO
Caesar 22: PQXOP
Caesar 23: QRYPQ
Caesar 24: RSZQR
Caesar 25: STARS
Caesar 26: TUBST

5 Official Ranking of Jake Vissicchio

1. Ruby

- Very beginner friendly and extremely writable. I will admit the readability does have some issues.

2. Scala

- As a big fan of Java, it's easy to see why I would like Scala as well. It being Java based allowed me to feel at home with slight modifications.

3. Pascal

- I really enjoy the neatness of the code since it is very readable.

4. Fortran

- I have a soft spot for Fortran since it's the language I used to figure out the caesar cipher but a lot of it is kind of weird. One annoying thing was that it caused errors when I indented which hurt the readability a ton.

6 Resources

- Here are a few resources that I used for this project.

<https://ideone.com/>

<https://fortran-lang.org/learn/quickstart>

<https://www.pascal-programming.info/lesson1.php>

<https://www.tutorialspoint.com/scala/index.htm>

<https://www.geeksforgeeks.org/scala-programming-language/>

<https://www.geeksforgeeks.org/ruby-tutorial/>