




# L8 – Neural networks




# Non-linear models: Neural networks



Linear Model  
(Perceptron)



Need a non-linear model!





# Non-linear models: Neural networks



What should we do in case the target is not linearly separable?

- Use **multiple linear functions** and combine them using **non-linear activation functions**

(**Before**) Linear score function:

$$f = Wx$$

(**Now**) 2-layer Neural Network

$$f = W_2 \max(0, W_1 x)$$

activation function



$$x \in \mathbb{R}^D, W_1 \in \mathbb{R}^{H \times D}, W_2 \in \mathbb{R}^{C \times H}$$



# Non-linear models: Neural networks



- A “neuron” computes a linear function  $f = Wx$
- Neural network is a nesting of ‘functions’
  - 2-layers:  $f = W_2 \max(0, W_1 x)$  ← activation function
  - 3-layers:  $f = W_3 \max(0, W_2 \max(0, W_1 x))$
  - 4-layers:  $f = W_4 \tanh(W_3, \max(0, W_2 \max(0, W_1 x)))$
  - 5-layers:  $f = W_5 \sigma(W_4 \tanh(W_3, \max(0, W_2 \max(0, W_1 x))))$
  - ... up to hundreds of layers




# Non-linear models: Neural networks



## Activation functions


### Sigmoid

$$\sigma(x) = \frac{1}{1+e^{-x}}$$




### tanh

$$\tanh(x)$$



### ReLU

$$\max(0, x)$$







# Non-linear models: Neural networks



## Neural networks: Architectures



“2-layer Neural Net”, or  
“1-hidden-layer Neural Net”




“3-layer Neural Net”, or  
“2-hidden-layer Neural Net”

“Fully-connected” layers



# Non-linear models: Neural networks






# Training recipe for MLP



- Split your data





Other splits are also possible (e.g., 80% / 10% / 10%)






# Training recipe for MLP



bad prediction



good prediction

- Select a suitable loss function



# Loss functions for classification



## Binary cross entropy loss

$$\mathcal{L}_{\text{BCE}} = -\frac{1}{N} \sum_{i=1}^N [y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i)]$$

- $N$  is the total number of samples
- $y_i$  is the true label for the  $i$ -th sample (either 0 or 1).
- $\hat{y}_i$  is the predicted probability for the  $i$ -th sample.



Yes! (0.8)

No! (0.2)

The network predicts the probability of the input belonging to the "yes" class




# Loss functions for classification



## Cross entropy loss

$$\mathcal{L}_{\text{CE}} = -\frac{1}{N} \sum_{i=1}^N \sum_{c=1}^C y_{i,c} \log(\hat{y}_{i,c})$$

- $N$  is the total number of samples
- $y_{i,c}$  is a binary indicator (1 if the true class of sample  $i$  is  $c$ , 0 otherwise)
- $\hat{y}_i$  is the predicted probability for the  $i$ -th sample.
- $C$  is the number of classes






# Training a neural net



- Minimize:  $L(\mathbf{y}, f_{\theta}(\mathbf{x}))$  w.r.t.  $\theta$
- We use gradient-based optimization: **gradient descent**



Iterative update:

Learning rate


$$\theta = \theta - \alpha \nabla_{\theta} L(\mathbf{y}, f_{\theta}(\mathbf{x}))$$



# Training a neural net



- Given inputs  $x$  and targets  $y$
- Given multi-layer NN
  - Need to propagate gradients from end to first layer ( $W_1$ )
- Backpropagation: Use chain rule to compute gradients





# Non-linear models: Neural networks



The flow of computations in a neural network goes in two ways:

1. **Left-to-right:** This is referred to as *forward propagation*, which results in computing the output of the network
2. **Right-to-left:** This is referred to as *back propagation*, which results in computing the gradients (or derivatives) of the parameters in the network




# Backpropagation



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$






# Backpropagation



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$







# Backpropagation



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$





# Backpropagation



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$

$$q = x + y$$


$$\frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz$$

$$\frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:

$$\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$$



$$\frac{\partial f}{\partial f}$$



# Backpropagation



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2, y = 5, z = -4$


$$q = x + y$$

$$\frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz$$

$$\frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$



# Backpropagation



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial q}$$



# Backpropagation



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial q}$$



# Backpropagation



Backpropagation: a simple example


$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y \quad \frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz \quad \frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:  $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$



# Backpropagation



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y$$


$$\frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz$$

$$\frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:

$$\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$$



Chain rule:

$$\frac{\partial f}{\partial y} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial y}$$

Upstream  
gradient

Local  
gradient

$$\frac{\partial f}{\partial y}$$



# Backpropagation



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y$$


$$\frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz$$

$$\frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:

$$\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$$



Chain rule:

$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$

Upstream  
gradient

Local  
gradient

$$\frac{\partial f}{\partial x}$$





# Backpropagation



Backpropagation: a simple example

$$f(x, y, z) = (x + y)z$$

e.g.  $x = -2$ ,  $y = 5$ ,  $z = -4$

$$q = x + y$$


$$\frac{\partial q}{\partial x} = 1, \frac{\partial q}{\partial y} = 1$$

$$f = qz$$

$$\frac{\partial f}{\partial q} = z, \frac{\partial f}{\partial z} = q$$

Want:

$$\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$$



$$\frac{\partial f}{\partial x}$$

Chain rule:

$$\frac{\partial f}{\partial x} = \frac{\partial f}{\partial q} \frac{\partial q}{\partial x}$$

Upstream  
gradient

Local  
gradient




# Backpropagation




## Patterns in gradient flow


**add** gate: gradient distributor




**mul** gate: “swap multiplier”



**copy** gate: gradient adder



**max** gate: gradient router





# Backpropagation



If we have a linear combination

$$W \cdot x = q$$

W matrix  
x matrix or vector

Using the chain rule we can compute the gradients:

$$\nabla f_W = \nabla f_q \cdot x^T$$

$$\nabla f_x = W^T \cdot \nabla f_q$$



At test time / validation time

- Perform the forward pass and get the probabilities
- Binary classification: Threshold the probability to find the predicted class

$$\begin{cases} \text{if } p(y = 1|x; \theta) < 0.5 \text{ predict class 0} \\ \text{if } p(y = 1|x; \theta) \geq 0.5 \text{ predict class 1} \end{cases}$$



# Exercises




Classify digits on the MNIST dataset

**TRAIN set**

[0]



[0]




[0]



[0]



[0]



**TEST set**


[1]




[0]



[0]



[0]



[0]






# Exercises



Implement this architecture and compute using backpropagation the gradients of the parameters



- Train the network on the training set
- Compute the accuracy on the test set