



Variational Autoencoders

Probabilistic spin on autoencoders - will let us sample from the model to generate data!




Variational Autoencoders

Probabilistic spin on autoencoders - will let us sample from the model to generate data!

Assume training data $\{x^{(i)}\}_{i=1}^N$ generated from underlying unobserved (latent) representation z

Sample from
true conditional
 $p_{\theta^*}(x \mid z^{(i)})$



Sample from
true prior
 $p_{\theta^*}(z)$

Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders

Probabilistic spin on autoencoders - will let us sample from the model to generate data!


Assume training data $\{x^{(i)}\}_{i=1}^N$ generated from underlying unobserved (latent) representation z

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



Intuition (remember from autoencoders!): x is an image, z is latent factors used to generate x : attributes, orientation, etc.

Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders


We want to estimate the true parameters θ^* of this generative model.

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^*
of this generative model.

How should we represent this model?

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^* of this generative model.

How should we represent this model?

Choose prior $p(z)$ to be simple, e.g. Gaussian.
Reasonable for latent attributes, e.g. pose, how much smile.

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^* of this generative model.

How should we represent this model?

Choose prior $p(z)$ to be simple, e.g. Gaussian.

Conditional $p(x|z)$ is complex (generates image)
=> represent with neural network

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^* of this generative model.

How to train the model?

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^* of this generative model.

[How to train the model?](#)

Remember strategy for training generative models from FVBMs. Learn model parameters to maximize likelihood of training data

$$p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$$

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^* of this generative model.

How to train the model?

Remember strategy for training generative models from FVBMs. Learn model parameters to maximize likelihood of training data

$$p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$$



Now with latent z

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^* of this generative model.

How to train the model?

Remember strategy for training generative models from FVBMs. Learn model parameters to maximize likelihood of training data

$$p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$$

Q: What is the problem with this?

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders

Sample from
true conditional

$$p_{\theta^*}(x \mid z^{(i)})$$

Sample from
true prior

$$p_{\theta^*}(z)$$



We want to estimate the true parameters θ^* of this generative model.

How to train the model?

Remember strategy for training generative models from FVBMs. Learn model parameters to maximize likelihood of training data

$$p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$$

Q: What is the problem with this?

Intractable!

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders: Intractability

Data likelihood: $p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders: Intractability

Data likelihood: $p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$



Simple Gaussian prior

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders: Intractability

Data likelihood: $p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$

Decoder neural network

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders: Intractability



Data likelihood: $p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$



Intractible to compute
 $p(x|z)$ for every z !

Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders: Intractability



Data likelihood: $p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$

Intuitively, need to figure out which z corresponds to each x in the dataset, but such mapping is unknown.

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders: Intractability



Data likelihood: $p_\theta(x) = \int p_\theta(z)p_\theta(x|z)dz$

Intuitively, need to figure out which z corresponds to each x in the dataset, but such mapping is unknown.

$$p_\theta(z|x) = p_\theta(x|z)p_\theta(z)/p_\theta(x)$$

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders: Intractability



Data likelihood: $p_{\theta}(x) = \int p_{\theta}(z)p_{\theta}(x|z)dz$

Intuitively, need to figure out which z corresponds to each x in the dataset, but such mapping is unknown.

Posterior density also intractable: $p_{\theta}(z|x) = p_{\theta}(x|z)p_{\theta}(z)/p_{\theta}(x)$

Intractable data likelihood

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders: Intractability



Data likelihood: $p_\theta(x) = \int p_\theta(z)p_\theta(x|z)dz$

Intuitively, need to figure out which z corresponds to each x in the dataset, but such mapping is unknown.

Posterior density also intractable: $p_\theta(z|x) = p_\theta(x|z)p_\theta(z)/p_\theta(x)$

Intractable data likelihood

Solution: In addition to decoder network modeling $p_\theta(x|z)$, define additional encoder network $q_\phi(z|x)$ that approximates $p_\theta(z|x)$

Will see that this allows us to derive a lower bound on the data likelihood that is tractable, which we can optimize


Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014




Variational Autoencoders

Since we're modeling probabilistic generation of data, encoder and decoder networks are probabilistic

Mean and (diagonal) covariance of z



Mean and (diagonal) covariance of x





Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders

Since we're modeling probabilistic generation of data, encoder and decoder networks are probabilistic





Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders

Since we're modeling probabilistic generation of data, encoder and decoder networks are probabilistic



Encoder and decoder networks also called
“recognition”/“inference” and “generation”
networks

Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\log p_{\theta}(x^{(i)}) = \mathbf{E}_{z \sim q_{\phi}(z|x^{(i)})} [\log p_{\theta}(x^{(i)})] \quad (p_{\theta}(x^{(i)}) \text{ Does not depend on } z)$$



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\log p_{\theta}(x^{(i)}) = \mathbf{E}_{z \sim q_{\phi}(z|x^{(i)})} [\log p_{\theta}(x^{(i)})] \quad (p_{\theta}(x^{(i)}) \text{ Does not depend on } z)$$



Taking expectation wrt. z
(using encoder network)
will come in handy later



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\begin{aligned}\log p_{\theta}(x^{(i)}) &= \mathbf{E}_{z \sim q_{\phi}(z|x^{(i)})} \left[\log p_{\theta}(x^{(i)}) \right] \quad (p_{\theta}(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_{\theta}(x^{(i)} | z)p_{\theta}(z)}{p_{\theta}(z | x^{(i)})} \right] \quad (\text{Bayes' Rule})\end{aligned}$$



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\begin{aligned}\log p_{\theta}(x^{(i)}) &= \mathbf{E}_{z \sim q_{\phi}(z|x^{(i)})} \left[\log p_{\theta}(x^{(i)}) \right] \quad (p_{\theta}(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_{\theta}(x^{(i)} | z)p_{\theta}(z)}{p_{\theta}(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\ &= \mathbf{E}_z \left[\log \frac{p_{\theta}(x^{(i)} | z)p_{\theta}(z)}{p_{\theta}(z | x^{(i)})} \frac{q_{\phi}(z | x^{(i)})}{q_{\phi}(z | x^{(i)})} \right] \quad (\text{Multiply by constant})\end{aligned}$$



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\begin{aligned}\log p_{\theta}(x^{(i)}) &= \mathbf{E}_{z \sim q_{\phi}(z|x^{(i)})} \left[\log p_{\theta}(x^{(i)}) \right] \quad (p_{\theta}(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_{\theta}(x^{(i)} | z)p_{\theta}(z)}{p_{\theta}(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\ &= \mathbf{E}_z \left[\log \frac{p_{\theta}(x^{(i)} | z)p_{\theta}(z)}{p_{\theta}(z | x^{(i)})} \frac{q_{\phi}(z | x^{(i)})}{q_{\phi}(z | x^{(i)})} \right] \quad (\text{Multiply by constant}) \\ &= \mathbf{E}_z \left[\log p_{\theta}(x^{(i)} | z) \right] - \mathbf{E}_z \left[\log \frac{q_{\phi}(z | x^{(i)})}{p_{\theta}(z)} \right] + \mathbf{E}_z \left[\log \frac{q_{\phi}(z | x^{(i)})}{p_{\theta}(z | x^{(i)})} \right] \quad (\text{Logarithms})\end{aligned}$$



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\begin{aligned}\log p_\theta(x^{(i)}) &= \mathbf{E}_{z \sim q_\phi(z | x^{(i)})} \left[\log p_\theta(x^{(i)}) \right] \quad (p_\theta(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \frac{q_\phi(z | x^{(i)})}{q_\phi(z | x^{(i)})} \right] \quad (\text{Multiply by constant}) \\ &= \mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z)} \right] + \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z | x^{(i)})} \right] \quad (\text{Logarithms}) \\ &= \mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z)) + D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z | x^{(i)}))\end{aligned}$$



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\begin{aligned}\log p_\theta(x^{(i)}) &= \mathbf{E}_{z \sim q_\phi(z | x^{(i)})} [\log p_\theta(x^{(i)})] \quad (p_\theta(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \frac{q_\phi(z | x^{(i)})}{q_\phi(z | x^{(i)})} \right] \quad (\text{Multiply by constant}) \\ &= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z)} \right] + \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z | x^{(i)})} \right] \quad (\text{Logarithms}) \\ &= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z)) + D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z | x^{(i)}))\end{aligned}$$

The expectation wrt. z
(using encoder network)
let us write nice KL terms



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\begin{aligned}\log p_\theta(x^{(i)}) &= \mathbf{E}_{z \sim q_\phi(z|x^{(i)})} [\log p_\theta(x^{(i)})] \quad (p_\theta(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \frac{q_\phi(z | x^{(i)})}{q_\phi(z | x^{(i)})} \right] \quad (\text{Multiply by constant}) \\ &= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z)} \right] + \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z | x^{(i)})} \right] \quad (\text{Logarithms}) \\ &= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z)) + D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z | x^{(i)}))\end{aligned}$$

Decoder network gives $p_\theta(x|z)$, can compute estimate of this term through sampling.
(Sampling differentiable through reparam. trick, see paper.)

This KL term (between Gaussians for encoder and z prior) has nice closed-form solution!

$p_\theta(z|x)$ intractable (saw earlier), can't compute this KL term :(But we know KL divergence always ≥ 0 .



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\log p_\theta(x^{(i)}) = \mathbf{E}_{z \sim q_\phi(z|x^{(i)})} [\log p_\theta(x^{(i)})] \quad (p_\theta(x^{(i)}) \text{ Does not depend on } z)$$

↗

$$= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \right] \quad (\text{Bayes' Rule})$$

We want to
maximize
the data
likelihood

$$= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \frac{q_\phi(z | x^{(i)})}{q_\phi(z | x^{(i)})} \right] \quad (\text{Multiply by constant})$$

$$= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z)} \right] + \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z | x^{(i)})} \right] \quad (\text{Logarithms})$$

$$= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z)) + D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z | x^{(i)}))$$

Decoder network gives $p_\theta(x|z)$, can compute estimate of this term through sampling.
(Sampling differentiable through reparam. trick, see paper.)

This KL term (between Gaussians for encoder and z prior) has nice closed-form solution!

$p_\theta(z|x)$ intractable (saw earlier), can't compute this KL term :(But we know KL divergence always ≥ 0 .



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

We want to maximize the data likelihood

$$\begin{aligned} \log p_\theta(x^{(i)}) &= \mathbf{E}_{z \sim q_\phi(z|x^{(i)})} [\log p_\theta(x^{(i)})] \quad (p_\theta(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\ &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \frac{q_\phi(z | x^{(i)})}{q_\phi(z | x^{(i)})} \right] \quad (\text{Multiply by constant}) \\ &= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z)} \right] + \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z | x^{(i)})} \right] \quad (\text{Logarithms}) \\ &= \underbrace{\mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)} + \underbrace{D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z | x^{(i)}))}_{\geq 0} \end{aligned}$$

Tractable lower bound which we can take gradient of and optimize! ($p_\theta(x|z)$ differentiable, KL term differentiable)



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

$$\begin{aligned}\log p_{\theta}(x^{(i)}) &= \mathbf{E}_{z \sim q_{\phi}(z|x^{(i)})} [\log p_{\theta}(x^{(i)})] \quad (p_{\theta}(x^{(i)}) \text{ Does not depend on } z) \\ &= \mathbf{E}_z \left[\log \frac{p_{\theta}(x^{(i)} | z)p_{\theta}(z)}{p_{\theta}(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\ &= \mathbf{E}_z \left[\log \frac{p_{\theta}(x^{(i)} | z)p_{\theta}(z)}{p_{\theta}(z | x^{(i)})} \frac{q_{\phi}(z | x^{(i)})}{q_{\phi}(z | x^{(i)})} \right] \quad (\text{Multiply by constant}) \\ &= \mathbf{E}_z [\log p_{\theta}(x^{(i)} | z)] - \mathbf{E}_z \left[\log \frac{q_{\phi}(z | x^{(i)})}{p_{\theta}(z)} \right] + \mathbf{E}_z \left[\log \frac{q_{\phi}(z | x^{(i)})}{p_{\theta}(z | x^{(i)})} \right] \quad (\text{Logarithms}) \\ &= \underbrace{\mathbf{E}_z [\log p_{\theta}(x^{(i)} | z)]}_{\mathcal{L}(x^{(i)}, \theta, \phi)} - D_{KL}(q_{\phi}(z | x^{(i)}) || p_{\theta}(z)) + \underbrace{D_{KL}(q_{\phi}(z | x^{(i)}) || p_{\theta}(z | x^{(i)}))}_{> 0}\end{aligned}$$

$$\log p_{\theta}(x^{(i)}) \geq \mathcal{L}(x^{(i)}, \theta, \phi)$$

Variational lower bound ("ELBO")

$$\theta^*, \phi^* = \arg \max_{\theta, \phi} \sum_{i=1}^N \mathcal{L}(x^{(i)}, \theta, \phi)$$

Training: Maximize lower bound



Variational Autoencoders

Now equipped with our encoder and decoder networks, let's work out the (log) data likelihood:

Reconstruct the input data

$$\begin{aligned}
 \log p_\theta(x^{(i)}) &= \mathbf{E}_{z \sim q_\phi(z|x^{(i)})} [\log p_\theta(x^{(i)})] \quad (p_\theta(x^{(i)}) \text{ Does not depend on } z) \\
 &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \right] \quad (\text{Bayes' Rule}) \\
 &= \mathbf{E}_z \left[\log \frac{p_\theta(x^{(i)} | z)p_\theta(z)}{p_\theta(z | x^{(i)})} \frac{q_\phi(z | x^{(i)})}{q_\phi(z | x^{(i)})} \right] \quad (\text{Multiply by constant}) \\
 &= \mathbf{E}_z [\log p_\theta(x^{(i)} | z)] - \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z)} \right] + \mathbf{E}_z \left[\log \frac{q_\phi(z | x^{(i)})}{p_\theta(z | x^{(i)})} \right] \quad (\text{Logarithms}) \\
 &= \underbrace{\mathbf{E}_z [\log p_\theta(x^{(i)} | z)]}_{\mathcal{L}(x^{(i)}, \theta, \phi)} - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z)) + \underbrace{D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z | x^{(i)}))}_{> 0} \quad (\text{Make approximate posterior distribution close to prior})
 \end{aligned}$$

$$\log p_\theta(x^{(i)}) \geq \mathcal{L}(x^{(i)}, \theta, \phi)$$

Variational lower bound ("ELBO")

$$\theta^*, \phi^* = \arg \max_{\theta, \phi} \sum_{i=1}^N \mathcal{L}(x^{(i)}, \theta, \phi)$$

Training: Maximize lower bound



Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_{\theta}(x^{(i)} | z) \right] - D_{KL}(q_{\phi}(z | x^{(i)}) || p_{\theta}(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$



Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$

Input Data x



Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$

Let's look at computing the bound (forward pass) for a given minibatch of input data


Input Data x



Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$





Variational Autoencoders


Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$

Make approximate posterior distribution close to prior

Encoder network
 $q_\phi(z|x)$

Input Data






Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$

Make approximate posterior distribution close to prior






Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$

Make approximate posterior distribution close to prior





Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound


$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$

Make approximate posterior distribution close to prior

Maximize likelihood of original input being reconstructed

Decoder network
 $p_\theta(x|z)$

Encoder network
 $q_\phi(z|x)$





Variational Autoencoders

Putting it all together: maximizing the likelihood lower bound

$$\underbrace{\mathbf{E}_z \left[\log p_\theta(x^{(i)} | z) \right] - D_{KL}(q_\phi(z | x^{(i)}) || p_\theta(z))}_{\mathcal{L}(x^{(i)}, \theta, \phi)}$$


Make approximate posterior distribution close to prior

For every minibatch of input data: compute this forward pass, and then backprop!

Maximize likelihood of original input being reconstructed

Decoder network
 $p_\theta(x|z)$


Encoder network
 $q_\phi(z|x)$





Variational Autoencoders: Generating Data!

Use decoder network. Now sample z from prior!





Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders: Generating Data!

Use decoder network. Now sample z from prior!




Kingma and Welling, “Auto-Encoding Variational Bayes”, ICLR 2014




Variational Autoencoders: Generating Data!

Use decoder network. Now sample z from prior!



Data manifold for 2-d z



Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders: Generating Data!

Diagonal prior on $z \Rightarrow$
independent latent
variables

Different dimensions
of z encode
interpretable factors
of variation

Degree of smile

Vary z_1




 Vary z_2  Head pose

Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders: Generating Data!

Diagonal prior on $\mathbf{z} \Rightarrow$
independent latent
variables

Different dimensions
of \mathbf{z} encode
interpretable factors
of variation

Also good feature representation that
can be computed using $q_\phi(\mathbf{z}|\mathbf{x})$!

Degree of smile
 \swarrow
 \downarrow
Vary \mathbf{z}_1



\longleftarrow Vary \mathbf{z}_2 \rightarrow Head pose


Kingma and Welling, "Auto-Encoding Variational Bayes", ICLR 2014



Variational Autoencoders: Generating Data!



32x32 CIFAR-10



Labeled Faces in the
Wild

Figures copyright (L) Dirk Kingma et al. 2016; (R) Anders Larsen et al. 2017. Reproduced with permission.