Real-Time Driver Drowsiness Detection System

Date: October 2026

Authors:

- Sumit Sharma (No.: 20233279)
- Sourabh Kumar (No.: 20233353)
- Swatantra Kumar Maurya (No.: 20233285)
- Vishwajeet Gupta (No.: 20233316)
- Viswa Ravindren (No.: 20233584)

Abstract

Driver fatigue remains a leading contributing factor to vehicular accidents worldwide. Often, the cognitive decline associated with drowsiness occurs before the driver is consciously aware of their impairment, necessitating an automated, non-invasive monitoring solution. This report details the development and implementation of a real-time, camera-based drowsiness detection system designed to evaluate facial cues and intervene when prolonged eye closure indicates potential sleepiness. The system processes live video feeds at the frame level, utilizing MediaPipe for high-fidelity facial landmark detection. By calculating the Eye Aspect Ratio (EAR) for both eyes, the software tracks the duration of eye closures against a configurable temporal threshold. Should a driver's eyes remain closed beyond the established baseline, the system initiates immediate visual warnings and an audible Pygame-driven alarm, incorporating a cooldown mechanism to mitigate alarm fatigue. The architecture operates entirely on local hardware using Python, OpenCV, and NumPy, thereby eliminating the need for continuous cloud connectivity or intrusive wearable sensors. Furthermore, a Flask-based web interface serves as the primary presentation layer for real-time monitoring. Software verification confirms that the core state-machine logic functions as specified, accurately differentiating between normal physiological blinking and dangerous microsleeps based on a calibrated EAR threshold of 0.21.

Keywords: Driver Drowsiness, Eye Aspect Ratio, MediaPipe, OpenCV, Real-Time Detection, Flask.

1. Introduction

Automotive safety is fundamentally dependent on the continuous alertness and reaction capability of the driver. However, drowsiness progressively degrades this alertness, often exhibiting subtle early physiological indicators that drivers themselves may fail to recognize. A fatigued driver typically demonstrates an increased blink rate, prolonged eyelid closures, and a notable reduction in micro-corrections to steering, all while subjectively perceiving themselves as capable of operating the vehicle. By the time the impairment manifests in erratic vehicle behavior, the margin for corrective action is frequently insufficient to prevent a collision.

A primary challenge in mitigating fatigue-related accidents is the difficulty of continuously measuring alertness in a non-invasive manner. Conventional Advanced Driver Assistance Systems (ADAS), such as lane departure warnings, are fundamentally reactive; they detect the consequences of driver inattention rather than the cognitive state of the driver. These systems intervene only after a critical vehicular error has been committed.

Computer vision provides a proactive methodology to address this deficiency. By leveraging standard optical sensors, it is possible to continuously monitor the driver's facial expressions and eye states without requiring intrusive biometric wearables. The ocular state, visible in every video frame, serves as a highly reliable proxy for overall cognitive alertness.

This research focuses on engineering a computationally efficient, automated system that processes webcam video locally. The proposed architecture is designed to identify potential drowsiness by analyzing prolonged eye closures and to alert the driver via simultaneous visual and auditory stimuli. Rather than deploying computationally expensive deep learning classification models for every frame, this system employs a geometric, time-series approach, ensuring high performance on standard hardware.

The primary objectives of this project are defined as follows:

- To capture and process real-time vehicular video streams efficiently using the OpenCV library.
- To accurately detect facial landmarks and isolate the ocular regions irrespective of minor head movements.
- To implement a mathematical model, specifically the Eye Aspect Ratio (EAR), to quantify the degree of eye openness.
- To engineer a robust, time-based state machine capable of distinguishing normal blinking patterns from hazardous eye closures.
- To generate timely, state-dependent visual warnings and auditory alarms.
- To construct a responsive web-based monitoring dashboard utilizing the Flask framework.

The efficacy of such a system relies on its determinism and adaptability across varying lighting conditions and user profiles, principles which guided the architectural decisions detailed in the subsequent methodology.

2. Methodology

2.1 System Architecture and Workflow

The system operates as a continuous, frame-by-frame processing pipeline. The workflow initiates by capturing live optical data via a standard webcam, which is passed to OpenCV for initial frame manipulation and color space conversion. MediaPipe is subsequently utilized to perform high-speed inference, mapping complex facial landmarks. Upon isolating the coordinates of the eyes, the Eye Aspect Ratio is calculated. If the EAR falls below a designated threshold for a sustained duration, a state transition is triggered, identifying the subject as drowsy. Finally, the system initiates a Pygame audio alert and updates the Flask-served frontend.

2.2 Technology Stack

To ensure the system remains lightweight and executes in real time without specialized GPU hardware, the technology stack was carefully optimized:

- **Python:** Core algorithmic logic and process execution
- **OpenCV:** Optical capture and primary frame processing
- **MediaPipe:** High-speed, real-time facial landmark detection
- **NumPy:** Matrix calculations for EAR metric extraction
- **Flask:** Backend routing for the monitoring dashboard
- **HTML/JS/CSS:** Frontend presentation and user interface controls
- **Pygame:** Asynchronous triggering of the auditory alarm

2.3 The Eye Aspect Ratio (EAR) and State Logic

The Eye Aspect Ratio is a scalar value that estimates eye openness independent of the subject's distance from the camera. Utilizing six specific landmarks per eye, the EAR is calculated. As the eyelids close, the vertical distances approach zero, causing a sharp decline in the ratio. The system averages the EAR of both eyes and applies an exponential moving average (smoothing factor of 0.65) to filter out single-frame tracking noise.

To prevent false positives from natural blinking (typically lasting 0.1 to 0.4 seconds), the system utilizes a strict state machine. In the NORMAL state, EAR values remain above the 0.21 threshold. If the EAR remains below threshold for 0.9 seconds or more, the system transitions to **WARNING**. If the closure persists for 1.8 seconds or more, it shifts to DROWSY, triggering the alarms. Should the face leave the frame for 0.5 seconds or more, a FACE NOT DETECTED state pauses the timer.

3. Results and Discussion

3.1 System Verification and Functional Testing

The primary validation phase focused on verifying the mathematical integrity of the detection logic. The EAR calculation function was subjected to synthetic facial coordinate injections to confirm its geometric accuracy. When provided with an explicitly open eye geometry, the function returned a baseline EAR of 0.600. Conversely, when provided with coordinates representing closed eyelids, the output was 0.100. Both values clearly demarcate the predefined algorithmic threshold of 0.21, validating the core mathematical model.

Following geometric validation, the time-based state machine was evaluated via controlled temporal simulations. The logic demonstrated deterministic state transitions. The system successfully disregarded transient closures (simulating normal blinks) and accurately escalated to the WARNING state precisely at the 1.0-second mark. Upon reaching 1.9 seconds of sustained closure, the DROWSY state was activated alongside the audio alarm. Furthermore, the 2.0-second cooldown mechanism functioned exactly as specified, preventing auditory overlap and ensuring the alarm mechanism remains effective without causing unnecessary auditory fatigue to the driver.

3.2 Architectural Strengths and Current Limitations

The foremost advantage of the implemented architecture is its transparency and minimal computational overhead. Because the detection criteria rely on deterministic geometric ratios rather than opaque neural network decision boundaries, the system's behavior is highly predictable and easily calibratable. Furthermore, the localized processing ensures absolute data privacy, as no optical data is transmitted to external servers.

Despite these successes, the current prototype exhibits limitations inherent to purely optical tracking. The system's efficacy is directly correlated with ambient illumination; operation in severely low-light environments without infrared camera hardware degrades landmark detection accuracy. Additionally, heavy ocular occlusions, such as thick-rimmed glasses or heavily polarized sunglasses, can disrupt the MediaPipe mesh generation. Finally, while the 0.21 EAR threshold serves as a statistically sound baseline, morphological variations in human eye shapes suggest that a production-grade deployment would require a brief, automated calibration sequence to establish a personalized baseline for each unique driver upon vehicle ignition.

4. Conclusion

This project successfully details the design, implementation, and verification of a real-time driver drowsiness detection system rooted in deterministic computer vision methodologies. By integrating OpenCV for optical processing and MediaPipe for precise facial landmark extraction, the system successfully extracts the Eye Aspect Ratio (EAR) at high frame rates. This geometric evaluation, coupled with a rigorously defined temporal state machine, allows the software to accurately differentiate between routine physiological blinking and dangerous, prolonged micro-sleeps.

The strategic decision to rely on local mathematical heuristics rather than hardware-intensive deep learning models ensures that the system is both privacy-preserving and capable of operating on standard, low-cost computing hardware. Verification procedures confirmed that the core logic operates seamlessly; the established thresholds correctly initiate warnings, and the auditory cooldowns prevent user frustration while maintaining safety protocols. Furthermore, the integration of a Flask web dashboard provides a scalable foundation for modern vehicular interfaces.

4.1 Future Scope

Moving forward, several enhancements are necessary to transition this prototype into a safety-critical automotive product.

First, the integration of secondary behavioral indicators, specifically yawning detection and head-pose estimation (monitoring pitch, yaw, and roll), would drastically reduce false positives and create a more comprehensive driver profile. If a driver is looking downward at a mobile device, their EAR may appear artificially low; head-pose estimation would contextualize this data.

Second, to address varying ambient light conditions, the software must be tested and optimized for infrared (IR) camera inputs, which are standard in modern automotive cabins.

Finally, future iterations should prioritize the deployment of this codebase onto embedded microcomputing platforms, such as the Raspberry Pi or NVIDIA Jetson Nano. Optimizing the Python pipeline for edge-computing environments will finalize the transition from a laboratory-tested software architecture into a highly robust, in-vehicle safety mechanism capable of actively preventing fatigue-induced collisions.