

Dynamic Programming | Set 7 (Coin Change)

Given a value N, if we want to make change for N cents, and we have infinite supply of each of S = { S1, S2, .. , Sm} valued coins, how many ways can we make the change? The order of coins doesn't matter.

For example, for N = 4 and S = {1,2,3}, there are four solutions: {1,1,1,1},{1,1,2},{2,2},{1,3}. So output should be 4. For N = 10 and S = {2, 5, 3, 6}, there are five solutions: {2,2,2,2,2}, {2,2,3,3}, {2,2,6}, {2,3,5} and {5,5}. So the output should be 5.

1) Optimal Substructure

To count total number solutions, we can divide all set solutions in two sets.

- 1) Solutions that do not contain mth coin (or Sm).
- 2) Solutions that contain at least one Sm.

Let count(S[], m, n) be the function to count the number of solutions, then it can be written as sum of count(S[], m-1, n) and count(S[], m, n-Sm).

Therefore, the problem has optimal substructure property as the problem can be solved using solutions to subproblems.

2) Overlapping Subproblems

Following is a simple recursive implementation of the Coin Change problem. The implementation simply follows the recursive structure mentioned above.

```
#include<stdio.h>

// Returns the count of ways we can sum S[0...m-1] coins to get sum n
int count( int S[], int m, int n )
{
    // If n is 0 then there is 1 solution (do not include any coin)
```


Google™ Custom Search



GeeksforGeeks



53,524 people like [GeeksforGeeks](#).



Facebook

[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

```

if (n == 0)
    return 1;

// If n is less than 0 then no solution exists
if (n < 0)
    return 0;

// If there are no coins and n is greater than 0, then no solution
if (m <= 0 && n >= 1)
    return 0;


// count is sum of solutions (i) including S[m-1] (ii) excluding S
return count( S, m - 1, n ) + count( S, m, n-S[m-1] );
}

// Driver program to test above function
int main()
{
    int i, j;
    int arr[] = {1, 2, 3};
    int m = sizeof(arr)/sizeof(arr[0]);
    printf("%d ", count(arr, m, 4));
    getchar();
    return 0;
}

```

It should be noted that the above function computes the same subproblems again and again. See the following recursion tree for $S = \{1, 2, 3\}$ and $n = 5$.

The function $C(\{1\}, 3)$ is called two times. If we draw the complete tree, then we can see that there are many subproblems being called more than once.



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)



Since same subproblems are called again, this problem has Overlapping Subproblems property. So the Coin Change problem has both properties (see [this](#) and [this](#)) of a dynamic programming problem. Like other typical **Dynamic Programming(DP) problems**, recomputations of same subproblems can be avoided by constructing a temporary array table[][] in bottom up manner.

Dynamic Programming Solution

```
#include<stdio.h>
```

```
int count( int S[], int m, int n )
{
    int i, j, x, y;


    // We need n+1 rows as the table is constructed in bottom up manner
    // the base case 0 value case (n = 0)
    int table[n+1][m];

    // Fill the entries for 0 value case (n = 0)
    for (i=0; i<m; i++)
        table[0][i] = 1;

    // Fill rest of the table entries in bottom up manner
    for (i = 1; i < n+1; i++)
    {
        for (j = 0; j < m; j++)
        {
            // Count of solutions including S[j]
            x = (i-S[j] >= 0)? table[i - S[j]][j]: 0;

            // Count of solutions excluding S[j]
            y = (j >= 1)? table[i][j-1]: 0;

            // total count
            table[i][j] = x + y;
        }
    }
    return table[n][m-1];
}
```



```
}
```

```
// Driver program to test above function
int main()
{
    int arr[] = {1, 2, 3};
    int m = sizeof(arr)/sizeof(arr[0]);
    int n = 4;
    printf(" %d ", count(arr, m, n));
    return 0;
}
```

Time Complexity: $O(mn)$

Following is a simplified version of method 2. The auxiliary space required here is $O(n)$ only.

```
int count( int S[], int m, int n )
{
    // table[i] will be storing the number of solutions for
    // value i. We need n+1 rows as the table is constructed
    // in bottom up manner using the base case (n = 0)
    int table[n+1];

    // Initialize all table values as 0
    memset(table, 0, sizeof(table));

    // Base case (If given value is 0)
    table[0] = 1;

    // Pick all coins one by one and update the table[] values
    // after the index greater than or equal to the value of the
    // picked coin
    for(int i=0; i<m; i++)
        for(int j=S[i]; j<=n; j++)
            table[j] += table[j-S[i]];

    return table[n];
}
```

Thanks to [Rohan Laishram](#) for suggesting this space optimized version.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

References:

http://www.algorithmist.com/index.php/Coin_Change

Recent Comments

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree · 38 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 42 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this

sentence "We can easily...


Count trailing zeroes in factorial of a number · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

newCoder3006 Code without using while loop. We can do it...


Find subarray with given sum · 1 hour ago

AdChoices 

[▶ Java Array](#)

[▶ Coin Coins](#)

[▶ Coin Map](#)



AdChoices

► [Coin Coins](#)

► [Coin Map](#)

► [Coin Sorting](#)

AdChoices

► [Coin Collection](#)

► [Programming C++](#)

► [Java Array](#)

Related Tpoics:

- [Backtracking | Set 8 \(Solving Cryptarithmic Puzzles\)](#)
- [Tail Recursion](#)
- [Find if two rectangles overlap](#)
- [Analysis of Algorithm | Set 4 \(Solving Recurrences\)](#)
- [Print all possible paths from top left to bottom right of a mXn matrix](#)
- [Generate all unique partitions of an integer](#)
- [Russian Peasant Multiplication](#)
- [Closest Pair of Points | O\(nlogn\) Implementation](#)



32



Tweet 2



8

Writing code in comment? Please use ideone.com and share the link here.

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team