

Count all possible groups of size 2 or 3 that have sum as multiple of 3

Given an unsorted integer (positive values only) array of size 'n', we can form a group of two or three, the group should be such that the sum of all elements in that group is a multiple of 3. Count all possible number of groups that can be generated in this way.

```
Input: arr[] = {3, 6, 7, 2, 9}
```

```
Output: 8
```

```
// Groups are {3,6}, {3,9}, {9,6}, {7,2}, {3,6,9},  
//           {3,7,2}, {7,2,6}, {7,2,9}
```

```
Input: arr[] = {2, 1, 3, 4}
```

```
Output: 4
```

```
// Groups are {2,1}, {2,4}, {2,1,3}, {2,4,3}
```

We strongly recommend to minimize the browser and try this yourself first.

The idea is to see remainder of every element when divided by 3. A set of elements can form a group only if sum of their remainders is multiple of 3. Since the task is to enumerate groups, we count all elements with different remainders.

1. Hash all elements in a count array based on remainder, i.e, for all elements $a[i]$, do $c[a[i]\%3]++$;
2. Now $c[0]$ contains the number of elements which when divided by 3 leave remainder 0 and similarly $c[1]$ for remainder 1 and $c[2]$ for 2.


Google™ Custom Search



GeeksforGeeks



53,519 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and](#)

[Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

3. Now for group of 2, we have 2 possibilities
 - a. 2 elements of remainder 0 group. Such possibilities are $c[0]*(c[0]-1)/2$
 - b. 1 element of remainder 1 and 1 from remainder 2 group
Such groups are $c[1]*c[2]$.
4. Now for group of 3, we have 4 possibilities
 - a. 3 elements from remainder group 0.
No. of such groups are $c[0]C3$
 - b. 3 elements from remainder group 1.
No. of such groups are $c[1]C3$
 - c. 3 elements from remainder group 2.
No. of such groups are $c[2]C3$
 - d. 1 element from each of 3 groups.
No. of such groups are $c[0]*c[1]*c[2]$.
5. Add all the groups in steps 3 and 4 to obtain the result.

```
#include<stdio.h>
```

```
// Returns count of all possible groups that can be formed from elements
// of a[].
int findgroups(int arr[], int n)
{
    // Create an array C[3] to store counts of elements with remainder
    // 0, 1 and 2. c[i] would store count of elements with remainder i
    int c[3] = {0}, i;

    int res = 0; // To store the result

    // Count elements with remainder 0, 1 and 2
    for (i=0; i<n; i++)
        c[arr[i]%3]++;

    // Case 3.a: Count groups of size 2 from 0 remainder elements
    res += ((c[0]*(c[0]-1))>>1);

    // Case 3.b: Count groups of size 2 with one element with 1
    // remainder and other with 2 remainder
    res += c[1] * c[2];

    // Case 4.a: Count groups of size 3 with all 0 remainder elements
    res += (c[0] * (c[0]-1) * (c[0]-2))/6;
```

```
// Case 4.b: Count groups of size 3 with all 1 remainder elements
res += (c[1] * (c[1]-1) * (c[1]-2))/6;

// Case 4.c: Count groups of size 3 with all 2 remainder elements
res += ((c[2]*(c[2]-1)*(c[2]-2))/6);

// Case 4.c: Count groups of size 3 with different remainders
res += c[0]*c[1]*c[2];

// Return total count stored in res
return res;
}

// Driver program to test above functions
int main()
{
    int arr[] = {3, 6, 7, 2, 9};
    int n = sizeof(arr)/sizeof(arr[0]);
    printf("Required number of groups are %d\n", findgroups(arr,n));
    return 0;
}
```


Output:

Required number of groups are 8

Time Complexity: $O(n)$

Auxiliary Space: $O(1)$


This article is contributed by [Amit Jain](#). Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Informix Database

 progress.com/Informix

JDBC Compliant w/ Major
Databases Fully Functional Eval -
Try Now!



 705



Recent Comments

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 3 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 28 minutes ago

GOPI GOPINATH @admin Highlight this

sentence "We can easily...

Count trailing zeroes in factorial of a number · 30 minutes ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 54 minutes ago

newCoder3006 Code without using while loop. We can do it...

Find subarray with given sum · 1 hour ago

Sanjay Agarwal You can also use the this method:...

Related Tpoics:

- Remove minimum elements from either side such that $2 \times \min$ becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Sort n numbers in range from 0 to $n^2 - 1$ in linear time



7



Tweet

3



1

Writing code in comment? Please use ideone.com and share the link here.

8 Comments

GeeksforGeeks

Sort by Newest ▼





JOIN THE DISCUSSION...

Count trailing zeroes in factorial of a number · 1

hour ago



AlienOnEarth · 8 days ago

@GeeksforGeeks Please address the issue for duplicates. Or the input is to

^ | v · Reply · Share ›



Sidharth · 25 days ago

Could anyone tell me why is the right shift operator used ?

^ | v · Reply · Share ›



Jumper → Sidharth · 16 days ago

>> 1 is equivalent to dividing by 2. Similarly <<1 is equivalent to multipl

^ | v · Reply · Share ›



Srini · a month ago

For the input arr

{3, 6, 7, 2, 9}

Is the following is not the possible group?

{3, 6, 7, 2}

why was this missed?

^ | v · Reply · Share ›



Alien → Srini · a month ago

Question is to make group of 2-3 members not more than that

^ | v · Reply · Share ›



zzzer · a month ago

there lack some boundary checks, such as check if $c[1] \geq 2$ and $c[0] \geq 2$ whe

AdChoices ▶

▶ [Math Geeks](#)

▶ [Java Array](#)

▶ [The SUM of All](#)

AdChoices ▶

▶ [SUM](#)

▶ [Memory Array](#)

▶ [Remainder](#)

AdChoices ▶

▶ [SUM Time](#)

▶ [SUM To](#)

▶ [Array](#)

1 ^ | v • Reply • Share ›



Guest • 2 months ago

The question is to count all possible groups , not just the unique ones

1 ^ | v • Reply • Share ›



Kshitij Gupta • 2 months ago

There is an assumption that the numbers in list are unique.

For a list like: {3, 6, 7, 2, 9, 9}

The code would print: 15 (treating both 9 as different)

Whereas the actual unique groups are only 11:

(6, 3), (9, 3), (9, 6), (9, 9), (7, 2), (9, 9, 6), (7, 6, 2), (9, 6, 3), (9, 9, 3), (9, 7, 2),

9 ^ | v • Reply • Share ›



Subscribe



Add Disqus to your site

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team