



## Convert a given Binary Tree to Doubly Linked List | Set 2

Given a Binary Tree (BT), convert it to a Doubly Linked List(DLL). The left and right pointers in nodes are to be used as previous and next pointers respectively in converted DLL. The order of nodes in DLL must be same as Inorder of the given Binary Tree. The first node of Inorder traversal (left most node in BT) must be head node of the DLL.



The above tree should be in-place converted to following Doubly Linked List(DLL).



A solution to this problem is discussed in [this post](#).

In this post, another simple and efficient solution is discussed. The solution discussed here has two simple steps.

**1) Fix Left Pointers:** In this step, we change left pointers to point to previous nodes in DLL. The idea is simple, we do inorder traversal of tree. In inorder traversal, we keep track of previous

Google™ Custom Search



GeeksforGeeks



52,731 people like GeeksforGeeks.



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

visited node and change left pointer to the previous node. See *fixPrevPtr()* in below implementation.

**2) Fix Right Pointers:** The above is intuitive and simple. How to change right pointers to point to next node in DLL? The idea is to use left pointers fixed in step 1. We start from the rightmost node in Binary Tree (BT). The rightmost node is the last node in DLL. Since left pointers are changed to point to previous node in DLL, we can linearly traverse the complete DLL using these pointers. The traversal would be from last to first node. While traversing the DLL, we keep track of the previously visited node and change the right pointer to the previous node. See *fixNextPtr()* in below implementation.

```
// A simple inorder traversal based program to convert a Binary Tree to DLL
#include<stdio.h>
#include<stdlib.h>

// A tree node
struct node
{
    int data;
    struct node *left, *right;
};

// A utility function to create a new tree node
struct node *newNode(int data)
{
    struct node *node = (struct node *)malloc(sizeof(struct node));
    node->data = data;
    node->left = node->right = NULL;
    return(node);
}

// Standard Inorder traversal of tree
void inorder(struct node *root)
{
    if (root != NULL)
    {
        inorder(root->left);
        printf("\t%d", root->data);
        inorder(root->right);
    }
}

// Changes left pointers to work as previous pointers in converted DLL
// The function simply does inorder traversal of Binary Tree and updates
```

# ITT Tech - Official Site

[itt-tech.edu](http://itt-tech.edu)

Tech-Oriented Degree Programs.  
Education for the Future.



## Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```
// left pointer using previously visited node
void fixPrevPtr(struct node *root)
{
    static struct node *pre = NULL;

    if (root != NULL)
    {
        fixPrevPtr(root->left);
        root->left = pre;
        pre = root;
        fixPrevPtr(root->right);
    }
}

// Changes right pointers to work as next pointers in converted DLL
struct node *fixNextPtr(struct node *root)
{
    struct node *prev = NULL;

    // Find the right most node in BT or last node in DLL
    while (root && root->right != NULL)
        root = root->right;

    // Start from the rightmost node, traverse back using left pointer
    // While traversing, change right pointer of nodes.
    while (root && root->left != NULL)
    {
        prev = root;
        root = root->left;
        root->right = prev;
    }

    // The leftmost node is head of linked list, return it
    return (root);
}

// The main function that converts BST to DLL and returns head of DLL
struct node *BTTToDLL(struct node *root)
{
    // Set the previous pointer
    fixPrevPtr(root);

    // Set the next pointer and return head of DLL
    return fixNextPtr(root);
}
```

Shouldn't you  
expect a  
cloud with:

# SYSTEM MONITORING

Plus the experts  
to help run it?

TRY MANAGED CLOUD ►



// Traverses the DLL from left to right



## Recent Comments

affiszerv Your example has two 4s on row 3, that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 29 minutes ago

**RVM** Can someone please elaborate this Qs from above...

[Flipkart Interview | Set 6](#) · 49 minutes ago

**Vishal Gupta** I talked about as an Interviewer in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 49 minutes ago

**@meya** Working solution for question 2 of 4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago

sandeep void rearrange(struct node \*head)  
{...

Given a linked list, reverse alternate nodes and append at the end · 2 hours ago

Neha I think that is what it should return as, in...

[Find depth of the deepest odd level leaf node](#) · 2 hours ago

AdChoices 

[► Binary Tree](#)

[► Linked List](#)

[► Java Tree](#)

```
void printList(struct node *root)
{
    while (root != NULL)
    {
        printf("\t%d", root->data);
        root = root->right;
    }
}

// Driver program to test above functions
int main(void)
{
    // Let us create the tree shown in above diagram
    struct node *root = newNode(10);
    root->left = newNode(12);
    root->right = newNode(15);
    root->left->left = newNode(25);
    root->left->right = newNode(30);
    root->right->left = newNode(36);

    printf("\n\t\tInorder Tree Traversal\n\n");
    inorder(root);

    struct node *head = BTToDLL(root);

    printf("\n\n\t\tDLL Traversal\n\n");
    printList(head);
    return 0;
}
```

Output:

Inorder Tree Traversal					
25	12	30	10	36	15
DLL Traversal					
25	12	30	10	36	15

Time Complexity:  $O(n)$  where  $n$  is the number of nodes in given Binary Tree. The solution simply does two traversals of all Binary Tree nodes.

This article is contributed by **Rala**. Please write comments if you find anything incorrect or you

This article is contributed by [Data](#). Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Better Than Hadoop.

HPCC Systems is Big Data Processing and Analytics  
Open Source. Proven. Trusted.

LexisNexis®


Learn More 

AdChoices 

[► Convert DLL](#)

[► Convert XML Data](#)

[► Convert C++](#)

AdChoices 

[► Convert VS Cast](#)

[► Convert Int](#)

[► Convert Java](#)

## Related Topics:

- [Print a Binary Tree in Vertical Order | Set 2 \(HashMap based Method\)](#)
- [Print Right View of a Binary Tree](#)
- [Red-Black Tree | Set 3 \(Delete\)](#)
- [Construct a tree from Inorder and Level order traversals](#)
- [Print all nodes at distance k from a given node](#)
- [Print a Binary Tree in Vertical Order | Set 1](#)
- [Interval Tree](#)
- [Check if a given Binary Tree is height balanced like a Red-Black Tree](#)



58



Tweet

3



1

Writing code in comment? Please use [ideone.com](#) and share the link here.