

## Find number of pairs such that $x^y > y^x$

Given two arrays  $X[]$  and  $Y[]$  of positive integers, find number of pairs such that  $x^y > y^x$  where  $x$  is an element from  $X[]$  and  $y$  is an element from  $Y[]$ .

Examples:

Input:  $X[] = \{2, 1, 6\}$ ,  $Y = \{1, 5\}$

Output: 3

// There are total 3 pairs where  $\text{pow}(x, y)$  is greater than  $\text{pow}(y, x)$

// Pairs are (2, 1), (2, 5) and (6, 1)

Input:  $X[] = \{10, 19, 18\}$ ,  $Y[] = \{11, 15, 9\}$ ;

Output: 2

// There are total 2 pairs where  $\text{pow}(x, y)$  is greater than  $\text{pow}(y, x)$

// Pairs are (10, 11) and (10, 15)

The **brute force solution** is to consider each element of  $X[]$  and  $Y[]$ , and check whether the given condition satisfies or not. Time Complexity of this solution is  $O(m*n)$  where  $m$  and  $n$  are sizes of given arrays.

Following is C++ code based on brute force solution.

```
int countPairsBruteForce(int X[], int Y[], int m, int n)
{
    int ans = 0;
    for (int i = 0; i < m; i++)
        for (int j = 0; j < n; j++)
            if (pow(X[i], Y[j]) > pow(Y[j], X[i]))
                ans++;
    return ans;
}
```

Google™ Custom Search



GeeksforGeeks



53,519 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

```

        ans++;
    return ans;
}

```

### Efficient Solution:

The problem can be solved in  $O(n\log n + m\log n)$  time. The trick here is, if  $y > x$  then  $x^y > y^x$  with some exceptions. Following are simple steps based on this trick.

- 1) Sort array  $Y[]$ .
- 2) For every  $x$  in  $X[]$ , find the index  $idx$  of smallest number greater than  $x$  (also called ceil of  $x$ ) in  $Y[]$  using binary search or we can use the inbuilt function `upper_bound()` in algorithm library.
- 3) All the numbers after  $idx$  satisfy the relation so just add  $(n - idx)$  to the count.

### Base Cases and Exceptions:

Following are exceptions for  $x$  from  $X[]$  and  $y$  from  $Y[]$

If  $x = 0$ , then the count of pairs for this  $x$  is 0.

If  $x = 1$ , then the count of pairs for this  $x$  is equal to count of 0s in  $Y[]$ .

The following cases must be handled separately as they don't follow the general rule that  $x$  smaller than  $y$  means  $x^y$  is greater than  $y^x$ .

a)  $x = 2, y = 3$  or 4

b)  $x = 3, y = 2$

Note that the case where  $x = 4$  and  $y = 2$  is not there

Following diagram shows all exceptions in tabular form. The value 1 indicates that the corresponding  $(x, y)$  form a valid pair.

		Y				
		0	1	2	3	4
X	0	0	0	0	0	0
	1	1	0	0	0	0
	2	1	1	0	0	0
	3	1	1	1	0	1
	4	1	1	0	0	0



## Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

Following is C++ implementation. In the following implementation, we pre-process the Y array and count 0, 1, 2, 3 and 4 in it, so that we can handle all exceptions in constant time. The array NoOfY[] is used to store the counts.

```
#include<iostream>
#include<algorithm>
using namespace std;

// This function return count of pairs with x as one element
// of the pair. It mainly looks for all values in Y[] where
//  $x \wedge Y[i] > Y[i] \wedge x$ 
int count(int x, int Y[], int n, int NoOfY[])
{
    // If x is 0, then there cannot be any value in Y such that
    //  $x \wedge Y[i] > Y[i] \wedge x$ 
    if (x == 0) return 0;

    // If x is 1, then the number of pairs is equal to number of
    // zeroes in Y[]
    if (x == 1) return NoOfY[0];

    // Find number of elements in Y[] with values greater than x
    // upper_bound() gets address of first greater element in Y[0..n-1]
    int* idx = upper_bound(Y, Y + n, x);
    int ans = (Y + n) - idx;

    // If we have reached here, then x must be greater than 1,
    // increase number of pairs for y=0 and y=1
    ans += (NoOfY[0] + NoOfY[1]);

    // Decrease number of pairs for x=2 and (y=4 or y=3)
    if (x == 2) ans -= (NoOfY[3] + NoOfY[4]);

    // Increase number of pairs for x=3 and y=2
    if (x == 3) ans += NoOfY[2];

    return ans;
}

// The main function that returns count of pairs (x, y) such that
// x belongs to X[], y belongs to Y[] and  $x \wedge y > y \wedge x$ 
int countPairs(int X[], int Y[], int m, int n)
{
    // To store counts of 0, 1, 2, 3 and 4 in array Y
    int NoOfY[5] = {0};
    for (int i = 0; i < n; i++)
```



```

        if (Y[i] < 5)
            NoOfY[Y[i]]++;

// Sort Y[] so that we can do binary search in it
sort(Y, Y + n);

int total_pairs = 0; // Initialize result

// Take every element of X and count pairs with it
for (int i=0; i<m; i++)
    total_pairs += count(X[i], Y, n, NoOfY);

return total_pairs;
}

// Driver program to test above functions
int main()
{
    int X[] = {2, 1, 6};
    int Y[] = {1, 5};

    int m = sizeof(X)/sizeof(X[0]);
    int n = sizeof(Y)/sizeof(Y[0]);

    cout << "Total pairs = " << countPairs(X, Y, m, n);

    return 0;
}

```

Output:

```
Total pairs = 3
```

**Time Complexity :** Let m and n be the sizes of arrays X[] and Y[] respectively. The sort step takes  $O(n\log n)$  time. Then every element of X[] is searched in Y[] using binary search. This step takes  $O(m\log n)$  time. Overall time complexity is  $O(n\log n + m\log n)$ .

This article is contributed by **Shubham Mittal**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

## Recent Comments

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 3 minutes ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 28 minutes ago

**GOPI GOPINATH** @admin Highlight this

sentence "We can easily...

Count trailing zeroes in factorial of a number · 30 minutes ago

**newCoder3006** If the array contains negative numbers also. We...


Find subarray with given sum · 54 minutes ago


**newCoder3006** Code without using while loop. We can do it...

Find subarray with given sum · 1 hour ago

**Sanjay Agarwal** You can also use the this method:...

Count trailing zeroes in factorial of a number · 1 hour ago

AdChoices 



[Full Source Code](#)

► [Java Source Code](#)

► [Math Number](#)

AdChoices

► [Programming C++](#)

► [Natural Number](#)

► [Real Number X](#)

AdChoices

► [Numbers Number](#)

► [Code Number](#)

► [Pairs](#)

## Related Tpoics:

- Remove minimum elements from either side such that  $2 \times \text{min}$  becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



29



Tweet 3



1

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

15 Comments

GeeksforGeeks

Sort by Newest ▼





with the algorithm...



**zzzer** • a month ago

excellent for Chaudhary.

step1: sort the array Y

step2: for every element v in X:

if  $v == 1$

continue;

if  $v == 2$

count += size of Y

else

if 1 exists in Y:

count+=1

count += num of elements in Y which is bigger than v: binary search---logm

time:  $O(m \log m + n \log m)$ ,

or else we can sort X and handle every element in Y time is  $O(n \log n + m \log n)$

^ | v • Reply • Share ›



**Ankit Chaudhary** • 4 months ago

$x^y = y^x$

take natural log on both sides.

$\Rightarrow y \ln(x) = x \ln(y)$

$\Rightarrow \ln(x)/x = \ln(y)/y$

now differentiate  $\ln(x)/x$  wrt x and compare it with zero.

$\Rightarrow d/dx(\ln(x)/x)$

$\Rightarrow 1/x^2 - \ln(x)/x^2$

$\Rightarrow (1 - \ln(x))/x^2$

for all real x,  $x^2 \geq 0$

therefore :  $(1 - \ln(x)) \geq 0$  for  $x \leq e$  ( $\sim 2.71$ )

$1 - \ln(x) < 0$  for  $x > e$

So  $\ln(x)/x$  is increasing in range  $\leq e$ , i.e. for integers, its increasing for 1,2 and decreasing else where.

Following are the cases :

[see more](#)

3  |  • Reply • Share ›



**Krishna**  Ankit Chaudhary • 4 months ago

Classic :), absolutely loved it :)

 |  • Reply • Share ›



**Guest**  Krishna • 4 months ago

Sound Mathematical Explanation!!!

 |  • Reply • Share ›



**New** • 7 months ago

why do you have to decrease the number of pairs for

if  $(x == 2)$  ans  $-= (\text{NoOfY}[3] + \text{NoOfY}[4]);$

The ans can be kept as it is. There is no need to decrease

 |  • Reply • Share ›



**lovey** • 7 months ago

we can also assume one exception that if there is a '1' in an array Y, then for e with '1' from Y.

i.e,  $(x_1, 1), (x_2, 1), \dots$  and so on..

1  |  • Reply • Share ›



**new1** • 7 months ago



<http://www.codechef.com/proble...>

I think this is similar to the codechef question for OCT'13

5 ^ | v • Reply • Share ›



guest • 7 months ago

@Author ,Geeksforgeeks

Please mention following case in explanation of exception

If x is >1 ,then add number of 1's and 0's in Y,  
ans += (NoOfY[0] + NoOfY[1]);

It is difficult map as its missing in exception..

1 ^ | v • Reply • Share ›



**Tutulive** ➔ guest • 7 months ago

Hi,

The author is adding the number of 0s and 1s to the final answer because the elements greater than x and assign this value to answer. But , then satisfy the required condition ( $x^y > y^x$ ) . These extra elements are 0 and 3<sup>1</sup> > 1<sup>3</sup> . For this reason , the author is adding number of 0s and 1s to

^ | v • Reply • Share ›



guest ➔ Tutulive • 7 months ago

Yeah..I got it..But i am asking them to add the same in the post others:)

^ | v • Reply • Share ›



nikita • 7 months ago

hello...can u pls xplain... how u narrowed down to the set of exceptions??

3 ^ | v • Reply • Share ›





**blackpearl** → nikita • 7 months ago

The above question can be converted to  $(\log x/x) > (\log y/y)$  after taking

If you check the graph of  $(\log x/x)$  vs  $x$ , it increases upto somewhere be  
From this you can deduce quite easily that for  $x$  and  $y$  greater than 3, if  
else vice versa.

3 ^ | v • Reply • Share ›



**IsAs** → blackpearl • 6 months ago

if  $\log x/x > \log y/y$  then  $x^y > y^x$

We can compute two arrays corresponding to  $X[]$  and  $Y[]$  which  
New $X[]$ , New $Y[]$

We can find the pairs using newly computed arrays

Now we can sort one of the arrays i.e say New $Y[]$  and find the u  
array. This eliminates the usage of exceptions table which com

2 ^ | v • Reply • Share ›



**e** → blackpearl • 7 months ago

hello,can someone please explain the following two statements

`int* idx = upper_bound(Y, Y + n, x);`

`int ans = (Y + n) - idx;`

^ | v • Reply • Share ›



**Tutulive** → e • 7 months ago

Refer to this , <http://www.cplusplus.com/refer...>

^ | v • Reply • Share ›

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team