GeeksforGeeks

A computer science portal for geeks

டப	u	
	J	

Home	Algorithms	DS	GATE	Interv	view Corner	Q&A	С	C++	Java	Books	Contribute	Ask a Q	About
Array	Bit Magic	C/C+	+ Arti	cles	GFacts	Linked L	ist	MCQ	Misc	Outpu	t String	Tree	Graph

How are parameters passed in Java?

In Java, parameters are always passed by value. For example, following program prints i = 10, j = 20.

```
Google™ Custom Search
```

```
// Test.java
class Test {
  // swap() doesn't swap i and j
  public static void swap(Integer i, Integer j) {
      Integer temp = new Integer(i);
      i = j;
      j = temp;
  public static void main(String[] args) {
      Integer i = new Integer(10);
      Integer j = new Integer (20);
      swap(i, j);
      System.out.println("i = " + i + ", j = " + j);
```

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



53,527 people like GeeksforGeeks.



Interview Experiences

Advanced Data Structures

Dynamic Programming



Related Tpoics:

- Inner class in java
- How to compare two arrays in Java?
- Can we override private methods in Java?
- Can we Overload or Override static methods in java?
- · Static class in Java
- Do we need forward declarations in Java?
- Checked vs Unchecked Exceptions in Java
- Bitwise right shift operators in Java









Writing code in comment? Please use ideone.com and share the link here.

11 Comments

GeeksforGeeks

Sort by Newest ▼



Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and







Ahmed Jamal • 8 days ago

It is something confusing.

Please check this http://stackoverflow.com/quest...

It describes this issue with good examples:)

Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST



tirzahshulamite • 9 months ago

Java always passes the references by value. However, you can swap two strill following code is via arrays.

```
/* public static void main(String[] args) {
    String a[] = {"hello", "world"};
    swap(a);
    System.out.println(a[0] + " " + a[1]);
static void swap(String[] a) {
    String t = a[0];
    a[0] = a[1];
    a[1] = t;
}) */
```



Brajesh Kumar → tirzahshulamite • 7 months ago

all wrapper classes are immutable so you can not swap using wrapper 1 ^ Reply · Share >



mani • 9 months ago

But when we pass objects, they are passed by reference. Please correct me if 1 ^ Reply · Share >



tirzahshulamite / mani • 9 months ago

Java always passes the references by value. However, you can swap classes. The following code is via arrays.

/* public static void main(String[] args) {

Deploy Early. Deploy Often.

DevOps from Rackspace:

Automation

FIND OUT HOW >



```
String a[] = {"hello", "world"};
    swap(a);
    System.out.println(a[0] + " " + a[1]);
static void swap(String[] a) {
    String t = a[0];
    a[0] = a[1];

✓ • Reply • Share ›
```



Arun • a year ago

In JAVA, parameters are passed by value. So, when we pass an object in JAV. is refered by the name of the object. Now, if we create the wrapper class and I modifying the variable through the object will change the value at the address : as parameter) which is demonstrated by the example above using wrapper cla However, in the first code, passing Integer object passes the object's address space...just local the variable pointing to the address are swapped and not the the control returns back, it founds the same values there as before.



```
biswajit · 2 years ago
   Guess this 11 do
  class Test {
          // swap() doesn't swap i and j
          public static void swap(Integer i, Integer j) {
                  Integer temp = new Integer(i);
                  i = j;
```





Recent Comments

Abhi You live US or India?

Google (Mountain View) interview 38 minutes ago

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 1 hour ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 1 hour ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1

hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 2 hours ago

AdChoices [>

- Java Array
- ▶ Parameters Java
- Java Void

```
j = temp;
                 System.out.println("i = " + i + ", j = " + j);
          }
         public static void main(String[] args) {
                 Integer i = new Integer(10);
                 Integer j = new Integer(20);
                 System.out.println("i = " + i + ", j = " + j);
                 swap(i, j);
 }
1 ^ Reply · Share >
Agraj · 4 years ago
Good to see finally some Java Tips coming up here...:-)
karan • 4 years ago
So how do we swap integers in java?
Shekhu → karan • 4 years ago
      We can have a wrapper class over int to swap.
      [sourcecode language="java"]class intWrap {
      int x;
      public class Main {
      public static void main(String[] args) {
```

open in browser PRO version Are you a developer? Try out the HTML to PDF API

AdChoices D

AdChoices [>

▶ String Java

▶ Java Object

▶ Java Algorithm

▶ Java Wrapper

▶ Java Var Args

► Test Java Code

```
i.x = 10;
intWrap j = new intWrap();
j.x = 20;
swap(i, j);
System.out.println("i.x = " + i.x + ", j.x = " + j.x);
public static void swap(intWrap i, intWrap j) {
int temp = i.x;
i.x = j.x;
j.x = temp;
1 ^ Reply · Share >
       Ajinkya Jadhav → Shekhu · 2 years ago
       Thanks. really helpful.
       Now i know why wrappers are given so much credit in Java
       1 ^ Reply • Share >
```

Subscribe

Add Disgus to your site