

Dynamic Programming | Set 17 (Palindrome Partitioning)

Given a string, a partitioning of the string is a *palindrome partitioning* if every substring of the partition is a palindrome. For example, “aba|b|bbabb|a|b|aba” is a palindrome partitioning of “ababbbabbababa”. Determine the fewest cuts needed for palindrome partitioning of a given string. For example, minimum 3 cuts are needed for “ababbbabbababa”. The three cuts are “a|babbbab|b|ababa”. If a string is palindrome, then minimum 0 cuts are needed. If a string of length n containing all different characters, then minimum n-1 cuts are needed.

Solution

This problem is a variation of [Matrix Chain Multiplication](#) problem. If the string is palindrome, then we simply return 0. Else, like the Matrix Chain Multiplication problem, we try making cuts at all possible places, recursively calculate the cost for each cut and return the minimum value.

Let the given string be str and minPalPartion() be the function that returns the fewest cuts needed for palindrome partitioning. following is the optimal substructure property.

```
// i is the starting index and j is the ending index. i must be passed as 0 and j as strlen(str)-1
minPalPartion(str, i, j) = 0 if i == j. // When string is of length 1.
minPalPartion(str, i, j) = 0 if str[i..j] is palindrome.
```

```
// If none of the above conditions is true, then minPalPartion(str, i, j) can be
// calculated recursively using the following formula.
minPalPartion(str, i, j) = Min { minPalPartion(str, i, k) + 1 +
                                minPalPartion(str, k+1, j) }
                                where k varies from i to j-1
```



Google™ Custom Search



GeeksforGeeks



52,731 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

Following is Dynamic Programming solution. It stores the solutions to subproblems in two arrays P[][] and C[], and reuses the calculated values.

```
// Dynamic Programming Solution for Palindrome Partitioning Problem
#include <stdio.h>
#include <string.h>
#include <limits.h>

// A utility function to get minimum of two integers
int min (int a, int b) { return (a < b)? a : b; }

// Returns the minimum number of cuts needed to partition a string
// such that every part is a palindrome
int minPalPartion(char *str)
{
    // Get the length of the string
    int n = strlen(str);

    /* Create two arrays to build the solution in bottom up manner
       C[i][j] = Minimum number of cuts needed for palindrome partitioning
                of substring str[i..j]
       P[i][j] = true if substring str[i..j] is palindrome, else false
       Note that C[i][j] is 0 if P[i][j] is true */
    int C[n][n];
    bool P[n][n];

    int i, j, k, L; // different looping variables

    // Every substring of length 1 is a palindrome
    for (i=0; i<n; i++)
    {
        P[i][i] = true;
        C[i][i] = 0;
    }

    /* L is substring length. Build the solution in bottom up manner by
       considering all substrings of length starting from 2 to n.
       The loop structure is same as Matrix Chain Multiplication problem
       See http://www.geeksforgeeks.org/archives/15553 */
    for (L=2; L<=n; L++)
    {
        // For substring of length L, set different possible starting
        for (i=0; i<n-L+1; i++)
        {
            j = i+L-1; // Set ending index

            // If L is 2, then we just need to compare two characters
```

Computer Algorithms

ITT Tech - Official Site

itt-tech.edu

Tech-Oriented Degree Programs.
Education for the Future.



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

// If L is 2, then we just need to compare two characters.
// need to check two corner characters and value of P[i+1]
if (L == 2)
    P[i][j] = (str[i] == str[j]);
else
    P[i][j] = (str[i] == str[j]) && P[i+1][j-1];

// IF str[i..j] is palindrome, then C[i][j] is 0
if (P[i][j] == true)
    C[i][j] = 0;
else
{
    // Make a cut at every possible localtion starting from i
    // and get the minimum cost cut.
    C[i][j] = INT_MAX;
    for (k=i; k<=j-1; k++)
        C[i][j] = min (C[i][j], C[i][k] + C[k+1][j]+1);
}
}

// Return the min cut value for complete string. i.e., str[0..n-1]
return C[0][n-1];
}

```

```

// Driver program to test above function
int main()
{
    char str[] = "ababbbabbababa";
    printf("Min cuts needed for Palindrome Partitioning is %d",
        minPalPartion(str));
    return 0;
}

```

Output:

Min cuts needed for Palindrome Partitioning is 3

Time Complexity: $O(n^3)$

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



695



Recent Comments

affiszerv Your example has two 4s on row 3, that's why it...

[Backtracking | Set 7 \(Sudoku\) · 16 minutes ago](#)

RVM Can someone please elaborate this Qs from above...

[Flipkart Interview | Set 6 · 36 minutes ago](#)

Vishal Gupta I talked about as an Interviewer in general,...

[Software Engineering Lab, Samsung Interview | Set 2 · 36 minutes ago](#)

@meya Working solution for question 2 of 4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\) · 1 hour ago](#)
sandeep void rearrange(struct node *head)
{...

Given a linked list, reverse alternate nodes and append at the end · 2 hours ago

Neha I think that is what it should return as, in...

[Find depth of the deepest odd level leaf node · 2 hours ago](#)

Related Topics:

- [Printing Longest Common Subsequence](#)
- [Suffix Array | Set 2 \(nLogn Algorithm\)](#)
- [Rearrange a string so that all same characters become d distance away](#)
- [Recursively remove all adjacent duplicates](#)
- [Find the first non-repeating character from a stream of characters](#)
- [Dynamic Programming | Set 33 \(Find if a string is interleaved of two other strings\)](#)
- [Remove "b" and "ac" from a given string](#)
- [Dynamic Programming | Set 29 \(Longest Common Substring\)](#)



3



0




Writing code in comment? Please use [ideone.com](#) and share the link here.

AdChoices 

▶ [Graph C++](#)

▶ [Palindrome](#)


▶ [Java to C++](#)

AdChoices 

▶ [Graph Java](#)

▶ [Partitioning](#)

▶ [String Java](#)

AdChoices 

▶ [I Palindrome I](#)

▶ [String Set](#)

▶ [String Functions](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team