

## Find four elements that sum to a given value | Set 1 ( $n^3$ solution)

Given an array of integers, find all combination of four elements in the array whose sum is equal to a given value X.

For example, if the given array is {10, 2, 3, 4, 5, 9, 7, 8} and X = 23, then your function should print "3 5 7 8" (3 + 5 + 7 + 8 = 23).

**Sources:** [Find Specific Sum](#) and [Amazon Interview Question](#)

A **Naive Solution** is to generate all possible quadruples and compare the sum of every quadruple with X. The following code implements this simple method using four nested loops

```
#include <stdio.h>

/* A naive solution to print all combination of 4 elements in A[]
with sum equal to X */
void findFourElements(int A[], int n, int X)
{
    // Fix the first element and find other three
    for (int i = 0; i < n-3; i++)
    {
        // Fix the second element and find other two
        for (int j = i+1; j < n-2; j++)
        {
            // Fix the third element and find the fourth
            for (int k = j+1; k < n-1; k++)
            {
                // find the fourth
                for (int l = k+1; l < n; l++)
                {
                    if (A[i] + A[j] + A[k] + A[l] == X)
                        printf("%d, %d, %d, %d", A[i], A[j], A[k], A[l]);
                }
            }
        }
    }
}
```


Google™ Custom Search



GeeksforGeeks



53,520 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```

    }
}

// Driver program to test above function
int main()
{
    int A[] = {10, 20, 30, 40, 1, 2};
    int n = sizeof(A) / sizeof(A[0]);
    int X = 91;
    findFourElements (A, n, X);
    return 0;
}

```

Output:

20, 30, 40, 1

Time Complexity:  $O(n^4)$

The time complexity can be improved to  $O(n^3)$  with the **use of sorting** as a preprocessing step, and then using method 1 of [this](#) post to reduce a loop.

Following are the detailed steps.

- 1) Sort the input array.
- 2) Fix the first element as  $A[i]$  where  $i$  is from 0 to  $n-3$ . After fixing the first element of quadruple, fix the second element as  $A[j]$  where  $j$  varies from  $i+1$  to  $n-2$ . Find remaining two elements in  $O(n)$  time, using the method 1 of [this](#) post

Following is C implementation of  $O(n^3)$  solution.

```

#include <stdio.h>
#include <stdlib.h>

/* Following function is needed for library function qsort(). Refer
http://www.cplusplus.com/reference/clibrary/cstdlib/qsort/ */
int compare (const void *a, const void * b)
{ return ( *(int *)a - *(int *)b ); }

/* A sorting based solution to print all combination of 4 elements in
with sum equal to X */
void find4Numbers(int A[], int n, int X)
{
    int l, r;

```

.....

Advertise locally or globally.

Get a \$75 credit when you spend your first \$25

Show me how



## Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```

// Sort the array in increasing order, using library
// function for quick sort
qsort (A, n, sizeof(A[0]), compare);

/* Now fix the first 2 elements one by one and find
the other two elements */
for (int i = 0; i < n - 3; i++)
{
    for (int j = i+1; j < n - 2; j++)
    {
        // Initialize two variables as indexes of the first and la
        // elements in the remaining elements
        l = j + 1;
        r = n-1;


        // To find the remaining two elements, move the index
        // variables (l & r) toward each other.
        while (l < r)
        {
            if( A[i] + A[j] + A[l] + A[r] == X)
            {
                printf("%d, %d, %d, %d", A[i], A[j],
                                A[l], A[r]);

                l++; r--;
            }
            else if (A[i] + A[j] + A[l] + A[r] < X)
                l++;
            else // A[i] + A[j] + A[l] + A[r] > X
                r--;
        } // end of while
    } // end of inner for loop
} // end of outer for loop
}

/* Driver program to test above function */
int main()
{
    int A[] = {1, 4, 45, 6, 10, 12};
    int X = 21;
    int n = sizeof(A)/sizeof(A[0]);
    find4Numbers(A, n, X);
    return 0;
}

```


Output:



Time Complexity:  $O(n^3)$

This problem can also be solved in  $O(n^2 \log n)$  complexity. We will soon be publishing the  $O(n^2 \log n)$  solution as a separate post.

Please write comments if you find any of the above codes/algorithms incorrect, or find other ways to solve the same problem.



## Related Tpoics:

- Remove minimum elements from either side such that  $2 \times \min$  becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)

## Recent Comments

**Aman** Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 9 minutes ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 12 minutes ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 37 minutes ago

**GOPI GOPINATH** @admin Highlight this sentence "We can easily...


Count trailing zeroes in factorial of a number · 39 minutes ago

**newCoder3006** If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 1 hour ago

**newCoder3006** Code without using while loop. We can do it...

[Find subarray with given sum](#) · 1 hour ago

AdChoices 

[► C++ Code](#)

[► SUM Function](#)

[► SUM Program](#)

- Count all possible groups of size 2 or 3 that have sum as multiple of 3



0



Tweet

0



0

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

9 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



**Messe** • 5 months ago

Hello please tell me how to extend from 4 combination to 5 or 6

^ | v • Reply • Share ›



**abhishek08aug** • a year ago

Intelligent :D

```
/* Paste your code here (You may delete these lines if not writing c
```

^ | v • Reply • Share ›



**pallavi711** • a year ago

what if the question is to find all possible combinations of numbers from the gi  
how to proceed for it?

eg  $A[] = \{1, 2, 4, 6, 7, 8\}$  and  $X=7$

ans would be 1,6;1,2,4;7

^ | v • Reply • Share ›



**Nishant** • 2 years ago

$O(n^2 \log n)$ :

AdChoices

► [SUM Function](#)

► [SUM Program](#)

► [SUM Time](#)

AdChoices

► [SUM To](#)

► [Java Array](#)

► [SUM SUM](#)

```

void find_result ( int32_t array[] , int32_t sum , int32_t count , int32_t number )
if (number>=max || sum<0 )
return;
if (sum==0 && count==4) {
print ( count );
count--;
sum=sum-array[number];
}
find_result ( array , sum , count , number+1 );
temp_array[count++]=array[number];
sum=sum-array[number];
find_result ( array , sum , count , number+1 );
}

```

^ | v • Reply • Share ›



**Nishant Mittal** • 2 years ago

code of  $O(n^2 \log n)$

```
#define max 100
```

```

int32_t temp_array[max];
void print ( int32_t c ) {
int32_t i=0;
for (i=0; i=max || sum<0 ) {
return;
}
if (sum==0) {
print ( count );
count--;
sum=sum-array[number];
}
find_result ( array , sum , count , number+1 );
temp_array[count++]=array[number];
}

```

```
temp_array[count++]=array[number],  
sum=sum+array[number];  
find_result(array, sum, count, number+1);
```

[see more](#)

^ | v • Reply • Share ›



**Nishant Mittal** → Nishant Mittal • 2 years ago

sorry some problem with pasting /\* ignore the above code \*/

^ | v • Reply • Share ›



**suresh** • 2 years ago

very helpful

thanks..... for this post

^ | v • Reply • Share ›



**Rajat** • 2 years ago

There are a couple of clarifications I wanted to add to the problems.

(1) As per the problem description we need to print ALL combinations that sum to X. For example, for the problem ({10, 2, 3, 4, 5, 9, 7, 8} and X=23), the expected output is only "3,5,7,8" correct. Consider rewriting the example with correct and complete expected output.

(2) It seems that there is an implicit assumption, that the numbers in the array are distinct. And if there can be duplicates, then the solution given above can print duplicates.

^ | v • Reply • Share ›



**shanky** • 2 years ago

Hi Can u please post O(N^2logn)

```
/* Paste your code here (You may delete these lines if not writing code)
```

^ | v • Reply • Share ›

 [Subscribe](#)

 [Add Disqus to your site](#)

@geeksforgeeks, **Some rights reserved**

[Contact Us!](#)

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team