

## Find the maximum element in an array which is first increasing and then decreasing

Given an array of integers which is initially increasing and then decreasing, find the maximum value in the array.

Input: arr[] = {8, 10, 20, 80, 100, 200, 400, 500, 3, 2, 1}

Output: 500

Input: arr[] = {1, 3, 50, 10, 9, 7, 6}

Output: 50

Corner case (No decreasing part)

Input: arr[] = {10, 20, 30, 40, 50}

Output: 50

Corner case (No increasing part)

Input: arr[] = {120, 100, 80, 20, 0}

Output: 120

### Method 1 (Linear Search)

We can traverse the array and keep track of maximum and element. And finally return the maximum element.

```
#include <stdio.h>

int findMaximum(int arr[], int low, int high)
{
    int max = arr[low];
```




Google™ Custom Search



GeeksforGeeks



53,521 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```

int i;
for (i = low; i <= high; i++)
{
    if (arr[i] > max)
        max = arr[i];
}
return max;
}

/* Driver program to check above functions */
int main()
{
    int arr[] = {1, 30, 40, 50, 60, 70, 23, 20};
    int n = sizeof(arr)/sizeof(arr[0]);
    printf("The maximum element is %d", findMaximum(arr, 0, n-1));
    getchar();
    return 0;
}

```

Time Complexity:  $O(n)$

## Method 2 (Binary Search)

We can modify the standard Binary Search algorithm for the given type of arrays.

- i) If the mid element is greater than both of its adjacent elements, then mid is the maximum.
- ii) If mid element is greater than its next element and smaller than the previous element then maximum lies on left side of mid. Example array: {3, 50, 10, 9, 7, 6}
- iii) If mid element is smaller than its next element and greater than the previous element then maximum lies on right side of mid. Example array: {2, 4, 6, 8, 10, 3, 1}

```
#include <stdio.h>
```

```

int findMaximum(int arr[], int low, int high)
{
    /* Base Case: Only one element is present in arr[low..high]*/
    if (low == high)
        return arr[low];

    /* If there are two elements and first is greater then
    the first element is maximum */
    if ((high == low + 1) && arr[low] >= arr[high])
        return arr[low];
}

```



## Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```

/* If there are two elements and second is greater then
the second element is maximum */
if ((high == low + 1) && arr[low] < arr[high])
    return arr[high];

int mid = (low + high)/2;    /*low + (high - low)/2;*/

/* If we reach a point where arr[mid] is greater than both of
its adjacent elements arr[mid-1] and arr[mid+1], then arr[mid]
is the maximum element*/
if ( arr[mid] > arr[mid + 1] && arr[mid] > arr[mid - 1])
    return arr[mid];

/* If arr[mid] is greater than the next element and smaller than the
element then maximum lies on left side of mid */
if (arr[mid] > arr[mid + 1] && arr[mid] < arr[mid - 1])
    return findMaximum(arr, low, mid-1);
else // when arr[mid] is greater than arr[mid-1] and smaller than a
    return findMaximum(arr, mid + 1, high);
}

/* Driver program to check above functions */
int main()
{
    int arr[] = {1, 3, 50, 10, 9, 7, 6};
    int n = sizeof(arr)/sizeof(arr[0]);
    printf("The maximum element is %d", findMaximum(arr, 0, n-1));
    getchar();
    return 0;
}

```

Time Complexity:  $O(\log n)$

This method works only for distinct numbers. For example, it will not work for an array like {0, 1, 1, 2, 2, 2, 2, 2, 3, 4, 4, 5, 3, 3, 2, 2, 1, 1}.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

**HIGH-PERFORMANCE COMPUTING ON A UNIVERSITY BUDGET**

*The quest to find tailored server capabilities on a shoestring*

To conduct successful university research and crunch massive amounts of data, you need the highest-performing hardware on the market. Unfortunately, the price tag of high performance can be daunting for researchers who rely on grants to fund their projects.

There are many off-the-shelf server options available, of course, and your department may even have a standardized, prescribed server.

The best bang for your buck, however, may be to configure a custom server to fit your exact high-performance computing needs.

Unsure of how to get the best performance out of your application? Do you need assistance answering any of these questions?

**WHAT NETWORKING INTERFACES ARE NEEDED?**

- ☐ 1GbE
- ☐ 10GbE
- ☐ 40GbE
- ☐ InfiniBand
- ☐ Unsure

**HOW MANY CPU CORES DO YOU WANT?**

- ☐ 4
- ☐ 8
- ☐ 12
- ☐ 16
- ☐ Unsure


**HOW MUCH STORAGE DO YOU WANT?**

- ☐ 1TB
- ☒ 2TB
- ☐ 4TB
- ☐ 8TB
- ☐ 16TB
- ☐ 32TB
- ☐ 64TB
- ☐ 128TB
- ☐ 256TB
- ☐ 512TB
- ☐ 1TB+
- ☐ Unsure

**WHAT OPERATING SYSTEM ARE YOU RUNNING?**

- ☐ Linux Variant
- ☐ Windows Server
- ☐ VMWare
- ☐ Unsure

**Download To See Entire Infographic**



## Related Topics:

- Remove minimum elements from either side such that  $2 \times \text{min}$  becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



2



Tweet

0



1

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

705



Subscribe

## Recent Comments

**Aman** Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 15 minutes

ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 19 minutes

ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 44

minutes ago

**GOPI GOPINATH** @admin Highlight this

sentence "We can easily...

Count trailing zeroes in factorial of a number · 45

minutes ago

**newCoder3006** If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

**newCoder3006** Code without using while loop. We can do it...


Find subarray with given sum · 1 hour ago

AdChoices 

▶ [JavaScript Array](#)

▶ [Java Array](#)


▶ [C++ Array](#)

AdChoices 

▶ [Array Max](#)

▶ [Array Reference](#)

▶ [C++ Code](#)

AdChoices 

▶ [An Array](#)

▶ [Array Element](#)

▶ [Programming C++](#)

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team