

| | | | | | | | | | | | | |
|-----------------------|----------------------------|-----------------------|--------------------------|----------------------------------|-----------------------------|---------------------|----------------------|------------------------|------------------------|----------------------------|-------------------------|-----------------------|
| Home | Algorithms | DS | GATE | Interview Corner | Q&A | C | C++ | Java | Books | Contribute | Ask a Q | About |
| Array | Bit Magic | C/C++ | Articles | GFactS | Linked List | MCQ | Misc | Output | String | Tree | Graph | |

Iterative Preorder Traversal

Given a Binary Tree, write an iterative function to print Preorder traversal of the given binary tree.

Refer [this](#) for recursive preorder traversal of Binary Tree. To convert an inherently recursive procedures to iterative, we need an explicit stack. Following is a simple stack based iterative process to print Preorder traversal.

- 1) Create an empty stack *nodeStack* and push root node to stack.
- 2) Do following while *nodeStack* is not empty.
 -a) Pop an item from stack and print it.
 -b) Push right child of popped item to stack
 -c) Push left child of popped item to stack

Right child is pushed before left child to make sure that left subtree is processed first.

```
#include <stdlib.h>
#include <stdio.h>
#include <iostream>
#include <stack>

using namespace std;

/* A binary tree node has data, left child and right child */
struct node
{
    int data;
    struct node* left;
    struct node* right;
};

/* Helper function that allocates a new node with the given data and
   NULL left and right pointers.*/
```



GeeksforGeeks



52,731 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

```

struct node* newNode(int data)
{
    struct node* node = new struct node;
    node->data = data;
    node->left = NULL;
    node->right = NULL;
    return (node);
}

```

```

// An iterative process to print preorder traversal of Binary tree
void iterativePreorder(node *root)
{
    // Base Case
    if (root == NULL)
        return;

    // Create an empty stack and push root to it
    stack<node *> nodeStack;
    nodeStack.push(root);

    /* Pop all items one by one. Do following for every popped item
    a) print it
    b) push its right child
    c) push its left child
    Note that right child is pushed first so that left is processed first */
    while (nodeStack.empty() == false)
    {
        // Pop the top item from stack and print it
        struct node *node = nodeStack.top();
        printf ("%d ", node->data);
        nodeStack.pop();

        // Push right and left children of the popped node to stack
        if (node->right)
            nodeStack.push(node->right);
        if (node->left)
            nodeStack.push(node->left);
    }
}

```

```

// Driver program to test above functions
int main()
{
    /* Constructed binary tree is
        10
       /  \
      8    2
    */
}

```

Shouldn't you expect a cloud with:

ONE-CLICK DEPLOYMENTS

Experience the Managed Cloud Difference

TRY TODAY ▶



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

      3   /   \   5   2   /
    */
struct node *root = newNode(10);
root->left      = newNode(8);
root->right     = newNode(2);
root->left->left = newNode(3);
root->left->right = newNode(5);
root->right->left = newNode(2);
iterativePreorder(root);
return 0;
}

```

Output:

10 8 3 5 2 2

This article is compiled by Saurabh Sharma and reviewed by GeeksforGeeks team. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Better Than Hadoop.

HPCC Systems is Big Data Processing and Analytics
Open Source. Proven. Trusted.

 LexisNexis®

Learn More 

Related Tpoics:



 **rackspace**®
the open cloud company

- Print a Binary Tree in Vertical Order | Set 2 (Hashmap based Method)
- Print Right View of a Binary Tree
- Red-Black Tree | Set 3 (Delete)
- Construct a tree from Inorder and Level order traversals
- Print all nodes at distance k from a given node
- Print a Binary Tree in Vertical Order | Set 1
- Interval Tree
- Check if a given Binary Tree is height balanced like a Red-Black Tree



5



0



0

Writing code in comment? Please use ideone.com and share the link here.

19 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



carmen cojocar · 3 months ago

Can you post an implementation for the post-order also? I've seen some versi complicated. Yours is so clean. Thank you.

^ | v · Reply · Share ›



Vivek · 6 months ago

no need to push the right child into the stack

```
void preOrderIterative(struct node *root)
```

695



Subscribe

Recent Comments

affiszerv Your example has two 4s on row 3, that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 35 minutes ago

RVM Can someone please elaborate this Qs from above...

[Flipkart Interview | Set 6](#) · 55 minutes ago

Vishal Gupta I talked about as an Interviewer in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 55 minutes ago

@meya Working solution for question 2 of 4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago

sandeep void rearrange(struct node *head) {...

[Given a linked list, reverse alternate nodes and append at the end](#) · 2 hours ago

Neha I think that is what it should return as, in...

[Find depth of the deepest odd level leaf node](#) · 3 hours ago

```

{

    struct stknode *st=NULL;

    while(!empty(st) || root)

    {

        while(root)

        {

            printf("%d ",root->data);

```

see more

^ | v • Reply • Share ›



Amit Bgl • 9 months ago

wow code :D

^ | v • Reply • Share ›



dex • 9 months ago

```

/*
    iterative preorder of bst using explicit stack
*/

```

```

#include<stdio.h>
#include<stdlib.h>

```

```

struct tree
{

```

AdChoices ▶

▶ [Graph Java](#)

▶ [Java to C++](#)

▶ [Preorder](#)

AdChoices ▶

▶ [Java Array](#)

▶ [Tree Root](#)

▶ [Node](#)

AdChoices ▶

▶ [Tree Block](#)

▶ [Stack](#)

▶ [Null Pointer](#)

```
    int data;
    struct tree *left;
    struct tree *right;
};
typedef struct tree node;
void addnode(node *,int);

struct llist
```

[see more](#)

2 ^ | v • Reply • Share ›



dex → dex • 9 months ago

debugged!,

I constructed the tree itself wrong while checking p->data and n .

^ | v • Reply • Share ›



dex • 9 months ago

/*

iterative preorder of bst using explicit stack

*/

```
#include
```

```
#include
```

```
struct tree
```

```
{
```

```
int data;
```

```
struct tree *left;
```

```
struct tree *right;
```

```
};
```

```
typedef struct tree node;
void addnode(node *,int);
```

```
struct llist
{
struct tree *to:
```

[see more](#)

^ | v • Reply • Share ›



zyzz • 10 months ago

i think this one is easy

```
/void preorder(struct node *temp){
int top=0;
struct node *s[20];
s[0]=NULL;
printf("preorder : \n");
while(temp!=NULL){
    printf("%d \t",temp->data);

    if(temp->right!=NULL){

        s[++top]=temp->right;
    }

    if(temp->left!=NULL){
```

[see more](#)

^ | v • Reply • Share ›



abhishek08aug · 11 months ago

Intelligent :D

^ | v · Reply · Share ›



SHASHI KUMAR · a year ago

#include

#include

struct node

{

int data;

struct node *right;

struct node *left;

}*root,*S[10];

int i=0;

void Push(struct node *p)

{

S[i++]=p;

}

struct node *Pop()

{

return S[--i];

}

void preorder()

[see more](#)

^ | v · Reply · Share ›



Veer Verma · a year ago

Is modified version of Morris Traversal possible for PreOrder??

^ | v · Reply · Share ›



Ashok · 2 years ago



Using stack is as good as using recursion. Modify the morris algorithm from in order to get the intended answer.

2 ^ | v • Reply • Share ›



Ashok • 2 years ago

Using stack is as good as using recursion. Modify the morris algorithm from in order to get the intended answer.

```
/* Paste your code here (You may delete these lines if not writing code)
```

^ | v • Reply • Share ›



Venki • 2 years ago

I guess the code can be refactored. Preorder relatively consumes less stack space than the nodes to stack, which is not necessary. See sample code (not tested),

```
void Preorder(Node *pRoot) {
    Node *pMove = pRoot;
    stack<Node *> s;

    s.push(NULL); // To recognize end of processing
    while( pMove ) {

        cout << pMove->key;

        if( pMove->right )
            s.push(pMove->right); // Only we need to keep track of right child

        if( pMove->left )
            pMove = pMove->left;
        else
            pMove = s.top();
        s.pop();
    }
}
```

```

    else {
        pMove = s.top();
        s.pop();
    }
}
}
}

```

^ | v • Reply • Share ›



Palash → Venki • a year ago

You'd at best be saving one node space in the stack, that you are anyway beginning. No point of this.

^ | v • Reply • Share ›



Venki → Palash • a year ago

It is nothing but do-undo behaviour. It consumes processing power. NULL doesn't cost much when compared to repeated do-undo

^ | v • Reply • Share ›



Suman • 2 years ago

[sourcecode language="JAVA"]

```

public static void traverseliterative(TreeNode root){
    Stack<TreeNode> stack = new Stack<TreeNode>();
    stack.push(root);
    TreeNode currentNode = root;
    while(!stack.isEmpty()){
        while (currentNode != null){
            System.out.println(currentNode.data);
            currentNode = currentNode.left;
            if (currentNode != null){
                stack.push(currentNode);
            }
        }
    }
}

```

```
}  
currentNode = stack.pop();  
currentNode = currentNode.right;  
if (currentNode != null){  
stack.push(currentNode);  
}  
}  
}
```

^ | v • Reply • Share ›



Leet • 2 years ago

Can we do preorder traversal without recursion and without stack?

^ | v • Reply • Share ›



Vikas → Leet • 2 years ago

That would be using Morris Traversal. Look it up on wiki.

^ | v • Reply • Share ›



atul → Vikas • 2 years ago

morris traversal does inorder traversal

```
/* Paste your code here (You may delete these lines if r
```

^ | v • Reply • Share ›



Subscribe



Add Disqus to your site

