

Find the two non-repeating elements in an array of repeating elements

Asked by SG

Given an array in which all numbers except two are repeated once. (i.e. we have $2n+2$ numbers and n numbers are occurring twice and remaining two have occurred once). Find those two numbers in the most efficient way.

Method 1(Use Sorting)

First sort all the elements. In the sorted array, by comparing adjacent elements we can easily get the non-repeating elements. Time complexity of this method is $O(n\log n)$

Method 2(Use XOR)

Let x and y be the non-repeating elements we are looking for and $arr[]$ be the input array. First calculate the XOR of all the array elements.

```
xor = arr[0]^arr[1]^arr[2].....arr[n-1]
```

All the bits that are set in xor will be set in one non-repeating element (x or y) and not in other. So if we take any set bit of xor and divide the elements of the array in two sets – one set of elements with same bit set and other set with same bit not set. By doing so, we will get x in one set and y in another set. Now if we do XOR of all the elements in first set, we will get first non-repeating element, and by doing same in other set we will get the second non-repeating element.

Let us see an example.

```
arr[] = {2, 4, 7, 9, 2, 4}
```

1) Get the XOR of all the elements.

```
xor = 2^4^7^9^2^4 = 14 (1110)
```

Google™ Custom Search



GeeksforGeeks



53,526 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

2) Get a number which has only one set bit of the xor.

Since we can easily get the rightmost set bit, let us use it.

$\text{set_bit_no} = \text{xor} \& \sim(\text{xor}-1) = (1110) \& \sim(1101) = 0010$

Now `set_bit_no` will have only set as rightmost set bit of `xor`.

3) Now divide the elements in two sets and do xor of elements in each set, and we get the non-repeating elements 7 and 9. Please see implementation for this step.

Implementation:

```
#include <stdio.h>
#include <stdlib.h>

/* This function sets the values of *x and *y to nonr-epeating
elements in an array arr[] of size n*/
void get2NonRepeatingNos(int arr[], int n, int *x, int *y)
{
    int xor = arr[0]; /* Will hold xor of all elements */
    int set_bit_no; /* Will have only single set bit of xor */
    int i;
    *x = 0;
    *y = 0;

    /* Get the xor of all elements */
    for(i = 1; i < n; i++)
        xor ^= arr[i];

    /* Get the rightmost set bit in set_bit_no */
    set_bit_no = xor & ~(xor-1);

    /* Now divide elements in two sets by comparing rightmost set
bit of xor with bit at same position in each element. */
    for(i = 0; i < n; i++)
    {
        if(arr[i] & set_bit_no)
            *x = *x ^ arr[i]; /*XOR of first set */
        else
            *y = *y ^ arr[i]; /*XOR of second set*/
    }
}

/* Driver program to test above function */
int main()
```

```

{
    int arr[] = {2, 3, 7, 9, 11, 2, 3, 11};
    int *x = (int *)malloc(sizeof(int));
    int *y = (int *)malloc(sizeof(int));
    get2NonRepeatingNos(arr, 8, x, y);
    printf("The non-repeating elements are %d and %d", *x, *y);
    getchar();
}

```

Time Complexity: $O(n)$

Auxiliary Space: $O(1)$

Find + Remove Duplicates

 dataladder.com/RemoveDuplicates

\$0 License and free support Clean up your duplicate data today!



Related Topics:

- Check if a number is multiple of 9 using bitwise operators
- How to swap two numbers without using a temporary variable?
- Divide and Conquer | Set 4 (Karatsuba algorithm for fast multiplication)
- Find position of the only set bit
- Swap all odd and even bits
- Add two bit strings
- Write your own strcmp that ignores cases

Deploy Early. Deploy Often.

DevOps from
Rackspace:

Automation

FIND OUT HOW ►



- Binary representation of a given number



2



Tweet

0



1

Writing code in comment? Please use ideone.com and share the link here.

705



Subscribe

Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 20 minutes ago

Aman Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 59 minutes ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

[Root to leaf path sum equal to a given number](#) · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

[Count trailing zeroes in factorial of a number](#) · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...


[Find subarray with given sum](#) · 1 hour ago

AdChoices

► [Java Array](#)

► [C++ Array](#)


► [Memory Array](#)

AdChoices 

► [An Array](#)

► [Math Array](#)

► [Repeating](#)

AdChoices 

► [Java Elements](#)

► [Array Elements](#)

► [Elements Time](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team