

Delete N nodes after M nodes of a linked list

Given a linked list and two integers M and N. Traverse the linked list such that you retain M nodes then delete next N nodes, continue the same till end of the linked list.

Difficulty Level: Rookie

Examples:

Input:

M = 2, N = 2

Linked List: 1->2->3->4->5->6->7->8

Output:

Linked List: 1->2->5->6

Input:

M = 3, N = 2

Linked List: 1->2->3->4->5->6->7->8->9->10

Output:

Linked List: 1->2->3->6->7->8

Input:

M = 1, N = 1

Linked List: 1->2->3->4->5->6->7->8->9->10

Output:

Linked List: 1->3->5->7->9

The main part of the problem is to maintain proper links between nodes, make sure that all corner



Google™ Custom Search



GeeksforGeeks



53,527 people like GeeksforGeeks.



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

cases are handled. Following is C implementation of function skipMdeleteN() that skips M nodes and delete N nodes till end of list. It is assumed that M cannot be 0.

```
// C program to delete N nodes after M nodes of a linked list
#include <stdio.h>
#include <stdlib.h>

// A linked list node
struct node
{
    int data;
    struct node *next;
};

/* Function to insert a node at the beginning */
void push(struct node ** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node = (struct node*) malloc(sizeof(struct node))

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*head_ref);

    /* move the head to point to the new node */
    (*head_ref) = new_node;
}

/* Function to print linked list */
void printList(struct node *head)
{
    struct node *temp = head;
    while (temp != NULL)
    {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

// Function to skip M nodes and then delete N nodes of the linked list
void skipMdeleteN(struct node *head, int M, int N)
{
    struct node *curr = head, *t;
    int count;
```



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```
// The main loop that traverses through the whole list
while (curr)
{
    // Skip M nodes
    for (count = 1; count<M && curr!= NULL; count++)
        curr = curr->next;

    // If we reached end of list, then return
    if (curr == NULL)
        return;

    // Start from next node and delete N nodes
    t = curr->next;
    for (count = 1; count<=N && t!= NULL; count++)
    {
        struct node *temp = t;
        t = t->next;
        free(temp);
    }
    curr->next = t; // Link the previous list with remaining nodes

    // Set current pointer for next iteration
    curr = t;
}
}
```

```
// Driver program to test above functions
int main()
{
    /* Create following linked list
    1->2->3->4->5->6->7->8->9->10 */
    struct node* head = NULL;
    int M=2, N=3;
    push(&head, 10);
    push(&head, 9);
    push(&head, 8);
    push(&head, 7);
    push(&head, 6);
    push(&head, 5);
    push(&head, 4);
    push(&head, 3);
    push(&head, 2);
    push(&head, 1);

    printf("M = %d, N = %d \nGiven Linked list is :\n", M, N);
    printList(head);
}
```

New SSD Cloud Server



```

skipMdeleteN(head, M, N);

printf("\nLinked list after deletion is :\n");
printList(head);

return 0;
}

```

Output:

```

M = 2, N = 3
Given Linked list is :
1 2 3 4 5 6 7 8 9 10

```


```

Linked list after deletion is :
1 2 6 7

```

Time Complexity: $O(n)$ where n is number of nodes in linked list.

This article is contributed by **Chandra Prakash**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 46 minutes ago

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 1 hour ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 1 hour ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...


Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 2 hours ago

AdChoices 

[▶ Linked List](#)

[▶ C++ Linked List](#)

[▶ Node](#)

AdChoices 

[▶ Programming C++](#)

[▶ Node 2](#)

Related Tpoics:

- Given a linked list, reverse alternate nodes and append at the end
- Pairwise swap elements of a given linked list by changing links
- Self Organizing List | Set 1 (Introduction)
- Merge a linked list into another linked list at alternate positions
- QuickSort on Singly Linked List
- Design a stack with operations on middle element
- Swap Kth node from beginning with Kth node from end in a Linked List
- QuickSort on Doubly Linked List



52



Tweet

4



1

Writing code in comment? Please use ideone.com and share the link here.

► [Dom Nodes](#)

AdChoices ►

► [Java Array](#)

► [C++ Java](#)

► [C++ Example](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team