

Comparison of static keyword in C++ and Java

Static keyword is used for almost same purpose in both C++ and Java. There are some differences though. This post covers similarities and differences of static keyword in C++ and Java.

Static Data Members: Like C++, static data members in Java are class members and shared among all objects. For example, in the following Java program, static variable *count* is used to count the number of objects created.

```
class Test {
    static int count = 0;


    Test() {
        count++;
    }
    public static void main(String arr[]) {
        Test t1 = new Test();
        Test t2 = new Test();
        System.out.println("Total " + count + " objects created");
    }
}
```

Output:

Total 2 objects created

Static Member Methods: Like C++, methods declared as static are class members and have following restrictions:


1) They can only call other static methods. For example, the following program fails in compilation. fun() is non-static and it is called in static main()



GeeksforGeeks



53,527 people like GeeksforGeeks.



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

```
class Main {
    public static void main(String args[]) {
        System.out.println(fun());
    }
    int fun() {
        return 20;
    }
}
```

2) They must only access static data.

3) They cannot access *this* or *super*. For example, the following program fails in compilation.

```
class Base {
    static int x = 0;
}

class Derived extends Base
{
    public static void fun() {
        System.out.println(super.x); // Compiler Error: non-static vari
        // cannot be referenced from a stati
    }
}
```

Like C++, static data members and static methods can be accessed without creating an object. They can be accessed using class name. For example, in the following program, static data member count and static method fun() are accessed without any object.

```
class Test {
    static int count = 0;
    public static void fun() {
        System.out.println("Static fun() called");
    }
}

class Main
{
    public static void main(String arr[]) {
        System.out.println("Test.count = " + Test.count);
        Test.fun();
    }
}
```

Static Block: Unlike C++, Java supports a special block, called static block (also called static



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)


[Sorted Linked List to Balanced BST](#)

clause) which can be used for static initialization of a class. This code inside static block is executed only once. See [Static blocks in Java](#) for details.

Static Local Variables: Unlike C++, Java doesn't support static local variables. For example, the following Java program fails in compilation.

```
class Test {  
    public static void main(String args[]) {  
        System.out.println(fun());  
    }  
    static int fun() {  
        static int x= 10; //Compiler Error: Static local variables are not allowed  
        return x--;  
    }  
}
```

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Related Topics:


- [Inner class in java](#)

Deploy Early. Deploy Often.

DevOps from
Rackspace:

Automation

[FIND OUT HOW ►](#)



the open cloud company

- inner class in java
- How to compare two arrays in Java?
- Can we override private methods in Java?
- Can we Overload or Override static methods in java ?
- Static class in Java
- Do we need forward declarations in Java?
- Checked vs Unchecked Exceptions in Java
- Bitwise right shift operators in Java



0



Tweet

0



0

Writing code in comment? Please use ideone.com and share the link here.

705



Subscribe

Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 38 minutes ago

Aman Hi, Why arent we checking for conditions...

Sort by Newest ▾



Join the discussion...

**Anonymous** · 3 months ago

A Static Variable is visible or accessible only within the class or only by memb throughout the program means it can hold the same value throughout the lifeti

Nice Reference here

<http://geeksprogrammings.blogs...>

^ | ▾ · Reply · Share ›

**shukun tokas** · 7 months ago

To summarize it we can say that whenever we use static modifier for anything

If a method is made static, it can be called without the object.

A static block is executed at first, even before creation of any class object. Sta initialization activities.

If a variable is static, it is not associated with any class and only one copy of th execution.

6 ^ | ▾ · Reply · Share ›

[Write a C program to Delete a Tree.](#) · 1 hour ago

[kzs please provide solution for the problem...](#)

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

Sanjay Agarwal bool

[tree::Root_to_leaf_path_given_sum\(tree...](#)

[Root to leaf path sum equal to a given number](#) · 1

hour ago

GOPI GOPINATH @admin Highlight this

sentence "We can easily...

[Count trailing zeroes in factorial of a number](#) · 1

hour ago

newCoder3006 If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 2 hours ago

AdChoices ▶

▶ [C++ Code](#)

▶ [C++ Java](#)

▶ [Java Array](#)

AdChoices ▶

▶ [Java Keyword](#)

▶ [Java Void](#)

▶ [Java VS C](#)

AdChoices ▶

▶ [String Java](#)

▶ [Java Object](#)

▶ [Java Variables](#)

✉ Subscribe

🗨 Add Disqus to your site

