


## Remove BST keys outside the given range

Given a Binary Search Tree (BST) and a range [min, max], remove all keys which are outside the given range. The modified tree should also be BST. For example, consider the following BST and range [-10, 13].



The given tree should be changed to following. Note that all keys outside the range [-10, 13] are removed and modified tree is BST.

Google™ Custom Search



GeeksforGeeks



52,731 people like GeeksforGeeks.




Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms



There are two possible cases for every node.

1) Node's key is outside the given range. This case has two sub-cases.

.....a) Node's key is smaller than the min value.

.....b) Node's key is greater than the max value.

2) Node's key is in range.

We don't need to do anything for case 2. In case 1, we need to remove the node and change root of sub-tree rooted with this node.

The idea is to fix the tree in Postorder fashion. When we visit a node, we make sure that its left and right sub-trees are already fixed. In case 1.a), we simply remove root and return right sub-tree as new root. In case 1.b), we remove root and return left sub-tree as new root.

Following is C++ implementation of the above approach.

```
// A C++ program to remove BST keys outside the given range
```

```
#include<stdio.h>
```

```
#include <iostream>
```

```
using namespace std;
```

```
// A BST node has key, and left and right pointers
```

```
struct node
```

```
{
```

```
    int key;
```

```
    struct node *left;
```

```
    struct node *right;
```

```
};
```

```
// Removes all nodes having value outside the given range and returns  
// of modified tree
```

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

## ITT Tech - Official Site

[itt-tech.edu](http://itt-tech.edu)

Associate, Bachelor Degree  
Programs Browse Programs Now &  
Learn More.

## Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without  
stack!

Structure Member Alignment, Padding and

Data Packing

Intersection point of two Linked Lists

```

node* removeOutsideRange(node *root, int min, int max)
{
    // Base Case
    if (root == NULL)
        return NULL;

    // First fix the left and right subtrees of root
    root->left = removeOutsideRange(root->left, min, max);
    root->right = removeOutsideRange(root->right, min, max);

    // Now fix the root. There are 2 possible cases for root
    // 1.a) Root's key is smaller than min value (root is not in range)
    if (root->key < min)
    {
        node *rChild = root->right;
        delete root;
        return rChild;
    }
    // 1.b) Root's key is greater than max value (root is not in range)
    if (root->key > max)
    {
        node *lChild = root->left;
        delete root;
        return lChild;
    }
    // 2. Root is in range
    return root;
}

```

// A utility function to create a new BST node with key as given num

```

node* newNode(int num)
{
    node* temp = new node;
    temp->key = num;
    temp->left = temp->right = NULL;
    return temp;
}

```

// A utility function to insert a given key to BST

```

node* insert(node* root, int key)
{
    if (root == NULL)
        return newNode(key);
    if (root->key > key)
        root->left = insert(root->left, key);
    else
        root->right = insert(root->right, key);
}

```

Intersection point of two linked lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

Shouldn't  
you expect  
a cloud with:

**ONE-CLICK  
DEPLOYMENTS**

Experience the  
Managed Cloud  
Difference

TRY TODAY ▶

 PaaS

```

    return root;
}

// Utility function to traverse the binary tree after conversion
void inorderTraversal(node* root)
{
    if (root)
    {
        inorderTraversal( root->left );
        cout << root->key << " ";
        inorderTraversal( root->right );
    }
}

// Driver program to test above functions
int main()
{
    node* root = NULL;
    root = insert(root, 6);
    root = insert(root, -13);
    root = insert(root, 14);
    root = insert(root, -8);
    root = insert(root, 15);
    root = insert(root, 13);
    root = insert(root, 7);

    cout << "Inorder traversal of the given tree is: ";
    inorderTraversal(root);

    root = removeOutsideRange(root, -10, 13);

    cout << "\nInorder traversal of the modified tree is: ";
    inorderTraversal(root);

    return 0;
}

```

Output:

```

Inorder traversal of the given tree is: -13 -8 6 7 13 14 15
Inorder traversal of the modified tree is: -8 6 7 13

```

**Time Complexity:**  $O(n)$  where  $n$  is the number of nodes in given BST.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



695



Subscribe

## Recent Comments

affiszerv Your example has two 4s on row 3, that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 32 minutes ago

**RVM** Can someone please elaborate this Qs from above...

[Flipkart Interview | Set 6](#) · 52 minutes ago

**Vishal Gupta** I talked about as an Interviewer in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 52 minutes ago

**@meya** Working solution for question 2 of 4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago

sandeep void rearrange(struct node \*head) {...

Given a linked list, reverse alternate nodes and append at the end · 2 hours ago

Neha I think that is what it should return as, in...

[Find depth of the deepest odd level leaf node](#) · 2 hours ago



AdChoices

► [Binary Tree](#)

► [Java Tree](#)

► [Node](#)

AdChoices

► [Java Keys](#)

► [Remove Tree Root](#)

► [Find Keys](#)

AdChoices

► [Tree Trim](#)

► [Key Keys](#)

► [Ancestor Tree](#)

## Related Topics:

- [Print a Binary Tree in Vertical Order | Set 2 \(HashMap based Method\)](#)
- [Print Right View of a Binary Tree](#)
- [Red-Black Tree | Set 3 \(Delete\)](#)
- [Construct a tree from Inorder and Level order traversals](#)
- [Print all nodes at distance k from a given node](#)
- [Print a Binary Tree in Vertical Order | Set 1](#)
- [Interval Tree](#)
- [Check if a given Binary Tree is height balanced like a Red-Black Tree](#)



42



Tweet

3



1

**Writing code in comment?** Please use [ideone.com](#) and share the link here.

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team