

## Write your own atoi()

The `atoi()` function takes a string (which represents an integer) as an argument and returns its value.

Following is a simple implementation. We initialize result as 0. We start from the first character and update result for every character.

```
// A simple C++ program for implementation of atoi
#include <stdio.h>


// A simple atoi() function
int myAtoi(char *str)
{
    int res = 0; // Initialize result

    // Iterate through all characters of input string and update result
    for (int i = 0; str[i] != '\0'; ++i)
        res = res*10 + str[i] - '0';

    // return result.
    return res;
}

// Driver program to test above function
int main()
{
    char str[] = "89789";
    int val = myAtoi(str);
    printf ("%d ", val);
    return 0;
}
```

Output:



GeeksforGeeks



52,731 people like [GeeksforGeeks](#).



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

The above function doesn't handle negative numbers. **Following is a simple extension to handle negative numbers.**

```
// A C++ program for implementation of atoi
#include <stdio.h>

// A simple atoi() function
int myAtoi(char *str)
{
    int res = 0; // Initialize result
    int sign = 1; // Initialize sign as positive
    int i = 0; // Initialize index of first digit

    // If number is negative, then update sign
    if (str[0] == '-')
    {
        sign = -1;
        i++; // Also update index of first digit
    }

    // Iterate through all digits and update the result
    for (; str[i] != '\0'; ++i)
        res = res*10 + str[i] - '0';

    // Return result with sign
    return sign*res;
}

// Driver program to test above function
int main()
{
    char str[] = "-123";
    int val = myAtoi(str);
    printf ("%d ", val);
    return 0;
}
```

Output:

-123

The above implementation doesn't handle errors. What if *str* is NULL or *str* contains non-numeric characters. **Following implementation handles errors.**



## Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```
// A simple C++ program for implementation of atoi

#include <stdio.h>

// A utility function to check whether x is numeric
bool isNumericChar(char x)
{
    return (x >= '0' && x <= '9')? true: false;
}

// A simple atoi() function. If the given string contains
// any invalid character, then this function returns 0
int myAtoi(char *str)
{
    if (*str == NULL)
        return 0;

    int res = 0; // Initialize result
    int sign = 1; // Initialize sign as positive
    int i = 0; // Initialize index of first digit

    // If number is negative, then update sign
    if (str[0] == '-')
    {
        sign = -1;
        i++; // Also update index of first digit
    }

    // Iterate through all digits of input string and update result
    for (; str[i] != '\0'; ++i)
    {
        if (isNumericChar(str[i]) == false)
            return 0; // You may add some lines to write error message
                        // to error stream
        res = res*10 + str[i] - '0';
    }

    // Return result with sign
    return sign*res;
}

// Driver program to test above function
int main()
{
    char str[] = "-134";
    int val = myAtoi(str);
}
```



```

printf("%d ", val);
return 0;
}

```

Time Complexity:  $O(n)$  where  $n$  is the number of characters in input string.

### Exercise

Write your own `atoi()` that takes a string (which represents an floating point value) as an argument and returns its value as double.

This article is compiled by **Abhay Rathi**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

If you like GeeksforGeeks and would like to contribute, you can also write an article and mail your article to [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org). See your article appearing on the GeeksforGeeks main page and help other Geeks.



### Related Topics:

- [Printing Longest Common Subsequence](#)
- [Suffix Array | Set 2 \(nLogn Algorithm\)](#)
- [Rearrange a string so that all same characters become d distance away](#)

### Recent Comments

[affizerv](#) Your example has two 4s on row 3, that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 13 minutes ago

[RVM](#) Can someone please elaborate this Qs from above...

[Flipkart Interview | Set 6](#) · 33 minutes ago

[Vishal Gupta](#) I talked about as an Interviewer in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 33 minutes ago

[@meya](#) Working solution for question 2 of 4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago  
sandeep void rearrange(struct node \*head)  
{...

[Given a linked list, reverse alternate nodes and append at the end](#) · 2 hours ago

[Neha](#) I think that is what it should return as, in...

[Find depth of the deepest odd level leaf node](#) · 2 hours ago

AdChoices

[▶ Math Geeks](#)

[▶ Atoi](#)

[▶ Java to C++](#)

- Recursively remove all adjacent duplicates
- Find the first non-repeating character from a stream of characters
- Dynamic Programming | Set 33 (Find if a string is interleaved of two other strings)
- Remove "b" and "ac" from a given string
- Dynamic Programming | Set 29 (Longest Common Substring)



26



Tweet 5



1

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

34 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



**jinqueshu** · 7 days ago

I think atoi() should be able to handle the following cases.

^ | v · Reply · Share ›



**jinqueshu** → jinqueshu · 7 days ago

I think atoi() should be able to handle the following cases.

1. check NULL

-- You did, but it's wrong. should check if (str == NULL) instead if (\*str :

2. skip leading space

-- You didn't

3. handle negative sign '-'

-- You did a good job.

4. handle optional positive sign '+'

-- You didn't

AdChoices ▶

▶ [C++ Source Code](#)

▶ [String Java](#)

▶ [C++](#)

AdChoices ▶

▶ [String Functions](#)

▶ [C String](#)

▶ [Java Array](#)

5. handle non-digit character

-- You did. but usually should return the integer of valid part.

6. handle overflow

-- You didn't

7. handle underflow

-- You didn't

^ | v • Reply • Share ›



**Nikhil** • 3 months ago

Sorry, but shouldn't we be checking for `str==NULL` before we de-reference it a

```
if (*str == NULL)
```

```
return 0;
```

add a check:

```
if(str==NULL)
```

```
// error processing ... exit(1) ?
```

^ | v • Reply • Share ›



**Pushkar** → Nikhil • 17 days ago

Yes... we should check the str pointer for NULL before checking wheth  
as value or not.

^ | v • Reply • Share ›



**Coder011** • 3 months ago

atoi: <http://ideone.com/gpjDSp>

atof: <http://ideone.com/O1HIY>

Recursive implementation of atoi and atof functions in C++.

^ | v • Reply • Share ›



**Chandra Mohan Sharma** · 5 months ago

write your own atof function

```
#include<stdio.h>
```

```
#include<string.h>
```

```
void atof(char* );
```

```
void atof(char* num)
```

```
{
```

```
double sum = 0;
```

```
/* Calculate the integer part. */
```

```
while (*num)
```

```
{
```

```
if (*num!='.')
```

---

[see more](#)

1 ^ | v · [Reply](#) · [Share](#) ›



**keye** · 5 months ago

```
int my_atoi(char *str, int &k)
```

```
{
```

```
if(str == NULL)
```

```
{
```

```
cout<<"error, input string is NULL"<<endl; return="" -1;="" }="" int="" minus="" 0
```

```
}- {- minus- 1, p++, - }- while( p!= 0 )- {- k= 10 (k) +- ( p- 0  
k="0" -="" (k);="" }="" return="" 1;="" }="">
```

^ | v • Reply • Share ›



**sumit007** • 7 months ago

your function doesn't handle Overflow conditions.

Forex:

Input: "98784568924545654"

Output: String can't be expressed as valid number.

You can handle it by little modification in your final code before computing

```
res = res*10 + (str[i]-'0');
```

Modified Statement:

```
if( res > (INT_MAX - (str[i]-'0') ) / 10) {  
    printf("%s\n", "Overflow !!! String can't be expressed as a valid number");  
    return 0;  
}  
else  
    res = res*10 + (str[i]-'0');
```

^ | v • Reply • Share ›



**devC#** • 8 months ago

```
public static int atoi(string str)
```

```
{
```

```
    if (str == null || str.Length == 0)
```

```
        throw new ArgumentNullException();
```

```
    int value = 0;
```



```
for (var idx = str.Length - 1; idx >= 0; --idx)
```

```
{
```

```
if (idx == 0 && str[idx] == '-')
```

```
{
```

```
value = value * -1;
```

```
}
```

[see more](#)

^ | v • Reply • Share ›



**minhaj** • 8 months ago

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
int myatoi(char* str)
```

```
{ int output = 0; int i=0,sign=1;
```

```
if (*str=='-')
```

```
{sign=-1;
```

```
i++;
```

```
}
```

```
while( '0' <= str[i] && str[i] <='9' )
```

```
{ output = output*10 + (str[i] - '0') ;
```

```
i++;
```

```
}
```

```
return output*sign;
```

```
}
```

```
int main ()
```

```
{ int i; char buffer[256];
```

```
printf ( "Enter a number. ",
fgets (buffer, 256, stdin);
i = myatoi (buffer);
printf ("The value entered is %d. Its double is %d.\n",i,i*2);
return 0;
}
```

^ | v • Reply • Share ›



**Arun Kumar** • 9 months ago

Your program does not handle the test case of " 1234sdgds" in this case your

^ | v • Reply • Share ›



**arun** • 9 months ago

```
/* Paste your code here (You may delete these lines if not writing c
/* atoi example */
#include <stdio.h>      /* printf, fgets */
#include <stdlib.h>     /* atoi */

int myatoi(char* str)
{
    int output = 0;
    int i=0;
    while( 48 <= str[i] && str[i] <=57 ){

        output = output*10 + (str[i] - 48) ;
        i++;
    }

    return output;
}
```

[see more](#)

^ | v · Reply · Share ›



**Karthikeya Yakkali** · 9 months ago

In the above code if(isNumericChar(str[i]) == false) return res instead of return requirement

^ | v · Reply · Share ›



**Kartikey** · 9 months ago

why is '-0' appended at the end please explain //

```
/* Paste your code here (You may delete these lines if not writing c
```

1 ^ | v · Reply · Share ›



**Neo\_T** · 10 months ago

why is '-0' added in code for calculation of res? I am missing something.

^ | v · Reply · Share ›



**Kartikey** ➔ Neo\_T · 9 months ago

k holds an integer, and it is recalculated by looking at the each character you the character's ASCII code and '0' as well. The difference gives the shifting of previous value.

For example, if p is given by "425?",

The first calculation of  $k = 0 * 10 + (*p) - '0' = 0 + 52 - 48 = 4$

The next calculation of  $k = 4 * 10 + (*p) - '0' = 40 + 50 - 48 = 42$

The final calculation of  $k = 42 * 10 + (*p) - '0' = 420 + 53 - 48 = 425$

Character ASCII code of "4" is 52, "2" is 50, "5" is 53, and "0" is 48.

Hope this would help you,



**see more**



```
}

// A simple atoi() function. If the given string contains.
// any invalid character, then this function returns 0.
int myAtoi(char *str).
{

if (*str == NULL).

return 0;.

int res = 0; // Initialize result.
```

---

[see more](#)

^ | v • Reply • Share ›



**caijinlong** • a year ago

```
#include <iostream>
#include <string>
using namespace std;

int Atoi(string str)
{
    if (str.length() == 0)
        return 0;
    int result = 0;
    bool negative = false;
    int begin = 0;

    if (str[0] == '-')
    {
        begin = 1;
```

```
}
```

[see more](#)

^ | v • Reply • Share ›



**caijinlong** • a year ago

```
#include <iostream>
```

```
using namespace std;
```

```
int Atoi(char *str)
```

```
{
```

```
    if (str == NULL)
```

```
        return 0;
```

```
    int result = 0;
```

```
    bool negative = false;
```

```
    int begin = 0;
```

```
    if (str[0] == '-')
```

```
    {
```

```
        begin = 1;
```

```
        negative = true;
```

```
    }
```

[see more](#)

^ | v • Reply • Share ›



**Poorvank Bhatia** • a year ago

When we input a string like "987hsg0987" to the atoi function it prints the solution. The code deals with this possibility!

1 ^ | v • Reply • Share ›



**Tushar Patil** • a year ago

```
int myAtoi(char *str)
{
    int i=0;

    while(*str)
    {
        i = (i << 3) + (i << 1) + (*str - '0');
        str++;
    }
    return(i);
}
```

1 ^ | v • Reply • Share ›



**Suhas Tilekar** ➔ Tushar Patil • a year ago

Tusssshhh..

Nice one dude...!

think also for if entered string has -ve sign.

```
/* Paste your code here (You may delete these lines if not writ
```

^ | v • Reply • Share ›



**CODER\_1** ➔ Tushar Patil • a year ago

Tusssshhh...

Nice .....!

```
/* Paste your code here (You may delete these lines if not writ
```



^ | v • Reply • Share ›



**Abhay** → Tushar Patil • a year ago

Good tricky implementation, love that :)

^ | v • Reply • Share ›



**GeeksforGeeks** • a year ago

Error checks have been added to the original code.

^ | v • Reply • Share ›



**depak** → GeeksforGeeks • a year ago

you didn't check when string is very long. which will lead to buffer overf

^ | v • Reply • Share ›



**depak** → depak • a year ago

```
cutoff = INT_MAX / 10;  
cutlim = INT_MAX % 10;
```

```
c = str[i] - '0';  
if (res > cutoff || (res == cutoff && c > cutlim))  
    overflow = 1;  
else  
{  
    res *= 10;  
    res += c;  
}
```

^ | v • Reply • Share ›



**Abhay** → depak • a year ago

My aim was to keep the post simple and readable, that is why c  
Does standard atoi() do buffer overflow check, I don't think so. I



Let me know if u have a simple and readable code with buffer c

^ | v · Reply · Share ›



**GeeksQuiz** · a year ago

Ahmed, Thanks for pointing this out. We have added code with error handling

^ | v · Reply · Share ›



**depak** · a year ago

No null string check, no buffer overflow check !!!

^ | v · Reply · Share ›



**galaxy01** · a year ago

does it matter if you do for (++;i) or for(;;i++)

^ | v · Reply · Share ›



**kartik** → galaxy01 · a year ago

As far as I know, compilers take care care of these optimizations and g  
We don't need to worry about them.

^ | v · Reply · Share ›



**Ahmed Saleh** · a year ago

There is a problem in your code. You must check also for values from 0 to 9 a  
don't also check for your inputs, you have to defense for a NULL input st

^ | v · Reply · Share ›

---

[Subscribe](#)

[Add Disqus to your site](#)

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team