

Segregate 0s and 1s in an array

Asked by [kapil](#).

You are given an array of 0s and 1s in random order. Segregate 0s on left side and 1s on right side of the array. Traverse array only once.

```
Input array  = [0, 1, 0, 1, 0, 0, 1, 1, 1, 0]
Output array = [0, 0, 0, 0, 0, 1, 1, 1, 1, 1]
```

Method 1 (Count 0s or 1s)

Thanks to [Naveen](#) for suggesting this method.

- 1) Count the number of 0s. Let count be C.
- 2) Once we have count, we can put C 0s at the beginning and 1s at the remaining $n - C$ positions in array.

Time Complexity: $O(n)$

The method 1 traverses the array two times. Method 2 does the same in a single pass.

Method 2 (Use two indexes to traverse)

Maintain two indexes. Initialize first index *left* as 0 and second index *right* as $n-1$.

Do following while *left* < *right*

- a) Keep incrementing index *left* while there are 0s at it
- b) Keep decrementing index *right* while there are 1s at it
- c) If *left* < *right* then exchange *arr*[*left*] and *arr*[*right*]

Implementation:

Google™ Custom Search



GeeksforGeeks



53,522 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```

#include<stdio.h>

/*Function to put all 0s on left and all 1s on right*/
void segregate0and1(int arr[], int size)
{
    /* Initialize left and right indexes */
    int left = 0, right = size-1;

    while(left < right)
    {
        /* Increment left index while we see 0 at left */
        while(arr[left] == 0 && left < right)
            left++;

        /* Decrement right index while we see 1 at right */
        while(arr[right] == 1 && left < right)
            right--;

        /* If left is smaller than right then there is a 1 at left
        and a 0 at right. Exchange arr[left] and arr[right]*/
        if(left < right)
        {
            arr[left] = 0;
            arr[right] = 1;
            left++;
            right--;
        }
    }
}

/* driver program to test */
int main()
{
    int arr[] = {0, 1, 0, 1, 1, 1};
    int arr_size = 6, i = 0;

    segregate0and1(arr, arr_size);

    printf("array after segregation ");
    for(i = 0; i < 6; i++)
        printf("%d ", arr[i]);

    getchar();
    return 0;
}

```

Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists


Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

Time Complexity: $O(n)$

Please write comments if you find any of the above algorithms/code incorrect, or a better ways to solve the same problem.



Related Topics:

- Remove minimum elements from either side such that $2 \times \text{min}$ becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



13



Tweet

1



0

Writing code in comment? Please use ideone.com and share the link here.



Recent Comments

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree · 24 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 28 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 53 minutes ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...


Count trailing zeroes in factorial of a number · 54 minutes ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

newCoder3006 Code without using while loop. We can do it...

Find subarray with given sum · 1 hour ago

AdChoices 

[▶ C++ Code](#)

[▶ Java Array](#)


[▶ C++ Array](#)

AdChoices 

► [Memory Array](#)

► [An Array](#)

► [Programming C++](#)

AdChoices 

► [Int Byte Array](#)

► [Array Pointer](#)

► [Array Function](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team