


Write a C program to Calculate Size of a tree

Size of a tree is the number of elements present in the tree. Size of the below tree is 5.



Size() function recursively calculates the size of a tree. It works as follows:

Size of a tree = Size of left subtree + 1 + Size of right subtree

Algorithm:

```
size(tree)
1. If tree is empty then return 0
2. Else
    (a) Get the size of left subtree recursively i.e., call
        size( tree->left-subtree)
    (a) Get the size of right subtree recursively i.e., call
        size( tree->right-subtree)
    (c) Calculate size of the tree as following:
```


Google™ Custom Search



GeeksforGeeks



52,731 people like GeeksforGeeks.



Facebook

Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

```
tree_size = size(left-subtree) + size(right-  
subtree) + 1
```

(d) Return tree_size

```
#include <stdio.h>  
#include <stdlib.h>  
  
/* A binary tree node has data, pointer to left child  
and a pointer to right child */  
struct node  
{  
    int data;  
    struct node* left;  
    struct node* right;  
};  
  
/* Helper function that allocates a new node with the  
given data and NULL left and right pointers. */  
struct node* newNode(int data)  
{  
    struct node* node = (struct node*)  
                        malloc(sizeof(struct node));  
    node->data = data;  
    node->left = NULL;  
    node->right = NULL;  
  
    return (node);  
}  
  
/* Computes the number of nodes in a tree. */  
int size(struct node* node)  
{  
    if (node==NULL)  
        return 0;  
    else  
        return (size(node->left) + 1 + size(node->right));  
}  
  
/* Driver program to test size function*/  
int main()  
{  
    struct node *root = newNode(1);  
    root->left = newNode(2);  
    root->right = newNode(3);  
    root->left->left = newNode(4);  
    root->left->right = newNode(5);
```

Shouldn't you expect a cloud with:

**ONE-CLICK
DEPLOYMENTS**

Experience the Managed Cloud Difference

TRY TODAY ▶

 **rackspace**
the open cloud company

Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without
stack!

Structure Member Alignment, Padding and
Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```
printf("Size of the tree is %d", size(root));
getchar();
return 0;
}
```

Time & Space Complexities: Since this program is similar to traversal of tree, time and space complexities will be same as Tree traversal (Please see our [Tree Traversal](#) post for details)



Better Than Hadoop.

HPCC Systems is Big Data Processing and Analytics
Open Source. Proven. Trusted.

LexisNexis® Learn More ▶

Related Tpoics:

- [Print a Binary Tree in Vertical Order | Set 2 \(HashMap based Method\)](#)
- [Print Right View of a Binary Tree](#)
- [Red-Black Tree | Set 3 \(Delete\)](#)
- [Construct a tree from Inorder and Level order traversals](#)
- [Print all nodes at distance k from a given node](#)
- [Print a Binary Tree in Vertical Order | Set 1](#)
- [Interval Tree](#)
- [Check if a given Binary Tree is height balanced like a Red-Black Tree](#)



BETTER THAN
**RAINBOWS IN
YOUR PANTS**

yah we said it

START YOUR FREE TRIAL

JRebel

NO CREDIT CARD REQUIRED
TAKES LESS THAN 1 MIN.



1



0



0



695



Subscribe

Writing code in comment? Please use ideone.com and share the link here.

17 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



san · 20 days ago

using System;

using System.Collections.Generic;

using System.Linq;

using System.Text;

namespace ConsoleApplication5

{

class Program

{

static void Main(string[] args)

{

Node<int> root = new Node<int>(1);

[see more](#)

^ | v · Reply · Share ›

Recent Comments

karthik it should have been max_wrap=
max_wrap -...

[Maximum circular subarray sum](#) · 1 minute ago

affiszerv Your example has two 4s on row 3,
that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 45 minutes ago

RVM Can someone please elaborate this Qs
from above...

[Flipkart Interview | Set 6](#) · 1 hour ago

Vishal Gupta I talked about as an Interviewer
in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 1 hour ago

@meya Working solution for question 2 of
4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago

sandeep void rearrange(struct node *head)
{...

Given a linked list, reverse alternate nodes and
append at the end · 3 hours ago

AdChoices ▶

[▶ Binary Tree](#)[▶ Java Tree](#)[▶ Java to C++](#)



rikitic • 10 months ago

inserting count variable in pre-order traversal will do it..i suppose . any one cor

```
/* Paste your code here (You may delete these lines if not writing cor
```

^ | v • Reply • Share ›



Vibhu Tiwari → rikitic • 10 months ago

I think any order traversal will do it because in the traversal of the trees increment the count variable as in these traversals every time we are c number of these elements will hold in the variable count.

1 ^ | v • Reply • Share ›



abhishek08aug • a year ago

Below is the C++ code for getting the size of the tree. I have just extended my <http://www.geeksforgeeks.org/6...>

Have made all the `_*` functions in tree class private as they are not called from member in tree class to keep track of the number of inserts i.e. size of the BS

```
#include<iostream>
using namespace std;

class tree_node {
private:
    int data;
    tree_node * left;
    tree_node * right;
public:
```

AdChoices ▶

▶ [XML Tree Viewer](#)

▶ [Red Black Tree](#)

▶ [JavaScript Tree](#)

AdChoices ▶

▶ [Tree Structure](#)

▶ [In the Tree](#)

▶ [Root Tree](#)

```
left=NULL;
```

```
right=NULL;
```

[see more](#)

^ | v • Reply • Share ›



abhishek08aug → abhishek08aug • a year ago

Preorder Traversal

5 3 1 7 6 50

Inorder Traversal

1 3 5 6 7 50

Postorder Traversal

1 3 6 50 7 5

Size of the tree (as stored in tree object) is: 6

Size of the tree is: 6

^ | v • Reply • Share ›



Nikin • a year ago

```
int size(node *sr)
{
    if(sr) return size(sr->left) + size(sr->right) + 1;
    return 0;
}
```

1 ^ | v • Reply • Share ›



Sun • 2 years ago

Why doesn't this code work ?

```
private int size(Node node,int count)
```

```
{  
  
    if(node == null)  
    {  
        return 0;  
    }  
  
    size(node.left, count);  
    count++;  
    size(node.right, count);  
  
    return count;  
  
}
```

^ | v • Reply • Share ›



varahi → Sun • 25 days ago

both left and right sub tree's count needs to be added

^ | v • Reply • Share ›



Srikar → Sun • 2 months ago

count value is not changing....

^ | v • Reply • Share ›



Gaurav pruthi → Sun • 4 months ago

Each count variable is having its local scope.. either take it global or us

1 ^ | v • Reply • Share ›



Karun → Sun • 5 months ago

You are not providing a pointer to the parameters you are passing. The

1 ^ | v • Reply • Share ›



Uma Trika → Sun • 5 months ago

```
void sizeUtil(struct node *node, int *size)
```

```
{  
    if(node == NULL)  
        return ;  
    *size = *size + 1;  
    sizeUtil(node->left, size);  
    sizeUtil(node->right, size);  
}
```

2 ^ | v • Reply • Share ›



prakash → Sun • a year ago

hi dude,

this wont work. since ur count variable is not a pointer so, count of left s

1 ^ | v • Reply • Share ›



enchantress → Sun • 2 years ago

count is local here to every recursive call..

either make count global or do count+=size(node.left,count);

count++;

count+=size(node.right,count);

^ | v • Reply • Share ›



Marsha Donna → enchantress • 2 months ago

@enchantress your code wil not work ...for the tree shwn in ab

returning approach is correct

^ | v • Reply • Share ›



Sunil • 3 years ago

The function to find the size of the tree can also be written like this.

```
int size(struct node* root)
{
    static int count=0;
    if(root!=NULL)
    {
        size(root->llink);
        count++;
        size(root->rlink);
    }
    return count;
}
```

^ | v • Reply • Share ›



Pandhari → Sunil • a year ago

Not needed `static int count=0;`

It requires extra memory and that exists throughout life of process as it

^ | v • Reply • Share ›

Subscribe

Add Disqus to your site

