


Root to leaf path sum equal to a given number

Given a binary tree and a number, return true if the tree has a root-to-leaf path such that adding up all the values along the path equals the given number. Return false if no such path can be found.



For example, in the above tree root to leaf paths exist with following sums.

21 → 10 – 8 – 3

23 → 10 – 8 – 5

14 → 10 – 2 – 2

So the returned value should be true only for numbers 21, 23 and 14. For any other number, returned value should be false.

Algorithm:

Recursively check if left or right child has path sum equal to (number – value at current node)

Implementation:


Google™ Custom Search



GeeksforGeeks



52,731 people like GeeksforGeeks.



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

```

#include<stdio.h>
#include<stdlib.h>
#define bool int

/* A binary tree node has data, pointer to left child
and a pointer to right child */
struct node
{
    int data;
    struct node* left;
    struct node* right;
};

/*
Given a tree and a sum, return true if there is a path from the root
down to a leaf, such that adding up all the values along the path
equals the given sum.

Strategy: subtract the node value from the sum when recurring down,
and check to see if the sum is 0 when you run out of tree.
*/
bool hasPathSum(struct node* node, int sum)
{
    /* return true if we run out of tree and sum==0 */
    if (node == NULL)
    {
        return (sum == 0);
    }

    else
    {
        bool ans = 0;

        /* otherwise check both subtrees */
        int subSum = sum - node->data;

        /* If we reach a leaf node and sum becomes 0 then return true*/
        if ( subSum == 0 && node->left == NULL && node->right == NULL )
            return 1;

        if(node->left)
            ans = ans || hasPathSum(node->left, subSum);
        if(node->right)
            ans = ans || hasPathSum(node->right, subSum);

        return ans;
    }
}

```

ITT Tech - Official Site

itt-tech.edu

Associate, Bachelor Degree
Programs Browse Programs Now &
Learn More.



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without
stack!

Structure Member Alignment, Padding and
Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

    }
}

/* UTILITY FUNCTIONS */
/* Helper function that allocates a new node with the
   given data and NULL left and right pointers. */
struct node* newnode(int data)
{
    struct node* node = (struct node*)
                        malloc(sizeof(struct node));

    node->data = data;
    node->left = NULL;
    node->right = NULL;

    return (node);
}

/* Driver program to test above functions*/
int main()
{
    int sum = 21;

    /* Constructed binary tree is
        10
       /  \
      8    2
     /  \  /
    3    5 2
    */
    struct node *root = newnode(10);
    root->left = newnode(8);
    root->right = newnode(2);
    root->left->left = newnode(3);
    root->left->right = newnode(5);
    root->right->left = newnode(2);

    if (hasPathSum(root, sum))
        printf("There is a root-to-leaf path with sum %d", sum);
    else
        printf("There is no root-to-leaf path with sum %d", sum);

    getchar();
    return 0;
}

```

Shouldn't you
expect a
cloud with:

SYSTEM MONITORING

Plus the experts
to help run it?

TRY MANAGED CLOUD ►



Time Complexity: $O(n)$

References:

<http://cslibrary.stanford.edu/110/BinaryTrees.html>

Author: Tushar Roy

Please write comments if you find any bug in above code/algorithm, or find other ways to solve the same problem



Related Topics:

- [Print a Binary Tree in Vertical Order | Set 2 \(Hashmap based Method\)](#)
- [Print Right View of a Binary Tree](#)
- [Red-Black Tree | Set 3 \(Delete\)](#)
- [Construct a tree from Inorder and Level order traversals](#)
- [Print all nodes at distance k from a given node](#)
- [Print a Binary Tree in Vertical Order | Set 1](#)
- [Interval Tree](#)

695



Subscribe

Recent Comments

[affiszerv](#) Your example has two 4s on row 3, that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 43 minutes ago

[RVM](#) Can someone please elaborate this Qs from above...

[Flipkart Interview | Set 6](#) · 1 hour ago

[Vishal Gupta](#) I talked about as an Interviewer in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 1 hour ago

[@meya](#) Working solution for question 2 of 4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago
`sandeep void rearrange(struct node *head)`
{...

Given a linked list, reverse alternate nodes and append at the end · 3 hours ago

[Neha](#) I think that is what it should return as, in...

[Find depth of the deepest odd level leaf node](#) · 3 hours ago

AdChoices

[▶ SUM Function](#)

[▶ Tree Root](#)

- Check if a given Binary Tree is height balanced like a Red-Black Tree



6



Tweet

1



2

Writing code in comment? Please use ideone.com and share the link here.

► [Binary Tree](#)

AdChoices ►

► [Tree Leaf](#)

► [The Root](#)

► [SUM To](#)

AdChoices ►

► [Java to C++](#)

► [SUM SUM](#)

► [Node](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team