

Multiply a given Integer with 3.5

Given a integer x, write a function that multiplies x with 3.5 and returns the integer result. You are not allowed to use %, /, *.

Examples:

Input: 2

Output: 7

Input: 5

Output: 17 (Ignore the digits after decimal point)

Solution:

1. We can get $x \times 3.5$ by adding $2 \times x$, x and $x/2$. To calculate $2 \times x$, left shift x by 1 and to calculate $x/2$, right shift x by 2.

```
#include <stdio.h>

int multiplyWith3Point5(int x)
{
    return (x<<1) + x + (x>>1);
}

/* Driver program to test above functions*/
int main()
{
    int x = 4;
    printf("%d", multiplyWith3Point5(x));
    getchar();
    return 0;
}
```

Google™ Custom Search



GeeksforGeeks



53,526 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)


[Recursion](#)

[Geometric Algorithms](#)

2. Another way of doing this could be $(8*x - x)/2$ (See below code). Thanks to [ajaym](#) for suggesting this.

```
#include <stdio.h>
int multiplyWith3Point5(int x)
{
    return ((x<<3) - x)>>1;
}
```

Please write comments if you find the above code/algorithm incorrect, or find better ways to solve the same problem



Related Topics:

- Check if a number is multiple of 9 using bitwise operators
- How to swap two numbers without using a temporary variable?
- Divide and Conquer | Set 4 (Karatsuba algorithm for fast multiplication)
- Find position of the only set bit
- Swap all odd and even bits
- Add two bit strings
- Write your own strcmp that ignores cases

HP Chromebook 11

 [google.com/chromebook](https://www.google.com/chromebook)

Everything you need in one laptop.
Made with Google. Learn more.



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

- Binary representation of a given number



1



0



0

Writing code in comment? Please use ideone.com and share the link here.

25 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



Ankit • 5 months ago

Why not, $(x \ll 2) - (x \gg 1)$

^ | v • Reply • Share ›



Tanish Gupta • 10 months ago

//this can also be done by.

#include <stdio.h>

```
int multiplyWith3Point5(int x).
{
return (((x >> 1) << 3) - (x >> 1));.
}
```

/* Driver program to test above functions*/.

```
int main()
{
int x = 4;.
printf("%d", multiplyWith3Point5(x));.
getchar();.
```



```
}
```

/*that is first calculating $x/2$ which is $x \gg 1$ then multiplying it with 7.
and to multiply number with 7 just use this $(x \ll 3) - x$.
so final expression become $((x \gg 1) \ll 3) - (x \gg 1) * /$.

^ | v • Reply • Share ›



Kirt • 2 years ago

i think, we can also use
 $(n \ll 1) | 1$
plz correct me, if i am wrong..

```
/* Paste your code here (You may delete these lines if not writing c
```

^ | v • Reply • Share ›



kirt → Kirt • 2 years ago

```
return  $(n \ll 1) | 1$ )
```

^ | v • Reply • Share ›



Kirt → kirt • 2 years ago

Sry, The shift operator are not displayed properly ..

so here is d logic..

(right shift the 'n' by 2 bit)-(left shift the 'n' by 1 bit and take it OI

plz correct me if i am wrong

^ | v • Reply • Share ›



Kirt → Kirt • 2 years ago

705



Subscribe

Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 28 minutes ago

Aman Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 1 hour ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

[Root to leaf path sum equal to a given number](#) · 1

hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

[Count trailing zeroes in factorial of a number](#) · 1

hour ago

newCoder3006 If the array contains negative numbers also. We...


[Find subarray with given sum](#) · 2 hours ago

AdChoices ▶

▶ [C++ Code](#)

▶ [Java Source Code](#)

▶ [Math Multiply](#)

 sry guys.. a lot of confusion over here..

(left shift the 'n' by 2 bit)-(right shift the 'n' by 1 bit and t

^ | v • Reply • Share ›



anan → kirt • 2 years ago

return n<<<>>>1)|1)


^ | v • Reply • Share ›

AdChoices 

▶ [C++ Code](#)

▶ [Java Source Code](#)

▶ [Multiply Numbers](#)

AdChoices 

▶ [Decimal Multiply](#)

▶ [Multiply 2 Digit](#)

▶ [Divide Multiply](#)



Anand • 3 years ago

simple we can do:

return ((x<>1));

^ | v • Reply • Share ›



Anand → Anand • 3 years ago

(x<>1)

^ | v • Reply • Share ›



Amit • 3 years ago

Why are we not doing this way :)

```
int multi3_5(int x)
```

```
{
```

```
x*3.5;
```

```
}
```

^ | v • Reply • Share ›



hari6988 → Amit • 3 years ago

the question clearly says that u are not allowed to use * operator

^ | v • Reply • Share ›



Nick • 4 years ago



we can do it without using + and - operator.....
here's the code

```
int add(int m, int n);
int main()
{
    int n,d,e,f;
    scanf("%d",&n);
    d=n<>1;
    f=add(d,e);
    printf("%d\n",add(f,n));
    return 0;
}
int add(int m,int n)
{
    int c;
    while(m&n)
    {
```

[see more](#)

^ | v • Reply • Share ›



wav • 4 years ago

```
return (n>>3 -n)>>1;
```

^ | v • Reply • Share ›



hariom • 4 years ago

Any way to print the output including digits after decimal point ?

^ | v • Reply • Share ›



Venki → hariom • 4 years ago

Explore IEEE 754 floating point format.

^ | v • Reply • Share ›



padhu • 4 years ago

can also be done by $4x-x/2$

^ | v • Reply • Share ›



kirt → padhu • 2 years ago

$n < > 1 || 1$

```
/* Paste your code here (You may delete these lines if not wr
```

^ | v • Reply • Share ›



Prem → padhu • 4 years ago

Hey, look at the problem statement dude, you cant use '/'

^ | v • Reply • Share ›



Venki → Prem • 4 years ago

Hi Prem, They are not using / operator. They are trying to repre powers of 2. So that, the expression can be implemented as st

^ | v • Reply • Share ›



Ravi Chandra → Venki • 4 years ago

$(4x-x)/2$ can be implemented as follows without using *

```
x= ((x<>1;
```

^ | v • Reply • Share ›



ravikant → Ravi Chandra • 4 years ago

Dude common you have a year to go !!

^ | v • Reply • Share ›



Man Chandra Man Chandra · 4 years ago

Sorry!,in my previous comment shift operators did not a
here is the line of code

```
x= ((x<<2)-x)>>1;
```

^ | v · Reply · Share ›



Shekhu → padhu · 4 years ago

This approach gives 18 for x = 5, but the expected output is 17 :)

^ | v · Reply · Share ›



ajaym · 4 years ago

Can also be achieved by $(8x-x)/2$

^ | v · Reply · Share ›



GeeksforGeeks → ajaym · 4 years ago

@ajaym: Thanks for suggesting a new method. We have included it to

^ | v · Reply · Share ›



Subscribe



Add Disqus to your site

