

Searching

Question 1

What is the output of following program?

```
#include <stdio.h>

void print(int n, int j)
{
    if (j >= n)
        return;
    if (n-j > 0 && n-j >= j)
        printf("%d %d\n", j, n-j);
    print(n, j+1);
}

int main()
{
    int n = 8;
    print(n, 1);
}
```

A

1 7
2 6
3 5
4 4
4 4



GeeksQuiz



4,126 people like [GeeksQuiz](#).



Facebook social plugin

amila

E-commerce your organization



FREE TRIAL

GET IT FREE

B

1 7
2 6
3 5
4 4

C

1 7
2 6
3 5

D

1 2
3 4
5 6
7 8

[Discuss it](#)

Question 2

Which of the following is correct recurrence for worst case of Binary Search?

A

$T(n) = 2T(n/2) + O(1)$ and $T(1) = T(0) = O(1)$

B

$T(n) = T(n-1) + O(1)$ and $T(1) = T(0) = O(1)$

C

$T(n) = T(n/2) + O(1)$ and $T(1) = T(0) = O(1)$

D

$T(n) = T(n-2) + O(1)$ and $T(1) = T(0) = O(1)$

[Discuss it](#)

Question 3

Given a sorted array of integers, what can be the minimum worst case time complexity to find ceiling of a number x in given array? Ceiling of an element x is the

Categories

[Articles \(28\)](#)

[C \(4\)](#)

[C++ \(2\)](#)

[Data Structures \(13\)](#)

[DBMS \(1\)](#)

[Operating Systems \(1\)](#)

[Searching and Sorting \(7\)](#)

[Programs \(7\)](#)

[Quizzes \(1,392\)](#)

[Aptitude \(1\)](#)

[Computer Science Quizzes \(1,391\)](#)

[Algorithms \(146\)](#)

[C \(203\)](#)

[C++ \(123\)](#)

[Data Structures \(131\)](#)

[GATE \(709\)](#)

[Java \(51\)](#)

[Operating Systems \(28\)](#)



smallest element present in array which is greater than or equal to x. Ceiling is not present if x is greater than the maximum element present in array. For example, if the given array is {12, 67, 90, 100, 300, 399} and x = 95, then output should be 100.

- A** $O(\text{LogLog}n)$
- B** $O(n)$
- C** $O(\text{Log}n)$
- D** $O(\text{Log}n * \text{Log}n)$

[Discuss it](#)

Question 4

Consider the following C program that attempts to locate an element x in an array Y[] using binary search. The program is erroneous. (GATE CS 2008)

```
1. f(int Y[10], int x) {
2.     int i, j, k;
3.     i = 0; j = 9;
4.     do {
5.         k = (i + j) / 2;
6.         if (Y[k] < x) i = k; else j = k;
7.     } while (Y[k] != x && i < j);
8.     if (Y[k] == x) printf ("x is in the array ") ;
9.     else printf (" x is not in the array ") ;
10. }
```

On which of the following contents of Y and x does the program fail?

- A** Y is [1 2 3 4 5 6 7 8 9 10] and x < 10



Recent Discussions

Sumit Khatri this is the sorting technique which can work...

Insertion Sort · 7 hours ago

Sumit Khatri no, quick sort requires more swaps than...

Selection Sort · 7 hours ago

Sumit Khatri yes, it is the only sorting technique which...

Selection Sort · 7 hours ago

BY is [1 3 5 7 9 11 13 15 17 19] and $x < 1$ **C**Y is [2 2 2 2 2 2 2 2 2] and $x > 2$ **D**Y is [2 4 6 8 10 12 14 16 18 20] and $2 < x < 20$ and x is even**Discuss it****Question 5**

In the above question, the correction needed in the program to make it work properly is (GATE CS 2008)

AChange line 6 to: if ($Y[k] < x$) $i = k + 1$; else $j = k - 1$;**B**Change line 6 to: if ($Y[k] < x$) $i = k - 1$; else $j = k + 1$;**C**Change line 6 to: if ($Y[k] \leq x$) $i = k$; else $j = k$;**D**Change line 7 to: } while ($(Y[k] == x) \ \&\& \ (i < j)$);**Discuss it****Question 6**

You are given a list of 5 integers and these integers are in the range from 1 to 6. There are no duplicates in list. One of the integers is missing in the list. Which of the following expression would give the missing number. \wedge is bitwise XOR operator. \sim is bitwise NOT operator. Let elements of list can be accessed as list[0], list[1], list[2], list[3], list[4]

Sudhakar Mishra I think it should be $2n + 1$



Data Structures | Binary Trees | Question 12 · 7 hours ago

Sudhakar Mishra $(2n)! / ((n+1)! * n!)$

Data Structures | Binary Trees | Question 6 · 1 day ago

Sudhakar Mishra Always Y will be more than one because after...

Data Structures | Stack | Question 7 · 1 day ago

AdChoices [▶ Data and Algorithms](#)[▶ C++ Algorithms](#)[▶ Sorting Algorithms](#)AdChoices [▶ Data Structure Algorithms](#)[▶ Complexity Algorithms](#)[▶ Search Algorithms](#)AdChoices [▶ Algorithms in Search](#)[▶ Algorithms Data](#)[▶ And Algorithms in C++](#)

A $\text{list}[0] \wedge \text{list}[1] \wedge \text{list}[2] \wedge \text{list}[3] \wedge \text{list}[4]$ **B** $\text{list}[0] \wedge \text{list}[1] \wedge \text{list}[2] \wedge \text{list}[3] \wedge \text{list}[4] \wedge 1 \wedge 2 \wedge 3 \wedge 4 \wedge 5 \wedge 6$ **C** $\text{list}[0] \wedge \text{list}[1] \wedge \text{list}[2] \wedge \text{list}[3] \wedge \text{list}[4] \wedge 1 \wedge 2 \wedge 3 \wedge 4 \wedge 5$ **D** $\sim(\text{list}[0] \wedge \text{list}[1] \wedge \text{list}[2] \wedge \text{list}[3] \wedge \text{list}[4])$

Discuss it

Question 7

Consider the C function given below. Assume that the array listA contains n (> 0) elements, sorted in ascending order.

```
int ProcessArray(int *listA, int x, int n)
{
    int i, j, k;
    i = 0;
    j = n-1;
    do
    {
        k = (i+j)/2;
        if (x <= listA[k])
            j = k-1;
        if (listA[k] <= x)
            i = k+1;
    }
    while (i <= j);
    if (listA[k] == x)
        return(k);
    else
        return -1;
}
```

Which one of the following statements about the function ProcessArray is CORRECT?

A

It will run into an infinite loop when x is not in listA.

B

It is an implementation of binary search.

C

It will always find the maximum element in listA.

D

It will return -1 even when x is present in listA.

Discuss it

There are 7 questions to complete.

Free C# Code Generator

 ironspeed.com

Create database & reporting apps
straight from your database! Try it



0

 Tweet

0



0

Valid **XHTML Strict 1.0**

Powered by **WordPress & MooTools** | MiniMoo 1.3.4