

Binary representation of a given number

Write a program to print Binary representation of a given number.

Source: [Microsoft Interview Set-3](#)

Method 1: Iterative

For any number, we can check whether its 'i'th bit is 0(OFF) or 1(ON) by bitwise ANDing it with "2ⁱ" (2 raise to i).

1) Let us take number 'NUM' and we want to check whether it's 0th bit is ON or OFF

```
bit = 2 ^ 0 (0th bit)
if NUM & bit == 1 means 0th bit is ON else 0th bit is OFF
```

2) Similarly if we want to check whether 5th bit is ON or OFF

```
bit = 2 ^ 5 (5th bit)
if NUM & bit == 1 means its 5th bit is ON else 5th bit is OFF.
```

Let us take unsigned integer (32 bit), which consist of 0-31 bits. To print binary representation of unsigned integer, start from 31th bit, check whether 31th bit is ON or OFF, if it is ON print "1" else print "0". Now check whether 30th bit is ON or OFF, if it is ON print "1" else print "0", do this for all bits from 31 to 0, finally we will get binary representation of number.

```
void bin(unsigned n)
{
    unsigned i;
    for (i = 1 << 31; i > 0; i = i / 2)
        (n & i)? printf("1") : printf("0");
}
```

```
int main(void)
```

Google™ Custom Search



GeeksforGeeks



53,527 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```
{
    bin(7);
    printf("\n");
    bin(4);
}
```

Method 2: Recursive

Following is recursive method to print binary representation of 'NUM'.

```
step 1) if NUM > 1
    a) push NUM on stack
    b) recursively call function with 'NUM / 2'
step 2)
    a) pop NUM from stack, divide it by 2 and print it's remainder.
```

```
void bin(unsigned n)
{
    /* step 1 */
    if (n > 1)
        bin(n/2);

    /* step 2 */
    printf("%d", n % 2);
}
```

```
int main(void)
{
    bin(7);
    printf("\n");
    bin(4);
}
```

This article is compiled by **Narendra Kangralkar**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

HP Chromebook 11

 google.com/chromebook

Everything you need in one laptop.
Made with Google. Learn more.



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)


[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two linked lists](#)




Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST



Related Topics:

- Check if a number is multiple of 9 using bitwise operators
- How to swap two numbers without using a temporary variable?
- Divide and Conquer | Set 4 (Karatsuba algorithm for fast multiplication)
- Find position of the only set bit
- Swap all odd and even bits
- Add two bit strings
- Write your own strcmp that ignores cases
- Find the element that appears once



6



Tweet

1



0

Writing code in comment? Please use ideone.com and share the link here.

22 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



Raj • 5 months ago

Hai frds I have got a new logic .. see it <http://www.codextream.com/?p=5...>

Deploy Early. Deploy Often.

DevOps from
Rackspace:

Automation

FIND OUT HOW ►



this works for both 16-bit and 32-bit word

^ | v • Reply • Share ›

705



Subscribe

Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 31 minutes ago

Aman Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 1 hour ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

[Root to leaf path sum equal to a given number](#) · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

[Count trailing zeroes in factorial of a number](#) · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 2 hours ago

AdChoices ▶

▶ [C++ Code](#)

▶ [Binary to BCD](#)

▶ [Binary](#)



groomnestle · 5 months ago

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
#include<string.h>
```

```
char *binary(int n)
```

```
{
```

```
char *bin = (char*)malloc(33);
```

```
memset(bin,0,33);
```

```
int i=31;
```

```
int j;
```

```
for(j=0;j<32;j++)
```

```
{
```

```
bin[j]=((1<=i)&n)?'1':'0'; i--; } return bin; } int main() { int  
binary(10)); return 0; }
```

^ | v • Reply • Share ›



neelabhsingh · 6 months ago

Method 2: Recursive this method can not be use for -ve number

^ | v · Reply · Share ›



atiq · 10 months ago

// For negative/positive 4byte representation

```
/*
#include<iostream>
using namespace std;
void Binary(signed int n)
{ char result[33];
  int i=31;
  result[32]='&#92;&#48';
  signed int k=1;
  while(i+1)
  {
    if(k&n)
    {
      result[i]=49;
    }
    else
    {
```

[see more](#)

^ | v · Reply · Share ›



neelabhsingh → atiq · 6 months ago

Above code will work for all types number -ve or positive.....
because i is taken as unsigned and it will always positive and u can use
and +ve number.....

```
#include<stdio.h>
void showbit(int num,int size)
```

AdChoices ▶

▶ [Binary](#)

▶ [Representation](#)

▶ [Print Number](#)

AdChoices ▶

▶ [Print Number](#)

▶ [4 Bit Binary](#)

▶ [Format C++](#)

```

unsigned int i=1<<size-1; while(i!=">=1)
{
(i&num)? printf("1"):printf("0");
i=i/2;
}
}
int main()
{
int n;
printf("Enter any digits\n");
scanf("%d",&n);
showbit(n,sizeof(int)*8);
return 0;
}

```

1 ^ | v • Reply • Share ›



Lomesh Meshram • 10 months ago

```

#include<stdio.h>
int main()
{
int num;
unsigned int i=0x80000000;.
int size=sizeof(num)*8;
scanf("%d",&num);
printf("n Binary Representation is-----n");.
while(size--)
{
if(num & i).

printf("1");.
else

```

```
printf("0");  
i=i>>1;  
}  
printf("n");  
return 0;  
}
```

^ | v • Reply • Share ›



Dj • a year ago

Above code works fine but

if((x&(0x80000000))>0) condition should work for <0

because

if first bit of x is 1, x&0x80000000 gives negative number -2147483648, which is

^ | v • Reply • Share ›



Dj • a year ago

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int x;
```

```
    scanf("%d",&x);
```

```
    x=0x80000000;
```

```
    printf("%d\n",x);
```

```
    for(int i=0;i<32;i++)
```

```
    {
```

```
        if((x&(0x80000000))>0)
```

```
            printf("1");
```

```
        else
```

```
            printf("0");
```

```
        x=x<<1;
```

```
    }
```



```
    return 0;
}
```

Above code works fine but

if((x&(0x80000000))>0) condition should work for <0

because

if first bit of x is 1, x&0x80000000 gives negative number -2147483648, which is

^ | v • Reply • Share ›



abhishek08aug • a year ago

My code:

```
#include<stdio.h>
#include<stdlib.h>

char * bit_representation(unsigned int num) {
    char * bit_string = (char *)malloc(sizeof(char)*sizeof(unsigned int));
    unsigned int i=1, j;
    for(i=i<=(sizeof(unsigned int)*8-1), j=0; i>0; i=i>>1, j++) {
        if(num&i) {
            *(bit_string+j)='1';
        } else {
            *(bit_string+j)='0';
        }
    }
    *(bit_string+j)='&#092;&#048';
    return bit_string;
}
```

[see more](#)

• Reply • Share ›



Amandeep Sharma · a year ago

This method works for both +ve and -ve numbers

```
#include<stdio.h>
#include<conio.h>
void showbits(int n)
{
    int mask=0x80000000;
    int format=0;//just for formatting
    if(mask & n) printf("1");
    else printf("0");
    mask=0x40000000;//remember i have not use here mask=mask>>1 b
    while(mask)
    {
        if(mask & n) printf("1");
        else printf("0");
        if(s=(++s%2))printf(" ");//for formatting
        mask=mask>>1;
    }
}
```

[see more](#)

^ | v · Reply · Share ›



Seelam Komalkumar · a year ago

will it takes care of negative numbers?

^ | v · Reply · Share ›



ASHISH · a year ago

```
void dec_to_bin(int n)
{

```

```

int rem,idx =7;
int count[8]={0};
while(n>1)
{
    rem = n%2;
    cout<<"rem="<<rem<<endl;
    n = n/2;
    count[idx--]=rem;
}
count[idx]=n;
for(int i=0;i<8;i++)
    cout<<count[i];
}

```

^ | v • Reply • Share ›



Frank • a year ago

Please, guys, when you only want to print a char, no need to use printf !
putchar() is largely sufficient !

^ | v • Reply • Share ›



Kanhaiya • a year ago

I think it will print the binary digits in reverse order. we need to use stack to print

^ | v • Reply • Share ›



Venki → Kanhaiya • a year ago

@Kanhaiya, it will not print in reverse order. It prints from MSB to LSB.
the same.

^ | v • Reply • Share ›



Agreed Venki. I was just thinking about that usually we write LSI

^ | v • Reply • Share ›



Pintu Gupta • a year ago

```
#include
```

```
using namespace std;
```

```
void binary_represent(unsigned);
```

```
int main()
```

```
{
```

```
    unsigned num;
```

```
    cin>>num;
```

```
    binary_represent(num);
```

```
    return 0;
```

```
}
```

```
void binary_represent(unsigned num)
```

```
{
```

```
    if(!num)
```

```
    {
```

```
        return;
```

```
    }
```

```
    binary_represent(num>>1);
```

```
    cout<<(num&1);
```

```
}
```

^ | v • Reply • Share ›



neelabhsingh → Pintu Gupta • 6 months ago

```
int main()
```

```
{
```

```
    int num;
```

```

cin>> num;
int i=1>>31;
while(i>=1)
{
(i&num)? cout<< "1" : cout<< "0";
i=i/2;

}

}

```

^ | v • Reply • Share ›



mahendra singh → Pintu Gupta • a year ago

#include

#include

```
void ConvertBinaryStr(unsigned int uiNum, char pcBinStr);
```

```
int main()
```

```
{
```

```
unsigned int uiNum;
```

```
char acBinRep[33]="";
```

```
clrscr();
```

```
printf("Enter Number\n");
```

```
scanf("%u", &uiNum);
```

```
ConvertBinaryStr(uiNum, acBinRep);
```

```
printf("Binary Representation: %s\n", acBinRep);
```

```
getch();
```

```
return 0;
```

[see more](#)

^ | v • Reply • Share ›



OP • a year ago

iterative program is cool :)

2 ^ | v • Reply • Share ›



neelabh Singh ➔ OP • 6 months ago

No it will not work for negative number.....

^ | v • Reply • Share ›



Anonymous bin Ich ➔ neelabh Singh • a month ago

That is not true. Just change
void bin(unsigned int n) to
void bin(int n)

The problem is mitigated because we use unsigned i.

^ | v • Reply • Share ›



Subscribe



Add Disqus to your site

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress & MooTools**, customized by geeksforgeeks team