



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and

Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

.....

3. Now for group of 2, we have 2 possibilities
 - a. 2 elements of remainder 0 group. Such possibilities are $c[0]*(c[0]-1)/2$
 - b. 1 element of remainder 1 and 1 from remainder 2 group
Such groups are $c[1]*c[2]$.
4. Now for group of 3, we have 4 possibilities
 - a. 3 elements from remainder group 0.
No. of such groups are $c[0]C3$
 - b. 3 elements from remainder group 1.
No. of such groups are $c[1]C3$
 - c. 3 elements from remainder group 2.
No. of such groups are $c[2]C3$
 - d. 1 element from each of 3 groups.
No. of such groups are $c[0]*c[1]*c[2]$.
5. Add all the groups in steps 3 and 4 to obtain the result.

```
#include<stdio.h>
```

```
// Returns count of all possible groups that can be formed from elements
// of a[].
int findgroups(int arr[], int n)
{
    // Create an array C[3] to store counts of elements with remainder
    // 0, 1 and 2. c[i] would store count of elements with remainder i
    int c[3] = {0}, i;

    int res = 0; // To store the result

    // Count elements with remainder 0, 1 and 2
    for (i=0; i<n; i++)
        c[arr[i]%3]++;

    // Case 3.a: Count groups of size 2 from 0 remainder elements
    res += ((c[0]*(c[0]-1))>>1);

    // Case 3.b: Count groups of size 2 with one element with 1
    // remainder and other with 2 remainder
    res += c[1] * c[2];

    // Case 4.a: Count groups of size 3 with all 0 remainder elements
    res += (c[0] * (c[0]-1) * (c[0]-2))/6;
```

```

// Case 4.b: Count groups of size 3 with all 1 remainder elements
res += (c[1] * (c[1]-1) * (c[1]-2))/6;

// Case 4.c: Count groups of size 3 with all 2 remainder elements
res += ((c[2]*(c[2]-1)*(c[2]-2))/6);

// Case 4.c: Count groups of size 3 with different remainders
res += c[0]*c[1]*c[2];

// Return total count stored in res
return res;
}

// Driver program to test above functions
int main()
{
    int arr[] = {3, 6, 7, 2, 9};
    int n = sizeof(arr)/sizeof(arr[0]);
    printf("Required number of groups are %d\n", findgroups(arr,n));
    return 0;
}

```

Output:

Required number of groups are 8

Time Complexity: $O(n)$

Auxiliary Space: $O(1)$

This article is contributed by [Amit Jain](#). Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Informix Database

 progress.com/Informix

JDBC Compliant w/ Major
Databases Fully Functional Eval -
Try Now!



 705



Recent Comments

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 3 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 28 minutes ago

GOPI GOPINATH @admin Highlight this

sentence "We can easily...

Count trailing zeroes in factorial of a number · 30 minutes ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 54 minutes ago

newCoder3006 Code without using while loop. We can do it...

Find subarray with given sum · 1 hour ago

Sanjay Agarwal You can also use the this method:...

Related Topics:

- Remove minimum elements from either side such that $2 \times \min$ becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Sort n numbers in range from 0 to $n^2 - 1$ in linear time



 7



Tweet  3



 1

Writing code in comment? Please use ideone.com and share the link here.

8 Comments

GeeksforGeeks

Sort by Newest ▼



1 ^ | v • Reply • Share ›



Guest • 2 months ago

The question is to count all possible groups , not just the unique ones

1 ^ | v • Reply • Share ›



Kshitij Gupta • 2 months ago

There is an assumption that the numbers in list are unique.

For a list like: {3, 6, 7, 2, 9, 9}

The code would print: 15 (treating both 9 as different)

Whereas the actual unique groups are only 11:

(6, 3), (9, 3), (9, 6), (9, 9), (7, 2), (9, 9, 6), (7, 6, 2), (9, 6, 3), (9, 9, 3), (9, 7, 2),

9 ^ | v • Reply • Share ›

 [Subscribe](#)

 [Add Disqus to your site](#)

@geeksforgeeks, **Some rights reserved**

[Contact Us!](#)

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team