GeeksforGeeks


A computer science portal for geeks

5		
---	--	--

Home	Algorithms	DS	GATE	Intervi	ew Corne	Q&A	С	C++	Java	Books	Contribute	Ask a Q	About
Array	Bit Magic	C/C+	+ Arti	cles (GFacts	Linked Li	ist	MCQ	Misc	Output	t String	Tree	Graph

How to check if a given point lies inside or outside a polygon?

Given a polygon and a point 'p', find if 'p' lies inside the polygon or not. The points lying on the border are considered inside.




We strongly recommend to see the following post first.

How to check if two given line segments intersect?

Following is a simple idea to check whether a point is inside or outside.

- 1) Draw a horizontal line to the right of each point and extend it to infinity
- 1) Count the number of times the line intersects with polygon edges.
- 2) A point is inside the polygon if either count of intersections is odd or point lies on an edge of polygon. If none of the conditions is true, then point lies outside.





53,525 people like GeeksforGeeks.











nterview E	xperiences
------------	------------

Advanced Data Structures Dynamic Programming

Greedy Algorithms

Backtracking


Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms



How to handle point 'g' in the above figure?

Note that we should return true if the point lies on the line or same as one of the vertices of the given polygon. To handle this, after checking if the line from 'p' to extreme intersects, we check whether 'p' is colinear with vertices of current line of polygon. If it is coliear, then we check if the point 'p' lies on current side of polygon, if it lies, we return true, else false.

Following is C++ implementation of the above idea.

```
// A C++ program to check if a given point lies inside a given polygon
// Refer http://www.qeeksforgeeks.org/check-if-two-given-line-segments
// for explanation of functions onSegment(), orientation() and doInter
#include <iostream>
using namespace std;
// Define Infinite (Using INT MAX caused overflow problems)
#define INF 10000
struct Point
    int x;
    int v;
};
// Given three colinear points p, q, r, the function checks if
// point g lies on line segment 'pr'
bool onSegment(Point p, Point q, Point r)
```

ITT Tech - Official Site

itt-tech.edu

Tech-Oriented Degree Programs. Education for the Future.



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and

Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```
if (q.x \le max(p.x, r.x) \&\& q.x \ge min(p.x, r.x) \&\&
            q.y \le \max(p.y, r.y) \&\& q.y >= \min(p.y, r.y)
        return true:
    return false:
// To find orientation of ordered triplet (p, q, r).
// The function returns following values
// 0 --> p, q and r are colinear
// 1 --> Clockwise
// 2 --> Counterclockwise
int orientation(Point p, Point q, Point r)
    int val = (q.y - p.y) * (r.x - q.x) -
              (q.x - p.x) * (r.y - q.y);
    if (val == 0) return 0; // colinear
    return (val > 0)? 1: 2; // clock or counterclock wise
// The function that returns true if line segment 'plq1'
// and 'p2q2' intersect.
bool doIntersect(Point p1, Point q1, Point p2, Point q2)
    // Find the four orientations needed for general and
    // special cases
    int o1 = orientation(p1, q1, p2);
    int o2 = orientation(p1, q1, q2);
    int o3 = orientation(p2, q2, p1);
    int o4 = orientation(p2, q2, q1);
    // General case
    if (o1 != o2 && o3 != o4)
        return true:
    // Special Cases
    // pl, q1 and p2 are colinear and p2 lies on segment p1q1
    if (o1 == 0 && onSegment(p1, p2, q1)) return true;
    // pl, q1 and p2 are colinear and q2 lies on segment plq1
    if (o2 == 0 && onSegment(p1, q2, q1)) return true;
    // p2, q2 and p1 are colinear and p1 lies on segment p2q2
    if (o3 == 0 && onSegment(p2, p1, q2)) return true;
     // p2, q2 and q1 are colinear and q1 lies on segment p2q2
    if (o4 == 0 && onSegment(p2, q1, q2)) return true;
```

Deploy Early. Deploy Often.

DevOps from Rackspace:

Automation

FIND OUT HOW ▶







```
return false; // Doesn't fall in any of the above cases
// Returns true if the point p lies inside the polygon[] with n vertice
bool isInside(Point polygon[], int n, Point p)
    // There must be at least 3 vertices in polygon[]
    if (n < 3) return false;</pre>
    // Create a point for line segment from p to infinite
    Point extreme = {INF, p.y};
    // Count intersections of the above line with sides of polygon
    int count = 0, i = 0;
    do
        int next = (i+1)%n;
        // Check if the line segment from 'p' to 'extreme' intersects
        // with the line segment from 'polygon[i]' to 'polygon[next]'
        if (doIntersect(polygon[i], polygon[next], p, extreme))
            // If the point 'p' is colinear with line segment 'i-next'
            // then check if it lies on segment. If it lies, return tr
            // otherwise false
            if (orientation(polygon[i], p, polygon[next]) == 0)
               return onSegment(polygon[i], p, polygon[next]);
            count++;
        i = next;
    } while (i != 0);
    // Return true if count is odd, false otherwise
    return count&1; // Same as (count%2 == 1)
// Driver program to test above functions
int main()
    Point polygon1[] = \{\{0, 0\}, \{10, 0\}, \{10, 10\}, \{0, 10\}\};
    int n = sizeof(polygon1)/sizeof(polygon1[0]);
    Point p = \{20, 20\};
    isInside(polygon1, n, p)? cout << "Yes \n": cout << "No \n";
    p = \{5, 5\};
```

Recent Comments

Abhi You live US or India?

Google (Mountain View) interview 9 minutes ago

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. 49 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 52 minutes ago

Sanjay Agarwal bool

tree::Root to leaf path given sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1

hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

AdChoices D

- ► Geometry Polygon
- ► Convex Polygon
- ▶ Is a Polygon

AdChoices [>

```
isInside(polygon1, n, p)? cout << "Yes \n": cout << "No \n";
Point polygon2[] = \{\{0, 0\}, \{5, 5\}, \{5, 0\}\};
p = \{3, 3\};
n = sizeof(polygon2)/sizeof(polygon2[0]);
isInside(polygon2, n, p)? cout << "Yes \n": cout << "No \n";
p = \{5, 1\};
isInside(polygon2, n, p)? cout << "Yes \n": cout << "No \n";
p = \{8, 1\};
isInside(polygon2, n, p)? cout << "Yes \n": cout << "No \n";</pre>
Point polygon3[] = {{0, 0}, {10, 0}, {10, 10}, {0, 10}};
p = \{-1, 10\};
n = sizeof(polygon3)/sizeof(polygon3[0]);
isInside(polygon3, n, p)? cout << "Yes \n": cout << "No \n";
return 0;
```

Output:

```
No
Yes
Yes
Yes
No
No
```

Time Complexity: O(n) where n is the number of vertices in the given polygon.

Source:

http://www.dcs.gla.ac.uk/~pat/52233/slides/Geometry1x1.pdf

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

- ► Polygon With
- ► Polygon Number
- ▶ Not Polygon AdChoices [>
- ► C++ Vector
- ► Math Geeks
- ► Matrix in Java

Cquate



The New Language of Computing Download the Free Beta Now



Related Tpoics:

- Backtracking | Set 8 (Solving Cryptarithmetic Puzzles)
- Tail Recursion
- Find if two rectangles overlap
- Analysis of Algorithm | Set 4 (Solving Recurrences)
- Print all possible paths from top left to bottom right of a mXn matrix
- Generate all unique partitions of an integer
- Russian Peasant Multiplication
- Closest Pair of Points | O(nlogn) Implementation









Writing code in comment? Please use ideone.com and share the link here.

@geeksforgeeks, Some rights reserved

Contact Us!

Powered by WordPress & MooTools, customized by geeksforgeeks team