

Rotate a Linked List

Given a singly linked list, rotate the linked list counter-clockwise by k nodes. Where k is a given positive integer. For example, if the given linked list is 10->20->30->40->50->60 and k is 4, the list should be modified to 50->60->10->20->30->40. Assume that k is smaller than the count of nodes in linked list.

To rotate the linked list, we need to change next of kth node to NULL, next of last node to previous head node, and finally change head to (k+1)th node. So we need to get hold of three nodes: kth node, (k+1)th node and last node.

Traverse the list from beginning and stop at kth node. Store pointer to kth node. We can get (k+1)th node using kthNode->next. Keep traversing till end and store pointer to last node also. Finally, change pointers as stated above.

```
// Program to rotate a linked list counter clock wise
#include<stdio.h>
#include<stdlib.h>

/* Link list node */
struct node
{
    int data;
    struct node* next;
};

// This function rotates a linked list counter-clockwise and updates t
// The function assumes that k is smaller than size of linked list. It
// modify the list if k is greater than or equal to size
void rotate (struct node **head_ref, int k)
{
    if (k == 0)
        return;
```

Google™ Custom Search



GeeksforGeeks



53,527 people like [GeeksforGeeks](#).



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

```

// Let us understand the below code for example k = 4 and
// list = 10->20->30->40->50->60.
struct node* current = *head_ref;

// current will either point to kth or NULL after this loop.
// current will point to node 40 in the above example
int count = 1;
while (count < k && current != NULL)
{
    current = current->next;
    count++;
}

// If current is NULL, k is greater than or equal to count
// of nodes in linked list. Don't change the list in this case
if (current == NULL)
    return;

// current points to kth node. Store it in a variable.
// kthNode points to node 40 in the above example
struct node *kthNode = current;

// current will point to last node after this loop
// current will point to node 60 in the above example
while (current->next != NULL)
    current = current->next;

// Change next of last node to previous head
// Next of 60 is now changed to node 10
current->next = *head_ref;

// Change head to (k+1)th node
// head is now changed to node 50
*head_ref = kthNode->next;

// change next of kth node to NULL
// next of 40 is now NULL
kthNode->next = NULL;
}

/* UTILITY FUNCTIONS */
/* Function to push a node */
void push (struct node** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node =

```

Build Applications With Fewer Bugs



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

    (struct node*) malloc(sizeof(struct node));

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*head_ref);

    /* move the head to point to the new node */
    (*head_ref) = new_node;
}

/* Function to print linked list */
void printList(struct node *node)
{
    while (node != NULL)
    {
        printf("%d ", node->data);
        node = node->next;
    }
}

/* Driver program to test above function*/
int main(void)
{
    /* Start with the empty list */
    struct node* head = NULL;

    // create a list 10->20->30->40->50->60
    for (int i = 60; i > 0; i -= 10)
        push(&head, i);

    printf("Given linked list \n");
    printList(head);
    rotate(&head, 4);

    printf("\nRotated Linked list \n");
    printList(head);

    return (0);
}

```

Output:

```

Given linked list
10 20 30 40 50 60

```


Custom market
research at scale.

Get \$75 off

 Google consumer surveys

Time Complexity: $O(n)$ where n is the number of nodes in Linked List. The code traverses the linked list only once.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Related Topics:

- [Given a linked list, reverse alternate nodes and append at the end](#)
- [Pairwise swap elements of a given linked list by changing links](#)
- [Self Organizing List | Set 1 \(Introduction\)](#)
- [Merge a linked list into another linked list at alternate positions](#)
- [QuickSort on Singly Linked List](#)
- [Delete N nodes after M nodes of a linked list](#)
- [Design a stack with operations on middle element](#)
- [Swap Kth node from beginning with Kth node from end in a Linked List](#)

Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 44 minutes ago

[Aman](#) Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 1 hour ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

[Sanjay Agarwal](#) bool

tree::Root_to_leaf_path_given_sum(tree...


Root to leaf path sum equal to a given number · 1 hour ago

[GOPI GOPINATH](#) @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

[newCoder3006](#) If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 2 hours ago

AdChoices 

[▶ Linked List](#)

[▶ C++ Code](#)

[▶ Programming C++](#)

AdChoices 

[▶ I Rotate](#)



8




Tweet

0



0

Writing code in comment? Please use ideone.com and share the link here.

[▶ Rotate With](#)[▶ Java C++](#)AdChoices [▶ Java Array](#)[▶ C++ Example](#)[▶ Null Pointer](#)

@geeksforgeeks, **Some rights reserved**

[Contact Us!](#)

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team