

## Reverse a Linked List in groups of given size

Given a linked list, write a function to reverse every k nodes (where k is an input to the function).

Example:

Inputs: 1->2->3->4->5->6->7->8->NULL and k = 3

Output: 3->2->1->6->5->4->8->7->NULL.

Inputs: 1->2->3->4->5->6->7->8->NULL and k = 5

Output: 5->4->3->2->1->8->7->6->NULL.

Algorithm: *reverse(head, k)*

- 1) Reverse the first sub-list of size k. While reversing keep track of the next node and previous node. Let the pointer to the next node be *next* and pointer to the previous node be *prev*. See [this post](#) for reversing a linked list.
- 2) *head->next = reverse(next, k)* /\* Recursively call for rest of the list and link the two sub-lists \*/
- 3) return *prev* /\* *prev* becomes the new head of the list (see the diagrams of iterative method of [this post](#)) \*/

```
#include<stdio.h>
#include<stdlib.h>
```

```
/* Link list node */
struct node
{
    int data;
    struct node* next;
};
```

```
/* Reverses the linked list in groups of size k and returns the
pointer to the new head node. */
```


Google™ Custom Search



GeeksforGeeks



53,528 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```

struct node *reverse (struct node *head, int k)
{
    struct node* current = head;
    struct node* next;
    struct node* prev = NULL;
    int count = 0;

    /*reverse first k nodes of the linked list */
    while (current != NULL && count < k)
    {
        next = current->next;
        current->next = prev;
        prev = current;
        current = next;
        count++;
    }

    /* next is now a pointer to (k+1)th node
       Recursively call for the list starting from current.
       And make rest of the list as next of first node */
    if (next != NULL)
    { head->next = reverse(next, k); }

    /* prev is new head of the input list */
    return prev;
}

/* UTILITY FUNCTIONS */
/* Function to push a node */
void push(struct node** head_ref, int new_data)
{
    /* allocate node */
    struct node* new_node =
        (struct node*) malloc(sizeof(struct node));

    /* put in the data */
    new_node->data = new_data;

    /* link the old list off the new node */
    new_node->next = (*head_ref);

    /* move the head to point to the new node */
    (*head_ref) = new_node;
}

/* Function to print linked list */
void printList(struct node *node)

```



## Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

{
    while (node != NULL)
    {
        printf("%d ", node->data);
        node = node->next;
    }
}

/* Drier program to test above function*/
int main(void)
{
    /* Start with the empty list */
    struct node* head = NULL;

    /* Created Linked list is 1->2->3->4->5->6->7->8 */
    push(&head, 8);
    push(&head, 7);
    push(&head, 6);
    push(&head, 5);
    push(&head, 4);
    push(&head, 3);
    push(&head, 2);
    push(&head, 1);

    printf("\n Given linked list \n");
    printList(head);
    head = reverse(head, 3);

    printf("\n Reversed Linked list \n");
    printList(head);

    getchar();
    return(0);
}

```

Time Complexity:  $O(n)$  where  $n$  is the number of nodes in the given list.

Please write comments if you find the above code/algorithm incorrect, or find other ways to solve the same problem.


Shouldn't you  
expect a  
cloud with:

# SYSTEM MONITORING

Plus the experts  
to help run it?

TRY MANAGED CLOUD ▶





705



Subscribe

## Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 50 minutes ago

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 1 hour ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 1 hour ago

Sanjay Agarwal bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 1

hour ago

GOPI GOPINATH @admin Highlight this

sentence "We can easily...

Count trailing zeroes in factorial of a number · 1

hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 2 hours ago

## Related Topics:

- Given a linked list, reverse alternate nodes and append at the end
- Pairwise swap elements of a given linked list by changing links
- Self Organizing List | Set 1 (Introduction)
- Merge a linked list into another linked list at alternate positions
- QuickSort on Singly Linked List
- Delete N nodes after M nodes of a linked list
- Design a stack with operations on middle element
- Swap Kth node from beginning with Kth node from end in a Linked List



5



Tweet

0



0


Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

AdChoices 

▶ [Linked List](#)

▶ [C++ Code](#)


▶ [C++ Reverse List](#)

AdChoices 

▶ [Java Reverse](#)

▶ [Reverse Polarity](#)

▶ [Programming C++](#)

AdChoices 

▶ [Array Reverse](#)

▶ [Reverse Function](#)

▶ [Reverse String](#)

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team