

## Count set bits in an integer

Write an efficient program to count number of 1s in binary representation of an integer.

**1. Simple Method** Loop through all bits in an integer, check if a bit is set and if it is then increment the set bit count. See below program.

```
/* Function to get no of set bits in binary
representation of passed binary no. */
int countSetBits(unsigned int n)
{
    unsigned int count = 0;
    while (n)
    {
        count += n & 1;
        n >>= 1;
    }
    return count;
}

/* Program to test function countSetBits */
int main()
{
    int i = 9;
    printf("%d", countSetBits(i));
    getchar();
    return 0;
}
```

**Time Complexity:**  $O(\log n)$  (Theta of  $\log n$ )

### 2. Brian Kernighan's Algorithm:

Subtraction of 1 from a number toggles all the bits (from right to left) till the rightmost set

Google™ Custom Search



GeeksforGeeks



53,526 people like GeeksforGeeks.



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

bit(including the rightmost set bit). So if we subtract a number by 1 and do bitwise & with itself ( $n \& (n-1)$ ), we unset the rightmost set bit. If we do  $n \& (n-1)$  in a loop and count the no of times loop executes we get the set bit count.

Beauty of this solution is number of times it loops is equal to the number of set bits in a given integer.

```

1 Initialize count: = 0
2 If integer n is not zero
  (a) Do bitwise & with (n-1) and assign the value back to n
      n: = n&(n-1)
  (b) Increment count by 1
  (c) go to step 2
3 Else return count

```

### Implementation of Brian Kernighan's Algorithm:

```

#include<stdio.h>

/* Function to get no of set bits in binary
representation of passed binary no. */
int countSetBits(int n)
{
    unsigned int count = 0;
    while (n)
    {
        n &= (n-1) ;
        count++;
    }
    return count;
}

/* Program to test function countSetBits */
int main()
{
    int i = 9;
    printf("%d", countSetBits(i));
    getchar();
    return 0;
}

```



### Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

### Example for Brian Kernighan's Algorithm:

```
n = 9 (1001)
count = 0
```

Since  $9 > 0$ , subtract by 1 and do bitwise & with  $(9-1)$

```
n = 9&8 (1001 & 1000)
n = 8
count = 1
```

Since  $8 > 0$ , subtract by 1 and do bitwise & with  $(8-1)$

```
n = 8&7 (1000 & 0111)
n = 0
count = 2
```

Since  $n = 0$ , return count which is 2 now.

## HP Chromebook 11

 [google.com/chromebook](https://google.com/chromebook)

Everything you need in one laptop. Made with Google. Learn more.




**Time Complexity:**  $O(\log n)$

**3. Using Lookup table:** We can count bits in  $O(1)$  time using lookup table. Please see <http://graphics.stanford.edu/~seander/bithacks.html#CountBitsSetTable> for details.

You can find one use of counting set bits at <http://geeksforgeeks.org/?p=1465>

#### References:

<http://graphics.stanford.edu/~seander/bithacks.html#CountBitsSetNaive>



705



Subscribe

## Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 20 minutes ago

**Aman** Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 59 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 1 hour ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

**GOPI GOPINATH** @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

**newCoder3006** If the array contains negative

## Related Topics:

- Check if a number is multiple of 9 using bitwise operators
- How to swap two numbers without using a temporary variable?
- Divide and Conquer | Set 4 (Karatsuba algorithm for fast multiplication)
- Find position of the only set bit
- Swap all odd and even bits
- Add two bit strings
- Write your own strcmp that ignores cases
- Binary representation of a given number



6



Tweet 0




2

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

numbers also. We...

Find subarray with given sum · 1 hour ago


---

AdChoices 

► [Bits Byte](#)

► [Java 64 Bits](#)


► [Hex Bits](#)

AdChoices 

► [Long Integer](#)

► [Int Bits](#)

► [Log Me Int](#)

AdChoices 

► [Convert Int](#)

► [From Int](#)

► [To Int](#)

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team