


Pattern Searching | Set 6 (Efficient Construction of Finite Automata)

In the [previous post](#), we discussed Finite Automata based pattern searching algorithm. The FA (Finite Automata) construction method discussed in previous post takes $O((m^3) \cdot \text{NO_OF_CHARS})$ time. FA can be constructed in $O(m \cdot \text{NO_OF_CHARS})$ time. In this post, we will discuss the $O(m \cdot \text{NO_OF_CHARS})$ algorithm for FA construction. The idea is similar to lps (longest prefix suffix) array construction discussed in the [KMP algorithm](#). We use previously filled rows to fill a new row.





Google™ Custom Search



GeeksforGeeks



53,524 people like [GeeksforGeeks](#).



Facebook

[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

state	character			
	A	C	G	T
0	1	0	0	0
1	1	2	0	0
2	3	0	0	0
3	1	4	0	0
4	5	0	0	0
5	1	4	6	0
6	7	0	0	0
7	1	2	0	0

The above diagrams represent graphical and tabular representations of pattern ACACAGA.

Algorithm:

- 1) Fill the first row. All entries in first row are always 0 except the entry for pat[0] character. For pat[0] character, we always need to go to state 1.
- 2) Initialize lps as 0. lps for the first index is always 0.
- 3) Do following for rows at index i = 1 to M. (M is the length of the pattern)
 -a) Copy the entries from the row at index equal to lps.
 -b) Update the entry for pat[i] character to i+1.
 -c) Update lps "lps = TF[lps][pat[i]]" where TF is the 2D array which is being constructed.

Implementation

Following is C implementation for the above algorithm.

```
#include<stdio.h>
#include<string.h>
#define NO_OF_CHARS 256

/* This function builds the TF table which represents Finite Automata
   given pattern */
void computeTransFun(char *pat, int M, int TF[][NO_OF_CHARS])
{
    int i, lps = 0, x;

    // Fill entries in first row
    for (x = 0; x < NO_OF_CHARS; x++)
        TF[0][x] = 0;
    TF[0][pat[0]] = 1;

    // Fill entries in other rows
```

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and](#)

[Data Packing](#)

```

for (i = 1; i <= M; i++)
{
    // Copy values from row at index lps
    for (x = 0; x < NO_OF_CHARS; x++)
        TF[i][x] = TF[lps][x];

    // Update the entry corresponding to this character
    TF[i][pat[i]] = i + 1;

    // Update lps for next row to be filled
    if (i < M)
        lps = TF[lps][pat[i]];
}
}

```

```

/* Prints all occurrences of pat in txt */
void search(char *pat, char *txt)
{
    int M = strlen(pat);
    int N = strlen(txt);

    int TF[M+1][NO_OF_CHARS];

    computeTransFun(pat, M, TF);

    // process text over FA.
    int i, j=0;
    for (i = 0; i < N; i++)
    {
        j = TF[j][txt[i]];
        if (j == M)
        {
            printf ("\n pattern found at index %d", i-M+1);
        }
    }
}

/* Driver program to test above function */
int main()
{
    char *txt = "GEEKS FOR GEEKS";
    char *pat = "GEEKS";
    search(pat, txt);
    getchar();
    return 0;
}

```

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST




Output:

```
pattern found at index 0
pattern found at index 10
```

Time Complexity for FA construction is $O(M \cdot \text{NO_OF_CHARS})$. The code for search is same as the [previous post](#) and time complexity for it is $O(n)$.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Related Tpoics:

- [Print all possible words from phone digits](#)
- [Printing Longest Common Subsequence](#)
- [Suffix Array | Set 2 \(nLogn Algorithm\)](#)
- [Rearrange a string so that all same characters become d distance away](#)
- [Recursively remove all adjacent duplicates](#)
- [Find the first non-repeating character from a stream of characters](#)
- [Dynamic Programming | Set 33 \(Find if a string is interleaved of two other strings\)](#)



705



Subscribe

Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 2 minutes ago

[Aman](#) Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 42 minutes ago

[kzs](#) please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 45 minutes ago

[Sanjay Agarwal](#) bool

[tree::Root_to_leaf_path_given_sum\(tree...](#)

[Root to leaf path sum equal to a given number](#) · 1 hour ago

[GOPI GOPINATH](#) @admin Highlight this sentence "We can easily...

[Count trailing zeroes in factorial of a number](#) · 1 hour ago

[newCoder3006](#) If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 1 hour ago

- Remove "b" and "ac" from a given string



3



Tweet

0



0

Writing code in comment? Please use ideone.com and share the link here.

10 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



Guest · 6 months ago

This code runs in $O(n)$ time with constant space ...please correct me if it is inc

```
int position[26] = {0};
```

```
int delta(int state,char input,char *fa,int i){
```

```
if( fa[state] == input ){
```

```
position[input - 97] = state;
```

```
return state+1;
```

```
}
```

```
return position[input-97];
```

```
}
```

```
int pattern_match(char *str,char *p,int n,int m){
```

```
int q = 0;
```

```
for(int i = 0 ; i < n; i++){
```

```
int old_q = q;
```

```
q = delta(q,str[i],p,i);
```

```
if(old_q != 0 && old_q - q > 1)
```

```
i--;
```

```
else if(q == m){
```

```
cout<<"pattern found at : "<<i-m+1<<endl; q="0;" }="" }="" }="" int="" main(){='
```

AdChoices ▶

► [C++ Code](#)

► [Pattern Matching](#)

► [Java Pattern](#)

AdChoices ▶

► [Java Pattern](#)

► [Programming C++](#)

► [Automata](#)

AdChoices ▶

► [Geeks to Go](#)

► [Automata](#)

► [Java Array](#)

```
char="" pattern[]="geeks" ;="" pattern_match(str,="" pattern,="" sizeof(str)="" ;
sizeof(char)="" -1);="" return="" 0;="" }="">
```

^ | v .



alien · 9 months ago

@GeeksforGeeks: Could you please explain why this algorithm is able to fill Tl at a given time?

1 ^ | v .



Dhiren · 10 months ago

Consider this example

Pattern – A C A C

At state-0, we have only “A”, so lps = 0

Transition from state-0 to state-1, probable cases may be

Case-1 a new ‘A’ comes, then we go back to our longest prefix suffix till now w what if a ‘A’ comes, in this case it is 1

Case-2 a new ‘G’ comes, then we go back to our longest prefix suffix till now a will be 0

Case-3 a new ‘C’ comes, then also value will be 0

That’s why we are first copying the lps row values into the current ith row.

Then we update the state transition for patt[i] in this case for ‘C’ state will be 2.

Then we calculate the current lps value, that is “AC” but still lps =0 as there is

Calculation of lps can be clear from state transition-2 to 3.

Current lps is 0, now ‘A’ comes so that new lps is 1 for “ACA” which can be fo

^ | v .



Arvind · 11 months ago

How does this algorithm work ? where is the proof for this ?

1 ^ | v .



Ram · 11 months ago



Wher is the proof ?????????????? please post the proof

1 ^ | v .



Akshay khare · a year ago

when i will become equal to M

then $TF[i][pat[i]] = i+1$. will give segmentation fault

since pat has length M and its index can be upto M-1 only

how will $TF[M][pat[M]]$ will work..pat[M] -> this location not exists..pls explain h
me if i am wrong...

2 ^ | v .



Shiwakant Bharti → Akshay khare · 9 months ago

Akshay khare Nice findings! I got the same error in Java.

Here is the test case which should break:

```
char[] txt2 = "AABAACAADAABAAABAA".toCharArray();
char[] pat2 = "AABA".toCharArray();

//This code fix worked for me. Not sure if this robust enough.
for (i = 1; i <= M; i++) {
    // Copy values from row at index lps
    // Is this powerful enough to handle case of i = M(
    // transition)?
    for (ch = 0; ch < NoOfChars; ch++) {
        TFDP[i][ch] = TFDP[lps][ch];
    }
    // This is special case where the last halt state i
    // for regular processing.
    // Here pat[M] is out of bound and further calculat
    //
```

[see more](#)



abhishek08aug · a year ago

Intelligent :D



vinu · 2 years ago

Yes... @GeeksForGeeks can you please me more clear with reasoning of ste

```
/* Paste your code here (You may delete these lines if not writing c
```



spandan · 2 years ago

If someone can please explain how has the transition function been computed



Subscribe



Add Disqus to your site