

Maximum Product Subarray

Given an array that contains both positive and negative integers, find the product of the maximum product subarray. Expected Time complexity is $O(n)$ and only $O(1)$ extra space can be used.

Examples:

Input: arr[] = {6, -3, -10, 0, 2}

Output: 180 // The subarray is {6, -3, -10}

Input: arr[] = {-1, -3, -10, 0, 60}

Output: 60 // The subarray is {60}

Input: arr[] = {-2, -3, 0, -2, -40}

Output: 80 // The subarray is {-2, -40}

The following solution assumes that the given input array always has a positive output. The solution works for all cases mentioned above. It doesn't work for arrays like {0, 0, -20, 0}, {0, 0, 0}.. etc. The solution can be easily modified to handle this case.

It is similar to [Largest Sum Contiguous Subarray](#) problem. The only thing to note here is, maximum product can also be obtained by minimum (negative) product ending with the previous element multiplied by this element. For example, in array {12, 2, -3, -5, -6, -2}, when we are at element -2, the maximum product is multiplication of, minimum product ending with -6 and -2.

```
#include <stdio.h>
```

```
// Utility functions to get minimum of two integers
int min (int x, int y) {return x < y? x : y; }
```

```
// Utility functions to get maximum of two integers
```


Google™ Custom Search



GeeksforGeeks



53,520 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```
int max (int x, int y) {return x > y? x : y; }
```

```
/* Returns the product of max product subarray. Assumes that the
given array always has a subarray with product more than 1 */
int maxSubarrayProduct(int arr[], int n)
{
    // max positive product ending at the current position
    int max_ending_here = 1;

    // min negative product ending at the current position
    int min_ending_here = 1;

    // Initialize overall max product
    int max_so_far = 1;

    /* Traverse through the array. Following values are maintained after
    max_ending_here is always 1 or some positive product ending with
    min_ending_here is always 1 or some negative product ending with
    for (int i = 0; i < n; i++)
    {
        /* If this element is positive, update max_ending_here. Update
        min_ending_here only if min_ending_here is negative */
        if (arr[i] > 0)
        {
            max_ending_here = max_ending_here*arr[i];
            min_ending_here = min (min_ending_here * arr[i], 1);
        }

        /* If this element is 0, then the maximum product cannot
        end here, make both max_ending_here and min_ending_here 0
        Assumption: Output is always greater than or equal to 1. */
        else if (arr[i] == 0)
        {
            max_ending_here = 1;
            min_ending_here = 1;
        }

        /* If element is negative. This is tricky
        max_ending_here can either be 1 or positive. min_ending_here
        or negative.
        next min_ending_here will always be prev. max_ending_here *
        next max_ending_here will be 1 if prev min_ending_here is 1
        next max_ending_here will be prev min_ending_here * arr[i]
        else
        {
            int temp = max_ending_here;
            max_ending_here = max (min_ending_here * arr[i], 1);
            min_ending_here = min (temp * arr[i], min_ending_here);
        }
    }
}
```



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

        min_ending_here = temp * arr[i];
    }

    // update max_so_far, if needed
    if (max_so_far < max_ending_here)
        max_so_far = max_ending_here;
}

return max_so_far;
}

// Driver Program to test above function
int main()
{
    int arr[] = {1, -2, -3, 0, 7, -8, -2};
    int n = sizeof(arr)/sizeof(arr[0]);
    printf("Maximum Sub array product is %d", maxSubarrayProduct(arr, n));
    return 0;
}

```

Output:

Maximum Sub array product is 112

Time Complexity: $O(n)$

Auxiliary Space: $O(1)$

This article is compiled by **Dheeraj Jain** and reviewed by GeeksforGeeks team. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Shouldn't
you expect
a cloud with:

**ONE-CLICK
DEPLOYMENTS**

Experience the
Managed Cloud
Difference

QAD Cloud ERP Application

 qad.com/ERP

Innovative, Secure, Flexible Cloud
ERP Global Solutions. Request Info!



 705



Recent Comments

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 4 minutes ago
kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 8 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 32 minutes ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 34 minutes ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 59 minutes ago

newCoder3006 Code without using while loop. We can do it...

Related Topics:

- Remove minimum elements from either side such that $2 \times \text{min}$ becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



 7




Tweet  0



 0


Writing code in comment? Please use ideone.com and share the link here.

AdChoices 

▶ [JavaScript Array](#)

▶ [C++ Code](#)


▶ [C++ Array](#)

AdChoices 

▶ [Java Array](#)

▶ [Array Max](#)

▶ [Json Array](#)

AdChoices 

▶ [An Array](#)

▶ [Jquery Array](#)

▶ [Programming C++](#)