

Backtracking | Set 4 (Subset Sum)

Subset sum problem is to find subset of elements that are selected from a given set whose sum adds up to a given number K. We are considering the set contains non-negative values. It is assumed that the input set is unique (no duplicates are presented).


Exhaustive Search Algorithm for Subset Sum

One way to find subsets that sum to K is to consider all possible subsets. A **power set** contains all those subsets generated from a given set. The size of such a power set is 2^N .

Backtracking Algorithm for Subset Sum

Using exhaustive search we consider all subsets irrespective of whether they satisfy given constraints or not. Backtracking can be used to make a systematic consideration of the elements to be selected.




Assume given set of 4 elements, say **w[1] ... w[4]**. Tree diagrams can be used to design backtracking algorithms. The following tree diagram depicts approach of generating variable sized tuple.



GeeksforGeeks



53,525 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

Greedy Algorithms

Backtracking


Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms



**Build Web Apps
in Minutes**

NEBULON SYSTEMS

THE ACME FOOD COMPANY

SALES REPRESENTATIVE

Free Download!

IRON SPEED*

Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and

In the above tree, a node represents function call and a branch represents candidate element. The root node contains 4 children. In other words, root considers every element of the set as different branch. The next level sub-trees correspond to the subsets that includes the parent node. The branches at each level represent tuple element to be considered. For example, if we are at level 1, `tuple_vector[1]` can take any value of four branches generated. If we are at level 2 of left most node, `tuple_vector[2]` can take any value of three branches generated, and so on...

For example the left most child of root generates all those subsets that include `w[1]`. Similarly the second child of root generates all those subsets that includes `w[2]` and excludes `w[1]`.

As we go down along depth of tree we add elements so far, and if the added sum is satisfying explicit constraints, we will continue to generate child nodes further. Whenever the constraints are not met, we stop further generation of sub-trees of that node, and backtrack to previous node to explore the nodes not yet explored. In many scenarios, it saves considerable amount of processing time.

The tree should trigger a clue to implement the backtracking algorithm (try yourself). It prints all those subsets whose sum add up to given number. We need to explore the nodes along the breadth and depth of the tree. Generating nodes along breadth is controlled by loop and nodes along the depth are generated using recursion (post order traversal). Pseudo code given below,

```
if(subset is satisfying the constraint)
    print the subset
    exclude the current element and consider next element
```

Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

else

generate the nodes of present level along breadth of tree and
recur for next levels

Following is C implementation of subset sum using variable size tuple vector. Note that the following program explores all possibilities similar to exhaustive search. It is to demonstrate how backtracking can be used. See next code to verify, how we can optimize the backtracking solution.

```
#include <stdio.h>
#include <stdlib.h>

#define ARRAYSIZE(a) (sizeof(a))/(sizeof(a[0]))

static int total_nodes;
// prints subset found
void printSubset(int A[], int size)
{
    for(int i = 0; i < size; i++)
    {
        printf("%*d", 5, A[i]);
    }

    printf("\n");
}

// inputs
// s          - set vector
// t          - tuple vector
// s_size     - set size
// t_size     - tuple size so far
// sum        - sum so far
// ite       - nodes count
// target_sum - sum to be found
void subset_sum(int s[], int t[],
               int s_size, int t_size,
               int sum, int ite,
               int const target_sum)
{
    total_nodes++;
    if( target_sum == sum )
    {
        // We found subset
        printSubset(t, t_size);
        // Exclude previously added item and consider next candidate
    }
}
```



```

        subset_sum(s, t, s_size, t_size-1, sum - s[ite], ite + 1, target_sum);
        return;
    }
    else
    {
        // generate nodes along the breadth
        for( int i = ite; i < s_size; i++ )
        {
            t[t_size] = s[i];
            // consider next level node (along depth)
            subset_sum(s, t, s_size, t_size + 1, sum + s[i], i + 1, target_sum);
        }
    }
}

// Wrapper to print subsets that sum to target_sum
// input is weights vector and target_sum
void generateSubsets(int s[], int size, int target_sum)
{
    int *tuple_vector = (int *)malloc(size * sizeof(int));

    subset_sum(s, tuple_vector, size, 0, 0, 0, target_sum);

    free(tuple_vector);
}

int main()
{
    int weights[] = {10, 7, 5, 18, 12, 20, 15};
    int size = ARRAYSIZE(weights);

    generateSubsets(weights, size, 35);
    printf("Nodes generated %d\n", total_nodes);
    return 0;
}

```

The power of backtracking appears when we combine explicit and implicit constraints, and we stop generating nodes when these checks fail. We can improve the above algorithm by strengthening the constraint checks and presorting the data. By sorting the initial array, we need not to consider rest of the array, once the sum so far is greater than target number. We can backtrack and check other possibilities.

Similarly, assume the array is presorted and we found one subset. We can generate next node excluding the present node only when inclusion of next node satisfies the constraints. Given

Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 8 minutes ago

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 47 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 51 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

AdChoices 

► [Backtracking](#)

► [Int](#)

► [SUM](#)

excluding the present node only when inclusion of next node satisfies the constraints. Given below is optimized implementation (it prunes the subtree if it is not satisfying constraints).

```
#include <stdio.h>
#include <stdlib.h>

#define ARRAYSIZE(a) (sizeof(a))/(sizeof(a[0]))

static int total_nodes;

// prints subset found
void printSubset(int A[], int size)
{
    for(int i = 0; i < size; i++)
    {
        printf("%d", A[i]);
    }

    printf("\n");
}

// qsort compare function
int comparator(const void *pLhs, const void *pRhs)
{
    int *lhs = (int *)pLhs;
    int *rhs = (int *)pRhs;

    return *lhs > *rhs;
}

// inputs
// s          - set vector
// t          - tuple vector
// s_size     - set size
// t_size     - tuple size so far
// sum        - sum so far
// ite       - nodes count
// target_sum - sum to be found
void subset_sum(int s[], int t[],
               int s_size, int t_size,
               int sum, int ite,
               int const target_sum)
{
    total_nodes++;

    if( target_sum == sum )
    {
```

```

    // We found sum
    printSubset(t, t_size);

    // constraint check
    if( ite + 1 < s_size && sum - s[ite] + s[ite+1] <= target_sum
    {
        // Exclude previous added item and consider next candidate
        subset_sum(s, t, s_size, t_size-1, sum - s[ite], ite + 1,
    }
    return;
}
else
{
    // constraint check
    if( ite < s_size && sum + s[ite] <= target_sum )
    {
        // generate nodes along the breadth
        for( int i = ite; i < s_size; i++ )
        {
            t[t_size] = s[i];

            if( sum + s[i] <= target_sum )
            {
                // consider next level node (along depth)
                subset_sum(s, t, s_size, t_size + 1, sum + s[i], i
            }
        }
    }
}

// Wrapper that prints subsets that sum to target_sum
void generateSubsets(int s[], int size, int target_sum)
{
    int *tuple_vector = (int *)malloc(size * sizeof(int));

    int total = 0;

    // sort the set
    qsort(s, size, sizeof(int), &comparator);

    for( int i = 0; i < size; i++ )
    {
        total += s[i];
    }

    if( s[0] <= target_sum && total >= target_sum )

```

```

{
    subset_sum(s, tuplelet_vector, size, 0, 0, 0, target_sum);
}

free(tuplelet_vector);
}

int main()
{
    int weights[] = {15, 22, 14, 26, 32, 9, 16, 8};
    int target = 53;

    int size = ARRAYSIZE(weights);

    generateSubsets(weights, size, target);


    printf("Nodes generated %d\n", total_nodes);

    return 0;
}

```

As another approach, we can generate the tree in fixed size tuple analogs to binary pattern. We will kill the sub-trees when the constraints are not satisfied.

— — — **Venki**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



Related Topics:

- [Backtracking | Set 8 \(Solving Cryptarithmic Puzzles\)](#)
- [Tail Recursion](#)
- [Find if two rectangles overlap](#)
- [Analysis of Algorithm | Set 4 \(Solving Recurrences\)](#)
- [Print all possible paths from top left to bottom right of a mXn matrix](#)
- [Generate all unique partitions of an integer](#)
- [Russian Peasant Multiplication](#)
- [Closest Pair of Points | O\(nlogn\) Implementation](#)



7



Tweet

0



0

Writing code in comment? Please use ideone.com and share the link here.

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team