


## Level order traversal in spiral form

Write a function to print spiral order traversal of a tree. For below tree, function should print 1, 2, 3, 4, 5, 6, 7.



### Method 1 (Recursive)

This problem can be seen as an extension of the [level order traversal](#) post.

To print the nodes in spiral order, nodes at different levels should be printed in alternating order. An additional Boolean variable *ltr* is used to change printing order of levels. If *ltr* is 1 then printGivenLevel() prints nodes from left to right else from right to left. Value of *ltr* is flipped in each iteration to change the order.

Function to print level order traversal of tree

```

printSpiral(tree)
    bool ltr = 0;
    for d = 1 to height(tree)
        printGivenLevel(tree, d, ltr);
  
```


Google™ Custom Search



GeeksforGeeks



52,731 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```
ltr ~= ltr /*flip ltr*/
```

Function to print all nodes at a given level

```
printGivenLevel(tree, level, ltr)
if tree is NULL then return;
if level is 1, then
    print(tree->data);
else if level greater than 1, then
    if(rtl)
        printGivenLevel(tree->right, level-1, ltr);
        printGivenLevel(tree->left, level-1, ltr);
    else
        printGivenLevel(tree->left, level-1, ltr);
        printGivenLevel(tree->right, level-1, ltr);
```

Following is C implementation of above algorithm.

```
#include <stdio.h>
#include <stdlib.h>
#include <stdbool.h>

/* A binary tree node has data, pointer to left child
and a pointer to right child */
struct node
{
    int data;
    struct node* left;
    struct node* right;
};

/* Function prototypes */
void printGivenLevel(struct node* root, int level, int ltr);
int height(struct node* node);
struct node* newNode(int data);

/* Function to print spiral traversal of a tree*/
void printSpiral(struct node* root)
{
    int h = height(root);
    int i;

    /*ltr -> Left to Right. If this variable is set,
```



## Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

    then the given level is traversed from left to right. */
bool ltr = false;
for(i=1; i<=h; i++)
{
    printGivenLevel(root, i, ltr);

    /*Revert ltr to traverse next level in opposite order*/
    ltr = !ltr;
}

/* Print nodes at a given level */
void printGivenLevel(struct node* root, int level, int ltr)
{
    if(root == NULL)
        return;
    if(level == 1)
        printf("%d ", root->data);
    else if (level > 1)
    {
        if(ltr)
        {
            printGivenLevel(root->left, level-1, ltr);
            printGivenLevel(root->right, level-1, ltr);
        }
        else
        {
            printGivenLevel(root->right, level-1, ltr);
            printGivenLevel(root->left, level-1, ltr);
        }
    }
}

/* Compute the "height" of a tree -- the number of
nodes along the longest path from the root node
down to the farthest leaf node.*/
int height(struct node* node)
{
    if (node==NULL)
        return 0;
    else
    {
        /* compute the height of each subtree */
        int lheight = height(node->left);
        int rheight = height(node->right);

        /* use the larger one */

```

Shouldn't you  
expect a  
cloud with:

# SYSTEM MONITORING

Plus the experts  
to help run it?

TRY MANAGED CLOUD ▶



```

        if (lheight > rheight)
            return(lheight+1);
        else return(rheight+1);
    }
}

/* Helper function that allocates a new node with the
   given data and NULL left and right pointers. */
struct node* newNode(int data)
{
    struct node* node = (struct node*)
                        malloc(sizeof(struct node));
    node->data = data;
    node->left = NULL;
    node->right = NULL;

    return(node);
}

/* Driver program to test above functions*/
int main()
{
    struct node *root = newNode(1);
    root->left = newNode(2);
    root->right = newNode(3);
    root->left->left = newNode(7);
    root->left->right = newNode(6);
    root->right->left = newNode(5);
    root->right->right = newNode(4);
    printf("Spiral Order traversal of binary tree is \n");
    printSpiral(root);

    return 0;
}

```

Output:

```

Spiral Order traversal of binary tree is
1 2 3 4 5 6 7

```

**Time Complexity:** Worst case time complexity of the above method is  $O(n^2)$ . Worst case occurs in case of skewed trees.

## Method 2 (Iterative)

## Recent Comments

karthik it should have been max\_wrap=  
max\_wrap -...

Maximum circular subarray sum · 1 minute ago

affiszerv Your example has two 4s on row 3,  
that's why it...

Backtracking | Set 7 (Sudoku) · 45 minutes ago

**RVM** Can someone please elaborate this Qs  
from above...

Flipkart Interview | Set 6 · 1 hour ago

**Vishal Gupta** I talked about as an Interviewer  
in general,...

Software Engineering Lab, Samsung Interview | Set  
2 · 1 hour ago

**@meya** Working solution for question 2 of  
4f2f round....

Amazon Interview | Set 53 (For SDE-1) · 1 hour ago  
sandeep void rearrange(struct node \*head)  
{...

Given a linked list, reverse alternate nodes and  
append at the end · 3 hours ago

AdChoices 

[▶ Binary Tree](#)

[▶ Java Tree](#)

[▶ Java to C++](#)

AdChoices 

We can print spiral order traversal in **O(n) time** and O(n) extra space. The idea is to use two stacks. We can use one stack for printing from left to right and other stack for printing from right to left. In every iteration, we have nodes of one level in one of the stacks. We print the nodes, and push nodes of next level in other stack.

```
// C++ implementation of a O(n) time method for spiral order traversal
#include <iostream>
#include <stack>
using namespace std;

// Binary Tree node
struct node
{
    int data;
    struct node *left, *right;
};
```

```
void printSpiral(struct node *root)
{
    if (root == NULL) return; // NULL check

    // Create two stacks to store alternate levels
    stack<struct node*> s1; // For levels to be printed from right to left
    stack<struct node*> s2; // For levels to be printed from left to right

    // Push first level to first stack 's1'
    s1.push(root);

    // Keep printing while any of the stacks has some nodes
    while (!s1.empty() || !s2.empty())
    {
        // Print nodes of current level from s1 and push nodes of
        // next level to s2
        while (!s1.empty())
        {
            struct node *temp = s1.top();
            s1.pop();
            cout << temp->data << " ";

            // Note that right is pushed before left
            if (temp->right)
                s2.push(temp->right);
            if (temp->left)
                s2.push(temp->left);
        }
    }
}
```

► [Node](#)

► [Spiral](#)

► [Java Array](#)

AdChoices

► [Tree Root](#)

► [Level of Tree](#)

► [Compare C++ Code](#)

```

// Print nodes of current level from s2 and push nodes of
// next level to s1
while (!s2.empty())
{
    struct node *temp = s2.top();
    s2.pop();
    cout << temp->data << " ";

    // Note that is left is pushed before right
    if (temp->left)
        s1.push(temp->left);
    if (temp->right)
        s1.push(temp->right);
}
}

```

// A utility function to create a new node

```

struct node* newNode(int data)
{
    struct node* node = new struct node;
    node->data = data;
    node->left = NULL;
    node->right = NULL;

    return (node);
}

int main()
{
    struct node *root = newNode(1);
    root->left = newNode(2);
    root->right = newNode(3);
    root->left->left = newNode(7);
    root->left->right = newNode(6);
    root->right->left = newNode(5);
    root->right->right = newNode(4);
    cout << "Spiral Order traversal of binary tree is \n";
    printSpiral(root);

    return 0;
}

```

Output:

Spiral Order traversal of binary tree is

Please write comments if you find any bug in the above program/algorithm; or if you want to share more information about spiral traversal.



## Related Topics:

- [Print a Binary Tree in Vertical Order | Set 2 \(HashMap based Method\)](#)
- [Print Right View of a Binary Tree](#)
- [Red-Black Tree | Set 3 \(Delete\)](#)
- [Construct a tree from Inorder and Level order traversals](#)
- [Print all nodes at distance k from a given node](#)
- [Print a Binary Tree in Vertical Order | Set 1](#)
- [Interval Tree](#)
- [Check if a given Binary Tree is height balanced like a Red-Black Tree](#)



10



Tweet 0



4

**Writing code in comment?** Please use [ideone.com](https://www.ideone.com) and share the link here.

