GeeksforGeeks

A computer science portal for geeks

Login

Home	Algorithms	DS	GATE	Intervie	w Corne	r Q&A	С	C++	Java	Books	Contribute	Ask a Q	About
Array	Bit Magic	C/C++	- Artic	les C	Facts	Linked Li	ist	MCQ	Misc	Output	t String	Tree	Graph

Red-Black Tree | Set 2 (Insert)

In the previous post, we discussed introduction to Red-Black Trees. In this post, insertion is discussed.

In AVL tree insertion, we used rotation as a tool to do balancing after insertion caused imbalance. In Red-Black tree, we use two tools to do balancing.


- 1) Recoloring
- 2) Rotation

We try recoloring first, if recoloring doesn't work, then we go for rotation. Following is detailed algorithm. The algorithms has mainly two cases depending upon the color of uncle. If uncle is red, we do recoloring. If uncle is black, we do rotations and/or recoloring.

Color of a NULL node is considered as BLACK.

Let x be the newly inserted node.

- 1) Perform standard BST insertion and make the color of newly inserted nodes as RED.
- 2) Do following if color of x's parent is not BLACK or x is not root.
-a) If x's uncle is RED (Grand parent must have been black from property 4)
-(i) Change color of parent and uncle as BLACK.
-(ii) color of grand parent as RED.
-(iii) Change x = x's grandparent, repeat steps 2 and 3 for new x.





52,731 people like GeeksforGeeks.











Interview Experiences


Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching



x: Current Node, p: Parent:, u: Uncle, g: Grandparent

T1, T2, T3, T4 and T5 are subtrees

....b) If x's uncle is BLACK, then there can be four configurations for x, x's parent (p) and x's grandparent (g) (This is similar to AVL Tree)


-i) Left Left Case (p is left child of g and x is left child of p)
-ii) Left Right Case (p is left child of g and x is right child of p)
-iii) Right Right Case (Mirror of case a)
-iv) Right Left Case (Mirror of case c)

3) If x is root, change color of x as BLACK (Black height of complete tree increases by 1).

Following are operations to be performed in four subcases when uncle is BLACK.

All four cases when Uncle is BLACK

Left Left Case (See g, p and x)



Left Right Case (See g, p and x)

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

ITT Tech - Official Site

itt-tech.edu

Associate, Bachelor Degree Programs Browse Programs Now & Learn More.



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C


Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and

Data Packing

Uncle Black and Left Right Case




Intersection point of two Linked Lists Lowest Common Ancestor in a BST. Check if a binary tree is BST or not

Sorted Linked List to Balanced BST



T1, T2, T3, T4 and T5 are subtrees

Right Right Case (See g, p and x)




x: Current Node, p: Parent:, u: Uncle, g: Grandparent

T1, T2, T3, T4 and T5 are subtrees

Right Left Case (See g, p and x)


Uncle Black and Right Left Case (Mirror of Left Right Case)




x: Current Node, p: Parent:, u: Uncle, g: Grandparent

T1, T2, T3, T4 and T5 are subtrees

Examples of Insertion



Insert 10, 20, 30 and 15 in an empty tree



We will soon be discussing implementation of above insertion algorithm.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.





Recent Comments

affiszerv Your example has two 4s on row 3, that's why it...

Backtracking | Set 7 (Sudoku) · 25 minutes ago

RVM Can someone please elaborate this Qs from above...

Flipkart Interview | Set 6 · 45 minutes ago

Vishal Gupta I talked about as an Interviewer in general,...

Software Engineering Lab, Samsung Interview | Set 2 · 45 minutes ago

@meya Working solution for question 2 of 4f2f round....

Amazon Interview | Set 53 (For SDE-1) · 1 hour ago sandeep void rearrange(struct node *head)

{...



Related Tpoics:

- Print a Binary Tree in Vertical Order | Set 2 (Hashmap based Method)
- Print Right View of a Binary Tree
- Red-Black Tree | Set 3 (Delete)
- Construct a tree from Inorder and Level order traversals.
- Print all nodes at distance k from a given node
- Print a Binary Tree in Vertical Order | Set 1
- Interval Tree
- Check if a given Binary Tree is height balanced like a Red-Black Tree









Writing code in comment? Please use ideone.com and share the link here.

6 Comments

GeeksforGeeks

Sort by Newest ▼



Given a linked list, reverse alternate nodes and

append at the end · 2 hours ago

Neha I think that is what it should return as.

in...

Find depth of the deepest odd level leaf node · 2

hours ago

AdChoices D

- ▶ Binary Tree
- ▶ Java Tree
- ► Red Black Tree

AdChoices D

- ► Java Source Code
- ▶ Tree Balancing
- ► Insert Java

AdChoices [>

- ► How to Insert IV
- ▶ Tree View
- ► Tree Root





kaushik Lele • 19 days ago

I ran RedBlackTreeViewer.java; mentioned below. But code is not correct. Wh 4,7,17; it showed a tree with 4 as root and 12 as left node!! that is wrong. So



kaushik Lele • 19 days ago

You can take complete Java code. Take java classes from here. As they are in http://cs.lmu.edu/~ray/notes/r...

http://cs.lmu.edu/~ray/notes/b...

http://cs.lmu.edu/~ray/notes/b...

Run RedBlackTreeViewer.java



kaushik Lele • 19 days ago

Very well Explained. Keep these rules handy and view this animation. http://www.youtube.com/watch?v...

After every insertion, apply these rule and guess what should be behaviour. Yc



robinhood • a month ago very well xplained.:)



sachi059 • 2 months ago

Good Explanation :-)



Anuj · 2 months ago



First time ever, I understood insertion in red-black tree. Thanks.





@geeksforgeeks, Some rights reserved

Contact Us!

Powered by WordPress & MooTools, customized by geeksforgeeks team