

When does the worst case of Quicksort occur?

The answer depends on strategy for choosing pivot. In early versions of Quick Sort where leftmost (or rightmost) element is chosen as pivot, the worst occurs in following cases.

- 1) Array is already sorted in same order.
- 2) Array is already sorted in reverse order.
- 3) All elements are same (special case of case 1 and 2)

Since these cases are very common use cases, the problem was easily solved by choosing either a random index for the pivot, choosing the middle index of the partition or (especially for longer partitions) choosing the median of the first, middle and last element of the partition for the pivot. With these modifications, the worst case of Quick sort has less chances to occur, but worst case can still occur if the input array is such that the maximum (or minimum) element is always chosen as pivot.

References:

<http://en.wikipedia.org/wiki/Quicksort>


Google™ Custom Search



GeeksforGeeks




53,523 people like [GeeksforGeeks](#).



Interview Experiences

Advanced Data Structures



Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Related Topics:

- Backtracking | Set 8 (Solving Cryptarithmic Puzzles)
- Tail Recursion
- Find if two rectangles overlap
- Analysis of Algorithm | Set 4 (Solving Recurrences)
- Print all possible paths from top left to bottom right of a mXn matrix
- Generate all unique partitions of an integer
- Russian Peasant Multiplication
- Closest Pair of Points | O(nlogn) Implementation



3



Tweet

0



4

Writing code in comment? Please use ideone.com and share the link here.

7 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion



with the algorithm...



groomnestle • 5 months ago

The worst case occurs if the chosen pivot happens to be the largest or smallest

So in early implementation which picks first element as pivot worst case would

In practice this is a very unlikely situation as pivot is chosen randomly or from

1 ^ | v .

Structure Member Alignment, Padding and

Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST



Rajesh · 2 years ago

explain output of merge sort in each pass but it is recursive in nature?

```
/* Paste your code here (You may delete these lines if not writing code)
```

1 ^ | v ·



Himanshu · 3 years ago

Any idea on how the C standard library or C++ standard library prevents these pathological cases?
Does the qsort() implementation in C/C++ standard library also suffers from C pathological cases?

^ | v ·



kartik → Himanshu · 3 years ago

@Himanshu: I am not sure how standard C++ library prevents worst case though which we can guarantee that worst case would never occur.

We can find median of array in $O(n)$ time using order statistics algorithm: use median as pivot. It will be an ideal pivot dividing the array in two halves and time complexity remains $O(n \log n)$ for all inputs. Finding median as pivot is $O(n)$ which is same as partition. But, this is slow and not followed.

^ | v ·



neha2210 → kartik · a year ago

But if median is found in $O(n)$ time, time complexity also depends on finding median.

Am I right?

^ | v ·

Market research
that's fast and
accurate.

Get \$75 off

 Google consumer surveys



bharath reddy → neha2210 · 8 months ago

But the number of steps is $O(\log n)$; so that won't chang

3 ^ | v ·



joh · 3 years ago

Could you give an example as why?

^ | v ·



Subscribe



Add Disqus to your site

705



Subscribe

Recent Comments

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree · 32 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 36 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...


Count trailing zeroes in factorial of a number · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

newCoder3006 Code without using while loop. We can do it...


Find subarray with given sum · 1 hour ago

AdChoices 

▶ [Java Source Code](#)

▶ [QuickSort](#)


▶ [Java Array](#)

AdChoices 

▶ [Java Algorithm](#)

▶ [Sorting](#)

▶ [Java Log](#)

AdChoices 

▶ [To Java](#)

▶ [Java Using](#)

▶ [Java 8](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team