

Searching for Patterns | Set 4 (A Naive Pattern Searching Question)

July 27, 2011

18 Comments | Filed under Strings

Question: We have discussed Naive String matching algorithm here. Consider a situation where all characters of pattern are different.

[Read More »](#)

Searching for Patterns | Set 3 (Rabin-Karp Algorithm)

May 18, 2011

27 Comments | Filed under Strings

Given a text `txt[0..n-1]` and a pattern `pat[0..m-1]`, write a function `search(char pat[], char txt[])` that prints all occurrences of `pat[]` in `txt[]`. You may assume that $n > m$.

[Read More »](#)

Searching for Patterns | Set 2 (KMP Algorithm)

April 3, 2011

60 Comments | Filed under Strings

Given a text `txt[0..n-1]` and a pattern `pat[0..m-1]`, write a function `search(char pat[], char txt[])` that prints all occurrences of `pat[]` in `txt[]`. You may assume that $n > m$.

[Read More »](#)


Google™ Custom Search



GeeksforGeeks



52,731 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

Searching for Patterns | Set 1 (Naive Pattern Searching)

April 1, 2011

Geometric Algorithms

14 Comments | Filed under [Strings](#)

Given a text `txt[0..n-1]` and a pattern `pat[0..m-1]`, write a function `search(char pat[], char txt[])` that prints all occurrences of `pat[]` in `txt[]`. You may assume that $n > m$.

[Read More »](#)

Find the smallest window in a string containing all characters of another string

March 9, 2011

69 Comments | Filed under [Strings](#)

Given two strings `string1` and `string2`, find the smallest substring in `string1` containing all characters of `string2` efficiently.

[Read More »](#)

Run Length Encoding

May 15, 2010

74 Comments | Filed under [Strings](#)

Given an input string, write a function that returns the Run Length Encoded string for the input string.

[Read More »](#)

Reverse words in a given string

May 3, 2010

71 Comments | Filed under [Strings](#)

Example: Let the input string be “i like this program very much”. The function should change the string to “much very program this like i”

[Read More »](#)



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding “extern” keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

Print list items containing all characters of a given word

April 2, 2010

[36 Comments](#) | Filed under [Strings](#)

There is a list of items. Given a specific word, e.g., “sun”, print out all the items in list which contain all the characters of “sum”

[Read More »](#)

Given a string, find its first non-repeating character

September 16, 2009

[82 Comments](#) | Filed under [Strings](#)

Given a string, find the first non-repeating character in it. For example, if the input string is “GeeksforGeeks”, then output should be ‘f’ and if input string is “GeeksQuiz”, then output should be ‘G’.

[Read More »](#)

Divide a string in N equal parts

September 9, 2009

[8 Comments](#) | Filed under [Strings](#)

Difficulty Level: Rookie Question: Write a program to print N equal parts of a given string.

[Read More »](#)

Write a C program to print all permutations of a given string

August 2, 2009

[236 Comments](#) | Filed under [Strings](#)

A permutation, also called an “arrangement number” or “order,” is a rearrangement of the elements of an ordered list S into a one-to-one correspondence with S itself. A string of length n has n! permutation.

Custom market
research at scale.

Get \$75 off

 Google consumer surveys

Print reverse of a string using recursion

June 19, 2009

31 Comments | Filed under [Strings](#)

Write a recursive C function to print reverse of a given string.

[Read More »](#)

A Program to check if strings are rotations of each other or not

May 26, 2009

49 Comments | Filed under [Strings](#)

Given a string s1 and a string s2, write a snippet to say whether s2 is a rotation of s1 using only one call to strstr routine? (eg given s1 = ABCD and s2 = CDAB, return true, given s1 = ABCD, and s2 = ACBD , return false) Algorithm: areRotations(str1, str2) 1. Create a [...]

[Read More »](#)

Remove characters from the first string which are present in the second string

May 23, 2009

24 Comments | Filed under [Strings](#)

Write an efficient C function that takes two strings as arguments and removes the characters from first string which are present in second string (mask string). Algorithm: Let first input string be "test string" and the string which has characters to be removed from first string be "mask" 1: Initialize: res_ind = 0 /* index to [...]

[Read More »](#)

Recent Comments

affizerv Your example has two 4s on row 3, that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 18 minutes ago

RVM Can someone please elaborate this Qs from above...

[Flipkart Interview | Set 6](#) · 38 minutes ago

Vishal Gupta I talked about as an Interviewer in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 38 minutes ago

@meya Working solution for question 2 of 4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago
sandeep void rearrange(struct node *head) {...

Given a linked list, reverse alternate nodes and append at the end · 2 hours ago

Neha I think that is what it should return as, in...

[Find depth of the deepest odd level leaf node](#) · 2 hours ago



Better Than Hadoop.

HPCC Systems is Big Data Processing and Analytics
Open Source. Proven. Trusted.

 LexisNexis® [Learn More](#) 

AdChoices [► C Strings](#)[► Strings 3](#)[► Strings All](#)AdChoices [► String Function](#)[► String Set](#)[► String Java](#)AdChoices [► For String](#)[► String String](#)[► The String](#)