

Rearrange an array so that $arr[i]$ becomes $arr[arr[i]]$ with $O(1)$ extra space

Given an array $arr[]$ of size n where every element is in range from 0 to $n-1$. Rearrange the given array so that $arr[i]$ becomes $arr[arr[i]]$. This should be done with $O(1)$ extra space.

Examples:

Input: $arr[] = \{3, 2, 0, 1\}$

Output: $arr[] = \{1, 0, 3, 2\}$

Input: $arr[] = \{4, 0, 2, 1, 3\}$

Output: $arr[] = \{3, 4, 2, 0, 1\}$

Input: $arr[] = \{0, 1, 2, 3\}$

Output: $arr[] = \{0, 1, 2, 3\}$

If the extra space condition is removed, the question becomes very easy. The main part of the question is to do it without extra space.

The credit for following solution goes to [Ganesh Ram Sundaram](#). Following are the steps.

- 1) Increase every array element $arr[i]$ by $(arr[arr[i]] \% n) * n$.
- 2) Divide every element by n .

Let us understand the above steps by an example array $\{3, 2, 0, 1\}$

In first step, every value is incremented by $(arr[arr[i]] \% n) * n$

After first step array becomes $\{7, 2, 12, 9\}$.

The important thing is, after the increment operation

Google™ Custom Search



GeeksforGeeks



53,519 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

of first step, every element holds both old values and new values. Old value can be obtained by $arr[i]\%n$ and new value can be obtained by $arr[i]/n$.

In second step, all elements are updated to new or output values by doing $arr[i] = arr[i]/n$.

After second step, array becomes {1, 0, 3, 2}

Following is C++ implementation of the above approach.

```
#include <iostream>
using namespace std;

// The function to rearrange an array in-place so that arr[i]
// becomes arr[arr[i]].
void rearrange(int arr[], int n)
{
    // First step: Increase all values by (arr[arr[i]]%n)*n
    for (int i=0; i < n; i++)
        arr[i] += (arr[arr[i]]%n)*n;

    // Second Step: Divide all values by n
    for (int i=0; i<n; i++)
        arr[i] /= n;
}

// A utility function to print an array of size n
void printArr(int arr[], int n)
{
    for (int i = 0; i < n; i++)
        cout << arr[i] << " ";
    cout << endl;
}

/* Driver program to test above functions*/
int main()
{
    int arr[] = {3, 2, 0, 1};
    int n = sizeof(arr)/sizeof(arr[0]);

    cout << "Given array is \n";
    printArr(arr, n);
}
```



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```

    rearrange(arr, n);

    cout << "Modified array is \n";
    printArr(arr, n);
    return 0;
}

```

Output:

Given array is

3 2 0 1

Modified array is


1 0 3 2

Time Complexity: $O(n)$

Auxiliary Space: $O(1)$

The only problem with above solution is, it may cause overflow.

This article is contributed by **Himanshu Gupta**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Sauce LABS

Supercharged Selenium Testing

Spin up browsers in seconds

[Test for free](#)

The advertisement features a speedometer graphic on the left with a needle pointing towards 100. On the right, there is a table showing test results with columns for Name, Environment, Type, Suite, and Results. The table contains several rows of data, some with green status indicators and others with red.



rackspace
the open cloud company

The advertisement consists of a large red rectangle at the top, followed by a white rectangle containing the Rackspace logo and tagline. The logo features a stylized red and black 'R' icon.

Related Tpoics:

- Remove minimum elements from either side such that $2 \times \text{min}$ becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



16



Tweet

3



2

Writing code in comment? Please use ideone.com and share the link here.

705



Subscribe

Recent Comments

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 3 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 28

minutes ago

GOPI GOPINATH @admin Highlight this

sentence "We can easily...

Count trailing zeroes in factorial of a number · 30

minutes ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 54 minutes ago

newCoder3006 Code without using while loop. We can do it...

Find subarray with given sum · 1 hour ago

Sanjay Agarwal You can also use the this method:...

Count trailing zeroes in factorial of a number · 1

hour ago

AdChoices

► [C++ Code](#)

► [Java Source Code](#)


► [Java Array](#)

AdChoices 

► [C++ Array](#)

► [An Array](#)

► [Linked List](#)

AdChoices 

► [Int in Array](#)

► [Array Function](#)

► [Array Element](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team